



TEST DATA OF PBA100F-9

Regulated DC Power Supply
Mar.30. 2004

Approved by : Kuniaki Nagahara
Kuniaki Nagahara Design Manager

Prepared by : Katsumi Ishikawa
Katsumi Ishikawa Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PBA100F-9	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—	—	—																																																			
1.Graph		2.Values																																																				
<p>Input Current [A]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.088</td><td>0.064</td><td>0.070</td></tr> <tr><td>2.00</td><td>0.284</td><td>0.204</td><td>0.187</td></tr> <tr><td>4.00</td><td>0.491</td><td>0.308</td><td>0.295</td></tr> <tr><td>6.00</td><td>0.696</td><td>0.402</td><td>0.375</td></tr> <tr><td>8.00</td><td>0.907</td><td>0.498</td><td>0.462</td></tr> <tr><td>10.00</td><td>1.123</td><td>0.597</td><td>0.543</td></tr> <tr><td>10.50</td><td>1.177</td><td>0.622</td><td>0.565</td></tr> <tr><td>11.55</td><td>1.292</td><td>0.674</td><td>0.611</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.088	0.064	0.070	2.00	0.284	0.204	0.187	4.00	0.491	0.308	0.295	6.00	0.696	0.402	0.375	8.00	0.907	0.498	0.462	10.00	1.123	0.597	0.543	10.50	1.177	0.622	0.565	11.55	1.292	0.674	0.611	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.088	0.064	0.070																																																			
2.00	0.284	0.204	0.187																																																			
4.00	0.491	0.308	0.295																																																			
6.00	0.696	0.402	0.375																																																			
8.00	0.907	0.498	0.462																																																			
10.00	1.123	0.597	0.543																																																			
10.50	1.177	0.622	0.565																																																			
11.55	1.292	0.674	0.611																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PBA100F-9	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Input Power (by Load Current)																																																						
Object																																																							
1.Graph																																																							
	—▲— Input Volt. 100V	—□— Input Volt. 200V	—○— Input Volt. 230V																																																				
	<p>The graph plots Input Power [W] on the Y-axis (0 to 200) against Load Current [A] on the X-axis (0 to 12). Three curves are shown for different input voltages: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (0, 10) and ending at approximately (11.5, 130), indicating the range of the rated load current.</p>																																																						
	2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>100[V]</th> <th>200[V]</th> <th>230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.4</td><td>4.0</td><td>4.0</td></tr> <tr><td>2.00</td><td>26.2</td><td>27.0</td><td>27.0</td></tr> <tr><td>4.00</td><td>47.7</td><td>47.0</td><td>48.0</td></tr> <tr><td>6.00</td><td>68.6</td><td>67.4</td><td>68.0</td></tr> <tr><td>8.00</td><td>90.0</td><td>87.9</td><td>88.0</td></tr> <tr><td>10.00</td><td>111.9</td><td>108.6</td><td>108.4</td></tr> <tr><td>10.50</td><td>117.3</td><td>113.8</td><td>113.5</td></tr> <tr><td>11.55</td><td>128.9</td><td>124.7</td><td>124.4</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			100[V]	200[V]	230[V]	0.00	4.4	4.0	4.0	2.00	26.2	27.0	27.0	4.00	47.7	47.0	48.0	6.00	68.6	67.4	68.0	8.00	90.0	87.9	88.0	10.00	111.9	108.6	108.4	10.50	117.3	113.8	113.5	11.55	128.9	124.7	124.4	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																						
	100[V]	200[V]	230[V]																																																				
0.00	4.4	4.0	4.0																																																				
2.00	26.2	27.0	27.0																																																				
4.00	47.7	47.0	48.0																																																				
6.00	68.6	67.4	68.0																																																				
8.00	90.0	87.9	88.0																																																				
10.00	111.9	108.6	108.4																																																				
10.50	117.3	113.8	113.5																																																				
11.55	128.9	124.7	124.4																																																				
—	—	—	—																																																				
—	—	—	—																																																				
—	—	—	—																																																				
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PBA100F-9	Temperature Testing Circuitry 25°C Figure A																																
Item	Efficiency (by Input Voltage)																																	
Object	—																																	
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line), Load 100% (solid line)</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>77.0</td> <td>78.7</td> </tr> <tr> <td>85</td> <td>77.7</td> <td>79.9</td> </tr> <tr> <td>100</td> <td>78.5</td> <td>81.0</td> </tr> <tr> <td>120</td> <td>79.0</td> <td>82.0</td> </tr> <tr> <td>200</td> <td>79.5</td> <td>83.7</td> </tr> <tr> <td>230</td> <td>79.2</td> <td>83.8</td> </tr> <tr> <td>264</td> <td>79.2</td> <td>83.9</td> </tr> <tr> <td>280</td> <td>79.2</td> <td>83.9</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	77.0	78.7	85	77.7	79.9	100	78.5	81.0	120	79.0	82.0	200	79.5	83.7	230	79.2	83.8	264	79.2	83.9	280	79.2	83.9	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	77.0	78.7																																
85	77.7	79.9																																
100	78.5	81.0																																
120	79.0	82.0																																
200	79.5	83.7																																
230	79.2	83.8																																
264	79.2	83.9																																
280	79.2	83.9																																
--	-	-																																


COSEL

Model	PBA100F-9	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - ○ - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>2.00</td><td>69.2</td><td>67.2</td><td>67.2</td></tr> <tr><td>4.00</td><td>76.0</td><td>77.1</td><td>75.5</td></tr> <tr><td>6.00</td><td>79.2</td><td>80.6</td><td>79.9</td></tr> <tr><td>8.00</td><td>80.5</td><td>82.4</td><td>82.4</td></tr> <tr><td>10.00</td><td>80.9</td><td>83.4</td><td>83.5</td></tr> <tr><td>10.50</td><td>81.0</td><td>83.5</td><td>83.8</td></tr> <tr><td>11.55</td><td>81.0</td><td>83.8</td><td>84.0</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	2.00	69.2	67.2	67.2	4.00	76.0	77.1	75.5	6.00	79.2	80.6	79.9	8.00	80.5	82.4	82.4	10.00	80.9	83.4	83.5	10.50	81.0	83.5	83.8	11.55	81.0	83.8	84.0																			
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
2.00	69.2	67.2	67.2																																																			
4.00	76.0	77.1	75.5																																																			
6.00	79.2	80.6	79.9																																																			
8.00	80.5	82.4	82.4																																																			
10.00	80.9	83.4	83.5																																																			
10.50	81.0	83.5	83.8																																																			
11.55	81.0	83.8	84.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>69.2</td><td>67.2</td><td>67.2</td></tr> <tr><td>4.00</td><td>76.0</td><td>77.1</td><td>75.5</td></tr> <tr><td>6.00</td><td>79.2</td><td>80.6</td><td>79.9</td></tr> <tr><td>8.00</td><td>80.5</td><td>82.4</td><td>82.4</td></tr> <tr><td>10.00</td><td>80.9</td><td>83.4</td><td>83.5</td></tr> <tr><td>10.50</td><td>81.0</td><td>83.5</td><td>83.8</td></tr> <tr><td>11.55</td><td>81.0</td><td>83.8</td><td>84.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	2.00	69.2	67.2	67.2	4.00	76.0	77.1	75.5	6.00	79.2	80.6	79.9	8.00	80.5	82.4	82.4	10.00	80.9	83.4	83.5	10.50	81.0	83.5	83.8	11.55	81.0	83.8	84.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
2.00	69.2	67.2	67.2																																																			
4.00	76.0	77.1	75.5																																																			
6.00	79.2	80.6	79.9																																																			
8.00	80.5	82.4	82.4																																																			
10.00	80.9	83.4	83.5																																																			
10.50	81.0	83.5	83.8																																																			
11.55	81.0	83.8	84.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PBA100F-9
Item	Power Factor (by Input Voltage)
Object	_____

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.991	0.997
85	0.986	0.994
100	0.975	0.991
120	0.954	0.983
200	0.808	0.930
230	0.741	0.875
264	0.674	0.815
280	0.583	0.727
-	-	-




COSEL

Model	PBA100F-9	Temperature Testing Circuitry	25°C Figure A																																																	
Item	Power Factor (by Load Current)																																																			
Object	_____																																																			
1.Graph	<p>—△— Input Volt. 100V - -□-- Input Volt. 200V - -○-- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.478</td><td>0.333</td><td>0.308</td></tr> <tr><td>2.00</td><td>0.917</td><td>0.675</td><td>0.643</td></tr> <tr><td>4.00</td><td>0.966</td><td>0.770</td><td>0.727</td></tr> <tr><td>6.00</td><td>0.981</td><td>0.845</td><td>0.791</td></tr> <tr><td>8.00</td><td>0.987</td><td>0.887</td><td>0.830</td></tr> <tr><td>10.00</td><td>0.991</td><td>0.920</td><td>0.870</td></tr> <tr><td>10.50</td><td>0.991</td><td>0.929</td><td>0.876</td></tr> <tr><td>11.55</td><td>0.992</td><td>0.945</td><td>0.887</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0.00	0.478	0.333	0.308	2.00	0.917	0.675	0.643	4.00	0.966	0.770	0.727	6.00	0.981	0.845	0.791	8.00	0.987	0.887	0.830	10.00	0.991	0.920	0.870	10.50	0.991	0.929	0.876	11.55	0.992	0.945	0.887															
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																																	
0.00	0.478	0.333	0.308																																																	
2.00	0.917	0.675	0.643																																																	
4.00	0.966	0.770	0.727																																																	
6.00	0.981	0.845	0.791																																																	
8.00	0.987	0.887	0.830																																																	
10.00	0.991	0.920	0.870																																																	
10.50	0.991	0.929	0.876																																																	
11.55	0.992	0.945	0.887																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.478</td><td>0.333</td><td>0.308</td></tr> <tr><td>2.00</td><td>0.917</td><td>0.675</td><td>0.643</td></tr> <tr><td>4.00</td><td>0.966</td><td>0.770</td><td>0.727</td></tr> <tr><td>6.00</td><td>0.981</td><td>0.845</td><td>0.791</td></tr> <tr><td>8.00</td><td>0.987</td><td>0.887</td><td>0.830</td></tr> <tr><td>10.00</td><td>0.991</td><td>0.920</td><td>0.870</td></tr> <tr><td>10.50</td><td>0.991</td><td>0.929</td><td>0.876</td></tr> <tr><td>11.55</td><td>0.992</td><td>0.945</td><td>0.887</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.478	0.333	0.308	2.00	0.917	0.675	0.643	4.00	0.966	0.770	0.727	6.00	0.981	0.845	0.791	8.00	0.987	0.887	0.830	10.00	0.991	0.920	0.870	10.50	0.991	0.929	0.876	11.55	0.992	0.945	0.887	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Power Factor																																																			
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																	
0.00	0.478	0.333	0.308																																																	
2.00	0.917	0.675	0.643																																																	
4.00	0.966	0.770	0.727																																																	
6.00	0.981	0.845	0.791																																																	
8.00	0.987	0.887	0.830																																																	
10.00	0.991	0.920	0.870																																																	
10.50	0.991	0.929	0.876																																																	
11.55	0.992	0.945	0.887																																																	
-	-	-	-																																																	
-	-	-	-																																																	
-	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PBA100F-9	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current	
Object	—	





Model	PBA100F-9	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.15	0.28	0.34	Operation
	One of phase	0.25	0.53	0.62	stand by
IEC60950	Both phases	0.15	0.34	0.38	Operation
	One of phase	0.25	0.58	0.67	stand by

The value for "One phase" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PBA100F-9																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+9V10.5A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>85</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>100</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>120</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>200</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>230</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>264</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>280</td> <td>9.033</td> <td>9.026</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	9.033	9.026	85	9.033	9.026	100	9.033	9.026	120	9.033	9.026	200	9.033	9.026	230	9.033	9.026	264	9.033	9.026	280	9.033	9.026	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	9.033	9.026																																
85	9.033	9.026																																
100	9.033	9.026																																
120	9.033	9.026																																
200	9.033	9.026																																
230	9.033	9.026																																
264	9.033	9.026																																
280	9.033	9.026																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	PBA100F-9	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+9V10.5A																																																						
1. Graph																																																							
<p style="text-align: center;"> Input Volt. 100V Input Volt. 200V Input Volt. 230V </p> 																																																							
2. Values																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>9.040</td><td>9.040</td><td>9.040</td></tr> <tr><td>2.00</td><td>9.036</td><td>9.036</td><td>9.036</td></tr> <tr><td>4.00</td><td>9.034</td><td>9.034</td><td>9.034</td></tr> <tr><td>6.00</td><td>9.031</td><td>9.031</td><td>9.031</td></tr> <tr><td>8.00</td><td>9.029</td><td>9.029</td><td>9.029</td></tr> <tr><td>10.00</td><td>9.026</td><td>9.026</td><td>9.026</td></tr> <tr><td>10.50</td><td>9.026</td><td>9.026</td><td>9.026</td></tr> <tr><td>11.55</td><td>9.024</td><td>9.024</td><td>9.024</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	9.040	9.040	9.040	2.00	9.036	9.036	9.036	4.00	9.034	9.034	9.034	6.00	9.031	9.031	9.031	8.00	9.029	9.029	9.029	10.00	9.026	9.026	9.026	10.50	9.026	9.026	9.026	11.55	9.024	9.024	9.024	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	9.040	9.040	9.040																																																				
2.00	9.036	9.036	9.036																																																				
4.00	9.034	9.034	9.034																																																				
6.00	9.031	9.031	9.031																																																				
8.00	9.029	9.029	9.029																																																				
10.00	9.026	9.026	9.026																																																				
10.50	9.026	9.026	9.026																																																				
11.55	9.024	9.024	9.024																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
<p>Note: Slanted line shows the range of the rated load current.</p>																																																							

COSEL


Model PBA100F-9

Item Dynamic Load Response

Object +9V10.5A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 100 V
Cycle 1000 ms

Load Current




Min. Load (0A) ↔

Load 100% (10.5A)

200 mV/div

10 ms/div




10 ms/div

Min. Load (0A) ↔

Load 50% (5.25A)

200 mV/div

10 ms/div



10 ms/div


* The characteristic of AC200V is equal.

COSEL

Model	PBA100F-9
Item	Ripple Voltage (by Load Current)
Object	+9V10.5A

1.Graph

—△— Input Volt. 100V
—○— Input Volt. 200V



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	15	15
2.00	35	35
4.00	40	40
6.00	40	40
8.00	40	40
10.00	45	45
10.50	50	50
11.55	50	50
—	—	—
—	—	—
—	—	—

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form

COSEL


Model PBA100F-9

Item Ripple-Noise

Object +9V10.5A

1. Graph

—△— Input Volt. 100V
 -·○--- Input Volt. 200V



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	30	30
2.00	55	55
4.00	55	55
6.00	70	80
8.00	80	80
10.00	80	80
10.50	80	80
11.55	80	80
-	-	-
-	-	-
-	-	-


T1: Due to AC Input Line
T2: Due to Switching


Fig. Complex Ripple Wave Form

coSEL

Model	PBA100F-9
Item	Ripple Voltage (by Ambient Temp.)
Object	+9V10.5A

1.Graph

--- □ --- Input Volt. 100V
 —△— Input Volt. 200V



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	230	225
-10	85	85
0	65	60
25	50	50
50	45	40
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model	PBA100F-9	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+9V10.5A																																																						
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>9.004</td><td>9.004</td><td>9.004</td></tr> <tr> <td>-10</td><td>9.009</td><td>9.009</td><td>9.009</td></tr> <tr> <td>0</td><td>9.013</td><td>9.014</td><td>9.014</td></tr> <tr> <td>10</td><td>9.019</td><td>9.020</td><td>9.020</td></tr> <tr> <td>25</td><td>9.028</td><td>9.028</td><td>9.029</td></tr> <tr> <td>30</td><td>9.032</td><td>9.032</td><td>9.032</td></tr> <tr> <td>40</td><td>9.035</td><td>9.035</td><td>9.035</td></tr> <tr> <td>50</td><td>9.036</td><td>9.036</td><td>9.036</td></tr> <tr> <td>60</td><td>9.036</td><td>9.036</td><td>9.036</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	9.004	9.004	9.004	-10	9.009	9.009	9.009	0	9.013	9.014	9.014	10	9.019	9.020	9.020	25	9.028	9.028	9.029	30	9.032	9.032	9.032	40	9.035	9.035	9.035	50	9.036	9.036	9.036	60	9.036	9.036	9.036	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
-20	9.004	9.004	9.004																																																				
-10	9.009	9.009	9.009																																																				
0	9.013	9.014	9.014																																																				
10	9.019	9.020	9.020																																																				
25	9.028	9.028	9.029																																																				
30	9.032	9.032	9.032																																																				
40	9.035	9.035	9.035																																																				
50	9.036	9.036	9.036																																																				
60	9.036	9.036	9.036																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	PBA100F-9	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+9V10.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 10.5A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	50	264	0	9.051	± 21	± 0.2
Minimum Voltage	-10	85	10.5	9.009		

COSEL

Model	PBA100F-9	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift																								
Object	+9V10.5A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>9.028</td></tr> <tr><td>0.5</td><td>9.028</td></tr> <tr><td>1.0</td><td>9.028</td></tr> <tr><td>2.0</td><td>9.028</td></tr> <tr><td>3.0</td><td>9.029</td></tr> <tr><td>4.0</td><td>9.028</td></tr> <tr><td>5.0</td><td>9.029</td></tr> <tr><td>6.0</td><td>9.029</td></tr> <tr><td>7.0</td><td>9.029</td></tr> <tr><td>8.0</td><td>9.029</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	9.028	0.5	9.028	1.0	9.028	2.0	9.028	3.0	9.029	4.0	9.028	5.0	9.029	6.0	9.029	7.0	9.029	8.0	9.029
Time since start [H]	Output Voltage [V]																								
0.0	9.028																								
0.5	9.028																								
1.0	9.028																								
2.0	9.028																								
3.0	9.029																								
4.0	9.028																								
5.0	9.029																								
6.0	9.029																								
7.0	9.029																								
8.0	9.029																								
* The characteristic of AC200V is equal.																									

COSEL

COSEL


Model	PBA100F-9	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+9V10.5A																																		
1.Graph																																			
<p>Legend: ---□--- Load 50% —△— Load 100%</p> <p>Y-axis: Hold-Up Time [mS] X-axis: Input Voltage [V]</p>																																			
2.Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>57</td> <td>23</td> </tr> <tr> <td>85</td> <td>59</td> <td>25</td> </tr> <tr> <td>100</td> <td>62</td> <td>28</td> </tr> <tr> <td>120</td> <td>64</td> <td>30</td> </tr> <tr> <td>200</td> <td>69</td> <td>33</td> </tr> <tr> <td>230</td> <td>70</td> <td>34</td> </tr> <tr> <td>264</td> <td>71</td> <td>34</td> </tr> <tr> <td>280</td> <td>71</td> <td>34</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	57	23	85	59	25	100	62	28	120	64	30	200	69	33	230	70	34	264	71	34	280	71	34	--	-	-
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	57	23																																	
85	59	25																																	
100	62	28																																	
120	64	30																																	
200	69	33																																	
230	70	34																																	
264	71	34																																	
280	71	34																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PBA100F-9
Item	Instantaneous Interruption Compensation
Object	+9V10.5A

1. Graph

Input Volt. 100V
 Input Volt. 200V
 Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Load Current [A]	Time [mS]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
2.00	164	180	197
4.00	84	92	95
6.00	54	61	62
8.00	39	45	46
10.00	30	35	36
10.50	28	34	34
11.55	23	30	31
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	PBA100F-9
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+9V10.5A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	41	55
-10	41	55
0	40	54
10	40	54
25	40	55
30	40	55
40	40	55
50	41	55
60	41	56
--	-	-
--	-	-

COSEL

Model	PBA100F-9
Item	Overshoot Protection
Object	+9V10.5A

1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 4.5V to 0V.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
9.00	12.74	12.70
8.55	12.85	12.82
8.10	12.97	12.95
7.20	13.17	13.15
6.30	13.23	13.13
5.40	13.33	13.29
4.50	13.55	13.53
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

COSEL

Model	PBA100F-9	Testing Circuitry Figure A																																						
Item	Overvoltage Protection																																							
Object	+9V10.5A																																							
1. Graph		2. Values																																						
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Legend: —△— Input Volt. 100V ---□--- Input Volt. 200V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>12.27</td><td>12.27</td></tr> <tr><td>-10</td><td>12.34</td><td>12.34</td></tr> <tr><td>0</td><td>12.41</td><td>12.41</td></tr> <tr><td>10</td><td>12.48</td><td>12.48</td></tr> <tr><td>25</td><td>12.54</td><td>12.55</td></tr> <tr><td>30</td><td>12.62</td><td>12.62</td></tr> <tr><td>40</td><td>12.61</td><td>12.62</td></tr> <tr><td>50</td><td>12.69</td><td>12.69</td></tr> <tr><td>60</td><td>12.76</td><td>12.76</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 200[V]	-20	12.27	12.27	-10	12.34	12.34	0	12.41	12.41	10	12.48	12.48	25	12.54	12.55	30	12.62	12.62	40	12.61	12.62	50	12.69	12.69	60	12.76	12.76	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 100[V]	Input Volt. 200[V]																																						
-20	12.27	12.27																																						
-10	12.34	12.34																																						
0	12.41	12.41																																						
10	12.48	12.48																																						
25	12.54	12.55																																						
30	12.62	12.62																																						
40	12.61	12.62																																						
50	12.69	12.69																																						
60	12.76	12.76																																						
--	-	-																																						
--	-	-																																						

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)