



# TEST DATA OF PBA1500F-15

Regulated DC Power Supply  
Jun.14. 2003

Approved by : Takahiro Yoneda  
Design Manager

Prepared by : Takahiro Sugimoto  
Design Engineer

**COSEL CO.,LTD.**



## CONTENTS


1.Input Current (by Load Current) .....	1
2.Input Power (by Load Current) .....	2
3.Efficiency (by Input Voltage) .....	3
4.Efficiency (by Load Current) .....	4
5.Power Factor (by Input Voltage) .....	5
6.Power Factor (by Load Current) .....	6
7.Inrush Current .....	7
8.Leakage Current .....	8
9.Line Regulation .....	9
10.Load Regulation .....	10
11.Dynamic Load Response .....	11
12.Ripple Voltage (by Load Current) .....	12
13.Ripple-Noise .....	13
14.Ripple Voltage (by Ambient Temperature) .....	14
15.Ambient Temperature Drift .....	15
16.Output Voltage Accuracy .....	16
17.Time Lapse Drift .....	17
18.Rise and Fall Time .....	18
19.Hold-Up Time .....	19
20.Instantaneous Interruption Compensation .....	20
21.Minimum Input Voltage for Regulated Output Voltage .....	21
22.Overcurrent Protection .....	22
23.Ovvoltage Protection .....	23
24.Figure of Testing Circuitry .....	24

(Final Page 24)

**COSEL**

Model	PBA1500F-15	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—	—	—																																																			
1.Graph	<p>—▲— Input Volt. 100V        - - - □--- Input Volt. 200V        - - ○--- Input Volt. 230V</p> <p>The graph shows three curves representing different input voltages: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). The curves show that as input voltage increases, the required load current decreases for a given input current. A diagonal line from the origin to approximately (100, 20) indicates the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.286</td><td>0.217</td><td>0.226</td></tr> <tr> <td>15</td><td>3.131</td><td>1.670</td><td>1.482</td></tr> <tr> <td>30</td><td>5.720</td><td>2.956</td><td>2.613</td></tr> <tr> <td>45</td><td>8.280</td><td>4.230</td><td>3.724</td></tr> <tr> <td>60</td><td>10.910</td><td>5.520</td><td>4.840</td></tr> <tr> <td>75</td><td>13.570</td><td>6.810</td><td>5.970</td></tr> <tr> <td>90</td><td>16.300</td><td>8.130</td><td>7.100</td></tr> <tr> <td>100</td><td>18.160</td><td>8.990</td><td>7.860</td></tr> <tr> <td>110</td><td>20.040</td><td>9.880</td><td>8.640</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.286	0.217	0.226	15	3.131	1.670	1.482	30	5.720	2.956	2.613	45	8.280	4.230	3.724	60	10.910	5.520	4.840	75	13.570	6.810	5.970	90	16.300	8.130	7.100	100	18.160	8.990	7.860	110	20.040	9.880	8.640	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.286	0.217	0.226																																																			
15	3.131	1.670	1.482																																																			
30	5.720	2.956	2.613																																																			
45	8.280	4.230	3.724																																																			
60	10.910	5.520	4.840																																																			
75	13.570	6.810	5.970																																																			
90	16.300	8.130	7.100																																																			
100	18.160	8.990	7.860																																																			
110	20.040	9.880	8.640																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


**COSEL**

Model	PBA1500F-15	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph																																																						
—▲— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V			2.Values																																																			
 <p>The graph plots Input Power [W] on the Y-axis (0 to 5000) against Load Current [A] on the X-axis (0 to 120). Three curves are shown for different input voltages: 100V (solid line with squares), 200V (dashed line with circles), and 230V (dash-dot line with triangles). A slanted line at approximately 100A indicates the rated load current range.</p>																																																						
Note: Slanted line shows the range of the rated load current.																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>20</td> <td>16</td> <td>14</td> </tr> <tr> <td>15</td> <td>292</td> <td>288</td> <td>287</td> </tr> <tr> <td>30</td> <td>550</td> <td>540</td> <td>539</td> </tr> <tr> <td>45</td> <td>809</td> <td>795</td> <td>791</td> </tr> <tr> <td>60</td> <td>1072</td> <td>1054</td> <td>1048</td> </tr> <tr> <td>75</td> <td>1342</td> <td>1312</td> <td>1306</td> </tr> <tr> <td>90</td> <td>1617</td> <td>1577</td> <td>1570</td> </tr> <tr> <td>100</td> <td>1803</td> <td>1752</td> <td>1745</td> </tr> <tr> <td>110</td> <td>1995</td> <td>1932</td> <td>1924</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	20	16	14	15	292	288	287	30	550	540	539	45	809	795	791	60	1072	1054	1048	75	1342	1312	1306	90	1617	1577	1570	100	1803	1752	1745	110	1995	1932	1924	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	20	16	14																																																			
15	292	288	287																																																			
30	550	540	539																																																			
45	809	795	791																																																			
60	1072	1054	1048																																																			
75	1342	1312	1306																																																			
90	1617	1577	1570																																																			
100	1803	1752	1745																																																			
110	1995	1932	1924																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSEL**

Model	PBA1500F-15	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—	—	—																																
<b>1. Graph</b>																																			
			<b>2. Values</b>																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>83.5</td><td>82.5</td></tr> <tr> <td>100</td><td>84.0</td><td>83.4</td></tr> <tr> <td>120</td><td>84.4</td><td>84.4</td></tr> <tr> <td>200</td><td>85.4</td><td>85.9</td></tr> <tr> <td>230</td><td>85.9</td><td>86.2</td></tr> <tr> <td>264</td><td>85.9</td><td>86.4</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	83.5	82.5	100	84.0	83.4	120	84.4	84.4	200	85.4	85.9	230	85.9	86.2	264	85.9	86.4	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	83.5	82.5																																	
100	84.0	83.4																																	
120	84.4	84.4																																	
200	85.4	85.9																																	
230	85.9	86.2																																	
264	85.9	86.4																																	
--	-	-																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


**COSEL**


Model	PBA1500F-15																																																				
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																		
Object	—	—	—																																																		
1.Graph	—▲— Input Volt. 100V - - □--- Input Volt. 200V - - ○--- Input Volt. 230V																																																				
			2.Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>15</td><td>77.0</td><td>78.1</td><td>78.4</td></tr> <tr> <td>30</td><td>82.0</td><td>83.5</td><td>83.6</td></tr> <tr> <td>45</td><td>83.6</td><td>85.1</td><td>85.5</td></tr> <tr> <td>60</td><td>84.3</td><td>85.7</td><td>86.2</td></tr> <tr> <td>75</td><td>84.2</td><td>86.1</td><td>86.5</td></tr> <tr> <td>90</td><td>83.8</td><td>85.9</td><td>86.3</td></tr> <tr> <td>100</td><td>83.5</td><td>85.9</td><td>86.2</td></tr> <tr> <td>110</td><td>83.0</td><td>85.7</td><td>86.1</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	15	77.0	78.1	78.4	30	82.0	83.5	83.6	45	83.6	85.1	85.5	60	84.3	85.7	86.2	75	84.2	86.1	86.5	90	83.8	85.9	86.3	100	83.5	85.9	86.2	110	83.0	85.7	86.1	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0	-	-	-																																																		
15	77.0	78.1	78.4																																																		
30	82.0	83.5	83.6																																																		
45	83.6	85.1	85.5																																																		
60	84.3	85.7	86.2																																																		
75	84.2	86.1	86.5																																																		
90	83.8	85.9	86.3																																																		
100	83.5	85.9	86.2																																																		
110	83.0	85.7	86.1																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

**COSEL**

Model	PBA1500F-15																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>0.981</td><td>0.996</td></tr> <tr> <td>100</td><td>0.979</td><td>0.994</td></tr> <tr> <td>120</td><td>0.974</td><td>0.991</td></tr> <tr> <td>200</td><td>0.945</td><td>0.974</td></tr> <tr> <td>230</td><td>0.929</td><td>0.965</td></tr> <tr> <td>264</td><td>0.858</td><td>0.926</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.981	0.996	100	0.979	0.994	120	0.974	0.991	200	0.945	0.974	230	0.929	0.965	264	0.858	0.926	--	-	-	--	-	-	--	-	-	
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
85	0.981	0.996																																
100	0.979	0.994																																
120	0.974	0.991																																
200	0.945	0.974																																
230	0.929	0.965																																
264	0.858	0.926																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**

Model	PBA1500F-15	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 100V  <span style="color: black;">---□---</span> Input Volt. 200V  <span style="color: black;">---○---</span> Input Volt. 230V         </p> 																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.703</td><td>0.372</td><td>0.269</td></tr> <tr><td>15</td><td>0.934</td><td>0.862</td><td>0.842</td></tr> <tr><td>30</td><td>0.963</td><td>0.914</td><td>0.897</td></tr> <tr><td>45</td><td>0.977</td><td>0.940</td><td>0.923</td></tr> <tr><td>60</td><td>0.983</td><td>0.955</td><td>0.941</td></tr> <tr><td>75</td><td>0.990</td><td>0.963</td><td>0.952</td></tr> <tr><td>90</td><td>0.993</td><td>0.970</td><td>0.961</td></tr> <tr><td>100</td><td>0.994</td><td>0.974</td><td>0.965</td></tr> <tr><td>110</td><td>0.996</td><td>0.978</td><td>0.969</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.703	0.372	0.269	15	0.934	0.862	0.842	30	0.963	0.914	0.897	45	0.977	0.940	0.923	60	0.983	0.955	0.941	75	0.990	0.963	0.952	90	0.993	0.970	0.961	100	0.994	0.974	0.965	110	0.996	0.978	0.969	-	-	-	-	-	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.703	0.372	0.269																																																			
15	0.934	0.862	0.842																																																			
30	0.963	0.914	0.897																																																			
45	0.977	0.940	0.923																																																			
60	0.983	0.955	0.941																																																			
75	0.990	0.963	0.952																																																			
90	0.993	0.970	0.961																																																			
100	0.994	0.974	0.965																																																			
110	0.996	0.978	0.969																																																			
-	-	-	-																																																			
-	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**



Model	PBA1500F-15	Temperature 25°C Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

### 1. Results

Standards		Input Volt.			Note
		100[V]	200[V]	240[V]	
DEN-AN	Both phases	0.31	0.58	0.71	Operation
	One of phase	0.57	1.20	1.36	stand by
IEC60950	Both phases	0.34	0.67	0.81	Operation
	One of phase	0.57	1.15	1.41	stand by

The value for "One phase" is the reference value only.


### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	PBA1500F-15																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+15V100A																																	
1.Graph																																		
		2.Values																																
<p>---□--- Load 50%</p> <p>—△— Load 100%</p>																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>15.094</td><td>15.088</td></tr> <tr> <td>100</td><td>15.093</td><td>15.088</td></tr> <tr> <td>120</td><td>15.092</td><td>15.087</td></tr> <tr> <td>200</td><td>15.092</td><td>15.087</td></tr> <tr> <td>230</td><td>15.091</td><td>15.086</td></tr> <tr> <td>264</td><td>15.090</td><td>15.085</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	15.094	15.088	100	15.093	15.088	120	15.092	15.087	200	15.092	15.087	230	15.091	15.086	264	15.090	15.085	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	15.094	15.088																																
100	15.093	15.088																																
120	15.092	15.087																																
200	15.092	15.087																																
230	15.091	15.086																																
264	15.090	15.085																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

**COSEL**


Model	PBA1500F-15																																																					
Item	Load Regulation	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	+15V100A																																																					
1.Graph	—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V																																																					
																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>15.079</td><td>15.079</td><td>15.085</td></tr> <tr> <td>15</td><td>15.079</td><td>15.080</td><td>15.085</td></tr> <tr> <td>30</td><td>15.079</td><td>15.081</td><td>15.084</td></tr> <tr> <td>45</td><td>15.078</td><td>15.082</td><td>15.084</td></tr> <tr> <td>60</td><td>15.078</td><td>15.083</td><td>15.084</td></tr> <tr> <td>75</td><td>15.078</td><td>15.083</td><td>15.084</td></tr> <tr> <td>90</td><td>15.077</td><td>15.083</td><td>15.084</td></tr> <tr> <td>100</td><td>15.077</td><td>15.083</td><td>15.083</td></tr> <tr> <td>110</td><td>15.077</td><td>15.083</td><td>15.083</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	15.079	15.079	15.085	15	15.079	15.080	15.085	30	15.079	15.081	15.084	45	15.078	15.082	15.084	60	15.078	15.083	15.084	75	15.078	15.083	15.084	90	15.077	15.083	15.084	100	15.077	15.083	15.083	110	15.077	15.083	15.083	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	15.079	15.079	15.085																																																			
15	15.079	15.080	15.085																																																			
30	15.079	15.081	15.084																																																			
45	15.078	15.082	15.084																																																			
60	15.078	15.083	15.084																																																			
75	15.078	15.083	15.084																																																			
90	15.077	15.083	15.084																																																			
100	15.077	15.083	15.083																																																			
110	15.077	15.083	15.083																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

**COSEL**

Model	PBA1500F-15
Item	Ripple Voltage (by Load Current)
Object	+15V100A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0	10	10
15	10	10
30	10	10
45	15	15
60	15	15
75	20	20
90	20	20
100	20	20
110	25	25
-	-	-
-	-	-


T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form


**COSEL**

Model	PBA1500F-15																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure A																																						
Object	+15V100A																																							
1. Graph																																								
<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 100V  <span style="color: gray;">---○---</span> Input Volt. 200V         </p>																																								
<p style="text-align: center;">Ripple-Noise [mV]</p> <p style="text-align: center;">Load Current [A]</p>																																								
<p>Measured by 20 MHz Oscilloscope.        Ripple-Noise is shown as p-p in the figure below.        Note: Slanted line shows the range of the rated load current.</p>																																								
<p style="text-align: center;">T1: Due to AC Input Line        T2: Due to Switching</p>																																								
<p style="text-align: center;">Fig. Complex Ripple Wave Form</p>																																								
2. Values																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>20</td> <td>20</td> </tr> <tr> <td>15</td> <td>20</td> <td>20</td> </tr> <tr> <td>30</td> <td>20</td> <td>20</td> </tr> <tr> <td>45</td> <td>30</td> <td>30</td> </tr> <tr> <td>60</td> <td>30</td> <td>30</td> </tr> <tr> <td>75</td> <td>40</td> <td>40</td> </tr> <tr> <td>90</td> <td>50</td> <td>50</td> </tr> <tr> <td>100</td> <td>50</td> <td>50</td> </tr> <tr> <td>110</td> <td>55</td> <td>55</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0	20	20	15	20	20	30	20	20	45	30	30	60	30	30	75	40	40	90	50	50	100	50	50	110	55	55	-	-	-	-	-	-	
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0	20	20																																						
15	20	20																																						
30	20	20																																						
45	30	30																																						
60	30	30																																						
75	40	40																																						
90	50	50																																						
100	50	50																																						
110	55	55																																						
-	-	-																																						
-	-	-																																						

**COSEL**

Model	PBA1500F-15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V100A

## 1. Graph




Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	100	100
-20	60	60
-10	40	40
0	30	30
10	20	20
20	20	20
25	20	20
30	20	20
40	20	20
50	20	20
60	15	15

**COSEL**

Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-30	15.167	15.167	15.167
-20	15.164	15.163	15.163
-10	15.161	15.160	15.159
0	15.139	15.133	15.131
10	15.125	15.123	15.122
20	15.113	15.112	15.110
25	15.109	15.104	15.101
30	15.099	15.098	15.098
40	15.078	15.074	15.070
50	15.052	15.044	15.041
60	15.032	15.023	15.021



Model	PBA1500F-15	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+15V100A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 100A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	85	0	15.164		
Minimum Voltage	50	264	100	15.016	±74	±0.5

**COSEL**

Model	PBA1500F-15	Temperature Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+15V100A																							
1.Graph		2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.124</td></tr> <tr><td>0.5</td><td>15.067</td></tr> <tr><td>1.0</td><td>15.062</td></tr> <tr><td>2.0</td><td>15.067</td></tr> <tr><td>3.0</td><td>15.062</td></tr> <tr><td>4.0</td><td>15.062</td></tr> <tr><td>5.0</td><td>15.066</td></tr> <tr><td>6.0</td><td>15.066</td></tr> <tr><td>7.0</td><td>15.066</td></tr> <tr><td>8.0</td><td>15.067</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.124	0.5	15.067	1.0	15.062	2.0	15.067	3.0	15.062	4.0	15.062	5.0	15.066	6.0	15.066	7.0	15.066	8.0	15.067
Time since start [H]	Output Voltage [V]																							
0.0	15.124																							
0.5	15.067																							
1.0	15.062																							
2.0	15.067																							
3.0	15.062																							
4.0	15.062																							
5.0	15.066																							
6.0	15.066																							
7.0	15.066																							
8.0	15.067																							

**COSEL**


Model PBA1500F-15

Item Rise and Fall Time

Object +15V100A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[mS]
100 V		382.5	4.0	386.5	22.3	8.8	
200 V		249.0	4.0	253.0	30.0	8.8	



**COSEL**
**Model PBA1500F-15**
**Item Hold-Up Time**
**Object +15V100A**
**1. Graph**

- - - □ - - Load 50%  
 — △ — Load 100%



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**Temperature 25°C  
Testing Circuitry Figure A**
**2. Values**

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
85	45	16
100	49	20
120	52	22
200	58	27
230	59	28
264	60	29
-	-	-
-	-	-
-	-	-

**COSEL**


Model	PBA1500F-15	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+15V100A																																																					
1.Graph																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>15</td><td>105</td><td>188</td><td>196</td></tr> <tr> <td>30</td><td>30</td><td>78</td><td>96</td></tr> <tr> <td>45</td><td>30</td><td>40</td><td>53</td></tr> <tr> <td>60</td><td>30</td><td>38</td><td>40</td></tr> <tr> <td>75</td><td>30</td><td>34</td><td>39</td></tr> <tr> <td>90</td><td>24</td><td>32</td><td>32</td></tr> <tr> <td>100</td><td>20</td><td>28</td><td>29</td></tr> <tr> <td>110</td><td>17</td><td>23</td><td>25</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	15	105	188	196	30	30	78	96	45	30	40	53	60	30	38	40	75	30	34	39	90	24	32	32	100	20	28	29	110	17	23	25	--	-	-	-	--	-	-	-
Load Current [A]	Time [mS]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
15	105	188	196																																																			
30	30	78	96																																																			
45	30	40	53																																																			
60	30	38	40																																																			
75	30	34	39																																																			
90	24	32	32																																																			
100	20	28	29																																																			
110	17	23	25																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model	PBA1500F-15
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V100A

**1. Graph**

---□--- Load 50%  
—△— Load 100%



Note: Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure A****2. Values**

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	71	71
-20	71	71
-10	71	71
0	71	71
10	71	71
20	71	71
25	71	71
30	71	71
40	71	71
50	71	71
60	71	71

**COSEL**

Model	PBA1500F-15																																										
Item	Overcurrent Protection	Temperature      25°C Testing Circuitry      Figure A																																									
Object	+15V100A																																										
1. Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p>																																											
2. Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>126.42</td><td>127.05</td></tr> <tr><td>14.3</td><td>127.03</td><td>127.18</td></tr> <tr><td>13.5</td><td>127.61</td><td>126.89</td></tr> <tr><td>12.0</td><td>127.54</td><td>127.06</td></tr> <tr><td>10.5</td><td>0.00</td><td>0.00</td></tr> <tr><td>9.0</td><td>0.00</td><td>0.00</td></tr> <tr><td>7.5</td><td>0.00</td><td>0.00</td></tr> <tr><td>6.0</td><td>0.00</td><td>0.00</td></tr> <tr><td>4.5</td><td>0.00</td><td>0.00</td></tr> <tr><td>3.0</td><td>0.00</td><td>0.00</td></tr> <tr><td>1.5</td><td>0.00</td><td>0.00</td></tr> <tr><td>0.0</td><td>0.00</td><td>0.00</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	15.0	126.42	127.05	14.3	127.03	127.18	13.5	127.61	126.89	12.0	127.54	127.06	10.5	0.00	0.00	9.0	0.00	0.00	7.5	0.00	0.00	6.0	0.00	0.00	4.5	0.00	0.00	3.0	0.00	0.00	1.5	0.00	0.00	0.0	0.00	0.00
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 200[V]																																									
15.0	126.42	127.05																																									
14.3	127.03	127.18																																									
13.5	127.61	126.89																																									
12.0	127.54	127.06																																									
10.5	0.00	0.00																																									
9.0	0.00	0.00																																									
7.5	0.00	0.00																																									
6.0	0.00	0.00																																									
4.5	0.00	0.00																																									
3.0	0.00	0.00																																									
1.5	0.00	0.00																																									
0.0	0.00	0.00																																									

**COSEL**

Model	PBA1500F-15																																								
Item	Overvoltage Protection																																								
Object	+15V100A																																								
1. Graph																																									
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V (solid line)</li> <li>Input Volt. 200V (dashed line)</li> </ul>																																									
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									
Testing Circuitry Figure A																																									
2. Values																																									
<table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Operating Point [V]</th> <th>Input Volt.</th> </tr> <tr> <th></th> <th>100[V]</th> <th>200[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>19.43</td><td>19.43</td></tr> <tr><td>-20</td><td>19.43</td><td>19.43</td></tr> <tr><td>-10</td><td>19.43</td><td>19.43</td></tr> <tr><td>0</td><td>19.43</td><td>19.43</td></tr> <tr><td>10</td><td>19.43</td><td>19.43</td></tr> <tr><td>20</td><td>19.43</td><td>19.43</td></tr> <tr><td>25</td><td>19.43</td><td>19.43</td></tr> <tr><td>30</td><td>19.43</td><td>19.43</td></tr> <tr><td>40</td><td>19.43</td><td>19.43</td></tr> <tr><td>50</td><td>19.43</td><td>19.43</td></tr> <tr><td>60</td><td>19.43</td><td>19.43</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]	Input Volt.		100[V]	200[V]	-30	19.43	19.43	-20	19.43	19.43	-10	19.43	19.43	0	19.43	19.43	10	19.43	19.43	20	19.43	19.43	25	19.43	19.43	30	19.43	19.43	40	19.43	19.43	50	19.43	19.43	60	19.43	19.43
Ambient Temperature [°C]	Operating Point [V]	Input Volt.																																							
	100[V]	200[V]																																							
-30	19.43	19.43																																							
-20	19.43	19.43																																							
-10	19.43	19.43																																							
0	19.43	19.43																																							
10	19.43	19.43																																							
20	19.43	19.43																																							
25	19.43	19.43																																							
30	19.43	19.43																																							
40	19.43	19.43																																							
50	19.43	19.43																																							
60	19.43	19.43																																							

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )