



TEST DATA OF PBA1500T-12

Regulated DC Power Supply
Mar. 27. 2007

Approved by : *Yoshiaki Shimizu*
Yoshiaki Shimizu Design Manager

Prepared by : *yousuke murata*
Yousuke Murata Design Engineer

COSEL CO.,LTD.

CONTENTS


1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model		PBA1500T-12		Input AC 3-phase																																																				
Item		Input Current (by Load Current)		Temperature 25°C																																																				
Object				Testing Circuitry Figure A																																																				
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>170 V</div></div><div><div>---□---</div><div>Input Volt.</div><div>200 V</div></div><div><div>---○---</div><div>Input Volt.</div><div>264 V</div></div></div> <div><p>Note: Slanted line shows the range of the rated load current.</p></div>		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>0.240</td><td>0.267</td><td>0.333</td></tr><tr><td>20.0</td><td>1.127</td><td>0.980</td><td>0.813</td></tr><tr><td>40.0</td><td>2.097</td><td>1.793</td><td>1.393</td></tr><tr><td>60.0</td><td>3.103</td><td>2.635</td><td>2.010</td></tr><tr><td>80.0</td><td>4.093</td><td>3.470</td><td>2.639</td></tr><tr><td>100.0</td><td>5.109</td><td>4.325</td><td>3.277</td></tr><tr><td>120.0</td><td>6.156</td><td>5.201</td><td>3.931</td></tr><tr><td>125.0</td><td>6.418</td><td>5.420</td><td>4.095</td></tr><tr><td>137.5</td><td>7.059</td><td>5.964</td><td>4.503</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>				Load Current [A]	Input Current [A]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	0.240	0.267	0.333	20.0	1.127	0.980	0.813	40.0	2.097	1.793	1.393	60.0	3.103	2.635	2.010	80.0	4.093	3.470	2.639	100.0	5.109	4.325	3.277	120.0	6.156	5.201	3.931	125.0	6.418	5.420	4.095	137.5	7.059	5.964	4.503	--	--	--	--	--	--	--	--
Load Current [A]	Input Current [A]																																																							
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																					
0	0.240	0.267	0.333																																																					
20.0	1.127	0.980	0.813																																																					
40.0	2.097	1.793	1.393																																																					
60.0	3.103	2.635	2.010																																																					
80.0	4.093	3.470	2.639																																																					
100.0	5.109	4.325	3.277																																																					
120.0	6.156	5.201	3.931																																																					
125.0	6.418	5.420	4.095																																																					
137.5	7.059	5.964	4.503																																																					
--	--	--	--																																																					
--	--	--	--																																																					



Model		PBA1500T-12	Input	AC 3-phase																																																			
Item		Input Power (by Load Current)	Temperature	25°C																																																			
Object			Testing Circuitry	Figure A																																																			
1.Graph																																																							
		—△— Input Volt.	170 V																																																				
		---□--- Input Volt.	200 V																																																				
		-·-○-·- Input Volt.	264 V																																																				
																																																							
Note: Slanted line shows the range of the rated load current.																																																							
2.Values																																																							
<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Input Power [W]</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>20</td><td>19</td><td>16</td></tr><tr><td>20.0</td><td>308</td><td>307</td><td>307</td></tr><tr><td>40.0</td><td>585</td><td>584</td><td>580</td></tr><tr><td>60.0</td><td>870</td><td>866</td><td>857</td></tr><tr><td>80.0</td><td>1150</td><td>1144</td><td>1137</td></tr><tr><td>100.0</td><td>1435</td><td>1427</td><td>1418</td></tr><tr><td>120.0</td><td>1730</td><td>1717</td><td>1706</td></tr><tr><td>125.0</td><td>1804</td><td>1790</td><td>1777</td></tr><tr><td>137.5</td><td>1984</td><td>1971</td><td>1955</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></table>					Load Current [A]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	20	19	16	20.0	308	307	307	40.0	585	584	580	60.0	870	866	857	80.0	1150	1144	1137	100.0	1435	1427	1418	120.0	1730	1717	1706	125.0	1804	1790	1777	137.5	1984	1971	1955	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
0	20	19	16																																																				
20.0	308	307	307																																																				
40.0	585	584	580																																																				
60.0	870	866	857																																																				
80.0	1150	1144	1137																																																				
100.0	1435	1427	1418																																																				
120.0	1730	1717	1706																																																				
125.0	1804	1790	1777																																																				
137.5	1984	1971	1955																																																				
—	—	—	—																																																				
—	—	—	—																																																				

- 2 -

BC-10078

COSEL

Model		PBA1500T-12		Input		AC 3-phase																															
Item		Efficiency (by Input Voltage)		Temperature		25°C																															
Object				Testing Circuitry		Figure A																															
1.Graph				2.Values																																	
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>---△---</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Load 50% Efficiency [%]</th><th>Load 100% Efficiency [%]</th></tr></thead><tbody><tr><td>150</td><td>84.4</td><td>84.2</td></tr><tr><td>160</td><td>84.5</td><td>84.4</td></tr><tr><td>170</td><td>84.5</td><td>84.7</td></tr><tr><td>180</td><td>84.6</td><td>84.9</td></tr><tr><td>200</td><td>84.9</td><td>85.3</td></tr><tr><td>220</td><td>85.3</td><td>85.7</td></tr><tr><td>240</td><td>85.4</td><td>85.8</td></tr><tr><td>264</td><td>85.6</td><td>85.9</td></tr><tr><td>--</td><td>--</td><td>--</td></tr></tbody></table>				Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	150	84.4	84.2	160	84.5	84.4	170	84.5	84.7	180	84.6	84.9	200	84.9	85.3	220	85.3	85.7	240	85.4	85.8	264	85.6	85.9	--	--	--				
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																																			
150	84.4	84.2																																			
160	84.5	84.4																																			
170	84.5	84.7																																			
180	84.6	84.9																																			
200	84.9	85.3																																			
220	85.3	85.7																																			
240	85.4	85.8																																			
264	85.6	85.9																																			
--	--	--																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					

COSEL

Model		PBA1500T-12	Input AC 3-phase																																																				
Item		Efficiency (by Load Current)	Temperature 25°C																																																				
Object			Testing Circuitry Figure A																																																				
1. Graph		2. Values																																																					
<div><div><div>—△—</div><div>---□---</div><div>-·-○-·-</div></div><div><div>Input Volt.</div><div>Input Volt.</div><div>Input Volt.</div></div><div><div>170 V</div><div>200 V</div><div>264 V</div></div></div> <div><p>Efficiency [%]</p><p>Load Current [A]</p></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>--</td><td>--</td><td>--</td></tr><tr><td>20.0</td><td>79.0</td><td>79.3</td><td>79.2</td></tr><tr><td>40.0</td><td>83.4</td><td>83.6</td><td>84.1</td></tr><tr><td>60.0</td><td>84.3</td><td>84.7</td><td>85.6</td></tr><tr><td>80.0</td><td>85.0</td><td>85.4</td><td>86.0</td></tr><tr><td>100.0</td><td>85.1</td><td>85.6</td><td>86.1</td></tr><tr><td>120.0</td><td>84.8</td><td>85.5</td><td>86.0</td></tr><tr><td>125.0</td><td>84.7</td><td>85.4</td><td>86.0</td></tr><tr><td>137.5</td><td>84.7</td><td>85.3</td><td>85.9</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>			Load Current [A]	Efficiency [%]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	--	--	--	20.0	79.0	79.3	79.2	40.0	83.4	83.6	84.1	60.0	84.3	84.7	85.6	80.0	85.0	85.4	86.0	100.0	85.1	85.6	86.1	120.0	84.8	85.5	86.0	125.0	84.7	85.4	86.0	137.5	84.7	85.3	85.9	--	--	--	--	--	--	--	--
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
0	--	--	--																																																				
20.0	79.0	79.3	79.2																																																				
40.0	83.4	83.6	84.1																																																				
60.0	84.3	84.7	85.6																																																				
80.0	85.0	85.4	86.0																																																				
100.0	85.1	85.6	86.1																																																				
120.0	84.8	85.5	86.0																																																				
125.0	84.7	85.4	86.0																																																				
137.5	84.7	85.3	85.9																																																				
--	--	--	--																																																				
--	--	--	--																																																				
Note: Slanted line shows the range of the rated load current.																																																							

COSEL


Model	PBA1500T-12	Input	AC 3-phase																																
Item	Power Factor (by Input Voltage)	Temperature	25°C																																
Object		Testing Circuitry	Figure A																																
1.Graph		2.Values																																	
<div><div>---□--- Load 50%</div><div>—△— Load 100%</div></div> <p>Power Factor</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Power Factor</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>150</td><td>0.957</td><td>0.959</td></tr><tr><td>160</td><td>0.955</td><td>0.957</td></tr><tr><td>170</td><td>0.954</td><td>0.957</td></tr><tr><td>180</td><td>0.953</td><td>0.957</td></tr><tr><td>200</td><td>0.950</td><td>0.956</td></tr><tr><td>220</td><td>0.947</td><td>0.955</td></tr><tr><td>240</td><td>0.944</td><td>0.954</td></tr><tr><td>264</td><td>0.937</td><td>0.952</td></tr><tr><td>--</td><td>--</td><td>--</td></tr></table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	150	0.957	0.959	160	0.955	0.957	170	0.954	0.957	180	0.953	0.957	200	0.950	0.956	220	0.947	0.955	240	0.944	0.954	264	0.937	0.952	--	--	--
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
150	0.957	0.959																																	
160	0.955	0.957																																	
170	0.954	0.957																																	
180	0.953	0.957																																	
200	0.950	0.956																																	
220	0.947	0.955																																	
240	0.944	0.954																																	
264	0.937	0.952																																	
--	--	--																																	

COSEL


Model	PBA1500T-12	Input	AC 3-phase																																																			
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div>—△— Input Volt. 170 V</div><div>---□--- Input Volt. 200 V</div><div>-·-○-·- Input Volt. 264 V</div></div> <p>Power Factor</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Power Factor</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>0.286</td><td>0.204</td><td>0.103</td></tr><tr><td>20.0</td><td>0.930</td><td>0.906</td><td>0.829</td></tr><tr><td>40.0</td><td>0.948</td><td>0.940</td><td>0.912</td></tr><tr><td>60.0</td><td>0.953</td><td>0.949</td><td>0.934</td></tr><tr><td>80.0</td><td>0.955</td><td>0.953</td><td>0.943</td></tr><tr><td>100.0</td><td>0.955</td><td>0.954</td><td>0.948</td></tr><tr><td>120.0</td><td>0.956</td><td>0.954</td><td>0.950</td></tr><tr><td>125.0</td><td>0.957</td><td>0.954</td><td>0.950</td></tr><tr><td>137.5</td><td>0.957</td><td>0.955</td><td>0.951</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>		Load Current [A]	Power Factor			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	0.286	0.204	0.103	20.0	0.930	0.906	0.829	40.0	0.948	0.940	0.912	60.0	0.953	0.949	0.934	80.0	0.955	0.953	0.943	100.0	0.955	0.954	0.948	120.0	0.956	0.954	0.950	125.0	0.957	0.954	0.950	137.5	0.957	0.955	0.951	--	--	--	--	--	--	--	--
Load Current [A]	Power Factor																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	0.286	0.204	0.103																																																			
20.0	0.930	0.906	0.829																																																			
40.0	0.948	0.940	0.912																																																			
60.0	0.953	0.949	0.934																																																			
80.0	0.955	0.953	0.943																																																			
100.0	0.955	0.954	0.948																																																			
120.0	0.956	0.954	0.950																																																			
125.0	0.957	0.954	0.950																																																			
137.5	0.957	0.955	0.951																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PBA1500T-12	Input	AC 3-phase
Item	Inrush Current	Temperature	25°C
Object		Testing Circuitry	Figure A



Input Voltage	200 V
Frequency	60 Hz
Load	100 %
Inrush Current	
①	18.3 A
②	20.4 A (0.2ms or less)*1
③	13.6 A



*1 The specification of the inrush current (primary surge) means that the surge current to a built-in noise filter (0.2ms or less : waveform ②) is excluded

COSEL

		Input AC 3-phase Temperature 25°C Testing Circuitry Figure B
Model	PBA1500T-12	
Item	Leakage Current	
Object		

1.Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A)DEN-AN	—	—	—
(B)IEC60950	—	—	—

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 240 [V]	Input Volt. 264 [V]
(B)IEC60950	0.77	1.12	1.25

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PBA1500T-12	Input	AC 3-phase																														
Item	Line Regulation	Temperature	25°C																														
Object	+12V125A	Testing Circuitry	Figure A																														
1.Graph		2.Values																															
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V] Load 50%</th><th>Output Voltage [V] Load 100%</th></tr></thead><tbody><tr><td>150</td><td>12.277</td><td>12.271</td></tr><tr><td>160</td><td>12.275</td><td>12.271</td></tr><tr><td>170</td><td>12.275</td><td>12.271</td></tr><tr><td>180</td><td>12.274</td><td>12.270</td></tr><tr><td>200</td><td>12.274</td><td>12.270</td></tr><tr><td>220</td><td>12.274</td><td>12.268</td></tr><tr><td>240</td><td>12.274</td><td>12.267</td></tr><tr><td>264</td><td>12.273</td><td>12.266</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></tbody></table>		Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%	150	12.277	12.271	160	12.275	12.271	170	12.275	12.271	180	12.274	12.270	200	12.274	12.270	220	12.274	12.268	240	12.274	12.267	264	12.273	12.266	—	—	—		
Input Voltage [V]	Output Voltage [V] Load 50%	Output Voltage [V] Load 100%																															
150	12.277	12.271																															
160	12.275	12.271																															
170	12.275	12.271																															
180	12.274	12.270																															
200	12.274	12.270																															
220	12.274	12.268																															
240	12.274	12.267																															
264	12.273	12.266																															
—	—	—																															
Note: Slanted line shows the range of the rated input voltage.																																	

COSEL

Model	PBA1500T-12	Input	AC 3-phase																																																			
Item	Load Regulation	Temperature	25°C																																																			
Object	+12V125A	Testing Circuitry	Figure A																																																			
1.Graph		2.Values																																																				
<div><div><div>—△—</div><div>Input Volt.</div><div>170 V</div></div><div><div>---□---</div><div>Input Volt.</div><div>200 V</div></div><div><div>---○---</div><div>Input Volt.</div><div>264 V</div></div></div> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 170[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 264[V]</th></tr><tr><td>0</td><td>12.265</td><td>12.266</td><td>12.267</td></tr><tr><td>20.0</td><td>12.265</td><td>12.266</td><td>12.267</td></tr><tr><td>40.0</td><td>12.264</td><td>12.265</td><td>12.266</td></tr><tr><td>60.0</td><td>12.264</td><td>12.265</td><td>12.266</td></tr><tr><td>80.0</td><td>12.263</td><td>12.264</td><td>12.265</td></tr><tr><td>100.0</td><td>12.263</td><td>12.264</td><td>12.265</td></tr><tr><td>120.0</td><td>12.262</td><td>12.263</td><td>12.264</td></tr><tr><td>125.0</td><td>12.262</td><td>12.263</td><td>12.264</td></tr><tr><td>137.5</td><td>12.262</td><td>12.263</td><td>12.264</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr><tr><td>--</td><td>--</td><td>--</td><td>--</td></tr></table>		Load Current [A]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	12.265	12.266	12.267	20.0	12.265	12.266	12.267	40.0	12.264	12.265	12.266	60.0	12.264	12.265	12.266	80.0	12.263	12.264	12.265	100.0	12.263	12.264	12.265	120.0	12.262	12.263	12.264	125.0	12.262	12.263	12.264	137.5	12.262	12.263	12.264	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	12.265	12.266	12.267																																																			
20.0	12.265	12.266	12.267																																																			
40.0	12.264	12.265	12.266																																																			
60.0	12.264	12.265	12.266																																																			
80.0	12.263	12.264	12.265																																																			
100.0	12.263	12.264	12.265																																																			
120.0	12.262	12.263	12.264																																																			
125.0	12.262	12.263	12.264																																																			
137.5	12.262	12.263	12.264																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note: Slanted line shows the range of the rated load current.																																																						

- 10 -

BC-10078

COSEL


Model	PBA1500T-12	Input	AC 3-phase
Item	Dynamic Load Response	Temperature	25°C
Object	+12V125A	Testing Circuitry	Figure A

Input Volt. 200 V
Cycle 1000 ms




Min.Load (0A) \longleftrightarrow
Load 100% (125A)

100mV/div




10ms/div




10ms/div

Min.Load (0A) \longleftrightarrow
Load 50% (62.5A)

100mV/div




10ms/div




10ms/div

COSEL




COSEL



COSEL

Model	PBA1500T-12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V125A

1. Graph



Measured by 20MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 240 [V]
-30	85	85
-20	50	50
-10	30	30
0	25	25
10	20	20
25	20	20
30	20	20
40	15	15
50	15	15
60	15	15
—	—	—

Input AC 3-phase
Testing Circuitry Figure A



Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
-30	12.295	12.295	12.301
-20	12.305	12.305	12.304
-10	12.303	12.302	12.301
0	12.299	12.298	12.297
10	12.295	12.294	12.293
25	12.286	12.285	12.284
30	12.284	12.283	12.281
40	12.274	12.273	12.271
50	12.256	12.254	12.255
60	12.238	12.236	12.231
—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

		Input AC 3-phase Testing Circuitry Figure A
Model	PBA1500T-12	
Item	Output Voltage Accuracy	
Object	+12V125A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 – 50°C

Input Voltage : 170 – 264V

Load Current : 0 – 125A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	264	0	12.307	±35	±0.3
Minimum Voltage	50	200	125	12.238		


COSEL

Model	PBA1500T-12	Input	AC 3-phase																						
Item	Time Lapse Drift	Temperature	25°C																						
Object	+12V125A	Testing Circuitry	Figure A																						
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 200V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.281</td></tr><tr><td>0.5</td><td>12.260</td></tr><tr><td>1.0</td><td>12.260</td></tr><tr><td>2.0</td><td>12.261</td></tr><tr><td>3.0</td><td>12.261</td></tr><tr><td>4.0</td><td>12.261</td></tr><tr><td>5.0</td><td>12.262</td></tr><tr><td>6.0</td><td>12.262</td></tr><tr><td>7.0</td><td>12.262</td></tr><tr><td>8.0</td><td>12.262</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.281	0.5	12.260	1.0	12.260	2.0	12.261	3.0	12.261	4.0	12.261	5.0	12.262	6.0	12.262	7.0	12.262	8.0	12.262
Time since start [H]	Output Voltage [V]																								
0.0	12.281																								
0.5	12.260																								
1.0	12.260																								
2.0	12.261																								
3.0	12.261																								
4.0	12.261																								
5.0	12.262																								
6.0	12.262																								
7.0	12.262																								
8.0	12.262																								

COSEL


Model	PBA1500T-12	Input	AC 3-phase
Item	Rise and Fall Time	Temperature	25°C
Object	+12V125A	Testing Circuitry	Figure A

1. Graph



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		253.0	2.5	255.5	59.0	11.0
100 %		251.5	3.0	254.5	27.8	7.3



COSEL

Model	PBA1500T-12	Input	AC 3-phase																																
Item	Hold-Up Time	Temperature	25°C																																
Object	+12V125A	Testing Circuitry	Figure A																																
1.Graph		2.Values																																	
<div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div></div> <div>Hold-Up Time [ms]</div> <div>Input Voltage [V]</div>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Hold-Up Time [ms]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>150</td><td>51</td><td>23</td></tr><tr><td>160</td><td>52</td><td>23</td></tr><tr><td>170</td><td>52</td><td>23</td></tr><tr><td>180</td><td>52</td><td>24</td></tr><tr><td>200</td><td>53</td><td>24</td></tr><tr><td>220</td><td>53</td><td>25</td></tr><tr><td>240</td><td>54</td><td>25</td></tr><tr><td>264</td><td>54</td><td>25</td></tr><tr><td>--</td><td>--</td><td>--</td></tr></table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	150	51	23	160	52	23	170	52	23	180	52	24	200	53	24	220	53	25	240	54	25	264	54	25	--	--	--
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
150	51	23																																	
160	52	23																																	
170	52	23																																	
180	52	24																																	
200	53	24																																	
220	53	25																																	
240	54	25																																	
264	54	25																																	
--	--	--																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model PBA1500T-12

Item Instantaneous Interruption Compensation

Object +12V125A


Input AC 3-phase

Temperature 25°C

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 170 V
 ---□--- Input Volt. 200 V
 -·-○-·- Input Volt. 264 V




Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Time [ms]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
0	--	--	--
20.0	148	169	172
40.0	56	85	86
60.0	35	45	56
80.0	34	35	41
100.0	30	31	32
120.0	24	25	26
125.0	24	24	25
137.5	20	21	22
--	--	--	--
--	--	--	--

Input AC 3-phase
Testing Circuitry Figure A

2.Values



- 21 -

BC-10078

Input AC 3-phase
Testing Circuitry Figure A



Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]
-30	15.74	15.74	15.74
-20	15.74	15.74	15.74
-10	15.74	15.74	15.74
0	15.74	15.74	15.74
10	15.74	15.74	15.74
25	15.74	15.74	15.74
30	15.74	15.74	15.74
40	15.74	15.74	15.74
50	15.74	15.74	15.74
60	15.73	15.73	15.73
—	—	—	—

- 23 -




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)