



# TEST DATA OF PBA150F-48

Regulated DC Power Supply  
Apr.7. 2004

Approved by : Kuniaki Nagahara  
Kuniaki Nagahara Design Manager

Prepared by : Tetsuo Koide  
Tetsuo Koide Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Overvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24

(Final Page 24)

**COSEL**

Model	PBA150F-48		
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A
Object			
1.Graph	<p>—△— Input Volt. 100V        - -□--- Input Volt. 200V        - -○--- Input Volt. 230V</p> 		
2.Values	Load Current [A]	Input Current [A]	
	Input Volt.	100[V]	200[V]
0.00	0.102	0.070	0.068
0.60	0.400	0.262	0.256
1.20	0.705	0.396	0.374
1.80	1.014	0.542	0.492
2.40	1.330	0.690	0.620
3.00	1.654	0.842	0.750
3.30	1.818	0.920	0.814
3.63	1.998	1.006	0.888
-	-	-	-
-	-	-	-
-	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**


Model	PBA150F-48																																																					
Item	Input Power (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	—	—	—																																																			
1.Graph	—▲— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V	2.Values																																																				
<p>The graph plots Input Power [W] on the Y-axis (0 to 500) against Load Current [A] on the X-axis (0.0 to 4.0). Three data series are shown: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show a non-linear increase in power with load current. A slanted line is drawn through the 100V curve, indicating the rated load current range between approximately 2.4A and 3.6A.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>6.0</td><td>6.0</td><td>6.0</td></tr> <tr><td>0.60</td><td>38.1</td><td>38.0</td><td>39.0</td></tr> <tr><td>1.20</td><td>69.0</td><td>68.0</td><td>68.0</td></tr> <tr><td>1.80</td><td>100.2</td><td>98.0</td><td>98.0</td></tr> <tr><td>2.40</td><td>132.0</td><td>129.0</td><td>129.0</td></tr> <tr><td>3.00</td><td>164.4</td><td>160.0</td><td>160.0</td></tr> <tr><td>3.30</td><td>180.8</td><td>176.0</td><td>175.0</td></tr> <tr><td>3.63</td><td>198.9</td><td>193.0</td><td>192.0</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	6.0	6.0	6.0	0.60	38.1	38.0	39.0	1.20	69.0	68.0	68.0	1.80	100.2	98.0	98.0	2.40	132.0	129.0	129.0	3.00	164.4	160.0	160.0	3.30	180.8	176.0	175.0	3.63	198.9	193.0	192.0	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	6.0	6.0	6.0																																																			
0.60	38.1	38.0	39.0																																																			
1.20	69.0	68.0	68.0																																																			
1.80	100.2	98.0	98.0																																																			
2.40	132.0	129.0	129.0																																																			
3.00	164.4	160.0	160.0																																																			
3.30	180.8	176.0	175.0																																																			
3.63	198.9	193.0	192.0																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	PBA150F-48	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—																																		
1. Graph																																			
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Load 50% (Dashed line with squares)</li> <li>Load 100% (Solid line with triangles)</li> </ul>																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>83.4</td> <td>84.7</td> </tr> <tr> <td>85</td> <td>84.4</td> <td>85.9</td> </tr> <tr> <td>100</td> <td>85.1</td> <td>87.2</td> </tr> <tr> <td>120</td> <td>85.6</td> <td>88.2</td> </tr> <tr> <td>200</td> <td>86.2</td> <td>89.3</td> </tr> <tr> <td>230</td> <td>86.1</td> <td>89.8</td> </tr> <tr> <td>264</td> <td>86.2</td> <td>89.8</td> </tr> <tr> <td>280</td> <td>86.1</td> <td>89.3</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	83.4	84.7	85	84.4	85.9	100	85.1	87.2	120	85.6	88.2	200	86.2	89.3	230	86.1	89.8	264	86.2	89.8	280	86.1	89.3	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	83.4	84.7																																	
85	84.4	85.9																																	
100	85.1	87.2																																	
120	85.6	88.2																																	
200	86.2	89.3																																	
230	86.1	89.8																																	
264	86.2	89.8																																	
280	86.1	89.3																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


**COSEL**

Model	PBA150F-48	Temperature	25°C																																																				
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																				
Object	_____																																																						
1.Graph	<p>—▲— Input Volt. 100V        - - -□- Input Volt. 200V        - - ○ - Input Volt. 230V</p>  <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>0.60</td><td>74.1</td><td>74.1</td><td>72.1</td></tr> <tr><td>1.20</td><td>82.3</td><td>83.7</td><td>83.4</td></tr> <tr><td>1.80</td><td>85.4</td><td>87.3</td><td>87.2</td></tr> <tr><td>2.40</td><td>86.5</td><td>88.4</td><td>88.5</td></tr> <tr><td>3.00</td><td>86.9</td><td>89.3</td><td>89.2</td></tr> <tr><td>3.30</td><td>86.9</td><td>89.3</td><td>89.7</td></tr> <tr><td>3.63</td><td>86.9</td><td>89.6</td><td>90.1</td></tr> </tbody> </table>				Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	0.60	74.1	74.1	72.1	1.20	82.3	83.7	83.4	1.80	85.4	87.3	87.2	2.40	86.5	88.4	88.5	3.00	86.9	89.3	89.2	3.30	86.9	89.3	89.7	3.63	86.9	89.6	90.1																			
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																				
0.60	74.1	74.1	72.1																																																				
1.20	82.3	83.7	83.4																																																				
1.80	85.4	87.3	87.2																																																				
2.40	86.5	88.4	88.5																																																				
3.00	86.9	89.3	89.2																																																				
3.30	86.9	89.3	89.7																																																				
3.63	86.9	89.6	90.1																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.60</td><td>74.1</td><td>74.1</td><td>72.1</td></tr> <tr><td>1.20</td><td>82.3</td><td>83.7</td><td>83.4</td></tr> <tr><td>1.80</td><td>85.4</td><td>87.3</td><td>87.2</td></tr> <tr><td>2.40</td><td>86.5</td><td>88.4</td><td>88.5</td></tr> <tr><td>3.00</td><td>86.9</td><td>89.3</td><td>89.2</td></tr> <tr><td>3.30</td><td>86.9</td><td>89.3</td><td>89.7</td></tr> <tr><td>3.63</td><td>86.9</td><td>89.6</td><td>90.1</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.60	74.1	74.1	72.1	1.20	82.3	83.7	83.4	1.80	85.4	87.3	87.2	2.40	86.5	88.4	88.5	3.00	86.9	89.3	89.2	3.30	86.9	89.3	89.7	3.63	86.9	89.6	90.1	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	-	-	-																																																				
0.60	74.1	74.1	72.1																																																				
1.20	82.3	83.7	83.4																																																				
1.80	85.4	87.3	87.2																																																				
2.40	86.5	88.4	88.5																																																				
3.00	86.9	89.3	89.2																																																				
3.30	86.9	89.3	89.7																																																				
3.63	86.9	89.6	90.1																																																				
-	-	-	-																																																				
-	-	-	-																																																				
-	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

**COSEL**

Model	PBA150F-48																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Legend: ---□--- Load 50% —△— Load 100%</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% Power Factor</th> <th>Load 100% Power Factor</th> </tr> </thead> <tbody> <tr><td>50</td><td>0.98</td><td>0.98</td></tr> <tr><td>100</td><td>0.97</td><td>0.97</td></tr> <tr><td>200</td><td>0.92</td><td>0.94</td></tr> <tr><td>250</td><td>0.75</td><td>0.88</td></tr> <tr><td>270</td><td>0.68</td><td>0.72</td></tr> <tr><td>300</td><td>0.62</td><td>0.82</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor	50	0.98	0.98	100	0.97	0.97	200	0.92	0.94	250	0.75	0.88	270	0.68	0.72	300	0.62	0.82											
Input Voltage [V]	Load 50% Power Factor	Load 100% Power Factor																																
50	0.98	0.98																																
100	0.97	0.97																																
200	0.92	0.94																																
250	0.75	0.88																																
270	0.68	0.72																																
300	0.62	0.82																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.998</td><td>0.999</td></tr> <tr><td>85</td><td>0.994</td><td>0.999</td></tr> <tr><td>100</td><td>0.991</td><td>0.997</td></tr> <tr><td>120</td><td>0.979</td><td>0.993</td></tr> <tr><td>200</td><td>0.901</td><td>0.962</td></tr> <tr><td>230</td><td>0.858</td><td>0.936</td></tr> <tr><td>264</td><td>0.746</td><td>0.911</td></tr> <tr><td>280</td><td>0.659</td><td>0.846</td></tr> <tr><td>—</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.998	0.999	85	0.994	0.999	100	0.991	0.997	120	0.979	0.993	200	0.901	0.962	230	0.858	0.936	264	0.746	0.911	280	0.659	0.846	—	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.998	0.999																																
85	0.994	0.999																																
100	0.991	0.997																																
120	0.979	0.993																																
200	0.901	0.962																																
230	0.858	0.936																																
264	0.746	0.911																																
280	0.659	0.846																																
—	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL




Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.588	0.429	0.375
0.60	0.955	0.731	0.661
1.20	0.982	0.861	0.791
1.80	0.990	0.907	0.867
2.40	0.995	0.935	0.908
3.00	0.997	0.952	0.930
3.30	0.997	0.957	0.936
3.63	0.998	0.960	0.941
-	-	-	-
-	-	-	-
-	-	-	-

COSEL





Model	PBA150F-48	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	_____		

### 1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.19	0.37	0.43	Operation
	One of phase	0.27	0.54	0.62	stand by
IEC60950	Both phases	0.19	0.38	0.48	Operation
	One of phase	0.27	0.58	0.71	stand by

The value for "One phase" is the reference value only.

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	PBA150F-48																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+48V3.3A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Load 50% (Dashed line with open squares)</li> <li>Load 100% (Solid line with solid squares)</li> </ul>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>48.098</td> <td>48.100</td> </tr> <tr> <td>85</td> <td>48.099</td> <td>48.101</td> </tr> <tr> <td>100</td> <td>48.099</td> <td>48.100</td> </tr> <tr> <td>120</td> <td>48.099</td> <td>48.100</td> </tr> <tr> <td>200</td> <td>48.101</td> <td>48.100</td> </tr> <tr> <td>230</td> <td>48.100</td> <td>48.100</td> </tr> <tr> <td>264</td> <td>48.101</td> <td>48.099</td> </tr> <tr> <td>280</td> <td>48.101</td> <td>48.099</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	48.098	48.100	85	48.099	48.101	100	48.099	48.100	120	48.099	48.100	200	48.101	48.100	230	48.100	48.100	264	48.101	48.099	280	48.101	48.099	-	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	48.098	48.100																																
85	48.099	48.101																																
100	48.099	48.100																																
120	48.099	48.100																																
200	48.101	48.100																																
230	48.100	48.100																																
264	48.101	48.099																																
280	48.101	48.099																																
-	-	-																																

**COSEL**

Model	PBA150F-48	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+48V3.3A																																																					
1.Graph	<p>—△— Input Volt. 100V        - -□--- Input Volt. 200V        - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (Input 100V)</th> <th>Output Voltage [V] (Input 200V)</th> <th>Output Voltage [V] (Input 230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>48.118</td><td>48.116</td><td>48.115</td></tr> <tr><td>0.60</td><td>48.110</td><td>48.109</td><td>48.108</td></tr> <tr><td>1.20</td><td>48.109</td><td>48.107</td><td>48.108</td></tr> <tr><td>1.80</td><td>48.108</td><td>48.106</td><td>48.107</td></tr> <tr><td>2.40</td><td>48.108</td><td>48.105</td><td>48.106</td></tr> <tr><td>3.00</td><td>48.107</td><td>48.105</td><td>48.106</td></tr> <tr><td>3.30</td><td>48.107</td><td>48.105</td><td>48.104</td></tr> <tr><td>3.63</td><td>48.106</td><td>48.104</td><td>48.103</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (Input 100V)	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 230V)	0.00	48.118	48.116	48.115	0.60	48.110	48.109	48.108	1.20	48.109	48.107	48.108	1.80	48.108	48.106	48.107	2.40	48.108	48.105	48.106	3.00	48.107	48.105	48.106	3.30	48.107	48.105	48.104	3.63	48.106	48.104	48.103															
Load Current [A]	Output Voltage [V] (Input 100V)	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 230V)																																																			
0.00	48.118	48.116	48.115																																																			
0.60	48.110	48.109	48.108																																																			
1.20	48.109	48.107	48.108																																																			
1.80	48.108	48.106	48.107																																																			
2.40	48.108	48.105	48.106																																																			
3.00	48.107	48.105	48.106																																																			
3.30	48.107	48.105	48.104																																																			
3.63	48.106	48.104	48.103																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>48.118</td><td>48.116</td><td>48.115</td></tr> <tr><td>0.60</td><td>48.110</td><td>48.109</td><td>48.108</td></tr> <tr><td>1.20</td><td>48.109</td><td>48.107</td><td>48.108</td></tr> <tr><td>1.80</td><td>48.108</td><td>48.106</td><td>48.107</td></tr> <tr><td>2.40</td><td>48.108</td><td>48.105</td><td>48.106</td></tr> <tr><td>3.00</td><td>48.107</td><td>48.105</td><td>48.106</td></tr> <tr><td>3.30</td><td>48.107</td><td>48.105</td><td>48.104</td></tr> <tr><td>3.63</td><td>48.106</td><td>48.104</td><td>48.103</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	48.118	48.116	48.115	0.60	48.110	48.109	48.108	1.20	48.109	48.107	48.108	1.80	48.108	48.106	48.107	2.40	48.108	48.105	48.106	3.00	48.107	48.105	48.106	3.30	48.107	48.105	48.104	3.63	48.106	48.104	48.103	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	48.118	48.116	48.115																																																			
0.60	48.110	48.109	48.108																																																			
1.20	48.109	48.107	48.108																																																			
1.80	48.108	48.106	48.107																																																			
2.40	48.108	48.105	48.106																																																			
3.00	48.107	48.105	48.106																																																			
3.30	48.107	48.105	48.104																																																			
3.63	48.106	48.104	48.103																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model PBA150F-48

Item Dynamic Load Response

Object +48V3.3A


Temperature  
Testing Circuitry25° C  
Figure AInput Volt. 100 V  
Cycle 1000 ms

Load Current

Min. Load (0A) ←→  
Load 100% (3.3A)

100 mV/div

10 ms/div




10 ms/div

Min. Load (0A) ←→  
Load 50% (1.65A)

100 mV/div

10 ms/div



10 ms/div

\* The characteristic of AC200V is equal.

COSEL


Model PBA150F-48

Item Ripple Voltage (by Load Current)

Object +48V3.3A

## 1. Graph

—▲— Input Volt. 100V  
 - -○- - Input Volt. 200V



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	10	10
0.60	20	20
1.20	30	30
1.80	35	35
2.40	40	40
3.00	45	45
3.30	50	45
3.63	55	50
-	-	-
-	-	-
-	-	-



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	PBA150F-48
Item	Ripple-Noise
Object	+48V3.3A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	55	60
0.60	70	80
1.20	80	85
1.80	85	85
2.40	85	85
3.00	95	95
3.30	100	100
3.63	100	100
—	—	—
—	—	—
—	—	—



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

<b>Model</b>	PBA150F-48
<b>Item</b>	Ripple Voltage (by Ambient Temp.)
<b>Object</b>	+48V3.3A

**1.Graph**

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure A****2.Values**

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [mV]	Input Volt. 200 [mV]
-30	185	185
-10	100	100
0	80	80
25	50	50
50	45	45
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

**COSSEL**

Model	PBA150F-48	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+48V3.3A																																																						
1.Graph	<p>—▲— Input Volt. 100V        - - +--- Input Volt. 200V        - - ○--- Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>48.043</td><td>48.043</td><td>48.043</td></tr> <tr> <td>-10</td><td>48.048</td><td>48.049</td><td>48.050</td></tr> <tr> <td>0</td><td>48.061</td><td>48.061</td><td>48.065</td></tr> <tr> <td>10</td><td>48.105</td><td>48.107</td><td>48.107</td></tr> <tr> <td>25</td><td>48.143</td><td>48.144</td><td>48.144</td></tr> <tr> <td>30</td><td>48.151</td><td>48.152</td><td>48.152</td></tr> <tr> <td>40</td><td>48.152</td><td>48.153</td><td>48.152</td></tr> <tr> <td>50</td><td>48.143</td><td>48.143</td><td>48.143</td></tr> <tr> <td>60</td><td>48.122</td><td>48.124</td><td>48.123</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	48.043	48.043	48.043	-10	48.048	48.049	48.050	0	48.061	48.061	48.065	10	48.105	48.107	48.107	25	48.143	48.144	48.144	30	48.151	48.152	48.152	40	48.152	48.153	48.152	50	48.143	48.143	48.143	60	48.122	48.124	48.123	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
-20	48.043	48.043	48.043																																																				
-10	48.048	48.049	48.050																																																				
0	48.061	48.061	48.065																																																				
10	48.105	48.107	48.107																																																				
25	48.143	48.144	48.144																																																				
30	48.151	48.152	48.152																																																				
40	48.152	48.153	48.152																																																				
50	48.143	48.143	48.143																																																				
60	48.122	48.124	48.123																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.



Model	PBA150F-48	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+48V3.3A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 3.3A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	25	264	0	48.161	±53	±0.1
Minimum Voltage	-10	85	3.3	48.056		


**COSEL**

Model PBA150F-48

Item Time Lapse Drift

Object +48V3.3A

## 1. Graph



\* The characteristic of AC200V is equal.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Time since start [H]	Output Voltage [V]
0.0	48.117
0.5	48.116
1.0	48.119
2.0	48.121
3.0	48.122
4.0	48.123
5.0	48.125
6.0	48.125
7.0	48.126
8.0	48.126

**COXEL**


Model PBA150F-48

Item Rise and Fall Time

Object +48V3.3A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Input Volt.	Time	Td	Tr	Ts	Th	Tf	[mS]
100 V		314.5	11.5	326.0	21.2	40.3	
200 V		263.0	11.0	274.0	27.4	40.6	



**COSEL**

Model	PBA150F-48
Item	Hold-Up Time
Object	+48V3.3A

## 1. Graph




This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
 Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
75	35	14
85	38	17
100	41	20
120	44	22
200	49	26
230	52	27
264	53	28
280	52	27
-	-	-

**COSSEL**

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Time [mS]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.60	91	132	138
1.20	63	73	74
1.80	40	48	50
2.40	29	36	37
3.00	22	29	29
3.30	20	26	27
3.63	15	24	24
-	-	-	-
-	-	-	-
-	-	-	-

**COSSEL**


Model	PBA150F-48																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+48V3.3A																																							
1. Graph																																								
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Load 50% (Dashed line with squares)</li> <li>Load 100% (Solid line with triangles)</li> </ul>																																								
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								
Testing Circuitry Figure A																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>48</td> <td>66</td> </tr> <tr> <td>-10</td> <td>47</td> <td>65</td> </tr> <tr> <td>0</td> <td>47</td> <td>65</td> </tr> <tr> <td>10</td> <td>47</td> <td>65</td> </tr> <tr> <td>25</td> <td>48</td> <td>65</td> </tr> <tr> <td>30</td> <td>48</td> <td>65</td> </tr> <tr> <td>40</td> <td>48</td> <td>66</td> </tr> <tr> <td>50</td> <td>48</td> <td>66</td> </tr> <tr> <td>60</td> <td>48</td> <td>66</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	48	66	-10	47	65	0	47	65	10	47	65	25	48	65	30	48	65	40	48	66	50	48	66	60	48	66	-	-	-	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	48	66																																						
-10	47	65																																						
0	47	65																																						
10	47	65																																						
25	48	65																																						
30	48	65																																						
40	48	66																																						
50	48	66																																						
60	48	66																																						
-	-	-																																						
-	-	-																																						

**COSEL**

Model	PBA150F-48																																										
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																									
Object	+48V3.3A																																										
1. Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 24V to 0V.</p>																																											
2. Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>48.0</td><td>3.39</td><td>3.33</td></tr> <tr><td>45.6</td><td>4.17</td><td>4.16</td></tr> <tr><td>43.2</td><td>4.18</td><td>4.17</td></tr> <tr><td>38.4</td><td>4.20</td><td>4.17</td></tr> <tr><td>33.6</td><td>4.20</td><td>4.17</td></tr> <tr><td>28.8</td><td>4.21</td><td>4.22</td></tr> <tr><td>24.0</td><td>4.20</td><td>4.19</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	48.0	3.39	3.33	45.6	4.17	4.16	43.2	4.18	4.17	38.4	4.20	4.17	33.6	4.20	4.17	28.8	4.21	4.22	24.0	4.20	4.19	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 200[V]																																									
48.0	3.39	3.33																																									
45.6	4.17	4.16																																									
43.2	4.18	4.17																																									
38.4	4.20	4.17																																									
33.6	4.20	4.17																																									
28.8	4.21	4.22																																									
24.0	4.20	4.19																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									

**COSEL**

<b>Model</b>	PBA150F-48
<b>Item</b>	Overvoltage Protection
<b>Object</b>	+48V3.3A

**1. Graph**

Note: Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure A****2.Values**

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	60.55	60.08
-10	61.08	61.08
0	61.59	61.59
10	62.06	62.06
25	62.94	62.94
30	63.18	63.18
40	63.78	63.78
50	64.31	64.31
60	64.78	64.78
--	-	-
--	-	-

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )