



## ***EXTRA TEST DATA OF PBA150F-9***

*Regulated DC Power Supply*  
Jun, 09, 2020

**COSEL CO.,LTD.**






## CONTENTS

1.Inrush Current (enlargement) . . . . .	1
2.Dynamic Line Regulation . . . . .	2
3.Ovvervoltage Protection (waveform) . . . . .	3
4.Hiccup cycle (by Overcurrent Protection) . . . . .	4
5.Power Consumption (by Input Voltage) . . . . .	5
6.Figure of Testing Circuitry . . . . .	6

(Final Page 6)




**COSEL**

Model	PBA150F-9	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		






**COSEL**

Model	PBA150F-9	Temperature Testing Circuitry Object	25°C A
Item	Dynamic Line Regulation		
Object	_____		






Model	PBA150F-9	Temperature	25°C
Item	Over Voltage Protection	Testing Circuitry	A
Object	—————	Input Voltage	: 100V

Output  
Voltage  
[2V/div]Load : 0%  
Overvoltage protection  
value : 13.0VTime  
[40ms/div]Output  
Voltage  
[2V/div]Load : 100%  
Overvoltage protection  
value : 13.0VTime  
[20ms/div]

**COSEL**

Model	PBA150F-9	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object	Load : Short		

Output  
Current  
[5A/div]Output  
Current  
[5A/div]

**COSEL**


Model	PBA150F-9
Item	Input voltage - Power consumption
Object	_____

Temperature 25°C  
Testing Circuitry -

Load : 0%

## 2.Values

Input voltage [V]	Power consumption [W]
85	0.28
100	0.42
115	0.94
200	1.43
230	1.80
264	2.10



Reducing standby power is possible by OFF signal of the remote control.




Figure A