



EXTRA TEST DATA OF PBA15F-5

*Regulated DC Power Supply
Jun, 01, 2020*

COSEL CO.,LTD.




CONTENTS

1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Overvoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Figure of Testing Circuitry	5





(Final Page 5)



Model	PBA15F-5		
Item	Inrush Current (enlargement)	Temperature	25°C
Object		Testing Circuitry	A



Model	PBA15F-5	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object			






Model	PBA15F-5	Temperature	25°C
Item	Over Voltage Protection	Testing Circuitry	A
Object		Input Voltage : 100V	

Output
Voltage
[1V/div]

GND




Load :0%
Overvoltage protection
value : 6.9V

Time
[40ms/div]


Output
Voltage
[1V/div]

GND




Load :100%
Overvoltage protection
value : 6.8V

Time
[20ms/div]



Model	PBA15F-5	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object		Load	: Short

Output Current
[2A/div]



Input Voltage : 100V


Short-circuit current : 9A

ON Time : 39ms

Hiccup mode time : 601ms

Time
[200ms/div]

Output Current
[2A/div]




Input Voltage : 200V

Short-circuit current : 10.1A

ON Time : 39ms

Hiccup mode time : 597ms

Time
[200ms/div]






Figure A