



EXTRA TEST DATA OF PBA15F-9

*Regulated DC Power Supply
Jun, 01, 2020*

COSEL CO.,LTD.



CONTENTS

1.Inrush Current (enlargement) 1

2.Dynamic Line Regulation 2

3.Overvoltage Protection (waveform) 3




4.Hiccup cycle (by Overcurrent Protection) 4

5.Figure of Testing Circuitry 5

(Final Page 5)






Model	PBA15F-9		
Item	Inrush Current (enlargement)	Temperature	25°C
Object		Testing Circuitry	A





Model		PBA15F-9	Temperature 25°C Testing Circuitry A
Item		Dynamic Line Regulation	
Object		_____	






Model	PBA15F-9	Temperature	25°C
Item	Over Voltage Protection	Testing Circuitry	A
Object		Input Voltage : 100V	

Output
Voltage
[2V/div]

GND




Load : 0%
Overvoltage protection
value : 13.2V

Time
[40ms/div]


Output
Voltage
[2V/div]

GND




Load : 100%
Overvoltage protection
value : 13.1V

Time
[20ms/div]



Model	PBA15F-9	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object		Load	: Short

Output Current
[1A/div]



Input Voltage : 100V


Short-circuit current : 6.2A

ON Time : 36ms

Hiccup mode time : 591ms

Time
[200ms/div]

Output Current
[1A/div]




Input Voltage : 200V

Short-circuit current : 6.2A

ON Time : 37ms

Hiccup mode time : 591ms

Time
[200ms/div]






Figure A