

COSEL

TEST DATA OF PBA300F-3R3

Regulated DC Power Supply

May 28, 2004

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Hajime Goto
Hajime Goto Design Engineer

COSEL CO.,LTD.




CONTENTS


1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PBA300F-3R3	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—	2. Values																																																				
1. Graph																																																						
—▲— Input Volt. 100V -□--- Input Volt. 200V -○--- Input Volt. 230V																																																						
 <p>The graph shows a linear increase of input current with load current for all input voltages. The 100V curve is the steepest, followed by 230V, and then 200V. A slanted line is drawn through the origin, representing the rated load current range.</p>																																																						
Note: Slanted line shows the range of the rated load current.																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.134</td> <td>0.142</td> <td>0.150</td> </tr> <tr> <td>10</td> <td>0.614</td> <td>0.356</td> <td>0.328</td> </tr> <tr> <td>20</td> <td>1.036</td> <td>0.544</td> <td>0.500</td> </tr> <tr> <td>30</td> <td>1.472</td> <td>0.766</td> <td>0.680</td> </tr> <tr> <td>40</td> <td>1.932</td> <td>1.002</td> <td>0.878</td> </tr> <tr> <td>50</td> <td>2.422</td> <td>1.238</td> <td>1.090</td> </tr> <tr> <td>60</td> <td>2.936</td> <td>1.480</td> <td>1.306</td> </tr> <tr> <td>66</td> <td>3.264</td> <td>1.630</td> <td>1.438</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.134	0.142	0.150	10	0.614	0.356	0.328	20	1.036	0.544	0.500	30	1.472	0.766	0.680	40	1.932	1.002	0.878	50	2.422	1.238	1.090	60	2.936	1.480	1.306	66	3.264	1.630	1.438	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.134	0.142	0.150																																																			
10	0.614	0.356	0.328																																																			
20	1.036	0.544	0.500																																																			
30	1.472	0.766	0.680																																																			
40	1.932	1.002	0.878																																																			
50	2.422	1.238	1.090																																																			
60	2.936	1.480	1.306																																																			
66	3.264	1.630	1.438																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


COSEL

Model	PBA300F-3R3																																																					
Item	Input Power (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1.Graph	<p>—▲— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>10.2</td><td>11.0</td><td>10.0</td></tr> <tr><td>10</td><td>59.1</td><td>58.0</td><td>58.0</td></tr> <tr><td>20</td><td>101.7</td><td>100.0</td><td>99.0</td></tr> <tr><td>30</td><td>145.5</td><td>142.0</td><td>142.0</td></tr> <tr><td>40</td><td>191.6</td><td>187.0</td><td>186.0</td></tr> <tr><td>50</td><td>240.3</td><td>234.0</td><td>232.0</td></tr> <tr><td>60</td><td>291.6</td><td>283.0</td><td>281.0</td></tr> <tr><td>66</td><td>324.0</td><td>313.0</td><td>311.0</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0	10.2	11.0	10.0	10	59.1	58.0	58.0	20	101.7	100.0	99.0	30	145.5	142.0	142.0	40	191.6	187.0	186.0	50	240.3	234.0	232.0	60	291.6	283.0	281.0	66	324.0	313.0	311.0																	
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																			
0	10.2	11.0	10.0																																																			
10	59.1	58.0	58.0																																																			
20	101.7	100.0	99.0																																																			
30	145.5	142.0	142.0																																																			
40	191.6	187.0	186.0																																																			
50	240.3	234.0	232.0																																																			
60	291.6	283.0	281.0																																																			
66	324.0	313.0	311.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10.2</td><td>11.0</td><td>10.0</td></tr> <tr><td>10</td><td>59.1</td><td>58.0</td><td>58.0</td></tr> <tr><td>20</td><td>101.7</td><td>100.0</td><td>99.0</td></tr> <tr><td>30</td><td>145.5</td><td>142.0</td><td>142.0</td></tr> <tr><td>40</td><td>191.6</td><td>187.0</td><td>186.0</td></tr> <tr><td>50</td><td>240.3</td><td>234.0</td><td>232.0</td></tr> <tr><td>60</td><td>291.6</td><td>283.0</td><td>281.0</td></tr> <tr><td>66</td><td>324.0</td><td>313.0</td><td>311.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	10.2	11.0	10.0	10	59.1	58.0	58.0	20	101.7	100.0	99.0	30	145.5	142.0	142.0	40	191.6	187.0	186.0	50	240.3	234.0	232.0	60	291.6	283.0	281.0	66	324.0	313.0	311.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	10.2	11.0	10.0																																																			
10	59.1	58.0	58.0																																																			
20	101.7	100.0	99.0																																																			
30	145.5	142.0	142.0																																																			
40	191.6	187.0	186.0																																																			
50	240.3	234.0	232.0																																																			
60	291.6	283.0	281.0																																																			
66	324.0	313.0	311.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PBA300F-3R3																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C																																
Object		Testing Circuitry Figure A																																
1. Graph																																		
<p style="text-align: center;"> --- □ --- Load 50% —△— Load 100% </p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency [Load 50%] [%]</th> <th>Efficiency [Load 100%] [%]</th> </tr> </thead> <tbody> <tr><td>80</td><td>68.8</td><td>67.5</td></tr> <tr><td>85</td><td>69.1</td><td>68.2</td></tr> <tr><td>100</td><td>69.7</td><td>69.2</td></tr> <tr><td>120</td><td>70.0</td><td>70.1</td></tr> <tr><td>200</td><td>70.8</td><td>71.6</td></tr> <tr><td>230</td><td>71.8</td><td>71.8</td></tr> <tr><td>264</td><td>71.8</td><td>72.4</td></tr> <tr><td>280</td><td>73.3</td><td>72.9</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [Load 50%] [%]	Efficiency [Load 100%] [%]	80	68.8	67.5	85	69.1	68.2	100	69.7	69.2	120	70.0	70.1	200	70.8	71.6	230	71.8	71.8	264	71.8	72.4	280	73.3	72.9						
Input Voltage [V]	Efficiency [Load 50%] [%]	Efficiency [Load 100%] [%]																																
80	68.8	67.5																																
85	69.1	68.2																																
100	69.7	69.2																																
120	70.0	70.1																																
200	70.8	71.6																																
230	71.8	71.8																																
264	71.8	72.4																																
280	73.3	72.9																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>80</td><td>68.8</td><td>67.5</td></tr> <tr><td>85</td><td>69.1</td><td>68.2</td></tr> <tr><td>100</td><td>69.7</td><td>69.2</td></tr> <tr><td>120</td><td>70.0</td><td>70.1</td></tr> <tr><td>200</td><td>70.8</td><td>71.6</td></tr> <tr><td>230</td><td>71.8</td><td>71.8</td></tr> <tr><td>264</td><td>71.8</td><td>72.4</td></tr> <tr><td>280</td><td>73.3</td><td>72.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	80	68.8	67.5	85	69.1	68.2	100	69.7	69.2	120	70.0	70.1	200	70.8	71.6	230	71.8	71.8	264	71.8	72.4	280	73.3	72.9	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
80	68.8	67.5																																
85	69.1	68.2																																
100	69.7	69.2																																
120	70.0	70.1																																
200	70.8	71.6																																
230	71.8	71.8																																
264	71.8	72.4																																
280	73.3	72.9																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL


Model	PBA300F-3R3	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Efficiency (by Load Current)																																																						
Object	—																																																						
1.Graph	—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V																																																						
																																																							
	2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>10</td><td>57.1</td><td>58.2</td><td>58.2</td></tr> <tr> <td>20</td><td>66.4</td><td>67.5</td><td>68.2</td></tr> <tr> <td>30</td><td>69.6</td><td>71.3</td><td>71.3</td></tr> <tr> <td>40</td><td>70.4</td><td>72.1</td><td>72.5</td></tr> <tr> <td>50</td><td>70.1</td><td>72.0</td><td>72.6</td></tr> <tr> <td>60</td><td>69.3</td><td>71.4</td><td>71.9</td></tr> <tr> <td>66</td><td>68.5</td><td>70.9</td><td>71.4</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	10	57.1	58.2	58.2	20	66.4	67.5	68.2	30	69.6	71.3	71.3	40	70.4	72.1	72.5	50	70.1	72.0	72.6	60	69.3	71.4	71.9	66	68.5	70.9	71.4	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0	-	-	-																																																				
10	57.1	58.2	58.2																																																				
20	66.4	67.5	68.2																																																				
30	69.6	71.3	71.3																																																				
40	70.4	72.1	72.5																																																				
50	70.1	72.0	72.6																																																				
60	69.3	71.4	71.9																																																				
66	68.5	70.9	71.4																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PBA300F-3R3																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Power Factor</p> <p>Input Voltage [V]</p> <p>Load 50%</p> <p>Load 100%</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>0.991</td><td>0.993</td></tr> <tr> <td>85</td><td>0.991</td><td>0.993</td></tr> <tr> <td>100</td><td>0.986</td><td>0.992</td></tr> <tr> <td>120</td><td>0.978</td><td>0.988</td></tr> <tr> <td>200</td><td>0.929</td><td>0.953</td></tr> <tr> <td>230</td><td>0.898</td><td>0.934</td></tr> <tr> <td>264</td><td>0.849</td><td>0.912</td></tr> <tr> <td>280</td><td>0.452</td><td>0.509</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.991	0.993	85	0.991	0.993	100	0.986	0.992	120	0.978	0.988	200	0.929	0.953	230	0.898	0.934	264	0.849	0.912	280	0.452	0.509	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
80	0.991	0.993																																
85	0.991	0.993																																
100	0.986	0.992																																
120	0.978	0.988																																
200	0.929	0.953																																
230	0.898	0.934																																
264	0.849	0.912																																
280	0.452	0.509																																
--	-	-																																

COSEL

Model	PBA300F-3R3	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph																																																						
<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p>																																																						
2.Values																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.761</td><td>0.379</td><td>0.286</td></tr> <tr><td>10</td><td>0.959</td><td>0.817</td><td>0.763</td></tr> <tr><td>20</td><td>0.980</td><td>0.917</td><td>0.861</td></tr> <tr><td>30</td><td>0.986</td><td>0.922</td><td>0.904</td></tr> <tr><td>40</td><td>0.990</td><td>0.930</td><td>0.916</td></tr> <tr><td>50</td><td>0.991</td><td>0.944</td><td>0.924</td></tr> <tr><td>60</td><td>0.992</td><td>0.953</td><td>0.934</td></tr> <tr><td>66</td><td>0.992</td><td>0.957</td><td>0.937</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.761	0.379	0.286	10	0.959	0.817	0.763	20	0.980	0.917	0.861	30	0.986	0.922	0.904	40	0.990	0.930	0.916	50	0.991	0.944	0.924	60	0.992	0.953	0.934	66	0.992	0.957	0.937	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.761	0.379	0.286																																																			
10	0.959	0.817	0.763																																																			
20	0.980	0.917	0.861																																																			
30	0.986	0.922	0.904																																																			
40	0.990	0.930	0.916																																																			
50	0.991	0.944	0.924																																																			
60	0.992	0.953	0.934																																																			
66	0.992	0.957	0.937																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL



Model	PBA300F-3R3	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

[mA]

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.14	0.25	0.28	Operation
	One of phase	0.23	0.45	0.52	stand by
IEC60950	Both phases	0.14	0.25	0.28	Operation
	One of phase	0.23	0.45	0.52	stand by

The value for "One phase" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PBA300F-3R3
Item	Line Regulation
Object	+3.3V60A

1.Graph

---□--- Load 50%
—△— Load 100%




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	3.378	3.372
85	3.378	3.372
100	3.378	3.372
120	3.378	3.371
200	3.378	3.371
230	3.378	3.371
264	3.378	3.371
280	3.378	3.371
--	-	-

COSEL

Model	PBA300F-3R3
Item	Load Regulation
Object	+3.3V60A
1. Graph	
<p style="text-align: center;"> △ Input Volt. 100V □ Input Volt. 200V ○ Input Volt. 230V </p> 	
<p>Note: Slanted line shows the range of the rated load current.</p>	

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0	3.384	3.384	3.384
10	3.382	3.382	3.382
20	3.380	3.380	3.380
30	3.378	3.378	3.378
40	3.376	3.376	3.376
50	3.374	3.374	3.374
60	3.372	3.372	3.372
66	3.371	3.370	3.370
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	PBA300F-3R3	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response 動的負荷變動		
Object	+3.3V60A		

Input Volt. 100 V
 Cycle 1000 ms




Min. Load (0A) ↔

Load 100% (60A)

100 mV/div

10 ms/div




10 ms/div

Min. Load (0A) ↔

Load 50% (30A)

100 mV/div

10 ms/div



10 ms/div

* The characteristic of AC200V is equal.


COSEL

Model	PBA300F-3R3																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+3.3V60A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0 to 60 A. Two curves are shown: one for Input Volt. 100V (solid line with circles) and one for Input Volt. 200V (dashed line with circles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>30</td><td>30</td></tr> <tr><td>10</td><td>30</td><td>30</td></tr> <tr><td>20</td><td>30</td><td>30</td></tr> <tr><td>30</td><td>30</td><td>30</td></tr> <tr><td>40</td><td>35</td><td>35</td></tr> <tr><td>50</td><td>40</td><td>40</td></tr> <tr><td>60</td><td>45</td><td>45</td></tr> <tr><td>66</td><td>55</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0	30	30	10	30	30	20	30	30	30	30	30	40	35	35	50	40	40	60	45	45	66	55	55	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																						
0	30	30																																						
10	30	30																																						
20	30	30																																						
30	30	30																																						
40	35	35																																						
50	40	40																																						
60	45	45																																						
66	55	55																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>30</td><td>30</td></tr> <tr><td>10</td><td>30</td><td>30</td></tr> <tr><td>20</td><td>30</td><td>30</td></tr> <tr><td>30</td><td>30</td><td>30</td></tr> <tr><td>40</td><td>35</td><td>35</td></tr> <tr><td>50</td><td>40</td><td>40</td></tr> <tr><td>60</td><td>45</td><td>45</td></tr> <tr><td>66</td><td>55</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0	30	30	10	30	30	20	30	30	30	30	30	40	35	35	50	40	40	60	45	45	66	55	55	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0	30	30																																						
10	30	30																																						
20	30	30																																						
30	30	30																																						
40	35	35																																						
50	40	40																																						
60	45	45																																						
66	55	55																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Figure showing a complex ripple wave form. The Y-axis is labeled "Ripple [mVp-p]" and the X-axis has time markers. Two time intervals are indicated: T1, which is the full width of the waveform, and T2, which is the width of one cycle of the switching component.</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	PBA300F-3R3
Item	Ripple-Noise
Object	+3.3V60A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0	40	40
10	50	50
20	50	50
30	55	55
40	60	60
50	65	65
60	70	70
66	75	75
--	-	-
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

COSEL

Model PBA300F-3R3																																							
Item Ripple Voltage (by Ambient Temp.)																																							
Object +3.3V60A																																							
1. Graph																																							
<p style="text-align: center;"> --- □ --- Input Volt. 100V —△— Input Volt. 200V </p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>65</td> <td>65</td> </tr> <tr> <td>-20</td> <td>40</td> <td>40</td> </tr> <tr> <td>0</td> <td>30</td> <td>30</td> </tr> <tr> <td>25</td> <td>20</td> <td>20</td> </tr> <tr> <td>50</td> <td>20</td> <td>20</td> </tr> </tbody> </table> <p style="text-align: center;">Load 100 %</p>		Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	-30	65	65	-20	40	40	0	30	30	25	20	20	50	20	20																				
Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																					
-30	65	65																																					
-20	40	40																																					
0	30	30																																					
25	20	20																																					
50	20	20																																					
Measured by 20 MHz Oscilloscope.																																							
Note: Slanted line shows the range of the rated ambient temperature.																																							
Testing Circuitry Figure A																																							
2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>65</td> <td>65</td> </tr> <tr> <td>-20</td> <td>40</td> <td>40</td> </tr> <tr> <td>0</td> <td>30</td> <td>30</td> </tr> <tr> <td>25</td> <td>20</td> <td>20</td> </tr> <tr> <td>50</td> <td>20</td> <td>20</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	-30	65	65	-20	40	40	0	30	30	25	20	20	50	20	20	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																						
	Input Volt. 100 [V]	Input Volt. 200 [V]																																					
-30	65	65																																					
-20	40	40																																					
0	30	30																																					
25	20	20																																					
50	20	20																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					

COSEL

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-30	3.377	3.377	3.377
-20	3.378	3.377	3.377
-10	3.377	3.377	3.377
0	3.376	3.376	3.376
10	3.376	3.376	3.376
25	3.375	3.374	3.374
30	3.374	3.374	3.373
40	3.371	3.370	3.369
50	3.364	3.363	3.362
60	3.351	3.349	3.348
--	-	-	-



Model	PBA300F-3R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V60A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 60A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	264	0	3.389	± 16	± 0.5
Minimum Voltage	50	264	60	3.358		

COSEL


Model	PBA300F-3R3	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3.3V60A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.374</td></tr> <tr><td>0.5</td><td>3.368</td></tr> <tr><td>1.0</td><td>3.368</td></tr> <tr><td>2.0</td><td>3.368</td></tr> <tr><td>3.0</td><td>3.368</td></tr> <tr><td>4.0</td><td>3.368</td></tr> <tr><td>5.0</td><td>3.368</td></tr> <tr><td>6.0</td><td>3.368</td></tr> <tr><td>7.0</td><td>3.369</td></tr> <tr><td>8.0</td><td>3.369</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.374	0.5	3.368	1.0	3.368	2.0	3.368	3.0	3.368	4.0	3.368	5.0	3.368	6.0	3.368	7.0	3.369	8.0	3.369
Time since start [H]	Output Voltage [V]																								
0.0	3.374																								
0.5	3.368																								
1.0	3.368																								
2.0	3.368																								
3.0	3.368																								
4.0	3.368																								
5.0	3.368																								
6.0	3.368																								
7.0	3.369																								
8.0	3.369																								

COSEL

COSEL

Model	PBA300F-3R3
Item	Hold-Up Time
Object	+3.3V60A

1.Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
80	65	29
85	66	29
100	68	31
120	72	33
200	82	38
230	85	40
264	86	41
280	93	43
--	-	-

COSSEL

Model	PBA300F-3R3	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+3.3V60A																																																					
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10</td><td>188</td><td>222</td><td>228</td></tr> <tr><td>20</td><td>98</td><td>121</td><td>123</td></tr> <tr><td>30</td><td>64</td><td>81</td><td>82</td></tr> <tr><td>40</td><td>48</td><td>60</td><td>62</td></tr> <tr><td>50</td><td>38</td><td>47</td><td>48</td></tr> <tr><td>60</td><td>30</td><td>37</td><td>39</td></tr> <tr><td>66</td><td>23</td><td>32</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	10	188	222	228	20	98	121	123	30	64	81	82	40	48	60	62	50	38	47	48	60	30	37	39	66	23	32	35	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [mS]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
10	188	222	228																																																			
20	98	121	123																																																			
30	64	81	82																																																			
40	48	60	62																																																			
50	38	47	48																																																			
60	30	37	39																																																			
66	23	32	35																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


COSEL

<p>Model PBA300F-3R3</p> <p>Item Minimum Input Voltage for Regulated Output Voltage</p> <p>Object +3.3V60A</p>	<p>Testing Circuitry Figure A</p>																																						
<p>1. Graph</p> <p style="text-align: center;">--- □ --- Load 50% — △ — Load 100%</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>74</td> <td>75</td> </tr> <tr> <td>-20</td> <td>73</td> <td>74</td> </tr> <tr> <td>-10</td> <td>73</td> <td>74</td> </tr> <tr> <td>0</td> <td>72</td> <td>73</td> </tr> <tr> <td>10</td> <td>71</td> <td>72</td> </tr> <tr> <td>25</td> <td>70</td> <td>71</td> </tr> <tr> <td>30</td> <td>70</td> <td>71</td> </tr> <tr> <td>40</td> <td>69</td> <td>69</td> </tr> <tr> <td>50</td> <td>67</td> <td>69</td> </tr> <tr> <td>60</td> <td>67</td> <td>69</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-30	74	75	-20	73	74	-10	73	74	0	72	73	10	71	72	25	70	71	30	70	71	40	69	69	50	67	69	60	67	69	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-30	74	75																																					
-20	73	74																																					
-10	73	74																																					
0	72	73																																					
10	71	72																																					
25	70	71																																					
30	70	71																																					
40	69	69																																					
50	67	69																																					
60	67	69																																					
--	-	-																																					

COSEL

Model	PBA300F-3R3
Item	Overcurrent Protection
Object	+3.3V60A

1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 1.98V to 0V.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
3.300	71.12	70.90
3.135	73.52	73.76
2.970	73.81	73.98
2.640	74.20	74.32
2.310	74.66	74.61
1.980	74.80	74.61
-	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

		Testing Circuitry Figure A																																							
Model	PBA300F-3R3																																								
Item	Overvoltage Protection																																								
Object	+3.3V60A																																								
1.Graph		2.Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>5.84</td> <td>5.95</td> </tr> <tr> <td>-20</td> <td>5.84</td> <td>5.84</td> </tr> <tr> <td>-10</td> <td>5.84</td> <td>5.84</td> </tr> <tr> <td>0</td> <td>5.72</td> <td>5.84</td> </tr> <tr> <td>10</td> <td>5.72</td> <td>5.72</td> </tr> <tr> <td>25</td> <td>5.72</td> <td>5.72</td> </tr> <tr> <td>30</td> <td>5.72</td> <td>5.72</td> </tr> <tr> <td>40</td> <td>5.66</td> <td>5.66</td> </tr> <tr> <td>50</td> <td>5.66</td> <td>5.66</td> </tr> <tr> <td>60</td> <td>5.54</td> <td>5.54</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 200[V]	-30	5.84	5.95	-20	5.84	5.84	-10	5.84	5.84	0	5.72	5.84	10	5.72	5.72	25	5.72	5.72	30	5.72	5.72	40	5.66	5.66	50	5.66	5.66	60	5.54	5.54	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 100[V]	Input Volt. 200[V]																																							
-30	5.84	5.95																																							
-20	5.84	5.84																																							
-10	5.84	5.84																																							
0	5.72	5.84																																							
10	5.72	5.72																																							
25	5.72	5.72																																							
30	5.72	5.72																																							
40	5.66	5.66																																							
50	5.66	5.66																																							
60	5.54	5.54																																							
--	-	-																																							

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)