



TEST DATA OF PBA300F-5

Regulated DC Power Supply
May 28, 2004

()

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Hajime Goto
Hajime Goto Design Engineer

()
COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PBA300F-5																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1. Graph																																																						
<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Load Current [A]</th> <th>100[V]</th> <th>200[V]</th> <th>230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.134</td><td>0.140</td><td>0.157</td></tr> <tr><td>10</td><td>0.814</td><td>0.442</td><td>0.420</td></tr> <tr><td>20</td><td>1.416</td><td>0.738</td><td>0.664</td></tr> <tr><td>30</td><td>2.046</td><td>1.062</td><td>0.934</td></tr> <tr><td>40</td><td>2.710</td><td>1.378</td><td>1.220</td></tr> <tr><td>50</td><td>3.408</td><td>1.700</td><td>1.500</td></tr> <tr><td>60</td><td>4.150</td><td>2.038</td><td>1.793</td></tr> <tr><td>66</td><td>4.620</td><td>2.250</td><td>1.975</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	100[V]	200[V]	230[V]	0	0.134	0.140	0.157	10	0.814	0.442	0.420	20	1.416	0.738	0.664	30	2.046	1.062	0.934	40	2.710	1.378	1.220	50	3.408	1.700	1.500	60	4.150	2.038	1.793	66	4.620	2.250	1.975	—	—	—	—	—	—	—	—	—	—	—	—	25°C Testing Circuitry Figure A					
Load Current [A]	100[V]	200[V]	230[V]																																																			
0	0.134	0.140	0.157																																																			
10	0.814	0.442	0.420																																																			
20	1.416	0.738	0.664																																																			
30	2.046	1.062	0.934																																																			
40	2.710	1.378	1.220																																																			
50	3.408	1.700	1.500																																																			
60	4.150	2.038	1.793																																																			
66	4.620	2.250	1.975																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
2. Values																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.134</td><td>0.140</td><td>0.157</td></tr> <tr><td>10</td><td>0.814</td><td>0.442</td><td>0.420</td></tr> <tr><td>20</td><td>1.416</td><td>0.738</td><td>0.664</td></tr> <tr><td>30</td><td>2.046</td><td>1.062</td><td>0.934</td></tr> <tr><td>40</td><td>2.710</td><td>1.378</td><td>1.220</td></tr> <tr><td>50</td><td>3.408</td><td>1.700</td><td>1.500</td></tr> <tr><td>60</td><td>4.150</td><td>2.038</td><td>1.793</td></tr> <tr><td>66</td><td>4.620</td><td>2.250</td><td>1.975</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.134	0.140	0.157	10	0.814	0.442	0.420	20	1.416	0.738	0.664	30	2.046	1.062	0.934	40	2.710	1.378	1.220	50	3.408	1.700	1.500	60	4.150	2.038	1.793	66	4.620	2.250	1.975	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.134	0.140	0.157																																																			
10	0.814	0.442	0.420																																																			
20	1.416	0.738	0.664																																																			
30	2.046	1.062	0.934																																																			
40	2.710	1.378	1.220																																																			
50	3.408	1.700	1.500																																																			
60	4.150	2.038	1.793																																																			
66	4.620	2.250	1.975																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PBA300F-5	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—	—	—																																																			
1. Graph																																																						
<p>—▲— Input Volt. 100V - - -□- Input Volt. 200V - - -○- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>10.2</td><td>11.0</td><td>11.0</td></tr> <tr><td>10</td><td>79.3</td><td>77.0</td><td>77.0</td></tr> <tr><td>20</td><td>139.8</td><td>137.0</td><td>136.0</td></tr> <tr><td>30</td><td>202.8</td><td>198.0</td><td>197.0</td></tr> <tr><td>40</td><td>269.1</td><td>261.0</td><td>260.0</td></tr> <tr><td>50</td><td>338.4</td><td>326.0</td><td>325.0</td></tr> <tr><td>60</td><td>413.0</td><td>395.0</td><td>393.0</td></tr> <tr><td>66</td><td>460.0</td><td>438.0</td><td>435.0</td></tr> </tbody> </table>				Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0	10.2	11.0	11.0	10	79.3	77.0	77.0	20	139.8	137.0	136.0	30	202.8	198.0	197.0	40	269.1	261.0	260.0	50	338.4	326.0	325.0	60	413.0	395.0	393.0	66	460.0	438.0	435.0															
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																			
0	10.2	11.0	11.0																																																			
10	79.3	77.0	77.0																																																			
20	139.8	137.0	136.0																																																			
30	202.8	198.0	197.0																																																			
40	269.1	261.0	260.0																																																			
50	338.4	326.0	325.0																																																			
60	413.0	395.0	393.0																																																			
66	460.0	438.0	435.0																																																			
2. Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10.2</td><td>11.0</td><td>11.0</td></tr> <tr><td>10</td><td>79.3</td><td>77.0</td><td>77.0</td></tr> <tr><td>20</td><td>139.8</td><td>137.0</td><td>136.0</td></tr> <tr><td>30</td><td>202.8</td><td>198.0</td><td>197.0</td></tr> <tr><td>40</td><td>269.1</td><td>261.0</td><td>260.0</td></tr> <tr><td>50</td><td>338.4</td><td>326.0</td><td>325.0</td></tr> <tr><td>60</td><td>413.0</td><td>395.0</td><td>393.0</td></tr> <tr><td>66</td><td>460.0</td><td>438.0</td><td>435.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	10.2	11.0	11.0	10	79.3	77.0	77.0	20	139.8	137.0	136.0	30	202.8	198.0	197.0	40	269.1	261.0	260.0	50	338.4	326.0	325.0	60	413.0	395.0	393.0	66	460.0	438.0	435.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	10.2	11.0	11.0																																																			
10	79.3	77.0	77.0																																																			
20	139.8	137.0	136.0																																																			
30	202.8	198.0	197.0																																																			
40	269.1	261.0	260.0																																																			
50	338.4	326.0	325.0																																																			
60	413.0	395.0	393.0																																																			
66	460.0	438.0	435.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PBA300F-5	Temperature	25°C																														
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																														
Object	—																																
1. Graph			2. Values																														
<p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>80</td><td>74.3</td><td>71.8</td></tr> <tr><td>85</td><td>74.7</td><td>72.5</td></tr> <tr><td>100</td><td>75.5</td><td>74.3</td></tr> <tr><td>120</td><td>76.2</td><td>75.4</td></tr> <tr><td>200</td><td>77.3</td><td>77.4</td></tr> <tr><td>230</td><td>77.7</td><td>77.8</td></tr> <tr><td>264</td><td>78.5</td><td>78.2</td></tr> <tr><td>280</td><td>78.9</td><td>78.8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	80	74.3	71.8	85	74.7	72.5	100	75.5	74.3	120	76.2	75.4	200	77.3	77.4	230	77.7	77.8	264	78.5	78.2	280	78.9	78.8	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																															
80	74.3	71.8																															
85	74.7	72.5																															
100	75.5	74.3																															
120	76.2	75.4																															
200	77.3	77.4																															
230	77.7	77.8																															
264	78.5	78.2																															
280	78.9	78.8																															
--	-	-																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	


Coxel

Model	PBA300F-5																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object	_____	Testing Circuitry	Figure A																																																			
1. Graph	<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - -○- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>10</td><td>64.1</td><td>65.9</td><td>66.0</td></tr> <tr><td>20</td><td>73.1</td><td>74.6</td><td>75.1</td></tr> <tr><td>30</td><td>75.5</td><td>77.3</td><td>77.7</td></tr> <tr><td>40</td><td>75.9</td><td>78.2</td><td>78.5</td></tr> <tr><td>50</td><td>75.4</td><td>78.2</td><td>78.5</td></tr> <tr><td>60</td><td>74.1</td><td>77.4</td><td>77.8</td></tr> <tr><td>66</td><td>73.1</td><td>76.8</td><td>77.3</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	10	64.1	65.9	66.0	20	73.1	74.6	75.1	30	75.5	77.3	77.7	40	75.9	78.2	78.5	50	75.4	78.2	78.5	60	74.1	77.4	77.8	66	73.1	76.8	77.3																			
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
10	64.1	65.9	66.0																																																			
20	73.1	74.6	75.1																																																			
30	75.5	77.3	77.7																																																			
40	75.9	78.2	78.5																																																			
50	75.4	78.2	78.5																																																			
60	74.1	77.4	77.8																																																			
66	73.1	76.8	77.3																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10</td><td>64.1</td><td>65.9</td><td>66.0</td></tr> <tr><td>20</td><td>73.1</td><td>74.6</td><td>75.1</td></tr> <tr><td>30</td><td>75.5</td><td>77.3</td><td>77.7</td></tr> <tr><td>40</td><td>75.9</td><td>78.2</td><td>78.5</td></tr> <tr><td>50</td><td>75.4</td><td>78.2</td><td>78.5</td></tr> <tr><td>60</td><td>74.1</td><td>77.4</td><td>77.8</td></tr> <tr><td>66</td><td>73.1</td><td>76.8</td><td>77.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	10	64.1	65.9	66.0	20	73.1	74.6	75.1	30	75.5	77.3	77.7	40	75.9	78.2	78.5	50	75.4	78.2	78.5	60	74.1	77.4	77.8	66	73.1	76.8	77.3	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
10	64.1	65.9	66.0																																																			
20	73.1	74.6	75.1																																																			
30	75.5	77.3	77.7																																																			
40	75.9	78.2	78.5																																																			
50	75.4	78.2	78.5																																																			
60	74.1	77.4	77.8																																																			
66	73.1	76.8	77.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PBA300F-5
Item	Power Factor (by Input Voltage)
Object	—

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values




Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.992	0.995
85	0.993	0.995
100	0.990	0.993
120	0.984	0.990
200	0.930	0.968
230	0.916	0.952
264	0.878	0.929
280	0.459	0.524
--	-	-

COSEL

Model	PBA300F-5	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Power Factor (by Load Current)																																																					
Object	—																																																					
1. Graph	<p>—▲— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.761</td><td>0.393</td><td>0.306</td></tr> <tr><td>10</td><td>0.971</td><td>0.865</td><td>0.794</td></tr> <tr><td>20</td><td>0.985</td><td>0.926</td><td>0.889</td></tr> <tr><td>30</td><td>0.989</td><td>0.930</td><td>0.916</td></tr> <tr><td>40</td><td>0.992</td><td>0.946</td><td>0.925</td></tr> <tr><td>50</td><td>0.992</td><td>0.956</td><td>0.939</td></tr> <tr><td>60</td><td>0.995</td><td>0.966</td><td>0.952</td></tr> <tr><td>66</td><td>0.996</td><td>0.971</td><td>0.954</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0	0.761	0.393	0.306	10	0.971	0.865	0.794	20	0.985	0.926	0.889	30	0.989	0.930	0.916	40	0.992	0.946	0.925	50	0.992	0.956	0.939	60	0.995	0.966	0.952	66	0.996	0.971	0.954															
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																																			
0	0.761	0.393	0.306																																																			
10	0.971	0.865	0.794																																																			
20	0.985	0.926	0.889																																																			
30	0.989	0.930	0.916																																																			
40	0.992	0.946	0.925																																																			
50	0.992	0.956	0.939																																																			
60	0.995	0.966	0.952																																																			
66	0.996	0.971	0.954																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.761</td><td>0.393</td><td>0.306</td></tr> <tr><td>10</td><td>0.971</td><td>0.865</td><td>0.794</td></tr> <tr><td>20</td><td>0.985</td><td>0.926</td><td>0.889</td></tr> <tr><td>30</td><td>0.989</td><td>0.930</td><td>0.916</td></tr> <tr><td>40</td><td>0.992</td><td>0.946</td><td>0.925</td></tr> <tr><td>50</td><td>0.992</td><td>0.956</td><td>0.939</td></tr> <tr><td>60</td><td>0.995</td><td>0.966</td><td>0.952</td></tr> <tr><td>66</td><td>0.996</td><td>0.971</td><td>0.954</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.761	0.393	0.306	10	0.971	0.865	0.794	20	0.985	0.926	0.889	30	0.989	0.930	0.916	40	0.992	0.946	0.925	50	0.992	0.956	0.939	60	0.995	0.966	0.952	66	0.996	0.971	0.954	—	-	-	-	—	-	-	-	—	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.761	0.393	0.306																																																			
10	0.971	0.865	0.794																																																			
20	0.985	0.926	0.889																																																			
30	0.989	0.930	0.916																																																			
40	0.992	0.946	0.925																																																			
50	0.992	0.956	0.939																																																			
60	0.995	0.966	0.952																																																			
66	0.996	0.971	0.954																																																			
—	-	-	-																																																			
—	-	-	-																																																			
—	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PBA300F-5	Temperature 25°C Testing Circuitry Figure A
Item	Inrush Current	
Object	—	





Model	PBA300F-5	Temperature Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.14	0.25	0.28	Operation
	One of phase	0.23	0.45	0.52	stand by
IEC60950	Both phases	0.14	0.25	0.28	Operation
	One of phase	0.23	0.45	0.52	stand by

The value for "One phase" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PBA300F-5																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+5V60A																																	
1. Graph																																		
<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p> <p>Output Voltage [V]</p> <p>Input Voltage [V]</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>5.086</td> <td>5.081</td> </tr> <tr> <td>85</td> <td>5.086</td> <td>5.081</td> </tr> <tr> <td>100</td> <td>5.086</td> <td>5.081</td> </tr> <tr> <td>120</td> <td>5.086</td> <td>5.081</td> </tr> <tr> <td>200</td> <td>5.086</td> <td>5.080</td> </tr> <tr> <td>230</td> <td>5.087</td> <td>5.080</td> </tr> <tr> <td>264</td> <td>5.087</td> <td>5.080</td> </tr> <tr> <td>280</td> <td>5.087</td> <td>5.080</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	80	5.086	5.081	85	5.086	5.081	100	5.086	5.081	120	5.086	5.081	200	5.086	5.080	230	5.087	5.080	264	5.087	5.080	280	5.087	5.080	-	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
80	5.086	5.081																																
85	5.086	5.081																																
100	5.086	5.081																																
120	5.086	5.081																																
200	5.086	5.080																																
230	5.087	5.080																																
264	5.087	5.080																																
280	5.087	5.080																																
-	-	-																																

COREL

Model	PBA300F-5	Temperature Testing Circuitry Figure A																																																			
Item	Load Regulation																																																				
Object	+5V60A																																																				
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p> 	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5.098</td><td>5.098</td><td>5.097</td></tr> <tr><td>10</td><td>5.096</td><td>5.096</td><td>5.094</td></tr> <tr><td>20</td><td>5.094</td><td>5.094</td><td>5.092</td></tr> <tr><td>30</td><td>5.092</td><td>5.091</td><td>5.090</td></tr> <tr><td>40</td><td>5.090</td><td>5.089</td><td>5.088</td></tr> <tr><td>50</td><td>5.088</td><td>5.087</td><td>5.086</td></tr> <tr><td>60</td><td>5.085</td><td>5.085</td><td>5.084</td></tr> <tr><td>66</td><td>5.084</td><td>5.083</td><td>5.082</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	5.098	5.098	5.097	10	5.096	5.096	5.094	20	5.094	5.094	5.092	30	5.092	5.091	5.090	40	5.090	5.089	5.088	50	5.088	5.087	5.086	60	5.085	5.085	5.084	66	5.084	5.083	5.082	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0	5.098	5.098	5.097																																																		
10	5.096	5.096	5.094																																																		
20	5.094	5.094	5.092																																																		
30	5.092	5.091	5.090																																																		
40	5.090	5.089	5.088																																																		
50	5.088	5.087	5.086																																																		
60	5.085	5.085	5.084																																																		
66	5.084	5.083	5.082																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PBA300F-5	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+5V60A		

Input Volt. 100 V
Cycle 1000 ms



Min. Load (0A) ↔
Load 100% (60A)

100 mV/div

10 ms/div

10 ms/div

Min. Load (0A) ↔
Load 50% (30A)

100 mV/div

10 ms/div

10 ms/div

* The characteristic of AC200V is equal.


COSEL

Model	PBA300F-5
Item	Ripple Voltage (by Load Current)
Object	+5V60A

Temperature 25°C
Testing Circuitry Figure A

1. Graph

—△— Input Volt. 100V
—○— Input Volt. 200V



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0	25	25
10	30	30
20	30	30
30	35	35
40	40	40
50	45	45
60	50	50
66	55	55
—	—	—
—	—	—
—	—	—

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	PBA300F-5
Item	Ripple-Noise
Object	+5V60A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0	40	40
10	50	50
20	50	50
30	55	55
40	60	60
50	65	65
60	75	75
66	80	80
-	-	-
-	-	-
-	-	-


T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL


Model	PBA300F-5
-------	-----------

Item	Ripple Voltage (by Ambient Temp.)
------	-----------------------------------

Object	+5V60A
--------	--------

1. Graph

---□--- Input Volt. 100V
 —△— Input Volt. 200V



Measured by 20 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	60	60
-20	60	60
0	55	55
25	55	55
50	55	55
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

COSEL

Model	PBA300F-5	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+5V60A																																																						
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> 																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td><td>5.085</td><td>5.086</td><td>5.086</td></tr> <tr> <td>-20</td><td>5.085</td><td>5.085</td><td>5.085</td></tr> <tr> <td>-10</td><td>5.084</td><td>5.085</td><td>5.085</td></tr> <tr> <td>0</td><td>5.085</td><td>5.085</td><td>5.085</td></tr> <tr> <td>10</td><td>5.087</td><td>5.086</td><td>5.086</td></tr> <tr> <td>25</td><td>5.085</td><td>5.085</td><td>5.084</td></tr> <tr> <td>30</td><td>5.083</td><td>5.082</td><td>5.082</td></tr> <tr> <td>40</td><td>5.076</td><td>5.074</td><td>5.074</td></tr> <tr> <td>50</td><td>5.066</td><td>5.063</td><td>5.061</td></tr> <tr> <td>60</td><td>5.044</td><td>5.038</td><td>5.034</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-30	5.085	5.086	5.086	-20	5.085	5.085	5.085	-10	5.084	5.085	5.085	0	5.085	5.085	5.085	10	5.087	5.086	5.086	25	5.085	5.085	5.084	30	5.083	5.082	5.082	40	5.076	5.074	5.074	50	5.066	5.063	5.061	60	5.044	5.038	5.034	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
-30	5.085	5.086	5.086																																																				
-20	5.085	5.085	5.085																																																				
-10	5.084	5.085	5.085																																																				
0	5.085	5.085	5.085																																																				
10	5.087	5.086	5.086																																																				
25	5.085	5.085	5.084																																																				
30	5.083	5.082	5.082																																																				
40	5.076	5.074	5.074																																																				
50	5.066	5.063	5.061																																																				
60	5.044	5.038	5.034																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	PBA300F-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V60A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 60A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	264	0	5.097	±23	±0.5
Minimum Voltage	50	264	60	5.051		

COSEL


Model	PBA300F-5	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+5V60A																							
1.Graph		2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.088</td></tr> <tr><td>0.5</td><td>5.073</td></tr> <tr><td>1.0</td><td>5.074</td></tr> <tr><td>2.0</td><td>5.074</td></tr> <tr><td>3.0</td><td>5.074</td></tr> <tr><td>4.0</td><td>5.074</td></tr> <tr><td>5.0</td><td>5.075</td></tr> <tr><td>6.0</td><td>5.075</td></tr> <tr><td>7.0</td><td>5.075</td></tr> <tr><td>8.0</td><td>5.075</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.088	0.5	5.073	1.0	5.074	2.0	5.074	3.0	5.074	4.0	5.074	5.0	5.075	6.0	5.075	7.0	5.075	8.0	5.075
Time since start [H]	Output Voltage [V]																							
0.0	5.088																							
0.5	5.073																							
1.0	5.074																							
2.0	5.074																							
3.0	5.074																							
4.0	5.074																							
5.0	5.075																							
6.0	5.075																							
7.0	5.075																							
8.0	5.075																							

* The characteristic of AC200V is equal.

COSEL


Model	PBA300F-5	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V60A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[mS]
100 V		190.5	1.5	192.0	20.9	2.1	
200 V		182.0	2.0	184.0	26.4	2.1	



COSEL

Model	PBA300F-5
Item	Hold-Up Time
Object	+5V60A

1. Graph


2. Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
80	43	17
85	44	18
100	46	19
120	49	20
200	56	25
230	58	26
264	59	27
280	65	29
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PBA300F-5
Item	Instantaneous Interruption Compensation
Object	+5V60A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Time [mS]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0	-	-	-
10	129	154	157
20	69	82	86
30	45	55	56
40	31	40	40
50	23	31	32
60	19	24	25
66	15	21	22
--	-	-	-
--	-	-	-
--	-	-	-



Model	PBA300F-5
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V60A

1. Graph

--- □ --- Load 50%
— △ — Load 100%

Input Voltage [V]

Ambient Temperature [°C]

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	73	75
-20	73	74
-10	72	73
0	71	73
10	70	72
25	69	71
30	69	71
40	68	70
50	67	69
60	66	69
--	-	-

COSEL
Model PBA300F-5

Item Overcurrent Protection

Object +5V60A

Temperature 25°C
Testing Circuitry Figure A

1. Graph


Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 4V to 0V.

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
5.00	68.03	67.65
4.75	71.89	71.98
4.50	72.07	72.09
4.00	72.33	72.31
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	PBA300F-5
Item	Overvoltage Protection
Object	+5V60A

1. Graph

Operating Point [V]

Ambient Temperature [°C]

Load 0%

—○— Input Volt. 100V
---□--- Input Volt. 200V

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-30	7.66	7.66
-20	7.66	7.66
-10	7.66	7.66
0	7.66	7.66
10	7.66	7.66
25	7.77	7.77
30	7.77	7.77
40	7.77	7.77
50	7.77	7.77
60	7.77	7.77
--	-	-

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)