



TEST DATA OF PBA30F-24

Regulated DC Power Supply
Sep 29, 2005

Approved by : Kuniaki Nagahara
Kuniaki Nagahara Design Manager

Prepared by : Akito Joboji
Akito Joboji Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24


(Final Page 24)

COSEL

Model	PBA30F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.047</td><td>0.041</td><td>0.039</td></tr> <tr><td>0.20</td><td>0.144</td><td>0.098</td><td>0.090</td></tr> <tr><td>0.40</td><td>0.233</td><td>0.150</td><td>0.136</td></tr> <tr><td>0.60</td><td>0.322</td><td>0.197</td><td>0.177</td></tr> <tr><td>0.80</td><td>0.412</td><td>0.247</td><td>0.224</td></tr> <tr><td>1.00</td><td>0.503</td><td>0.296</td><td>0.268</td></tr> <tr><td>1.20</td><td>0.596</td><td>0.346</td><td>0.312</td></tr> <tr><td>1.30</td><td>0.644</td><td>0.371</td><td>0.336</td></tr> <tr><td>1.43</td><td>0.709</td><td>0.404</td><td>0.364</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.00	0.047	0.041	0.039	0.20	0.144	0.098	0.090	0.40	0.233	0.150	0.136	0.60	0.322	0.197	0.177	0.80	0.412	0.247	0.224	1.00	0.503	0.296	0.268	1.20	0.596	0.346	0.312	1.30	0.644	0.371	0.336	1.43	0.709	0.404	0.364											
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																			
0.00	0.047	0.041	0.039																																																			
0.20	0.144	0.098	0.090																																																			
0.40	0.233	0.150	0.136																																																			
0.60	0.322	0.197	0.177																																																			
0.80	0.412	0.247	0.224																																																			
1.00	0.503	0.296	0.268																																																			
1.20	0.596	0.346	0.312																																																			
1.30	0.644	0.371	0.336																																																			
1.43	0.709	0.404	0.364																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.047</td><td>0.041</td><td>0.039</td></tr> <tr><td>0.20</td><td>0.144</td><td>0.098</td><td>0.090</td></tr> <tr><td>0.40</td><td>0.233</td><td>0.150</td><td>0.136</td></tr> <tr><td>0.60</td><td>0.322</td><td>0.197</td><td>0.177</td></tr> <tr><td>0.80</td><td>0.412</td><td>0.247</td><td>0.224</td></tr> <tr><td>1.00</td><td>0.503</td><td>0.296</td><td>0.268</td></tr> <tr><td>1.20</td><td>0.596</td><td>0.346</td><td>0.312</td></tr> <tr><td>1.30</td><td>0.644</td><td>0.371</td><td>0.336</td></tr> <tr><td>1.43</td><td>0.709</td><td>0.404</td><td>0.364</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.047	0.041	0.039	0.20	0.144	0.098	0.090	0.40	0.233	0.150	0.136	0.60	0.322	0.197	0.177	0.80	0.412	0.247	0.224	1.00	0.503	0.296	0.268	1.20	0.596	0.346	0.312	1.30	0.644	0.371	0.336	1.43	0.709	0.404	0.364	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.047	0.041	0.039																																																			
0.20	0.144	0.098	0.090																																																			
0.40	0.233	0.150	0.136																																																			
0.60	0.322	0.197	0.177																																																			
0.80	0.412	0.247	0.224																																																			
1.00	0.503	0.296	0.268																																																			
1.20	0.596	0.346	0.312																																																			
1.30	0.644	0.371	0.336																																																			
1.43	0.709	0.404	0.364																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PBA30F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>2.02</td> <td>2.86</td> <td>3.14</td> </tr> <tr> <td>0.20</td> <td>7.57</td> <td>7.90</td> <td>8.29</td> </tr> <tr> <td>0.40</td> <td>13.08</td> <td>13.50</td> <td>13.80</td> </tr> <tr> <td>0.60</td> <td>18.68</td> <td>18.70</td> <td>18.70</td> </tr> <tr> <td>0.80</td> <td>24.38</td> <td>24.30</td> <td>24.50</td> </tr> <tr> <td>1.00</td> <td>30.21</td> <td>29.70</td> <td>30.00</td> </tr> <tr> <td>1.20</td> <td>36.17</td> <td>35.20</td> <td>35.40</td> </tr> <tr> <td>1.30</td> <td>39.20</td> <td>38.00</td> <td>38.20</td> </tr> <tr> <td>1.43</td> <td>43.30</td> <td>41.60</td> <td>41.80</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	2.02	2.86	3.14	0.20	7.57	7.90	8.29	0.40	13.08	13.50	13.80	0.60	18.68	18.70	18.70	0.80	24.38	24.30	24.50	1.00	30.21	29.70	30.00	1.20	36.17	35.20	35.40	1.30	39.20	38.00	38.20	1.43	43.30	41.60	41.80	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	2.02	2.86	3.14																																																			
0.20	7.57	7.90	8.29																																																			
0.40	13.08	13.50	13.80																																																			
0.60	18.68	18.70	18.70																																																			
0.80	24.38	24.30	24.50																																																			
1.00	30.21	29.70	30.00																																																			
1.20	36.17	35.20	35.40																																																			
1.30	39.20	38.00	38.20																																																			
1.43	43.30	41.60	41.80																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PBA30F-24	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	_____																																		
1.Graph			2.Values																																
<p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing from approximately 75% at 75V to about 78% at 100V, then remaining relatively flat up to 250V. A slanted line on the graph indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>76.3</td> <td>75.7</td> </tr> <tr> <td>85</td> <td>77.0</td> <td>77.8</td> </tr> <tr> <td>100</td> <td>78.0</td> <td>79.8</td> </tr> <tr> <td>120</td> <td>78.4</td> <td>81.2</td> </tr> <tr> <td>200</td> <td>77.4</td> <td>82.5</td> </tr> <tr> <td>230</td> <td>77.1</td> <td>82.1</td> </tr> <tr> <td>264</td> <td>77.1</td> <td>81.5</td> </tr> <tr> <td>280</td> <td>76.7</td> <td>81.0</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	76.3	75.7	85	77.0	77.8	100	78.0	79.8	120	78.4	81.2	200	77.4	82.5	230	77.1	82.1	264	77.1	81.5	280	76.7	81.0	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	76.3	75.7																																	
85	77.0	77.8																																	
100	78.0	79.8																																	
120	78.4	81.2																																	
200	77.4	82.5																																	
230	77.1	82.1																																	
264	77.1	81.5																																	
280	76.7	81.0																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PBA30F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V</p> <p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Load Current [A] on the x-axis (0.0 to 1.6). Three data series are shown: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show efficiency increasing with load current. A diagonal line from approximately (0.3, 65) to (1.3, 80) marks the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>63.9</td><td>61.2</td><td>58.3</td></tr> <tr><td>0.40</td><td>73.7</td><td>71.4</td><td>69.9</td></tr> <tr><td>0.60</td><td>77.4</td><td>77.3</td><td>77.3</td></tr> <tr><td>0.80</td><td>79.0</td><td>79.3</td><td>78.7</td></tr> <tr><td>1.00</td><td>79.7</td><td>81.1</td><td>80.3</td></tr> <tr><td>1.20</td><td>79.9</td><td>82.1</td><td>81.6</td></tr> <tr><td>1.30</td><td>79.8</td><td>82.4</td><td>81.9</td></tr> <tr><td>1.43</td><td>79.5</td><td>82.8</td><td>82.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	63.9	61.2	58.3	0.40	73.7	71.4	69.9	0.60	77.4	77.3	77.3	0.80	79.0	79.3	78.7	1.00	79.7	81.1	80.3	1.20	79.9	82.1	81.6	1.30	79.8	82.4	81.9	1.43	79.5	82.8	82.4	--	-	-	-	--	-	-	-	2.Values				
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.20	63.9	61.2	58.3																																																			
0.40	73.7	71.4	69.9																																																			
0.60	77.4	77.3	77.3																																																			
0.80	79.0	79.3	78.7																																																			
1.00	79.7	81.1	80.3																																																			
1.20	79.9	82.1	81.6																																																			
1.30	79.8	82.4	81.9																																																			
1.43	79.5	82.8	82.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.20</td><td>63.9</td><td>61.2</td><td>58.3</td></tr> <tr><td>0.40</td><td>73.7</td><td>71.4</td><td>69.9</td></tr> <tr><td>0.60</td><td>77.4</td><td>77.3</td><td>77.3</td></tr> <tr><td>0.80</td><td>79.0</td><td>79.3</td><td>78.7</td></tr> <tr><td>1.00</td><td>79.7</td><td>81.1</td><td>80.3</td></tr> <tr><td>1.20</td><td>79.9</td><td>82.1</td><td>81.6</td></tr> <tr><td>1.30</td><td>79.8</td><td>82.4</td><td>81.9</td></tr> <tr><td>1.43</td><td>79.5</td><td>82.8</td><td>82.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	63.9	61.2	58.3	0.40	73.7	71.4	69.9	0.60	77.4	77.3	77.3	0.80	79.0	79.3	78.7	1.00	79.7	81.1	80.3	1.20	79.9	82.1	81.6	1.30	79.8	82.4	81.9	1.43	79.5	82.8	82.4	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.20	63.9	61.2	58.3																																																			
0.40	73.7	71.4	69.9																																																			
0.60	77.4	77.3	77.3																																																			
0.80	79.0	79.3	78.7																																																			
1.00	79.7	81.1	80.3																																																			
1.20	79.9	82.1	81.6																																																			
1.30	79.8	82.4	81.9																																																			
1.43	79.5	82.8	82.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PBA30F-24																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____	_____																																
1.Graph																																		
<p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line with squares) Load 100% (solid line with triangles) 																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.625</td><td>0.653</td></tr> <tr> <td>85</td><td>0.606</td><td>0.631</td></tr> <tr> <td>100</td><td>0.578</td><td>0.607</td></tr> <tr> <td>120</td><td>0.550</td><td>0.579</td></tr> <tr> <td>200</td><td>0.473</td><td>0.499</td></tr> <tr> <td>230</td><td>0.458</td><td>0.485</td></tr> <tr> <td>264</td><td>0.440</td><td>0.468</td></tr> <tr> <td>280</td><td>0.436</td><td>0.462</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.625	0.653	85	0.606	0.631	100	0.578	0.607	120	0.550	0.579	200	0.473	0.499	230	0.458	0.485	264	0.440	0.468	280	0.436	0.462	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.625	0.653																																
85	0.606	0.631																																
100	0.578	0.607																																
120	0.550	0.579																																
200	0.473	0.499																																
230	0.458	0.485																																
264	0.440	0.468																																
280	0.436	0.462																																
--	-	-																																

COSEL


Model	PBA30F-24	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Power Factor (by Load Current)																																																						
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - -○- - Input Volt. 230V</p>																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.425</td><td>0.349</td><td>0.350</td></tr> <tr><td>0.20</td><td>0.526</td><td>0.403</td><td>0.400</td></tr> <tr><td>0.40</td><td>0.562</td><td>0.449</td><td>0.439</td></tr> <tr><td>0.60</td><td>0.579</td><td>0.473</td><td>0.459</td></tr> <tr><td>0.80</td><td>0.591</td><td>0.492</td><td>0.476</td></tr> <tr><td>1.00</td><td>0.600</td><td>0.502</td><td>0.486</td></tr> <tr><td>1.20</td><td>0.606</td><td>0.509</td><td>0.493</td></tr> <tr><td>1.30</td><td>0.609</td><td>0.512</td><td>0.495</td></tr> <tr><td>1.43</td><td>0.611</td><td>0.515</td><td>0.499</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.425	0.349	0.350	0.20	0.526	0.403	0.400	0.40	0.562	0.449	0.439	0.60	0.579	0.473	0.459	0.80	0.591	0.492	0.476	1.00	0.600	0.502	0.486	1.20	0.606	0.509	0.493	1.30	0.609	0.512	0.495	1.43	0.611	0.515	0.499	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	0.425	0.349	0.350																																																				
0.20	0.526	0.403	0.400																																																				
0.40	0.562	0.449	0.439																																																				
0.60	0.579	0.473	0.459																																																				
0.80	0.591	0.492	0.476																																																				
1.00	0.600	0.502	0.486																																																				
1.20	0.606	0.509	0.493																																																				
1.30	0.609	0.512	0.495																																																				
1.43	0.611	0.515	0.499																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

Model PBA30F-24


Item Inrush Current

Object

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]


Input Voltage 100 V
Frequency 60 Hz
Load 100 %

Primary inrush current : 12.1 A
Secondary inrush current : 1.7 A

Input
Current
[20A/div]

Input Voltage 200 V
Frequency 60 Hz
Load 100 %

Primary inrush current : 27.9 A
Secondary inrush current : 1.4 A





Model	PBA30F-24	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

[mA]

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.15	0.32	0.39	Operation
	One of phase	0.30	0.64	0.79	stand by
IEC60950	Both phases	0.19	0.44	0.52	Operation
	One of phase	0.29	0.64	0.79	stand by

The value for "One of phase" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


COSEL

Model	PBA30F-24
Item	Line Regulation
Object	+24V1.3A

Temperature 25°C
Testing Circuitry Figure A

1.Graph

---□--- Load 50%
—△— Load 100%





Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	24.016	24.011
85	24.017	24.013
100	24.018	24.014
120	24.019	24.015
200	24.021	24.018
230	24.022	24.019
264	24.023	24.020
280	24.023	24.020
--	-	-

COSEL

Model	PBA30F-24	Temperature Testing Circuitry	25°C Figure A																																																				
Item	Load Regulation																																																						
Object	+24V1.3A	2.Values																																																					
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - - ○ - - Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>24.026</td><td>24.028</td><td>24.028</td></tr> <tr> <td>0.20</td><td>24.023</td><td>24.026</td><td>24.026</td></tr> <tr> <td>0.40</td><td>24.020</td><td>24.024</td><td>24.025</td></tr> <tr> <td>0.60</td><td>24.019</td><td>24.023</td><td>24.023</td></tr> <tr> <td>0.80</td><td>24.018</td><td>24.022</td><td>24.023</td></tr> <tr> <td>1.00</td><td>24.017</td><td>24.021</td><td>24.022</td></tr> <tr> <td>1.20</td><td>24.016</td><td>24.020</td><td>24.021</td></tr> <tr> <td>1.30</td><td>24.015</td><td>24.020</td><td>24.020</td></tr> <tr> <td>1.43</td><td>24.014</td><td>24.019</td><td>24.019</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	24.026	24.028	24.028	0.20	24.023	24.026	24.026	0.40	24.020	24.024	24.025	0.60	24.019	24.023	24.023	0.80	24.018	24.022	24.023	1.00	24.017	24.021	24.022	1.20	24.016	24.020	24.021	1.30	24.015	24.020	24.020	1.43	24.014	24.019	24.019	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	24.026	24.028	24.028																																																				
0.20	24.023	24.026	24.026																																																				
0.40	24.020	24.024	24.025																																																				
0.60	24.019	24.023	24.023																																																				
0.80	24.018	24.022	24.023																																																				
1.00	24.017	24.021	24.022																																																				
1.20	24.016	24.020	24.021																																																				
1.30	24.015	24.020	24.020																																																				
1.43	24.014	24.019	24.019																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						


COSEL

COSEL

Model	PBA30F-24
Item	Ripple Voltage (by Load Current)
Object	+24V1.3A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	5	5
0.20	15	10
0.40	20	10
0.60	25	10
0.80	30	15
1.00	35	15
1.20	40	15
1.30	45	15
1.43	50	20
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form


COSEL

Model PBA30F-24

Item Ripple-Noise

Object +24V1.3A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	20	20
0.20	25	20
0.40	30	20
0.60	35	25
0.80	45	25
1.00	50	25
1.20	55	30
1.30	60	30
1.43	65	30
--	-	-
-	-	-



T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL

Model	PBA30F-24
Item	Ripple Voltage (by Ambient Temp.)
Object	+24V1.3A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	170	100
-10	80	40
0	60	30
25	45	15
50	30	15
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

<p>Model PBA30F-24</p> <p>Item Ambient Temperature Drift</p> <p>Object +24V1.3A</p>	Testing Circuitry Figure A																																																				
	2.Values																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>24.011</td><td>24.019</td><td>24.021</td></tr> <tr> <td>-10</td><td>24.010</td><td>24.016</td><td>24.017</td></tr> <tr> <td>0</td><td>24.011</td><td>24.016</td><td>24.018</td></tr> <tr> <td>10</td><td>24.014</td><td>24.019</td><td>24.020</td></tr> <tr> <td>20</td><td>24.012</td><td>24.018</td><td>24.019</td></tr> <tr> <td>25</td><td>24.014</td><td>24.019</td><td>24.020</td></tr> <tr> <td>30</td><td>24.012</td><td>24.017</td><td>24.019</td></tr> <tr> <td>40</td><td>24.009</td><td>24.014</td><td>24.015</td></tr> <tr> <td>50</td><td>23.990</td><td>23.995</td><td>23.996</td></tr> <tr> <td>60</td><td>23.972</td><td>23.977</td><td>23.978</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	24.011	24.019	24.021	-10	24.010	24.016	24.017	0	24.011	24.016	24.018	10	24.014	24.019	24.020	20	24.012	24.018	24.019	25	24.014	24.019	24.020	30	24.012	24.017	24.019	40	24.009	24.014	24.015	50	23.990	23.995	23.996	60	23.972	23.977	23.978	--	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
-20	24.011	24.019	24.021																																																		
-10	24.010	24.016	24.017																																																		
0	24.011	24.016	24.018																																																		
10	24.014	24.019	24.020																																																		
20	24.012	24.018	24.019																																																		
25	24.014	24.019	24.020																																																		
30	24.012	24.017	24.019																																																		
40	24.009	24.014	24.015																																																		
50	23.990	23.995	23.996																																																		
60	23.972	23.977	23.978																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																					



Model	PBA30F-24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V1.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 1.3A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	10	264	0	24.028	± 19	± 0.1
Minimum Voltage	50	85	1.3	23.990		

COSEL


Model	PBA30F-24	Temperature 25°C																						
Item	Time Lapse Drift	Testing Circuitry Figure A																						
Object	+24V1.3A																							
1. Graph		2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>24.017</td></tr> <tr><td>0.5</td><td>24.014</td></tr> <tr><td>1.0</td><td>24.014</td></tr> <tr><td>2.0</td><td>24.015</td></tr> <tr><td>3.0</td><td>24.015</td></tr> <tr><td>4.0</td><td>24.015</td></tr> <tr><td>5.0</td><td>24.014</td></tr> <tr><td>6.0</td><td>24.016</td></tr> <tr><td>7.0</td><td>24.016</td></tr> <tr><td>8.0</td><td>24.016</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	24.017	0.5	24.014	1.0	24.014	2.0	24.015	3.0	24.015	4.0	24.015	5.0	24.014	6.0	24.016	7.0	24.016	8.0	24.016
Time since start [H]	Output Voltage [V]																							
0.0	24.017																							
0.5	24.014																							
1.0	24.014																							
2.0	24.015																							
3.0	24.015																							
4.0	24.015																							
5.0	24.014																							
6.0	24.016																							
7.0	24.016																							
8.0	24.016																							

* The characteristic of AC200V is equal.

COSEL


Model	PBA30F-24	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+24V1.3A	

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[mS]
100 V		163.3	17.5	180.8	24.8	33.0	
200 V		147.3	17.3	164.6	125.3	33.5	



COSEL

Model	PBA30F-24	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time																																	
Object	+24V1.3A																																	
1.Graph		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>22</td><td>9</td></tr> <tr><td>85</td><td>32</td><td>14</td></tr> <tr><td>100</td><td>49</td><td>23</td></tr> <tr><td>120</td><td>77</td><td>37</td></tr> <tr><td>200</td><td>244</td><td>124</td></tr> <tr><td>230</td><td>331</td><td>169</td></tr> <tr><td>264</td><td>445</td><td>229</td></tr> <tr><td>280</td><td>507</td><td>261</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	22	9	85	32	14	100	49	23	120	77	37	200	244	124	230	331	169	264	445	229	280	507	261	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
75	22	9																																
85	32	14																																
100	49	23																																
120	77	37																																
200	244	124																																
230	331	169																																
264	445	229																																
280	507	261																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL


Model	PBA30F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+24V1.3A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - -○- - Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.20</td><td>53</td><td>221</td><td>295</td></tr> <tr> <td>0.40</td><td>46</td><td>198</td><td>265</td></tr> <tr> <td>0.60</td><td>40</td><td>179</td><td>239</td></tr> <tr> <td>0.80</td><td>37</td><td>162</td><td>215</td></tr> <tr> <td>1.00</td><td>31</td><td>147</td><td>198</td></tr> <tr> <td>1.20</td><td>30</td><td>135</td><td>182</td></tr> <tr> <td>1.30</td><td>29</td><td>130</td><td>174</td></tr> <tr> <td>1.43</td><td>27</td><td>123</td><td>165</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	53	221	295	0.40	46	198	265	0.60	40	179	239	0.80	37	162	215	1.00	31	147	198	1.20	30	135	182	1.30	29	130	174	1.43	27	123	165	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.20	53	221	295																																																			
0.40	46	198	265																																																			
0.60	40	179	239																																																			
0.80	37	162	215																																																			
1.00	31	147	198																																																			
1.20	30	135	182																																																			
1.30	29	130	174																																																			
1.43	27	123	165																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PBA30F-24																																								
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																							
Object	+24V1.3A																																								
1.Graph																																									
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>--- □ --- Load 50%</p> <p>— △ — Load 100%</p>																																									
2.Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>44</td><td>54</td> </tr> <tr> <td>-10</td><td>44</td><td>53</td> </tr> <tr> <td>0</td><td>43</td><td>54</td> </tr> <tr> <td>10</td><td>43</td><td>54</td> </tr> <tr> <td>20</td><td>42</td><td>54</td> </tr> <tr> <td>25</td><td>43</td><td>54</td> </tr> <tr> <td>30</td><td>43</td><td>55</td> </tr> <tr> <td>40</td><td>44</td><td>55</td> </tr> <tr> <td>50</td><td>44</td><td>56</td> </tr> <tr> <td>60</td><td>43</td><td>57</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	44	54	-10	44	53	0	43	54	10	43	54	20	42	54	25	43	54	30	43	55	40	44	55	50	44	56	60	43	57	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-20	44	54																																							
-10	44	53																																							
0	43	54																																							
10	43	54																																							
20	42	54																																							
25	43	54																																							
30	43	55																																							
40	44	55																																							
50	44	56																																							
60	43	57																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

COSEL

Model	PBA30F-24
Item	Overcurrent Protection
Object	+24V1.3A

1. Graph

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is less than rated output voltage.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
24.0	2.44	3.16
22.8	-	-
21.6	-	-
19.2	-	-
16.8	-	-
14.4	-	-
12.0	-	-
9.6	-	-
7.2	-	-
4.8	-	-
2.4	-	-
0.0	-	-

COSEL

Model	PBA30F-24
Item	Overvoltage Protection
Object	+24V1.3A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	32.80	32.73
-10	33.07	33.00
0	33.27	33.27
10	33.54	33.54
20	33.75	33.75
25	33.88	33.88
30	34.02	33.95
40	34.22	34.22
50	34.49	34.49
60	34.69	34.69
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)