



# TEST DATA OF PBA600F-36

Regulated DC Power Supply  
Sep.26. 2003

Approved by : *Kuniaki Nagahara*  
Kuniaki Nagahara Design Manager

Prepared by : *Haruki Morita*  
Haruki Morita Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Input Power (by Load Current) . . . . .	2
3.Efficiency (by Input Voltage) . . . . .	3
4.Efficiency (by Load Current) . . . . .	4
5.Power Factor (by Input Voltage) . . . . .	5
6.Power Factor (by Load Current) . . . . .	6
7.Inrush Current . . . . .	7
8.Leakage Current . . . . .	8
9.Line Regulation . . . . .	9
10.Load Regulation . . . . .	10
11.Dynamic Load Response . . . . .	11
12.Ripple Voltage (by Load Current) . . . . .	12
13.Ripple-Noise . . . . .	13
14.Ripple Voltage (by Ambient Temperature) . . . . .	14
15.Ambient Temperature Drift . . . . .	15
16.Output Voltage Accuracy . . . . .	16
17.Time Lapse Drift . . . . .	17
18.Rise and Fall Time . . . . .	18
19.Hold-Up Time . . . . .	19
20.Instantaneous Interruption Compensation . . . . .	20
21.Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22.Overcurrent Protection . . . . .	22
23.Overvoltage Protection . . . . .	23
24.Figure of Testing Circuitry . . . . .	24

(Final Page 24)



<b>Model</b> PBA600F-36		Temperature 25°C Testing Circuitry Figure A																																																		
<b>Item</b>	Input Current (by Load Current)																																																			
<b>Object</b>	_____																																																			
<b>1.Graph</b> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 60%;"> </div> <div style="width: 35%;"> <b>2.Values</b> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0,234</td><td>0.218</td><td>0.214</td></tr> <tr><td>3.0</td><td>1.776</td><td>0.900</td><td>0.802</td></tr> <tr><td>6.0</td><td>2.967</td><td>1.468</td><td>1.288</td></tr> <tr><td>9.0</td><td>4.200</td><td>2.054</td><td>1.790</td></tr> <tr><td>12.0</td><td>5.440</td><td>2.650</td><td>2.304</td></tr> <tr><td>15.0</td><td>6.730</td><td>3.256</td><td>2.828</td></tr> <tr><td>18.0</td><td>7.990</td><td>3.880</td><td>3.357</td></tr> <tr><td>19.8</td><td>8.820</td><td>4.250</td><td>3.680</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> </div> </div>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0,234	0.218	0.214	3.0	1.776	0.900	0.802	6.0	2.967	1.468	1.288	9.0	4.200	2.054	1.790	12.0	5.440	2.650	2.304	15.0	6.730	3.256	2.828	18.0	7.990	3.880	3.357	19.8	8.820	4.250	3.680	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																			
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																	
0.0	0,234	0.218	0.214																																																	
3.0	1.776	0.900	0.802																																																	
6.0	2.967	1.468	1.288																																																	
9.0	4.200	2.054	1.790																																																	
12.0	5.440	2.650	2.304																																																	
15.0	6.730	3.256	2.828																																																	
18.0	7.990	3.880	3.357																																																	
19.8	8.820	4.250	3.680																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
<p>Note: Slanted line shows the range of the rated load current.</p>																																																				



<b>Model</b> PBA600F-36		Temperature 25°C Testing Circuitry Figure A																																																			
<b>Item</b>	Input Power (by Load Current)																																																				
<b>Object</b>	_____																																																				
<p>1.Graph</p> <p>—△— Input Volt. 100V          ---□--- Input Volt. 200V          -·-○-·- Input Volt. 230V</p> <p>Input Power [W]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>19.2</td><td>19.0</td><td>17.0</td></tr> <tr><td>3.0</td><td>175.1</td><td>171.0</td><td>170.0</td></tr> <tr><td>6.0</td><td>293.0</td><td>287.0</td><td>285.0</td></tr> <tr><td>9.0</td><td>415.0</td><td>405.0</td><td>402.0</td></tr> <tr><td>12.0</td><td>540.0</td><td>524.0</td><td>521.0</td></tr> <tr><td>15.0</td><td>667.0</td><td>645.0</td><td>642.0</td></tr> <tr><td>18.0</td><td>794.0</td><td>769.0</td><td>764.0</td></tr> <tr><td>19.8</td><td>875.0</td><td>845.0</td><td>838.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	19.2	19.0	17.0	3.0	175.1	171.0	170.0	6.0	293.0	287.0	285.0	9.0	415.0	405.0	402.0	12.0	540.0	524.0	521.0	15.0	667.0	645.0	642.0	18.0	794.0	769.0	764.0	19.8	875.0	845.0	838.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	19.2	19.0	17.0																																																		
3.0	175.1	171.0	170.0																																																		
6.0	293.0	287.0	285.0																																																		
9.0	415.0	405.0	402.0																																																		
12.0	540.0	524.0	521.0																																																		
15.0	667.0	645.0	642.0																																																		
18.0	794.0	769.0	764.0																																																		
19.8	875.0	845.0	838.0																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



<b>Model</b> PBA600F-36		<b>Temperature</b> 25°C <b>Testing Circuitry</b> Figure A																																
<b>Item</b>	Efficiency (by Input Voltage)																																	
<b>Object</b>	_____																																	
<p>1. Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>77</td><td>76.3</td><td>79.9</td></tr> <tr><td>85</td><td>77.7</td><td>81.3</td></tr> <tr><td>100</td><td>78.2</td><td>81.8</td></tr> <tr><td>120</td><td>78.6</td><td>82.4</td></tr> <tr><td>200</td><td>79.9</td><td>84.3</td></tr> <tr><td>230</td><td>80.5</td><td>84.9</td></tr> <tr><td>264</td><td>81.3</td><td>85.5</td></tr> <tr><td>280</td><td>81.5</td><td>85.9</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	77	76.3	79.9	85	77.7	81.3	100	78.2	81.8	120	78.6	82.4	200	79.9	84.3	230	80.5	84.9	264	81.3	85.5	280	81.5	85.9	-	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
77	76.3	79.9																																
85	77.7	81.3																																
100	78.2	81.8																																
120	78.6	82.4																																
200	79.9	84.3																																
230	80.5	84.9																																
264	81.3	85.5																																
280	81.5	85.9																																
-	-	-																																



<p><b>Model</b> PBA600F-36</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																				
<p><b>Item</b> Efficiency (by Load Current)</p>																																																						
<p><b>Object</b> _____</p>																																																						
<p>1. Graph</p> <p>                     —△— Input Volt. 100V                      - - □ - - Input Volt. 200V                      - · ○ · - Input Volt. 230V                 </p> <p>                     Efficiency [%]                      Load Current [A]                 </p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>61.9</td><td>63.3</td><td>63.7</td></tr> <tr><td>6.0</td><td>73.9</td><td>75.4</td><td>75.9</td></tr> <tr><td>9.0</td><td>78.2</td><td>80.1</td><td>80.7</td></tr> <tr><td>12.0</td><td>80.1</td><td>82.5</td><td>83.0</td></tr> <tr><td>15.0</td><td>81.0</td><td>83.8</td><td>84.2</td></tr> <tr><td>18.0</td><td>81.7</td><td>84.3</td><td>84.9</td></tr> <tr><td>19.8</td><td>81.5</td><td>84.4</td><td>85.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	3.0	61.9	63.3	63.7	6.0	73.9	75.4	75.9	9.0	78.2	80.1	80.7	12.0	80.1	82.5	83.0	15.0	81.0	83.8	84.2	18.0	81.7	84.3	84.9	19.8	81.5	84.4	85.1	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
3.0	61.9	63.3	63.7																																																			
6.0	73.9	75.4	75.9																																																			
9.0	78.2	80.1	80.7																																																			
12.0	80.1	82.5	83.0																																																			
15.0	81.0	83.8	84.2																																																			
18.0	81.7	84.3	84.9																																																			
19.8	81.5	84.4	85.1																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						






<b>Model</b>		PBA600F-36		Temperature 25°C Testing Circuitry Figure A																																
<b>Item</b>		Power Factor (by Input Voltage)																																		
<b>Object</b>		_____																																		
<p>1. Graph</p> <p style="text-align: right;">             ---□--- Load 50%              ---△--- Load 100%         </p>			<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>77</td> <td>0.991</td> <td>0.990</td> </tr> <tr> <td>85</td> <td>0.992</td> <td>0.990</td> </tr> <tr> <td>100</td> <td>0.993</td> <td>0.997</td> </tr> <tr> <td>120</td> <td>0.995</td> <td>0.999</td> </tr> <tr> <td>200</td> <td>0.988</td> <td>0.995</td> </tr> <tr> <td>230</td> <td>0.981</td> <td>0.991</td> </tr> <tr> <td>264</td> <td>0.964</td> <td>0.984</td> </tr> <tr> <td>280</td> <td>0.909</td> <td>0.961</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	77	0.991	0.990	85	0.992	0.990	100	0.993	0.997	120	0.995	0.999	200	0.988	0.995	230	0.981	0.991	264	0.964	0.984	280	0.909	0.961	--	-	-
Input Voltage [V]	Power Factor																																			
	Load 50%	Load 100%																																		
77	0.991	0.990																																		
85	0.992	0.990																																		
100	0.993	0.997																																		
120	0.995	0.999																																		
200	0.988	0.995																																		
230	0.981	0.991																																		
264	0.964	0.984																																		
280	0.909	0.961																																		
--	-	-																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																				



<b>Model</b> PBA600F-36		Temperature 25°C Testing Circuitry Figure A																																																			
<b>Item</b>	Power Factor (by Load Current)																																																				
<b>Object</b>	_____																																																				
<b>1.Graph</b> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 45%;"> </div> <div style="width: 45%;"> <p>—△— Input Volt. 100V              - - □ - - Input Volt. 200V              - · ○ · - Input Volt. 230V</p> </div> </div>		<b>2.Values</b> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.824</td><td>0.432</td><td>0.347</td></tr> <tr><td>3.0</td><td>0.989</td><td>0.950</td><td>0.924</td></tr> <tr><td>6.0</td><td>0.991</td><td>0.980</td><td>0.963</td></tr> <tr><td>9.0</td><td>0.993</td><td>0.988</td><td>0.978</td></tr> <tr><td>12.0</td><td>0.996</td><td>0.992</td><td>0.987</td></tr> <tr><td>15.0</td><td>0.997</td><td>0.994</td><td>0.991</td></tr> <tr><td>18.0</td><td>0.999</td><td>0.995</td><td>0.992</td></tr> <tr><td>19.8</td><td>0.998</td><td>0.998</td><td>0.993</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.824	0.432	0.347	3.0	0.989	0.950	0.924	6.0	0.991	0.980	0.963	9.0	0.993	0.988	0.978	12.0	0.996	0.992	0.987	15.0	0.997	0.994	0.991	18.0	0.999	0.995	0.992	19.8	0.998	0.998	0.993	-	-	-	-	-	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	0.824	0.432	0.347																																																		
3.0	0.989	0.950	0.924																																																		
6.0	0.991	0.980	0.963																																																		
9.0	0.993	0.988	0.978																																																		
12.0	0.996	0.992	0.987																																																		
15.0	0.997	0.994	0.991																																																		
18.0	0.999	0.995	0.992																																																		
19.8	0.998	0.998	0.993																																																		
-	-	-	-																																																		
-	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



<b>Model</b>		PBA600F-36	
<b>Item</b>		Inrush Current	
<b>Object</b>		_____	
		<b>Temperature</b>	25°C
		<b>Testing Circuitry</b>	Figure A





<b>COSEL</b>		Temperature 25°C Testing Circuitry Figure B
Model	PBA600F-36	
Item	Leakage Current	
Object	_____	

1.Results

Standards		Input Volt.			Note
		100[V]	200[V]	240[V]	
DEN-AN	Both phases	0.30	0.47	0.58	Operation
	One of phase	0.38	0.77	0.98	stand by
IEC60950	Both phases	0.24	0.42	0.56	Operation
	One of phase	0.34	0.77	0.91	stand by

[mA]

The value for "One phase" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



<b>COSEL</b>																																			
Model	PBA600F-36	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+36V18A																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>77</td><td>36.182</td><td>36.177</td></tr> <tr><td>85</td><td>36.182</td><td>36.177</td></tr> <tr><td>100</td><td>36.183</td><td>36.178</td></tr> <tr><td>120</td><td>36.183</td><td>36.178</td></tr> <tr><td>200</td><td>36.181</td><td>36.177</td></tr> <tr><td>230</td><td>36.181</td><td>36.176</td></tr> <tr><td>264</td><td>36.180</td><td>36.175</td></tr> <tr><td>280</td><td>36.180</td><td>36.174</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	77	36.182	36.177	85	36.182	36.177	100	36.183	36.178	120	36.183	36.178	200	36.181	36.177	230	36.181	36.176	264	36.180	36.175	280	36.180	36.174	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
77	36.182	36.177																																	
85	36.182	36.177																																	
100	36.183	36.178																																	
120	36.183	36.178																																	
200	36.181	36.177																																	
230	36.181	36.176																																	
264	36.180	36.175																																	
280	36.180	36.174																																	
--	-	-																																	



<b>Model</b> PBA600F-36		Temperature 25°C Testing Circuitry Figure A																																																			
<b>Item</b>	Load Regulation																																																				
<b>Object</b>	+36V18A																																																				
<p>1.Graph</p> <p>                 —△— Input Volt. 100V                  - - - □ - - - Input Volt. 200V                  - - - ○ - - - Input Volt. 230V             </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>36.180</td><td>36.181</td><td>36.182</td></tr> <tr><td>3.0</td><td>36.181</td><td>36.181</td><td>36.182</td></tr> <tr><td>6.0</td><td>36.180</td><td>36.180</td><td>36.181</td></tr> <tr><td>9.0</td><td>36.180</td><td>36.180</td><td>36.181</td></tr> <tr><td>12.0</td><td>36.179</td><td>36.180</td><td>36.181</td></tr> <tr><td>15.0</td><td>36.179</td><td>36.179</td><td>36.180</td></tr> <tr><td>18.0</td><td>36.178</td><td>36.179</td><td>36.180</td></tr> <tr><td>19.8</td><td>36.178</td><td>36.179</td><td>36.180</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	36.180	36.181	36.182	3.0	36.181	36.181	36.182	6.0	36.180	36.180	36.181	9.0	36.180	36.180	36.181	12.0	36.179	36.180	36.181	15.0	36.179	36.179	36.180	18.0	36.178	36.179	36.180	19.8	36.178	36.179	36.180	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	36.180	36.181	36.182																																																		
3.0	36.181	36.181	36.182																																																		
6.0	36.180	36.180	36.181																																																		
9.0	36.180	36.180	36.181																																																		
12.0	36.179	36.180	36.181																																																		
15.0	36.179	36.179	36.180																																																		
18.0	36.178	36.179	36.180																																																		
19.8	36.178	36.179	36.180																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		




<b>Model</b>		PBA600F-36	
<b>Item</b>		Dynamic Load Response	
<b>Object</b>		+36V18A	
		<b>Temperature</b>	25°C
		<b>Testing Circuitry</b>	Figure A

Input Volt. 100 V  
 Cycle 1000 mS


Load Current

Min.Load (0A) ←→  
 Load 100% (18A)

100mV/div




10ms/div




10ms/div

Min.Load (0A) ←→  
 Load 50% (9A)

100mV/div



10ms/div



10ms/div


\* The characteristic of AC200V is equal.



<b>COSEL</b>																																									
Model	PBA600F-36	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure A																																						
Object	+36V18A																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 100V</p> <p>- -○- - Input Volt. 200V</p> </div> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>20</td><td>20</td></tr> <tr><td>6.0</td><td>30</td><td>30</td></tr> <tr><td>9.0</td><td>30</td><td>30</td></tr> <tr><td>12.0</td><td>35</td><td>35</td></tr> <tr><td>15.0</td><td>40</td><td>40</td></tr> <tr><td>18.0</td><td>40</td><td>40</td></tr> <tr><td>19.8</td><td>40</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	10	10	3.0	20	20	6.0	30	30	9.0	30	30	12.0	35	35	15.0	40	40	18.0	40	40	19.8	40	40	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.0	10	10																																							
3.0	20	20																																							
6.0	30	30																																							
9.0	30	30																																							
12.0	35	35																																							
15.0	40	40																																							
18.0	40	40																																							
19.8	40	40																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 20 MHz Oscilloscope.                  Ripple Voltage is shown as p-p in the figure below.                  Note: Stiated line shows the range of the rated load current.</p>																																									
<div style="text-align: center;"> <p>T1: Due to AC Input Line</p> <p>T2: Due to Switching</p> </div> <p style="text-align: center;">Ripple [mVp-p]</p> <p style="text-align: center;">T1</p> <p style="text-align: center;">T2</p>																																									
<p>Fig. Complex Ripple Wave Form</p>																																									



Model	PBA600F-36	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure A
Object	+36V18A		



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	40	40
3.0	50	50
6.0	50	50
9.0	55	50
12.0	60	60
15.0	60	60
18.0	60	60
19.8	70	70
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.  
 Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.





Fig. Complex Ripple Wave Form



Model	PBA600F-36
Item	Ripple Voltage (by Ambient Temp.)
Object	+36V18A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	90	90
-20	50	50
0	45	45
25	40	40
50	45	45
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.  
 Note: Slanted line shows the range of the rated ambient temperature.




Model	PBA600F-36
Item	Ambient Temperature Drift
Object	+36V18A

Testing Circuitry Figure A

1. Graph

- △— Input Volt. 100V
- Input Volt. 200V
- Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-30	36.245	36.244	36.243
-20	36.235	36.233	36.232
-10	36.223	36.222	36.221
0	36.217	36.216	36.216
10	36.212	36.211	36.212
25	36.209	36.207	36.207
30	36.203	36.200	36.199
40	36.181	36.177	36.175
50	36.150	36.144	36.141
60	36.088	36.078	36.072
--	-	-	-



<b>COSEL</b>		Testing Circuitry Figure A
Model	PBA600F-36	
Item	Output Voltage Accuracy	
Object	+36V18A	

**1. Output Voltage Accuracy**

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 18A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

**2. Values**

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	264	0	36.231	±54	±0.2
Minimum Voltage	50	264	18	36.124		




<b>Model</b> PBA600F-36		Temperature 25°C Testing Circuitry Figure A																						
<b>Item</b>	Time Lapse Drift																							
<b>Object</b>	+36V18A																							
<b>1.Graph</b>   <p style="text-align: center;">Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<b>2.Values</b>  <table border="1" data-bbox="885 492 1268 1041"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>36.184</td></tr> <tr><td>0.5</td><td>36.157</td></tr> <tr><td>1.0</td><td>36.157</td></tr> <tr><td>2.0</td><td>36.157</td></tr> <tr><td>3.0</td><td>36.157</td></tr> <tr><td>4.0</td><td>36.157</td></tr> <tr><td>5.0</td><td>36.157</td></tr> <tr><td>6.0</td><td>36.157</td></tr> <tr><td>7.0</td><td>36.157</td></tr> <tr><td>8.0</td><td>36.157</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	36.184	0.5	36.157	1.0	36.157	2.0	36.157	3.0	36.157	4.0	36.157	5.0	36.157	6.0	36.157	7.0	36.157	8.0	36.157
Time since start [H]	Output Voltage [V]																							
0.0	36.184																							
0.5	36.157																							
1.0	36.157																							
2.0	36.157																							
3.0	36.157																							
4.0	36.157																							
5.0	36.157																							
6.0	36.157																							
7.0	36.157																							
8.0	36.157																							
<p>* The characteristic of AC200V is equal.</p>																								




Model	PBA600F-36	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+36V18A		

1. Graph




2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		335.5	10.5	346.0	25.6	25.8
200 V		222.5	10.5	233.0	31.6	25.9





Model	PBA600F-36	Temperature	25°C
Item	Hold-Up Time	Testing Circuitry	Figure A
Object	+36V18A		



2. Values

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
77	44	16
85	46	18
100	49	21
120	52	23
200	57	27
230	57	28
264	58	28
280	58	28
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.



<p><b>Model</b> PBA600F-36</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p><b>Item</b> Instantaneous Interruption Compensation</p>																																																					
<p><b>Object</b> +36V18A</p>																																																					
<p>1.Graph</p> <p>                     —△— Input Volt. 100V                      - - - □ - - - Input Volt. 200V                      - · - ○ - · - - Input Volt. 230V                 </p> <p>Instantaneous Compensation Time [mS]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>55</td><td>146</td><td>151</td></tr> <tr><td>6.0</td><td>34</td><td>63</td><td>80</td></tr> <tr><td>9.0</td><td>34</td><td>36</td><td>54</td></tr> <tr><td>12.0</td><td>34</td><td>36</td><td>37</td></tr> <tr><td>15.0</td><td>27</td><td>22</td><td>17</td></tr> <tr><td>18.0</td><td>21</td><td>16</td><td>14</td></tr> <tr><td>19.8</td><td>18</td><td>11</td><td>11</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [mS]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	3.0	55	146	151	6.0	34	63	80	9.0	34	36	54	12.0	34	36	37	15.0	27	22	17	18.0	21	16	14	19.8	18	11	11	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [mS]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
3.0	55	146	151																																																		
6.0	34	63	80																																																		
9.0	34	36	54																																																		
12.0	34	36	37																																																		
15.0	27	22	17																																																		
18.0	21	16	14																																																		
19.8	18	11	11																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



<b>Model</b>		PBA600F-36		Testing Circuitry Figure A																																						
<b>Item</b>		Minimum Input Voltage for Regulated Output Voltage																																								
<b>Object</b>		+36V18A																																								
1. Graph			2. Values																																							
<p style="text-align: center;"> <span style="margin-right: 20px;">---□---</span> Load 50%  <span>—△—</span> Load 100%         </p>			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-30</td><td>70</td><td>71</td></tr> <tr><td>-20</td><td>70</td><td>71</td></tr> <tr><td>-10</td><td>70</td><td>71</td></tr> <tr><td>0</td><td>70</td><td>71</td></tr> <tr><td>10</td><td>70</td><td>71</td></tr> <tr><td>25</td><td>70</td><td>71</td></tr> <tr><td>30</td><td>70</td><td>71</td></tr> <tr><td>40</td><td>70</td><td>71</td></tr> <tr><td>50</td><td>70</td><td>71</td></tr> <tr><td>60</td><td>70</td><td>71</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-30	70	71	-20	70	71	-10	70	71	0	70	71	10	70	71	25	70	71	30	70	71	40	70	71	50	70	71	60	70	71	-	-	-
Ambient Temperature [°C]	Input Voltage [V]																																									
	Load 50%	Load 100%																																								
-30	70	71																																								
-20	70	71																																								
-10	70	71																																								
0	70	71																																								
10	70	71																																								
25	70	71																																								
30	70	71																																								
40	70	71																																								
50	70	71																																								
60	70	71																																								
-	-	-																																								
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																										




<b>Model</b> PBA600F-36		Temperature 25°C Testing Circuitry Figure A																																												
<b>Item</b>	Overcurrent Protection																																													
<b>Object</b>	+36V18A																																													
<p>1. Graph</p> <div style="text-align: right;"> <p>————— Input Volt. 100V</p> <p>————— Input Volt. 200V</p> </div> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 23V to 0V.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>36.0</td><td>22.02</td><td>21.98</td></tr> <tr><td>34.2</td><td>21.95</td><td>21.88</td></tr> <tr><td>32.4</td><td>21.94</td><td>21.87</td></tr> <tr><td>28.8</td><td>22.12</td><td>22.38</td></tr> <tr><td>25.2</td><td>22.51</td><td>22.43</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	36.0	22.02	21.98	34.2	21.95	21.88	32.4	21.94	21.87	28.8	22.12	22.38	25.2	22.51	22.43	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																													
	Input Volt. 100[V]	Input Volt. 200[V]																																												
36.0	22.02	21.98																																												
34.2	21.95	21.88																																												
32.4	21.94	21.87																																												
28.8	22.12	22.38																																												
25.2	22.51	22.43																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												



Model	PBA600F-36
Item	Overvoltage Protection
Object	+36V18A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-30	46.63	46.63
-20	46.63	46.63
-10	46.63	46.63
0	46.75	46.75
10	46.75	46.75
25	46.75	46.75
30	46.75	46.75
40	46.87	46.87
50	46.87	46.87
60	46.87	46.87
-	-	-




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )