



# TEST DATA OF PBA75F-12

Regulated DC Power Supply  
Apr.8. 2004

Approved by : Kuniaki Nagahara  
Kuniaki Nagahara Design Manager

Prepared by : Akito Jobaji  
Akito Jobaji Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Overvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24

(Final Page 24)

**COSEL**

Model	PBA75F-12	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>—▲— Input Volt. 100V        - - -□- Input Volt. 200V        - - -○- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.073</td><td>0.051</td><td>0.048</td></tr> <tr><td>1.20</td><td>0.229</td><td>0.158</td><td>0.156</td></tr> <tr><td>2.40</td><td>0.389</td><td>0.228</td><td>0.214</td></tr> <tr><td>3.60</td><td>0.554</td><td>0.303</td><td>0.279</td></tr> <tr><td>4.80</td><td>0.724</td><td>0.383</td><td>0.347</td></tr> <tr><td>6.00</td><td>0.897</td><td>0.464</td><td>0.418</td></tr> <tr><td>6.30</td><td>0.941</td><td>0.484</td><td>0.436</td></tr> <tr><td>6.93</td><td>1.034</td><td>0.528</td><td>0.472</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.00	0.073	0.051	0.048	1.20	0.229	0.158	0.156	2.40	0.389	0.228	0.214	3.60	0.554	0.303	0.279	4.80	0.724	0.383	0.347	6.00	0.897	0.464	0.418	6.30	0.941	0.484	0.436	6.93	1.034	0.528	0.472	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																			
0.00	0.073	0.051	0.048																																																			
1.20	0.229	0.158	0.156																																																			
2.40	0.389	0.228	0.214																																																			
3.60	0.554	0.303	0.279																																																			
4.80	0.724	0.383	0.347																																																			
6.00	0.897	0.464	0.418																																																			
6.30	0.941	0.484	0.436																																																			
6.93	1.034	0.528	0.472																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.073</td><td>0.051</td><td>0.048</td></tr> <tr><td>1.20</td><td>0.229</td><td>0.158</td><td>0.156</td></tr> <tr><td>2.40</td><td>0.389</td><td>0.228</td><td>0.214</td></tr> <tr><td>3.60</td><td>0.554</td><td>0.303</td><td>0.279</td></tr> <tr><td>4.80</td><td>0.724</td><td>0.383</td><td>0.347</td></tr> <tr><td>6.00</td><td>0.897</td><td>0.464</td><td>0.418</td></tr> <tr><td>6.30</td><td>0.941</td><td>0.484</td><td>0.436</td></tr> <tr><td>6.93</td><td>1.034</td><td>0.528</td><td>0.472</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.073	0.051	0.048	1.20	0.229	0.158	0.156	2.40	0.389	0.228	0.214	3.60	0.554	0.303	0.279	4.80	0.724	0.383	0.347	6.00	0.897	0.464	0.418	6.30	0.941	0.484	0.436	6.93	1.034	0.528	0.472	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.073	0.051	0.048																																																			
1.20	0.229	0.158	0.156																																																			
2.40	0.389	0.228	0.214																																																			
3.60	0.554	0.303	0.279																																																			
4.80	0.724	0.383	0.347																																																			
6.00	0.897	0.464	0.418																																																			
6.30	0.941	0.484	0.436																																																			
6.93	1.034	0.528	0.472																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

<p><b>Model</b></p> <p><b>Item</b></p> <p><b>Object</b></p>	<p><b>PBA75F-12</b></p> <p><b>Temperature</b> 25°C</p> <p><b>Testing Circuitry</b> Figure A</p>																																																				
	1. Graph	<p>—▲— Input Volt. 100V</p> <p>- - □ - - Input Volt. 200V</p> <p>- - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.8</td><td>4.0</td><td>5.0</td></tr> <tr><td>1.20</td><td>21.9</td><td>22.0</td><td>23.0</td></tr> <tr><td>2.40</td><td>38.3</td><td>38.0</td><td>38.0</td></tr> <tr><td>3.60</td><td>55.0</td><td>54.1</td><td>55.0</td></tr> <tr><td>4.80</td><td>72.2</td><td>70.5</td><td>71.0</td></tr> <tr><td>6.00</td><td>89.6</td><td>87.1</td><td>87.0</td></tr> <tr><td>6.30</td><td>94.0</td><td>91.2</td><td>91.0</td></tr> <tr><td>6.93</td><td>103.4</td><td>100.2</td><td>99.9</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0.00	4.8	4.0	5.0	1.20	21.9	22.0	23.0	2.40	38.3	38.0	38.0	3.60	55.0	54.1	55.0	4.80	72.2	70.5	71.0	6.00	89.6	87.1	87.0	6.30	94.0	91.2	91.0	6.93	103.4	100.2	99.9															
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																		
0.00	4.8	4.0	5.0																																																		
1.20	21.9	22.0	23.0																																																		
2.40	38.3	38.0	38.0																																																		
3.60	55.0	54.1	55.0																																																		
4.80	72.2	70.5	71.0																																																		
6.00	89.6	87.1	87.0																																																		
6.30	94.0	91.2	91.0																																																		
6.93	103.4	100.2	99.9																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.8</td><td>4.0</td><td>5.0</td></tr> <tr><td>1.20</td><td>21.9</td><td>22.0</td><td>23.0</td></tr> <tr><td>2.40</td><td>38.3</td><td>38.0</td><td>38.0</td></tr> <tr><td>3.60</td><td>55.0</td><td>54.1</td><td>55.0</td></tr> <tr><td>4.80</td><td>72.2</td><td>70.5</td><td>71.0</td></tr> <tr><td>6.00</td><td>89.6</td><td>87.1</td><td>87.0</td></tr> <tr><td>6.30</td><td>94.0</td><td>91.2</td><td>91.0</td></tr> <tr><td>6.93</td><td>103.4</td><td>100.2</td><td>99.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	4.8	4.0	5.0	1.20	21.9	22.0	23.0	2.40	38.3	38.0	38.0	3.60	55.0	54.1	55.0	4.80	72.2	70.5	71.0	6.00	89.6	87.1	87.0	6.30	94.0	91.2	91.0	6.93	103.4	100.2	99.9	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	4.8	4.0	5.0																																																		
1.20	21.9	22.0	23.0																																																		
2.40	38.3	38.0	38.0																																																		
3.60	55.0	54.1	55.0																																																		
4.80	72.2	70.5	71.0																																																		
6.00	89.6	87.1	87.0																																																		
6.30	94.0	91.2	91.0																																																		
6.93	103.4	100.2	99.9																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

**COSEL**

Model	PBA75F-12	Temperature	25°C																																		
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																		
Object	—	2. Values																																			
1. Graph																																					
<p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing from approximately 78% at 75V to about 80% at 280V. A diagonal line from (75, 78) to (280, 78) represents the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>76.8</td> <td>78.6</td> </tr> <tr> <td>85</td> <td>77.5</td> <td>79.8</td> </tr> <tr> <td>100</td> <td>78.2</td> <td>81.0</td> </tr> <tr> <td>120</td> <td>79.2</td> <td>81.9</td> </tr> <tr> <td>200</td> <td>79.2</td> <td>83.4</td> </tr> <tr> <td>230</td> <td>79.2</td> <td>83.6</td> </tr> <tr> <td>264</td> <td>77.6</td> <td>83.6</td> </tr> <tr> <td>280</td> <td>79.2</td> <td>83.6</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	76.8	78.6	85	77.5	79.8	100	78.2	81.0	120	79.2	81.9	200	79.2	83.4	230	79.2	83.6	264	77.6	83.6	280	79.2	83.6	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
75	76.8	78.6																																			
85	77.5	79.8																																			
100	78.2	81.0																																			
120	79.2	81.9																																			
200	79.2	83.4																																			
230	79.2	83.6																																			
264	77.6	83.6																																			
280	79.2	83.6																																			
--	-	-																																			
Note: Slanted line shows the range of the rated input voltage.																																					

**COSEL**

Model	PBA75F-12																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1.Graph	—▲— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V																																																					
<p>The graph plots Efficiency [%] on the Y-axis (30 to 86) against Load Current [A] on the X-axis (0 to 6). Three data series are shown: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show efficiency increasing with load current. A slanted line is drawn through the 100V curve between approximately 3.5A and 5.5A, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency 100V [%]</th> <th>Efficiency 200V [%]</th> <th>Efficiency 230V [%]</th> </tr> </thead> <tbody> <tr><td>1.20</td><td>66.1</td><td>65.8</td><td>65.8</td></tr> <tr><td>2.40</td><td>75.6</td><td>76.2</td><td>76.3</td></tr> <tr><td>3.60</td><td>79.0</td><td>80.3</td><td>80.5</td></tr> <tr><td>4.80</td><td>80.3</td><td>82.3</td><td>82.8</td></tr> <tr><td>6.00</td><td>80.8</td><td>83.2</td><td>83.3</td></tr> <tr><td>6.30</td><td>81.0</td><td>83.3</td><td>83.6</td></tr> <tr><td>6.93</td><td>81.0</td><td>83.6</td><td>83.8</td></tr> </tbody> </table>			Load Current [A]	Efficiency 100V [%]	Efficiency 200V [%]	Efficiency 230V [%]	1.20	66.1	65.8	65.8	2.40	75.6	76.2	76.3	3.60	79.0	80.3	80.5	4.80	80.3	82.3	82.8	6.00	80.8	83.2	83.3	6.30	81.0	83.3	83.6	6.93	81.0	83.6	83.8																				
Load Current [A]	Efficiency 100V [%]	Efficiency 200V [%]	Efficiency 230V [%]																																																			
1.20	66.1	65.8	65.8																																																			
2.40	75.6	76.2	76.3																																																			
3.60	79.0	80.3	80.5																																																			
4.80	80.3	82.3	82.8																																																			
6.00	80.8	83.2	83.3																																																			
6.30	81.0	83.3	83.6																																																			
6.93	81.0	83.6	83.8																																																			
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.20</td><td>66.1</td><td>65.8</td><td>65.8</td></tr> <tr><td>2.40</td><td>75.6</td><td>76.2</td><td>76.3</td></tr> <tr><td>3.60</td><td>79.0</td><td>80.3</td><td>80.5</td></tr> <tr><td>4.80</td><td>80.3</td><td>82.3</td><td>82.8</td></tr> <tr><td>6.00</td><td>80.8</td><td>83.2</td><td>83.3</td></tr> <tr><td>6.30</td><td>81.0</td><td>83.3</td><td>83.6</td></tr> <tr><td>6.93</td><td>81.0</td><td>83.6</td><td>83.8</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.20	66.1	65.8	65.8	2.40	75.6	76.2	76.3	3.60	79.0	80.3	80.5	4.80	80.3	82.3	82.8	6.00	80.8	83.2	83.3	6.30	81.0	83.3	83.6	6.93	81.0	83.6	83.8	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
1.20	66.1	65.8	65.8																																																			
2.40	75.6	76.2	76.3																																																			
3.60	79.0	80.3	80.5																																																			
4.80	80.3	82.3	82.8																																																			
6.00	80.8	83.2	83.3																																																			
6.30	81.0	83.3	83.6																																																			
6.93	81.0	83.6	83.8																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model	PBA75F-12																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Legend:</p> <ul style="list-style-type: none"> <li>Load 50% (dashed line with squares)</li> <li>Load 100% (solid line with triangles)</li> </ul> <p>Input Voltage [V]</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.994</td><td>0.997</td></tr> <tr> <td>85</td><td>0.991</td><td>0.996</td></tr> <tr> <td>100</td><td>0.984</td><td>0.993</td></tr> <tr> <td>120</td><td>0.960</td><td>0.989</td></tr> <tr> <td>200</td><td>0.873</td><td>0.939</td></tr> <tr> <td>230</td><td>0.828</td><td>0.910</td></tr> <tr> <td>264</td><td>0.766</td><td>0.875</td></tr> <tr> <td>280</td><td>0.667</td><td>0.813</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.994	0.997	85	0.991	0.996	100	0.984	0.993	120	0.960	0.989	200	0.873	0.939	230	0.828	0.910	264	0.766	0.875	280	0.667	0.813	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.994	0.997																																
85	0.991	0.996																																
100	0.984	0.993																																
120	0.960	0.989																																
200	0.873	0.939																																
230	0.828	0.910																																
264	0.766	0.875																																
280	0.667	0.813																																
--	-	-																																


**COSEL**

Model	PBA75F-12
Item	Power Factor (by Load Current)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph

—△— Input Volt. 100V  
 - -□-- Input Volt. 200V  
 - -○-- Input Volt. 230V






## 2.Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.655	0.447	0.426
1.20	0.951	0.721	0.635
2.40	0.979	0.835	0.784
3.60	0.987	0.889	0.847
4.80	0.992	0.916	0.880
6.00	0.994	0.935	0.905
6.30	0.994	0.938	0.908
6.93	0.995	0.945	0.917
-	-	-	-
-	-	-	-
-	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	PBA75F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	—		





Model	PBA75F-12	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	<hr/>		

### 1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.16	0.26	0.30	Operation
	One of phase	0.24	0.45	0.53	stand by
IEC60950	Both phases	0.16	0.28	0.37	Operation
	One of phase	0.24	0.47	0.57	stand by

The value for "One phase" is the reference value only.

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	PBA75F-12
Item	Line Regulation
Object	+12V6.3A

**1. Graph**

--- □ --- Load 50%  
— △ — Load 100%

Input Voltage [V]	Output Voltage [V] (Load 50%)	Output Voltage [V] (Load 100%)
75	12.047	12.043
85	12.048	12.042
100	12.048	12.042
120	12.048	12.042
200	12.048	12.042
230	12.048	12.042
264	12.048	12.042
280	12.048	12.042

**Note:** Slanted line shows the range of the rated input voltage.

Temperature Testing Circuitry	25°C Figure A	
	Load 50%	Load 100%
75	12.047	12.043
85	12.048	12.042
100	12.048	12.042
120	12.048	12.042
200	12.048	12.042
230	12.048	12.042
264	12.048	12.042
280	12.048	12.042
--	-	-

**COSEL**

Model	PBA75F-12	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V6.3A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—○— Input Volt. 100V</li> <li>-□- Input Volt. 200V</li> <li>-△- Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.055</td><td>12.055</td><td>12.055</td></tr> <tr><td>1.20</td><td>12.053</td><td>12.053</td><td>12.052</td></tr> <tr><td>2.40</td><td>12.050</td><td>12.050</td><td>12.050</td></tr> <tr><td>3.60</td><td>12.048</td><td>12.048</td><td>12.048</td></tr> <tr><td>4.80</td><td>12.046</td><td>12.046</td><td>12.046</td></tr> <tr><td>6.00</td><td>12.044</td><td>12.044</td><td>12.043</td></tr> <tr><td>6.30</td><td>12.044</td><td>12.043</td><td>12.043</td></tr> <tr><td>6.93</td><td>12.042</td><td>12.042</td><td>12.042</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	12.055	12.055	12.055	1.20	12.053	12.053	12.052	2.40	12.050	12.050	12.050	3.60	12.048	12.048	12.048	4.80	12.046	12.046	12.046	6.00	12.044	12.044	12.043	6.30	12.044	12.043	12.043	6.93	12.042	12.042	12.042	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	12.055	12.055	12.055																																																			
1.20	12.053	12.053	12.052																																																			
2.40	12.050	12.050	12.050																																																			
3.60	12.048	12.048	12.048																																																			
4.80	12.046	12.046	12.046																																																			
6.00	12.044	12.044	12.043																																																			
6.30	12.044	12.043	12.043																																																			
6.93	12.042	12.042	12.042																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	PBA75F-12
Item	Dynamic Load Response
Object	+12V6.3A

Temperature 25°C  
Testing Circuitry Figure AInput Volt. 100 V  
Cycle 1000 ms


Load Current




Min. Load (0A) ↔

Load 100% (6.3A)

100 mV/div



10 ms/div




10 ms/div


Min. Load (0A) ↔

Load 50% (3.15A)

100 mV/div



10 ms/div



10 ms/div


\* The characteristic of AC200V is equal.

COSEL

Model	PBA75F-12
Item	Ripple Voltage (by Load Current)
Object	+12V6.3A

Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	10	10
1.20	30	30
2.40	30	30
3.60	30	30
4.80	30	30
6.00	30	30
6.30	30	30
6.93	30	30
-	-	-
-	-	-
-	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line  
 T2: Due to Switching




Fig. Complex Ripple Wave Form

# COSEL

Model	PBA75F-12	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure A																																						
Object	+12V6.3A																																								
1.Graph	2.Values																																								
	<p>—▲— Input Volt. 100V        - -○- - Input Volt. 200V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 100V)</th> <th>Ripple-Noise [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>20</td></tr> <tr><td>1.20</td><td>35</td><td>35</td></tr> <tr><td>2.40</td><td>40</td><td>40</td></tr> <tr><td>3.60</td><td>40</td><td>40</td></tr> <tr><td>4.80</td><td>40</td><td>40</td></tr> <tr><td>6.00</td><td>40</td><td>40</td></tr> <tr><td>6.30</td><td>40</td><td>40</td></tr> <tr><td>6.93</td><td>40</td><td>40</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)	0.00	20	20	1.20	35	35	2.40	40	40	3.60	40	40	4.80	40	40	6.00	40	40	6.30	40	40	6.93	40	40											
Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)																																							
0.00	20	20																																							
1.20	35	35																																							
2.40	40	40																																							
3.60	40	40																																							
4.80	40	40																																							
6.00	40	40																																							
6.30	40	40																																							
6.93	40	40																																							
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>20</td></tr> <tr><td>1.20</td><td>35</td><td>35</td></tr> <tr><td>2.40</td><td>40</td><td>40</td></tr> <tr><td>3.60</td><td>40</td><td>40</td></tr> <tr><td>4.80</td><td>40</td><td>40</td></tr> <tr><td>6.00</td><td>40</td><td>40</td></tr> <tr><td>6.30</td><td>40</td><td>40</td></tr> <tr><td>6.93</td><td>40</td><td>40</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	20	20	1.20	35	35	2.40	40	40	3.60	40	40	4.80	40	40	6.00	40	40	6.30	40	40	6.93	40	40	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.00	20	20																																							
1.20	35	35																																							
2.40	40	40																																							
3.60	40	40																																							
4.80	40	40																																							
6.00	40	40																																							
6.30	40	40																																							
6.93	40	40																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
	<p>Measured by 20 MHz Oscilloscope.        Ripple-Noise is shown as p-p in the figure below.        Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line        T2: Due to Switching</p> <p>Ripple-Noise [mVp-p]</p>																																								
	<p>Fig. Complex Ripple Wave Form</p>																																								

**COSEL**


Model PBA75F-12

Item Ripple Voltage (by Ambient Temp.)

Object +12V6.3A

1. Graph

---□--- Input Volt. 100V  
—△— Input Volt. 200V



Measured by 20 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	130	130
-10	55	55
0	40	40
25	30	30
50	25	25
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—
—	—	—

**COSEL**

Model      PBA75F-12																																																				
Item      Ambient Temperature Drift	<b>Testing Circuitry   Figure A</b>																																																			
Object      +12V6.3A																																																				
1.Graph  <p>Input Volt. 100V Input Volt. 200V Input Volt. 230V</p>	2.Values																																																			
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>12.030</td><td>12.030</td><td>12.030</td></tr> <tr> <td>-10</td><td>12.033</td><td>12.033</td><td>12.033</td></tr> <tr> <td>0</td><td>12.037</td><td>12.037</td><td>12.037</td></tr> <tr> <td>10</td><td>12.041</td><td>12.040</td><td>12.041</td></tr> <tr> <td>25</td><td>12.046</td><td>12.046</td><td>12.045</td></tr> <tr> <td>30</td><td>12.047</td><td>12.047</td><td>12.047</td></tr> <tr> <td>40</td><td>12.047</td><td>12.047</td><td>12.046</td></tr> <tr> <td>50</td><td>12.045</td><td>12.045</td><td>12.044</td></tr> <tr> <td>60</td><td>12.040</td><td>12.040</td><td>12.040</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	12.030	12.030	12.030	-10	12.033	12.033	12.033	0	12.037	12.037	12.037	10	12.041	12.040	12.041	25	12.046	12.046	12.045	30	12.047	12.047	12.047	40	12.047	12.047	12.046	50	12.045	12.045	12.044	60	12.040	12.040	12.040	-	-	-	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																			
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																	
-20	12.030	12.030	12.030																																																	
-10	12.033	12.033	12.033																																																	
0	12.037	12.037	12.037																																																	
10	12.041	12.040	12.041																																																	
25	12.046	12.046	12.045																																																	
30	12.047	12.047	12.047																																																	
40	12.047	12.047	12.046																																																	
50	12.045	12.045	12.044																																																	
60	12.040	12.040	12.040																																																	
-	-	-	-																																																	
-	-	-	-																																																	
Note: Slanted line shows the range of the rated ambient temperature.																																																				



Model	PBA75F-12	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V6.3A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 6.3A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	40	85	0	12.059		
Minimum Voltage	-10	200	6.3	12.033	±13	±0.1

**COSEL**

Model	PBA75F-12	Temperature Testing Circuitry	25°C																						
Item	Time Lapse Drift		Figure A																						
Object	+12V6.3A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.044</td></tr> <tr><td>0.5</td><td>12.042</td></tr> <tr><td>1.0</td><td>12.042</td></tr> <tr><td>2.0</td><td>12.042</td></tr> <tr><td>3.0</td><td>12.042</td></tr> <tr><td>4.0</td><td>12.043</td></tr> <tr><td>5.0</td><td>12.043</td></tr> <tr><td>6.0</td><td>12.043</td></tr> <tr><td>7.0</td><td>12.043</td></tr> <tr><td>8.0</td><td>12.043</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.044	0.5	12.042	1.0	12.042	2.0	12.042	3.0	12.042	4.0	12.043	5.0	12.043	6.0	12.043	7.0	12.043	8.0	12.043
Time since start [H]	Output Voltage [V]																								
0.0	12.044																								
0.5	12.042																								
1.0	12.042																								
2.0	12.042																								
3.0	12.042																								
4.0	12.043																								
5.0	12.043																								
6.0	12.043																								
7.0	12.043																								
8.0	12.043																								

COSEL


Model PBA75F-12

Item Rise and Fall Time

Object +12V6.3A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[mS]
100 V		324.0	11.5	335.5	27.2	12.3	
200 V		269.0	12.0	281.0	31.3	12.3	



**COSEL**

<b>Model</b>	PBA75F-12
<b>Item</b>	<b>Hold-Up Time</b>
<b>Object</b>	+12V6.3A

**1.Graph**

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C  
 Testing Circuitry Figure A
**2.Values**

Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
75	50	21
85	52	23
100	55	25
120	57	27
200	60	29
230	61	30
264	62	30
280	62	30
--	-	-


# COSEL

Model	PBA75F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+12V6.3A																																																					
1.Graph	<p>—▲— Input Volt. 100V      - - - □ - - Input Volt. 200V      - - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>1.20</td><td>130</td><td>123</td><td>139</td></tr> <tr><td>2.40</td><td>71</td><td>72</td><td>72</td></tr> <tr><td>3.60</td><td>47</td><td>47</td><td>45</td></tr> <tr><td>4.80</td><td>34</td><td>38</td><td>38</td></tr> <tr><td>6.00</td><td>26</td><td>30</td><td>30</td></tr> <tr><td>6.30</td><td>23</td><td>29</td><td>30</td></tr> <tr><td>6.93</td><td>22</td><td>22</td><td>23</td></tr> </tbody> </table>			Load Current [A]	100V [ms]	200V [ms]	230V [ms]	1.20	130	123	139	2.40	71	72	72	3.60	47	47	45	4.80	34	38	38	6.00	26	30	30	6.30	23	29	30	6.93	22	22	23																			
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																			
1.20	130	123	139																																																			
2.40	71	72	72																																																			
3.60	47	47	45																																																			
4.80	34	38	38																																																			
6.00	26	30	30																																																			
6.30	23	29	30																																																			
6.93	22	22	23																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.20</td><td>130</td><td>123</td><td>139</td></tr> <tr><td>2.40</td><td>71</td><td>72</td><td>72</td></tr> <tr><td>3.60</td><td>47</td><td>47</td><td>45</td></tr> <tr><td>4.80</td><td>34</td><td>38</td><td>38</td></tr> <tr><td>6.00</td><td>26</td><td>30</td><td>30</td></tr> <tr><td>6.30</td><td>23</td><td>29</td><td>30</td></tr> <tr><td>6.93</td><td>22</td><td>22</td><td>23</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.20	130	123	139	2.40	71	72	72	3.60	47	47	45	4.80	34	38	38	6.00	26	30	30	6.30	23	29	30	6.93	22	22	23	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [mS]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
1.20	130	123	139																																																			
2.40	71	72	72																																																			
3.60	47	47	45																																																			
4.80	34	38	38																																																			
6.00	26	30	30																																																			
6.30	23	29	30																																																			
6.93	22	22	23																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

**COSEL**

Model	PBA75F-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V6.3A

### 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

### Testing Circuitry Figure A

### 2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	46	62
-10	45	60
0	45	61
10	45	61
25	45	59
30	45	60
40	45	60
50	45	60
60	45	61
--	-	-
--	-	-

# COSEL

Model	PBA75F-12	Temperature Testing Circuitry	25°C Figure A																																												
Item	Overcurrent Protection																																														
Object	+12V6.3A																																														
1. Graph			2. Values																																												
<p>Input Volt. 100V</p> <p>Input Volt. 200V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>6.71</td><td>6.71</td></tr> <tr><td>11.4</td><td>7.85</td><td>7.85</td></tr> <tr><td>10.8</td><td>7.89</td><td>7.88</td></tr> <tr><td>9.6</td><td>7.92</td><td>7.92</td></tr> <tr><td>8.4</td><td>7.92</td><td>7.90</td></tr> <tr><td>7.2</td><td>8.07</td><td>8.05</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	12.0	6.71	6.71	11.4	7.85	7.85	10.8	7.89	7.88	9.6	7.92	7.92	8.4	7.92	7.90	7.2	8.07	8.05	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																														
	Input Volt. 100[V]	Input Volt. 200[V]																																													
12.0	6.71	6.71																																													
11.4	7.85	7.85																																													
10.8	7.89	7.88																																													
9.6	7.92	7.92																																													
8.4	7.92	7.90																																													
7.2	8.07	8.05																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													

**COSEL**

Model	PBA75F-12
Item	Ovvoltage Protection
Object	+12V6.3A

**1. Graph**

Note: Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure A****2. Values**

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	15.98	15.91
-10	16.05	16.05
0	16.19	16.12
10	16.26	16.26
25	16.40	16.40
30	16.47	16.47
40	16.54	16.54
50	16.68	16.61
60	16.75	16.75
--	-	-
--	-	-




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )