



## ***EXTRA TEST DATA OF PBA75F-12***

*Regulated DC Power Supply*  
Jun, 08, 2020

**COSEL CO.,LTD.**






## CONTENTS

1.Inrush Current (enlargement) . . . . .	1
2.Dynamic Line Regulation . . . . .	2
3.Ovvervoltage Protection (waveform) . . . . .	3
4.Hiccup cycle (by Overcurrent Protection) . . . . .	4
5.Power Consumption (by Input Voltage) . . . . .	5
6.Figure of Testing Circuitry . . . . .	6

(Final Page 6)




**COSEL**

Model	PBA75F-12	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		



Model	PBA75F-12
Item	Dynamic Line Regulation
Object	_____

Temperature 25°C  
Testing Circuitry A




**COSEL**



Model	PBA75F-12	Temperature 25°C
Item	Over Voltage Protection	Testing Circuitry A
Object	_____	Input Voltage : 100V

Output  
Voltage  
[2V/div]

GND




Load : 0%  
Overvoltage protection  
value : 17.1VTime  
[40ms/div]Output  
Voltage  
[2V/div]

GND

Load : 100%  
Overvoltage protection  
value : 17.1VTime  
[20ms/div]

**COSEL**

Model	PBA75F-12	Temperature Testing Circuitry	25°C A
Item	Hiccup cycle (by Overcurrent Protection)		
Object	Load : Short		

Output Current  
[2A/div]Output Current  
[2A/div]

**COSEL**


Model	PBA75F-12
Item	Input voltage - Power consumption
Object	_____

Temperature 25°C  
Testing Circuitry -

Load : 0%

## 2.Values

Input voltage [V]	Power consumption [W]
85	0.97
100	0.93
115	0.95
200	1.22
230	1.34
264	1.82



Reducing standby power is possible by OFF signal of the remote control.




Figure A