



## ***EXTRA TEST DATA OF PBA75F-36***

*Regulated DC Power Supply*  
Jun, 08, 2020

**COSEL CO.,LTD.**






## CONTENTS

1.Inrush Current (enlargement) . . . . .	1
2.Dynamic Line Regulation . . . . .	2
3.Ovvervoltage Protection (waveform) . . . . .	3
4.Hiccup cycle (by Overcurrent Protection) . . . . .	4
5.Power Consumption (by Input Voltage) . . . . .	5
6.Figure of Testing Circuitry . . . . .	6

(Final Page 6)




**COSEL**

Model	PBA75F-36	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		






**COSEL**

Model	PBA75F-36	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object	_____		






**COSEL**

Model	PBA75F-36	Temperature 25°C
Item	Over Voltage Protection	Testing Circuitry A
Object	_____	Input Voltage : 100V

Output  
Voltage  
[10V/div]Load : 0%  
Overvoltage protection  
value : 48.9VOutput  
Voltage  
[10V/div]Load : 100%  
Overvoltage protection  
value : 48.7V

**COSEL**

Model	PBA75F-36	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object	Load : Short		

Output  
Current  
[1A/div]Output  
Current  
[1A/div]

**COSEL**


Model	PBA75F-36
Item	Input voltage - Power consumption
Object	_____

Temperature 25°C  
Testing Circuitry -

Load : 0%

## 2.Values

Input voltage [V]	Power consumption [W]
85	0.91
100	0.89
115	0.92
200	1.18
230	1.32
264	2.14



Reducing standby power is possible by OFF signal of the remote control.




Figure A