



TEST DATA OF PBW50F-15

Regulated DC Power Supply
Sep 29, 2005

Approved by : Kuniaki Nagahara
Kuniaki Nagahara Design Manager

Prepared by : Atsushi Yoshiyama
Atsushi Yoshiyama Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	13
13. Ripple-Noise	15
14. Ripple Voltage (by Ambient Temperature)	17
15. Ambient Temperature Drift	18
16. Output Voltage Accuracy	19
17. Time Lapse Drift	20
18. Rise and Fall Time	21
19. Hold-Up Time	23
20. Instantaneous Interruption Compensation	25
21. Minimum Input Voltage for Regulated Output Voltage	27
22. Overcurrent Protection	28
23. Overvoltage Protection	29
24. Figure of Testing Circuitry	30

(Final Page 30)

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																														
Item	Input Current (by Load Current)																																
Object	_____	2.Values																															
1.Graph	<p>—△— Input Volt. 100V - -□-- Input Volt. 200V - -○-- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Current [A] (100V)</th> <th>Input Current [A] (200V)</th> <th>Input Current [A] (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.062</td><td>0.055</td><td>0.052</td></tr> <tr><td>20</td><td>0.176</td><td>0.121</td><td>0.118</td></tr> <tr><td>40</td><td>0.286</td><td>0.170</td><td>0.161</td></tr> <tr><td>60</td><td>0.399</td><td>0.222</td><td>0.204</td></tr> <tr><td>80</td><td>0.513</td><td>0.275</td><td>0.250</td></tr> <tr><td>100</td><td>0.630</td><td>0.329</td><td>0.298</td></tr> <tr><td>110</td><td>0.689</td><td>0.358</td><td>0.322</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A] (100V)	Input Current [A] (200V)	Input Current [A] (230V)	0	0.062	0.055	0.052	20	0.176	0.121	0.118	40	0.286	0.170	0.161	60	0.399	0.222	0.204	80	0.513	0.275	0.250	100	0.630	0.329	0.298	110	0.689	0.358	0.322
Load Ration [%]	Input Current [A] (100V)	Input Current [A] (200V)	Input Current [A] (230V)																														
0	0.062	0.055	0.052																														
20	0.176	0.121	0.118																														
40	0.286	0.170	0.161																														
60	0.399	0.222	0.204																														
80	0.513	0.275	0.250																														
100	0.630	0.329	0.298																														
110	0.689	0.358	0.322																														

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 100V - -□- - Input Volt. 200V - -○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>20</td><td>16.78</td><td>17.40</td><td>17.70</td></tr> <tr><td>40</td><td>33.56</td><td>34.80</td><td>35.40</td></tr> <tr><td>60</td><td>50.34</td><td>52.20</td><td>53.10</td></tr> <tr><td>80</td><td>67.12</td><td>69.60</td><td>71.40</td></tr> <tr><td>100</td><td>83.90</td><td>86.30</td><td>88.30</td></tr> <tr><td>110</td><td>92.28</td><td>95.30</td><td>97.30</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0	0	0	0	20	16.78	17.40	17.70	40	33.56	34.80	35.40	60	50.34	52.20	53.10	80	67.12	69.60	71.40	100	83.90	86.30	88.30	110	92.28	95.30	97.30																					
Load Ration [%]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																			
0	0	0	0																																																			
20	16.78	17.40	17.70																																																			
40	33.56	34.80	35.40																																																			
60	50.34	52.20	53.10																																																			
80	67.12	69.60	71.40																																																			
100	83.90	86.30	88.30																																																			
110	92.28	95.30	97.30																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>4.71</td><td>5.30</td><td>5.10</td></tr> <tr><td>20</td><td>16.78</td><td>17.40</td><td>17.70</td></tr> <tr><td>40</td><td>28.05</td><td>28.30</td><td>28.50</td></tr> <tr><td>60</td><td>39.60</td><td>39.20</td><td>39.40</td></tr> <tr><td>80</td><td>51.20</td><td>50.30</td><td>50.40</td></tr> <tr><td>100</td><td>62.90</td><td>61.50</td><td>61.50</td></tr> <tr><td>110</td><td>68.90</td><td>67.50</td><td>67.20</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	4.71	5.30	5.10	20	16.78	17.40	17.70	40	28.05	28.30	28.50	60	39.60	39.20	39.40	80	51.20	50.30	50.40	100	62.90	61.50	61.50	110	68.90	67.50	67.20	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	4.71	5.30	5.10																																																			
20	16.78	17.40	17.70																																																			
40	28.05	28.30	28.50																																																			
60	39.60	39.20	39.40																																																			
80	51.20	50.30	50.40																																																			
100	62.90	61.50	61.50																																																			
110	68.90	67.50	67.20																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	PBW50F-15	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object																																			
1.Graph			2.Values																																
<p>The graph plots Efficiency [%] from 30 to 86 against Input Voltage [V] from 50 to 300. Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. A slanted line indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>75.6</td> <td>78.9</td> </tr> <tr> <td>85</td> <td>76.5</td> <td>80.6</td> </tr> <tr> <td>100</td> <td>77.4</td> <td>82.0</td> </tr> <tr> <td>120</td> <td>77.7</td> <td>83.0</td> </tr> <tr> <td>200</td> <td>77.4</td> <td>83.9</td> </tr> <tr> <td>230</td> <td>76.7</td> <td>84.1</td> </tr> <tr> <td>264</td> <td>76.5</td> <td>84.0</td> </tr> <tr> <td>280</td> <td>76.3</td> <td>83.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	75.6	78.9	85	76.5	80.6	100	77.4	82.0	120	77.7	83.0	200	77.4	83.9	230	76.7	84.1	264	76.5	84.0	280	76.3	83.8	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	75.6	78.9																																	
85	76.5	80.6																																	
100	77.4	82.0																																	
120	77.7	83.0																																	
200	77.4	83.9																																	
230	76.7	84.1																																	
264	76.5	84.0																																	
280	76.3	83.8																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																													
Item	Efficiency (by Load Current)																															
Object	_____	2.Values																														
1.Graph	<p>—△— Input Volt. 100V - -□- - Input Volt. 200V - -○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>20</td><td>64.1</td><td>61.8</td><td>60.7</td></tr> <tr><td>40</td><td>74.6</td><td>74.0</td><td>73.5</td></tr> <tr><td>60</td><td>78.9</td><td>79.7</td><td>79.2</td></tr> <tr><td>80</td><td>80.9</td><td>82.4</td><td>82.2</td></tr> <tr><td>100</td><td>82.1</td><td>83.9</td><td>84.0</td></tr> <tr><td>110</td><td>82.4</td><td>84.1</td><td>84.5</td></tr> </tbody> </table>	Load Ration [%]		Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	20	64.1	61.8	60.7	40	74.6	74.0	73.5	60	78.9	79.7	79.2	80	80.9	82.4	82.2	100	82.1	83.9	84.0	110	82.4	84.1	84.5		
Load Ration [%]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																													
20	64.1	61.8	60.7																													
40	74.6	74.0	73.5																													
60	78.9	79.7	79.2																													
80	80.9	82.4	82.2																													
100	82.1	83.9	84.0																													
110	82.4	84.1	84.5																													

COSEL

Model	PBW50F-15
Item	Power Factor (by Input Voltage)
Object	—

1.Graph



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.997	0.999
85	0.997	0.999
100	0.987	0.998
120	0.973	0.992
200	0.860	0.933
230	0.811	0.896
264	0.733	0.858
280	0.684	0.844
--	-	-

COSEL

Model	PBW50F-15	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1. Graph		2. Values																																																				
<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.756</td><td>0.486</td><td>0.425</td></tr> <tr><td>20</td><td>0.953</td><td>0.716</td><td>0.651</td></tr> <tr><td>40</td><td>0.981</td><td>0.832</td><td>0.768</td></tr> <tr><td>60</td><td>0.992</td><td>0.883</td><td>0.838</td></tr> <tr><td>80</td><td>0.998</td><td>0.913</td><td>0.875</td></tr> <tr><td>100</td><td>0.998</td><td>0.933</td><td>0.898</td></tr> <tr><td>110</td><td>0.999</td><td>0.943</td><td>0.907</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.756	0.486	0.425	20	0.953	0.716	0.651	40	0.981	0.832	0.768	60	0.992	0.883	0.838	80	0.998	0.913	0.875	100	0.998	0.933	0.898	110	0.999	0.943	0.907	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.756	0.486	0.425																																																			
20	0.953	0.716	0.651																																																			
40	0.981	0.832	0.768																																																			
60	0.992	0.883	0.838																																																			
80	0.998	0.913	0.875																																																			
100	0.998	0.933	0.898																																																			
110	0.999	0.943	0.907																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL



Model	PBW50F-15	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		


1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
DEN-AN	Both phases	0.18	0.40	0.54	Operation
	One of phase	0.27	0.54	0.63	stand by
IEC60950	Both phases	0.18	0.40	0.54	Operation
	One of phase	0.27	0.54	0.63	stand by

The value for "One of phase" is the reference value only.

2. Condition



Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


COSEL

 Temperature 25°C
 Testing Circuitry Figure A
2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	15.123	15.064
85	15.123	15.064
100	15.123	15.064
120	15.123	15.064
200	15.123	15.064
230	15.123	15.064
264	15.124	15.065
280	15.124	15.065
--	-	-

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	-15.157	-15.105
85	-15.157	-15.105
100	-15.157	-15.104
120	-15.156	-15.105
200	-15.156	-15.105
230	-15.157	-15.105
264	-15.157	-15.105
280	-15.157	-15.105
--	-	-

COSELTemperature 25°C
Testing Circuitry Figure A

COSEL

COSEL

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage (by Load Current)																																								
Object	+15V1.7A																																								
1. Graph			2. Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.3</td><td>25</td><td>25</td></tr> <tr><td>0.7</td><td>30</td><td>30</td></tr> <tr><td>1.0</td><td>35</td><td>35</td></tr> <tr><td>1.4</td><td>35</td><td>35</td></tr> <tr><td>1.7</td><td>35</td><td>35</td></tr> <tr><td>1.9</td><td>35</td><td>35</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V : Rated output current 1</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	10	10	0.3	25	25	0.7	30	30	1.0	35	35	1.4	35	35	1.7	35	35	1.9	35	35	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.0	10	10																																							
0.3	25	25																																							
0.7	30	30																																							
1.0	35	35																																							
1.4	35	35																																							
1.7	35	35																																							
1.9	35	35																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig. Complex Ripple Wave Form</p>																																									

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage (by Load Current)																																								
Object	-15V1.7A																																								
1.Graph	<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0.0 to 2.0 A. Two curves are plotted: Input Volt. 100V (solid line with open circles) and Input Volt. 200V (dashed line with open circles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.3</td><td>15</td><td>15</td></tr> <tr><td>0.7</td><td>20</td><td>20</td></tr> <tr><td>1.0</td><td>20</td><td>20</td></tr> <tr><td>1.4</td><td>20</td><td>20</td></tr> <tr><td>1.7</td><td>20</td><td>20</td></tr> <tr><td>1.9</td><td>20</td><td>20</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0.0	10	10	0.3	15	15	0.7	20	20	1.0	20	20	1.4	20	20	1.7	20	20	1.9	20	20	-	-	-	-	-	-	-	-	-	-	-	-		
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																							
0.0	10	10																																							
0.3	15	15																																							
0.7	20	20																																							
1.0	20	20																																							
1.4	20	20																																							
1.7	20	20																																							
1.9	20	20																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.3</td><td>15</td><td>15</td></tr> <tr><td>0.7</td><td>20</td><td>20</td></tr> <tr><td>1.0</td><td>20</td><td>20</td></tr> <tr><td>1.4</td><td>20</td><td>20</td></tr> <tr><td>1.7</td><td>20</td><td>20</td></tr> <tr><td>1.9</td><td>20</td><td>20</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V : Rated output current .</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	10	10	0.3	15	15	0.7	20	20	1.0	20	20	1.4	20	20	1.7	20	20	1.9	20	20	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.0	10	10																																							
0.3	15	15																																							
0.7	20	20																																							
1.0	20	20																																							
1.4	20	20																																							
1.7	20	20																																							
1.9	20	20																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																									

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																								
Item	Ripple-Noise																										
Object	+15V1.7A	2. Values																									
1. Graph	<p>The graph plots Ripple-Noise [mV] on the Y-axis (0 to 100) against Load Current [A] on the X-axis (0.0 to 2.0). Two data series are shown: Input Volt. 100V (solid line with open circles) and Input Volt. 200V (dashed line with solid circles). Both series show an upward trend. A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 100V)</th> <th>Ripple-Noise [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.3</td><td>30</td><td>30</td></tr> <tr><td>0.7</td><td>40</td><td>40</td></tr> <tr><td>1.0</td><td>45</td><td>45</td></tr> <tr><td>1.4</td><td>50</td><td>50</td></tr> <tr><td>1.7</td><td>55</td><td>55</td></tr> <tr><td>1.9</td><td>60</td><td>60</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)	0.0	20	20	0.3	30	30	0.7	40	40	1.0	45	45	1.4	50	50	1.7	55	55	1.9	60	60
Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)																									
0.0	20	20																									
0.3	30	30																									
0.7	40	40																									
1.0	45	45																									
1.4	50	50																									
1.7	55	55																									
1.9	60	60																									

Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.




Fig. Complex Ripple Wave Form

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	20	20
0.3	30	30
0.7	40	40
1.0	45	45
1.4	50	50
1.7	55	55
1.9	60	60
-	-	-
-	-	-
-	-	-
-	-	-

-15V : Rated output current 1

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise																																								
Object	-15V1.7A																																								
1. Graph			2. Values																																						
<p>—△— Input Volt. 100V - - ○ - - Input Volt. 200V</p> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.3</td><td>25</td><td>25</td></tr> <tr><td>0.7</td><td>35</td><td>35</td></tr> <tr><td>1.0</td><td>35</td><td>35</td></tr> <tr><td>1.4</td><td>35</td><td>35</td></tr> <tr><td>1.7</td><td>35</td><td>35</td></tr> <tr><td>1.9</td><td>35</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table> <p>+15V : Rated output current 1</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	20	20	0.3	25	25	0.7	35	35	1.0	35	35	1.4	35	35	1.7	35	35	1.9	35	35	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.0	20	20																																							
0.3	25	25																																							
0.7	35	35																																							
1.0	35	35																																							
1.4	35	35																																							
1.7	35	35																																							
1.9	35	35																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Measured by 20 MHz Oscilloscope.</p> <p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																									
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple-Noise [mVp-p]</p> <p>T1</p>																																									
<p>Fig. Complex Ripple Wave Form</p>																																									

COSEL

Model	PBW50F-15	Testing Circuitry Figure A																																						
Item	Ripple Voltage (by Ambient Temp.)																																							
Object	+15V1.7A																																							
1.Graph																																								
<p>Y-axis: Ripple Voltage [mV] X-axis: Ambient Temperature [°C] Load 100%</p>																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage[mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>150</td><td>150</td></tr> <tr><td>-10</td><td>70</td><td>65</td></tr> <tr><td>0</td><td>50</td><td>50</td></tr> <tr><td>25</td><td>35</td><td>35</td></tr> <tr><td>50</td><td>35</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V : Rated output current 1</p>			Ambient Temperature [°C]	Ripple Voltage[mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	-30	150	150	-10	70	65	0	50	50	25	35	35	50	35	35	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage[mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
-30	150	150																																						
-10	70	65																																						
0	50	50																																						
25	35	35																																						
50	35	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Object	+15V1.7A	2.Values																																						
1.Graph																																								
<p>Y-axis: Ripple Voltage [mV] X-axis: Ambient Temperature [°C] Load 100%</p>																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage[mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>150</td><td>140</td></tr> <tr><td>-10</td><td>70</td><td>60</td></tr> <tr><td>0</td><td>50</td><td>50</td></tr> <tr><td>25</td><td>35</td><td>35</td></tr> <tr><td>50</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V : Rated output current 1</p>			Ambient Temperature [°C]	Ripple Voltage[mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	-30	150	140	-10	70	60	0	50	50	25	35	35	50	30	30	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-			
Ambient Temperature [°C]	Ripple Voltage[mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
-30	150	140																																						
-10	70	60																																						
0	50	50																																						
25	35	35																																						
50	30	30																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Measured by 20 MHz Oscilloscope.																																								
Note: Slanted line shows the range of the rated ambient temperature.																																								

COSEL

<p>Model PBW50F-15</p> <p>Item Ambient Temperature Drift</p> <p>Object +15V1.7A</p>	Testing Circuitry Figure A																																																					
	1.Graph <ul style="list-style-type: none"> —△— Input Volt. 100V - -□- - Input Volt. 200V - -○- - Input Volt. 230V <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																					
	2.Values <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>15.068</td><td>15.067</td><td>15.067</td></tr> <tr> <td>-10</td><td>15.073</td><td>15.072</td><td>15.072</td></tr> <tr> <td>0</td><td>15.077</td><td>15.076</td><td>15.076</td></tr> <tr> <td>10</td><td>15.082</td><td>15.081</td><td>15.082</td></tr> <tr> <td>20</td><td>15.085</td><td>15.084</td><td>15.084</td></tr> <tr> <td>25</td><td>15.086</td><td>15.085</td><td>15.085</td></tr> <tr> <td>30</td><td>15.086</td><td>15.085</td><td>15.085</td></tr> <tr> <td>40</td><td>15.084</td><td>15.084</td><td>15.084</td></tr> <tr> <td>50</td><td>15.079</td><td>15.078</td><td>15.078</td></tr> <tr> <td>60</td><td>15.073</td><td>15.073</td><td>15.073</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	15.068	15.067	15.067	-10	15.073	15.072	15.072	0	15.077	15.076	15.076	10	15.082	15.081	15.082	20	15.085	15.084	15.084	25	15.086	15.085	15.085	30	15.086	15.085	15.085	40	15.084	15.084	15.084	50	15.079	15.078	15.078	60	15.073	15.073	15.073	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
-20	15.068	15.067	15.067																																																			
-10	15.073	15.072	15.072																																																			
0	15.077	15.076	15.076																																																			
10	15.082	15.081	15.082																																																			
20	15.085	15.084	15.084																																																			
25	15.086	15.085	15.085																																																			
30	15.086	15.085	15.085																																																			
40	15.084	15.084	15.084																																																			
50	15.079	15.078	15.078																																																			
60	15.073	15.073	15.073																																																			
--	-	-	-																																																			
Object -15V1.7A																																																						
<p>1.Graph</p> <ul style="list-style-type: none"> —△— Input Volt. 100V - -□- - Input Volt. 200V - -○- - Input Volt. 230V <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>-15.109</td><td>-15.110</td><td>-15.111</td></tr> <tr> <td>-10</td><td>-15.113</td><td>-15.114</td><td>-15.115</td></tr> <tr> <td>0</td><td>-15.116</td><td>-15.117</td><td>-15.117</td></tr> <tr> <td>10</td><td>-15.121</td><td>-15.122</td><td>-15.122</td></tr> <tr> <td>20</td><td>-15.123</td><td>-15.124</td><td>-15.124</td></tr> <tr> <td>25</td><td>-15.124</td><td>-15.125</td><td>-15.125</td></tr> <tr> <td>30</td><td>-15.124</td><td>-15.125</td><td>-15.125</td></tr> <tr> <td>40</td><td>-15.123</td><td>-15.124</td><td>-15.124</td></tr> <tr> <td>50</td><td>-15.117</td><td>-15.118</td><td>-15.117</td></tr> <tr> <td>60</td><td>-15.111</td><td>-15.112</td><td>-15.112</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	-15.109	-15.110	-15.111	-10	-15.113	-15.114	-15.115	0	-15.116	-15.117	-15.117	10	-15.121	-15.122	-15.122	20	-15.123	-15.124	-15.124	25	-15.124	-15.125	-15.125	30	-15.124	-15.125	-15.125	40	-15.123	-15.124	-15.124	50	-15.117	-15.118	-15.117	60	-15.111	-15.112	-15.112	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
-20	-15.109	-15.110	-15.111																																																			
-10	-15.113	-15.114	-15.115																																																			
0	-15.116	-15.117	-15.117																																																			
10	-15.121	-15.122	-15.122																																																			
20	-15.123	-15.124	-15.124																																																			
25	-15.124	-15.125	-15.125																																																			
30	-15.124	-15.125	-15.125																																																			
40	-15.123	-15.124	-15.124																																																			
50	-15.117	-15.118	-15.117																																																			
60	-15.111	-15.112	-15.112																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						



Model	PBW50F-15	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current (AVR 1) : 0 - 1.7A (AVR 2) : 0 - 1.7A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object	+15V1.7A			Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	50	264	0	15.328	±123	±0.9	
Minimum Voltage	-10	200	1.7	15.083			

Object	-15V1.7A			Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	50	264	0	-15.330	±118	±0.8	
Minimum Voltage	-10	85	1.7	-15.094			

COSEL

Model	PBW50F-15
Item	Time Lapse Drift
Object	+15V1.7A


1.Graph



2.Values

Time since start [H]	Output Voltage [V]
0.0	15.065
0.5	15.068
1.0	15.069
2.0	15.069
3.0	15.069
4.0	15.069
5.0	15.069
6.0	15.069
7.0	15.069
8.0	15.069

Object -15V1.7A



2.Values


Time since start [H]	Output Voltage [V]
0.0	-15.108
0.5	-15.110
1.0	-15.111
2.0	-15.111
3.0	-15.111
4.0	-15.111
5.0	-15.111
6.0	-15.111
7.0	-15.111
8.0	-15.111

★The characteristic of AC200V is equal.

COSEL


Model	PBW50F-15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V1.7A		


1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[mS]
100 V		330.5	15.5	346.0	27.0	19.3	
200 V		269.5	16.0	285.5	31.8	19.5	



COSEL

COSEL


Model	PBW50F-15	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time																																	
Object	+15V1.7A																																	
1. Graph		2. Values																																
<p>Graph showing Hold-Up Time [ms] vs Input Voltage [V] for PBW50F-15 at 25°C. The Y-axis is logarithmic from 1 to 1000 ms. The X-axis is linear from 50 to 300 V. Two series are shown: Load 50% (dashed line with squares) and Load 100% (solid line with triangles). Both series show a slight increase in hold-up time as input voltage increases. A slanted line indicates the rated input voltage range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>48</td> <td>20</td> </tr> <tr> <td>85</td> <td>50</td> <td>22</td> </tr> <tr> <td>100</td> <td>53</td> <td>24</td> </tr> <tr> <td>120</td> <td>55</td> <td>26</td> </tr> <tr> <td>200</td> <td>58</td> <td>29</td> </tr> <tr> <td>230</td> <td>60</td> <td>30</td> </tr> <tr> <td>264</td> <td>60</td> <td>30</td> </tr> <tr> <td>280</td> <td>61</td> <td>31</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	48	20	85	50	22	100	53	24	120	55	26	200	58	29	230	60	30	264	60	30	280	61	31	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
75	48	20																																
85	50	22																																
100	53	24																																
120	55	26																																
200	58	29																																
230	60	30																																
264	60	30																																
280	61	31																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time																																		
Object	-15V1.7A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>48</td><td>20</td> </tr> <tr> <td>85</td><td>50</td><td>22</td> </tr> <tr> <td>100</td><td>53</td><td>24</td> </tr> <tr> <td>120</td><td>55</td><td>26</td> </tr> <tr> <td>200</td><td>58</td><td>29</td> </tr> <tr> <td>230</td><td>60</td><td>30</td> </tr> <tr> <td>264</td><td>60</td><td>30</td> </tr> <tr> <td>280</td><td>61</td><td>31</td> </tr> <tr> <td>-</td><td>-</td><td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	48	20	85	50	22	100	53	24	120	55	26	200	58	29	230	60	30	264	60	30	280	61	31	-	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	48	20																																	
85	50	22																																	
100	53	24																																	
120	55	26																																	
200	58	29																																	
230	60	30																																	
264	60	30																																	
280	61	31																																	
-	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PBW50F-15
Item	Instantaneous Interruption Compensation
Object	+15V1.7A

 Temperature 25°C
 Testing Circuitry Figure A


2. Values


Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.30	53	65	61
0.60	39	50	51
0.90	35	39	40
1.20	30	39	40
1.50	28	37	36
1.70	26	37	35
1.87	26	28	29
--	-	-	-
--	-	-	-
--	-	-	-

-15V : Rated output current 1

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PBW50F-15
Item	Instantaneous Interruption Compensation
Object	-15V1.7A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.30	53	65	61
0.60	39	50	51
0.90	35	39	40
1.20	30	39	40
1.50	28	37	36
1.70	26	37	35
1.87	26	28	29
-	-	-	-
-	-	-	-
-	-	-	-

+15V : Rated output current 1

COSEL

Model	PBW50F-15
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V1.7A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	51	62
-10	51	65
0	50	66
10	50	65
20	50	66
25	50	65
30	50	65
40	50	66
50	50	66
60	51	65
--	-	-

Object	-15V1.7A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	50	63
-10	50	63
0	49	63
10	49	64
20	49	63
25	50	63
30	50	63
40	49	63
50	49	65
60	50	64
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


COSEL

Model	PBW50F-15	Temperature Testing Circuitry	25°C Figure A																																											
Item	Overcurrent Protection																																													
Object	+15V1.7A																																													
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																												
			<table border="1"> <thead> <tr> <th rowspan="3">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>100[V]</th> <th>200[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>2.26</td><td>2.09</td></tr> <tr><td>14.3</td><td>2.37</td><td>2.38</td></tr> <tr><td>13.5</td><td>2.50</td><td>2.50</td></tr> <tr><td>12.0</td><td>2.75</td><td>2.75</td></tr> <tr><td>10.5</td><td>2.98</td><td>2.96</td></tr> <tr><td>9.0</td><td>3.13</td><td>3.15</td></tr> <tr><td>7.5</td><td>3.34</td><td>3.33</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt.	Input Volt.	100[V]	200[V]	15.0	2.26	2.09	14.3	2.37	2.38	13.5	2.50	2.50	12.0	2.75	2.75	10.5	2.98	2.96	9.0	3.13	3.15	7.5	3.34	3.33	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																													
	Input Volt.	Input Volt.																																												
	100[V]	200[V]																																												
15.0	2.26	2.09																																												
14.3	2.37	2.38																																												
13.5	2.50	2.50																																												
12.0	2.75	2.75																																												
10.5	2.98	2.96																																												
9.0	3.13	3.15																																												
7.5	3.34	3.33																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
Intermittent operation occurs when the output voltage is from 7.5V to 0V.																																														
Object	-15V1.7A	2.Values																																												
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																													
			<table border="1"> <thead> <tr> <th rowspan="3">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>100[V]</th> <th>200[V]</th> </tr> </thead> <tbody> <tr><td>-15.0</td><td>2.28</td><td>2.28</td></tr> <tr><td>-14.3</td><td>2.41</td><td>2.41</td></tr> <tr><td>-13.5</td><td>2.53</td><td>2.54</td></tr> <tr><td>-12.0</td><td>2.76</td><td>2.77</td></tr> <tr><td>-10.5</td><td>2.97</td><td>2.97</td></tr> <tr><td>-9.0</td><td>3.14</td><td>3.16</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt.	Input Volt.	100[V]	200[V]	-15.0	2.28	2.28	-14.3	2.41	2.41	-13.5	2.53	2.54	-12.0	2.76	2.77	-10.5	2.97	2.97	-9.0	3.14	3.16	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-			
Output Voltage [V]	Load Current [A]																																													
	Input Volt.	Input Volt.																																												
	100[V]	200[V]																																												
-15.0	2.28	2.28																																												
-14.3	2.41	2.41																																												
-13.5	2.53	2.54																																												
-12.0	2.76	2.77																																												
-10.5	2.97	2.97																																												
-9.0	3.14	3.16																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
Note: Slanted line shows the range of the rated load current.																																														
Intermittent operation occurs when the output voltage is from -9V to 0V.																																														

COSEL

Model	PBW50F-15
Item	Overvoltage Protection
Object	+15V1.7A


1.Graph

Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	25.95	25.85
-10	26.15	26.08
0	26.21	26.27
10	26.37	26.34
20	26.53	26.47
25	26.60	26.65
30	26.73	26.68
40	26.95	26.80
50	27.02	26.93
60	27.08	27.06
-	-	-

Object	-15V1.7A
1.Graph	

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-20	-25.22	-25.22
-10	-25.26	-25.34
0	-25.46	-25.45
10	-25.54	-25.62
20	-25.69	-25.82
25	-25.88	-25.83
30	-26.02	-26.01
40	-26.09	-26.14
50	-26.29	-26.27
60	-26.40	-26.44
-	-	-



Note: Slanted line shows the range of the rated ambient temperature.

coSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)