

TEST DATA OF PCA1000F-48

Regulated DC Power Supply
February 22, 2019

Approved by : Koji Todo
Koji Todo Design Manager

Prepared by : Terumasa Araki
Terumasa Araki Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)



<p>Model PCA1000F-48</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Input Current (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V · · · ○ · · · Input Volt. 230V </p> <p>Input Current [A]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.241</td><td>0.217</td><td>0.229</td></tr> <tr><td>4.0</td><td>2.238</td><td>1.187</td><td>1.065</td></tr> <tr><td>8.0</td><td>4.300</td><td>2.188</td><td>1.939</td></tr> <tr><td>12.0</td><td>6.380</td><td>3.199</td><td>2.815</td></tr> <tr><td>16.0</td><td>8.480</td><td>4.230</td><td>3.820</td></tr> <tr><td>20.0</td><td>10.640</td><td>5.320</td><td>4.700</td></tr> <tr><td>22.0</td><td>11.740</td><td>5.840</td><td>5.150</td></tr> <tr><td>24.2</td><td>12.950</td><td>6.410</td><td>5.640</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.241	0.217	0.229	4.0	2.238	1.187	1.065	8.0	4.300	2.188	1.939	12.0	6.380	3.199	2.815	16.0	8.480	4.230	3.820	20.0	10.640	5.320	4.700	22.0	11.740	5.840	5.150	24.2	12.950	6.410	5.640	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	0.241	0.217	0.229																																																		
4.0	2.238	1.187	1.065																																																		
8.0	4.300	2.188	1.939																																																		
12.0	6.380	3.199	2.815																																																		
16.0	8.480	4.230	3.820																																																		
20.0	10.640	5.320	4.700																																																		
22.0	11.740	5.840	5.150																																																		
24.2	12.950	6.410	5.640																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		






<p>Model PCA1000F-48</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 200V - · - ○ - · - - Input Volt. 230V </p> <p>Efficiency [%]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.0</td><td>88.3</td><td>89.9</td><td>89.1</td></tr> <tr><td>8.0</td><td>91.7</td><td>92.9</td><td>92.8</td></tr> <tr><td>12.0</td><td>92.1</td><td>93.6</td><td>93.8</td></tr> <tr><td>16.0</td><td>92.0</td><td>93.8</td><td>93.6</td></tr> <tr><td>20.0</td><td>91.6</td><td>93.5</td><td>93.5</td></tr> <tr><td>22.0</td><td>91.4</td><td>93.4</td><td>93.6</td></tr> <tr><td>24.2</td><td>91.0</td><td>93.3</td><td>93.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	4.0	88.3	89.9	89.1	8.0	91.7	92.9	92.8	12.0	92.1	93.6	93.8	16.0	92.0	93.8	93.6	20.0	91.6	93.5	93.5	22.0	91.4	93.4	93.6	24.2	91.0	93.3	93.4	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
4.0	88.3	89.9	89.1																																																		
8.0	91.7	92.9	92.8																																																		
12.0	92.1	93.6	93.8																																																		
16.0	92.0	93.8	93.6																																																		
20.0	91.6	93.5	93.5																																																		
22.0	91.4	93.4	93.6																																																		
24.2	91.0	93.3	93.4																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model		PCA1000F-48		Temperature 25°C																																																				
Item		Power Factor (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			2.Values																																																					
<p> —△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V </p> <p>Power Factor</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.695</td><td>0.295</td><td>0.254</td></tr> <tr><td>4.0</td><td>0.986</td><td>0.911</td><td>0.891</td></tr> <tr><td>8.0</td><td>0.993</td><td>0.960</td><td>0.944</td></tr> <tr><td>12.0</td><td>0.997</td><td>0.977</td><td>0.961</td></tr> <tr><td>16.0</td><td>0.998</td><td>0.982</td><td>0.947</td></tr> <tr><td>20.0</td><td>0.998</td><td>0.978</td><td>0.961</td></tr> <tr><td>22.0</td><td>0.998</td><td>0.981</td><td>0.965</td></tr> <tr><td>24.2</td><td>0.998</td><td>0.983</td><td>0.971</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.695	0.295	0.254	4.0	0.986	0.911	0.891	8.0	0.993	0.960	0.944	12.0	0.997	0.977	0.961	16.0	0.998	0.982	0.947	20.0	0.998	0.978	0.961	22.0	0.998	0.981	0.965	24.2	0.998	0.983	0.971	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																							
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																					
0.0	0.695	0.295	0.254																																																					
4.0	0.986	0.911	0.891																																																					
8.0	0.993	0.960	0.944																																																					
12.0	0.997	0.977	0.961																																																					
16.0	0.998	0.982	0.947																																																					
20.0	0.998	0.978	0.961																																																					
22.0	0.998	0.981	0.965																																																					
24.2	0.998	0.983	0.971																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		PCA1000F-48	Temperature 25°C Testing Circuitry Figure A
Item		Inrush Current	
Object		_____	





COSEL		Temperature 25°C Testing Circuitry Figure B
Model	PCA1000F-48	
Item	Leakage Current	
Object	_____	

1.Results

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
			[mA]			
DEN-AN	Figure B-1	Both phases	0.11	0.29	0.31	Operation
		One of phases	0.22	0.56	0.59	Stand by
IEC62368-1	Figure B-2	Both phases	0.10	0.28	0.30	Operation
		One of phases	0.22	0.56	0.60	Stand by
	Figure B-3	Both phases	0.11	0.29	0.31	Operation
		One of phases	0.22	0.57	0.61	Stand by
IEC60601-1	Figure B-4	Both phases	0.11	0.28	0.29	Operation
		One of phases	0.22	0.55	0.57	Stand by

The value for "One of phases" is the reference value only.

2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



<p>Model PCA1000F-48</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Line Regulation</p>																																		
<p>Object +48V22A</p>																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>48.562</td> <td>-</td> </tr> <tr> <td>85</td> <td>48.565</td> <td>-</td> </tr> <tr> <td>100</td> <td>48.564</td> <td>48.535</td> </tr> <tr> <td>120</td> <td>48.566</td> <td>48.533</td> </tr> <tr> <td>200</td> <td>48.562</td> <td>48.533</td> </tr> <tr> <td>230</td> <td>48.563</td> <td>48.532</td> </tr> <tr> <td>264</td> <td>48.565</td> <td>48.532</td> </tr> <tr> <td>280</td> <td>48.565</td> <td>48.533</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	80	48.562	-	85	48.565	-	100	48.564	48.535	120	48.566	48.533	200	48.562	48.533	230	48.563	48.532	264	48.565	48.532	280	48.565	48.533	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
80	48.562	-																																
85	48.565	-																																
100	48.564	48.535																																
120	48.566	48.533																																
200	48.562	48.533																																
230	48.563	48.532																																
264	48.565	48.532																																
280	48.565	48.533																																
--	-	-																																




<p>Model PCA1000F-48</p>																																																						
Item	Load Regulation	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	+48V22A																																																					
<p>1.Graph</p> <p> —△— Input Volt. 100V ---□--- Input Volt. 200V -·-○-·- Input Volt. 230V </p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>48.573</td><td>48.572</td><td>48.573</td></tr> <tr><td>4.0</td><td>48.568</td><td>48.566</td><td>48.568</td></tr> <tr><td>8.0</td><td>48.560</td><td>48.560</td><td>48.560</td></tr> <tr><td>12.0</td><td>48.553</td><td>48.553</td><td>48.554</td></tr> <tr><td>16.0</td><td>48.547</td><td>48.546</td><td>48.546</td></tr> <tr><td>20.0</td><td>48.538</td><td>48.539</td><td>48.538</td></tr> <tr><td>22.0</td><td>48.531</td><td>48.532</td><td>48.532</td></tr> <tr><td>24.2</td><td>48.526</td><td>48.528</td><td>48.528</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	48.573	48.572	48.573	4.0	48.568	48.566	48.568	8.0	48.560	48.560	48.560	12.0	48.553	48.553	48.554	16.0	48.547	48.546	48.546	20.0	48.538	48.539	48.538	22.0	48.531	48.532	48.532	24.2	48.526	48.528	48.528	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	48.573	48.572	48.573																																																			
4.0	48.568	48.566	48.568																																																			
8.0	48.560	48.560	48.560																																																			
12.0	48.553	48.553	48.554																																																			
16.0	48.547	48.546	48.546																																																			
20.0	48.538	48.539	48.538																																																			
22.0	48.531	48.532	48.532																																																			
24.2	48.526	48.528	48.528																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
		Testing Circuitry	Figure C																																																			
Object	+48V22A																																																					
<p>1.Graph</p> <p>Input Voltage 200V Load 100%</p>																																																						





Model		PCA1000F-48	
Item		Dynamic Load Response	
Object		+48V22A	
		Temperature	25°C
		Testing Circuitry	Figure A



Input Volt. 100 V
 Cycle 1000 ms
 Response. $t_1=t_2=50\mu\text{s}$. Typ



Load 0%(0A) \longleftrightarrow
 Load 100%(22A)




Load 0%(0A) \longleftrightarrow
 Load 50%(11A)






Model		PCA1000F-48	Temperature 25°C Testing Circuitry Figure A
Item		Rise and Fall Time	
Object		+48V22A	

1. Graph



2. Values

		[ms]				
Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		692.0	10.0	702.0	16.1	10.7
230 V		690.0	10.0	700.0	20.7	10.6





<p>Model PCA1000F-48</p> <p>Item Hold-Up Time</p> <p>Object +48V22A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																
<p>1.Graph</p> <p>---□--- Load 50%</p> <p>—△— Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>80</td><td>29</td><td>-</td></tr> <tr><td>85</td><td>29</td><td>-</td></tr> <tr><td>100</td><td>29</td><td>15</td></tr> <tr><td>120</td><td>29</td><td>15</td></tr> <tr><td>200</td><td>38</td><td>19</td></tr> <tr><td>230</td><td>39</td><td>19</td></tr> <tr><td>264</td><td>39</td><td>19</td></tr> <tr><td>280</td><td>41</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	29	-	85	29	-	100	29	15	120	29	15	200	38	19	230	39	19	264	39	19	280	41	20	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
80	29	-																																
85	29	-																																
100	29	15																																
120	29	15																																
200	38	19																																
230	39	19																																
264	39	19																																
280	41	20																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model PCA1000F-48</p> <p>Item Instantaneous Interruption Compensation</p> <p>Object +48V22A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																			
<p>1.Graph</p> <p>—△— Input Volt. 100V</p> <p>---□--- Input Volt. 200V</p> <p>-·-○-·- Input Volt. 230V</p> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.0</td><td>66</td><td>91</td><td>93</td></tr> <tr><td>8.0</td><td>46</td><td>62</td><td>61</td></tr> <tr><td>12.0</td><td>30</td><td>45</td><td>45</td></tr> <tr><td>16.0</td><td>19</td><td>29</td><td>31</td></tr> <tr><td>20.0</td><td>16</td><td>23</td><td>22</td></tr> <tr><td>22.0</td><td>15</td><td>20</td><td>20</td></tr> <tr><td>24.2</td><td>14</td><td>17</td><td>18</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	4.0	66	91	93	8.0	46	62	61	12.0	30	45	45	16.0	19	29	31	20.0	16	23	22	22.0	15	20	20	24.2	14	17	18	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
4.0	66	91	93																																																		
8.0	46	62	61																																																		
12.0	30	45	45																																																		
16.0	19	29	31																																																		
20.0	16	23	22																																																		
22.0	15	20	20																																																		
24.2	14	17	18																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



COSEL																																														
Model	PCA1000F-48																																													
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																												
Object	+48V22A																																													
<p>1. Graph</p> <div style="text-align: right;"> <p>— Input Volt. 100V</p> <p>— Input Volt. 230V</p> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Hiccup mode activates when the output voltage is from 24 to 0V.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>45.6</td><td>25.24</td><td>25.22</td></tr> <tr><td>43.2</td><td>25.25</td><td>25.24</td></tr> <tr><td>38.4</td><td>25.30</td><td>25.28</td></tr> <tr><td>33.6</td><td>25.32</td><td>25.31</td></tr> <tr><td>28.8</td><td>25.39</td><td>25.31</td></tr> <tr><td>24.0</td><td>25.36</td><td>25.31</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	45.6	25.24	25.22	43.2	25.25	25.24	38.4	25.30	25.28	33.6	25.32	25.31	28.8	25.39	25.31	24.0	25.36	25.31	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																													
	Input Volt. 100[V]	Input Volt. 230[V]																																												
45.6	25.24	25.22																																												
43.2	25.25	25.24																																												
38.4	25.30	25.28																																												
33.6	25.32	25.31																																												
28.8	25.39	25.31																																												
24.0	25.36	25.31																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												



COSEL		
Model	PCA1000F-48	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+48V22A	

1.Values Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-20	48.402	48.401	48.401
25	48.536	48.534	48.535
40	48.594	48.594	48.595
50	-	48.625	48.626

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+48V22A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	74	78
25	74	79
40	74	79

Item	Oversvoltage Protection	Testing Circuitry Figure A
Object	+48V22A	

1.Values Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	61.65	61.65
25	61.65	61.65
40	61.65	61.65
50	61.65	61.65




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)




Figure B-4 (IEC60601-1)




Figure C