



DATA SHEET		Date	25-Mar-19
Model	PCA300F-5-T	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	M.Yamamoto




Frequency MHz	Line Phase	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/Fail	Remark
		QP	AV	QP	AV	QP	AV		
0.222	L1	43.0	41.7	62.7	52.7	19.7	11.0	Pass	
0.222	N	45.2	44.7	62.8	52.8	17.6	8.1	Pass	




Frequency MHz	Polarization	Stability	Reading dB(μV)	Limit dB(μV/m)	Margi dB(μV/m)	Pass/Fail	Height cm	Angle deg	Remark
			QP	QP	QP				
61.681	V	Stable	30.6	40	9.4	Pass	100.0	218.9	
61.368	V	Stable	31.0	40	9.0	Pass	100.0	226.9	
165.544	V	Stable	30.9	40	9.1	Pass	100.2	256.4	
166.140	H	Stable	27.2	40	12.8	Pass	199.1	323.6	
166.908	V	Stable	32.5	40	7.5	Pass	100.0	308.1	

DATA SHEET		Date	25-Mar-19
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	M.Yamamoto

1. Line conduction



2. Radiated emission



Conditions

Test : EMI

Model Name : PCA300F

○Photographs of Test Set-Up

1.LINE CONDUCTION



2.RADIATED EMISSION

