



DATA SHEET		Date	14-Jul-17
Model	PJA300F-48	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Kawahata




Frequency MHz	Line Phase	Reading dB(μV)		Factor dB	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/Fail	Remark
		QP	AV		QP	AV	QP	AV	QP	AV		
0.19765	VA	27.8	23.7	20.3	48.1	44	63.7	53.7	15.6	9.7	Pass	
0.19656	VB	27	22.7	20.3	47.3	43	63.8	53.8	16.5	10.8	Pass	
4.59338	VA	20.9	19.4	20.6	41.5	40	56	46	14.5	6	Pass	



Frequency MHz	Polarization	Stability	Reading dB(μV)		Factor dB(1/m)	Reading dB(μV)		Limit dB(μV/m)	Margin dB(μV/m)	Pass/Fail	Height cm	Angle deg	Remark
			QP			QP							
81.858	V	Stable	46.9	-16.7		30.2		40.0	9.8	Pass	140	256	
88.767	V	Stable	47.9	-16.8		31.1		40.0	8.9	Pass	124	183	
160.664	H	Stable	46.7	-13.6		33.1		40.0	6.9	Pass	155	38	

DATA SHEET		Date	14-Jul-17
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Kawahata

### 1. Line conduction



### 2. Radiated emission

