



EXTRA TEST DATA OF PJA600F-36


Regulated DC Power Supply
Nov 20, 2021

COSEL CO.,LTD.

CONTENTS




1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Overvoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Power Consumption (by Input Voltage)	5
6.Figure of Testing Circuitry	6

(Final Page 6)

COSEL

COSEL

Model	PJA600F-36	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object	_____		




COSEL

Model	PJA600F-36	Temperature	25°C
Item	Over Voltage Protection	Testing Circuitry	A
Object	_____	Input Voltage : 100V	

Output Voltage
[10V/div]


GND




Load : 0%

Overvoltage protection
value : 46.4VTime
[40ms/div]Output Voltage
[10V/div]

GND




Load : 100%

Overvoltage protection
value : 46.4VTime
[20ms/div]

COSEL


Model	PJA600F-36	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object	_____	Load	: Short

Output Current
[5A/div]

Input Voltage : 100V

Short-circuit
current : 25.6A


ON Time : 1141ms

Short circuit
period : 9068msTime
[2000ms/div]Output Current
[5A/div]


Input Voltage : 230V

Short-circuit
current : 26A

ON Time : 1136ms

Short circuit
period : 9046msTime
[2000ms/div]

COSEL

Model	PJA600F-36-R																
Item	Input voltage - Power consumption	Temperature	25°C														
Object	_____	Testing Circuitry	-														
1.Graph		Load :0%															
<div></div>		2.Values															
		<table><tr><th>Input voltage [V]</th><th>Power consumption [W]</th></tr><tr><td>85</td><td>0.14</td></tr><tr><td>100</td><td>0.19</td></tr><tr><td>115</td><td>0.23</td></tr><tr><td>200</td><td>1.12</td></tr><tr><td>230</td><td>1.56</td></tr><tr><td>264</td><td>2.08</td></tr></table>		Input voltage [V]	Power consumption [W]	85	0.14	100	0.19	115	0.23	200	1.12	230	1.56	264	2.08
Input voltage [V]	Power consumption [W]																
85	0.14																
100	0.19																
115	0.23																
200	1.12																
230	1.56																
264	2.08																
Reducing standby power is possible by OFF signal of the remote control.																	

