



TEST DATA OF PJMA1500F-36

Regulated DC Power Supply
September 20, 2022

Approved by : _____
Takashi Kajii
Design Manager

Prepared by : _____
Akihisa Mukai
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
10.Ripple-Noise	10
11.Dynamic Load Response	11
12.Time Lapse Drift	12
13.Rise and Fall Time	13
14.Hold-Up Time	14
15.Instantaneous Interruption Compensation	15
17.Overcurrent Protection	16
19.Ambient Temperature Drift	17
20.Minimum Input Voltage for Regulated Output Voltage	17
21.Overvoltage Protection	17
22.Figure of Testing Circuitry	18


(Final Page 18)

COSEL

Model	PJMA1500F-36
Item	Input Current (by Load Current)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	0.129	0.132	0.193
8.4	3.755	3.267	1.700
16.8	7.199	6.227	3.148
25.2	10.722	9.261	4.611
33.6	14.357	12.363	6.103
37.8	16.227	13.973	6.858
42.0	18.145	15.577	7.642
46.2	-	17.240	8.407
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PJMA1500F-36	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 115V ---○--- Input Volt. 230V </p> 																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td><td>5</td></tr> <tr><td>8.4</td><td>368</td><td>366</td><td>358</td></tr> <tr><td>16.8</td><td>714</td><td>709</td><td>693</td></tr> <tr><td>25.2</td><td>1066</td><td>1058</td><td>1032</td></tr> <tr><td>33.6</td><td>1429</td><td>1416</td><td>1376</td></tr> <tr><td>37.8</td><td>1617</td><td>1599</td><td>1551</td></tr> <tr><td>42.0</td><td>1808</td><td>1785</td><td>1728</td></tr> <tr><td>46.2</td><td>-</td><td>1975</td><td>1908</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	5	5	5	8.4	368	366	358	16.8	714	709	693	25.2	1066	1058	1032	33.6	1429	1416	1376	37.8	1617	1599	1551	42.0	1808	1785	1728	46.2	-	1975	1908	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	5	5	5																																																			
8.4	368	366	358																																																			
16.8	714	709	693																																																			
25.2	1066	1058	1032																																																			
33.6	1429	1416	1376																																																			
37.8	1617	1599	1551																																																			
42.0	1808	1785	1728																																																			
46.2	-	1975	1908																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PJMA1500F-36	Temperature Testing Circuitry	25°C Figure A																														
Item	Efficiency (by Input Voltage)																																
Object	_____																																
1. Graph			2. Values																														
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>85</td><td>84.8</td><td>82.4</td></tr> <tr><td>100</td><td>85.5</td><td>84.0</td></tr> <tr><td>115</td><td>86.1</td><td>85.1</td></tr> <tr><td>200</td><td>87.8</td><td>87.4</td></tr> <tr><td>230</td><td>88.2</td><td>87.8</td></tr> <tr><td>264</td><td>88.7</td><td>88.2</td></tr> <tr><td>280</td><td>88.9</td><td>88.4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	85	84.8	82.4	100	85.5	84.0	115	86.1	85.1	200	87.8	87.4	230	88.2	87.8	264	88.7	88.2	280	88.9	88.4	--	-	-	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																															
85	84.8	82.4																															
100	85.5	84.0																															
115	86.1	85.1																															
200	87.8	87.4																															
230	88.2	87.8																															
264	88.7	88.2																															
280	88.9	88.4																															
--	-	-																															
--	-	-																															
			$\ast 1$: Load 80% $\ast 2$: Load 90%																														
Note: Slanted line shows the range of the rated input voltage.																																	

COSEL


Model	PJMA1500F-36	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8.4</td><td>82.6</td><td>83.1</td><td>84.9</td></tr> <tr> <td>16.8</td><td>85.1</td><td>85.7</td><td>87.8</td></tr> <tr> <td>25.2</td><td>85.5</td><td>86.1</td><td>88.3</td></tr> <tr> <td>33.6</td><td>85.0</td><td>85.8</td><td>88.3</td></tr> <tr> <td>37.8</td><td>84.6</td><td>85.5</td><td>88.1</td></tr> <tr> <td>42.0</td><td>84.0</td><td>85.1</td><td>87.9</td></tr> <tr> <td>46.2</td><td>-</td><td>84.6</td><td>87.6</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	-	-	-	8.4	82.6	83.1	84.9	16.8	85.1	85.7	87.8	25.2	85.5	86.1	88.3	33.6	85.0	85.8	88.3	37.8	84.6	85.5	88.1	42.0	84.0	85.1	87.9	46.2	-	84.6	87.6	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
8.4	82.6	83.1	84.9																																																			
16.8	85.1	85.7	87.8																																																			
25.2	85.5	86.1	88.3																																																			
33.6	85.0	85.8	88.3																																																			
37.8	84.6	85.5	88.1																																																			
42.0	84.0	85.1	87.9																																																			
46.2	-	84.6	87.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PJMA1500F-36
Item	Power Factor (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
85	0.997	0.998 ※1
100	0.995	0.998 ※2
115	0.994	0.997
200	0.979	0.990
230	0.968	0.985
264	0.950	0.975
280	0.901	0.968
--	-	-
--	-	-

※1 : Load 80%

※2 : Load 90%


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PJMA1500F-36	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Graph showing Power Factor vs Load Current for three input voltages: 100V, 115V, and 230V. The x-axis is Load Current [A] from 0 to 50, and the y-axis is Power Factor from 0.0 to 1.0. All curves start at (0,0) and approach 1.0 as load current increases. A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.371</td><td>0.305</td><td>0.117</td></tr> <tr> <td>8.4</td><td>0.982</td><td>0.977</td><td>0.916</td></tr> <tr> <td>16.8</td><td>0.993</td><td>0.991</td><td>0.957</td></tr> <tr> <td>25.2</td><td>0.996</td><td>0.995</td><td>0.973</td></tr> <tr> <td>33.6</td><td>0.997</td><td>0.996</td><td>0.981</td></tr> <tr> <td>37.8</td><td>0.997</td><td>0.997</td><td>0.984</td></tr> <tr> <td>42.0</td><td>0.998</td><td>0.997</td><td>0.986</td></tr> <tr> <td>46.2</td><td>-</td><td>0.997</td><td>0.987</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	0.371	0.305	0.117	8.4	0.982	0.977	0.916	16.8	0.993	0.991	0.957	25.2	0.996	0.995	0.973	33.6	0.997	0.996	0.981	37.8	0.997	0.997	0.984	42.0	0.998	0.997	0.986	46.2	-	0.997	0.987	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	0.371	0.305	0.117																																																			
8.4	0.982	0.977	0.916																																																			
16.8	0.993	0.991	0.957																																																			
25.2	0.996	0.995	0.973																																																			
33.6	0.997	0.996	0.981																																																			
37.8	0.997	0.997	0.984																																																			
42.0	0.998	0.997	0.986																																																			
46.2	-	0.997	0.987																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						


COSEL

Model	PJMA1500F-36	Temperature Testing Circuitry Figure A	25°C
Item	Inrush Current		
Object	_____		



Input Voltage 115 V
 Frequency 50 Hz
 Load 100 %

Primary inrush current 7.6 A
 Secondary inrush current 32.8 A





Model	PJMA1500F-36	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results

Standards		Input Volt.			Note
		230 [V]	240 [V]	264 [V]	
IEC60601-1	Both phases	0.21	0.24	0.27	Operation
	One of phases	0.39	0.40	0.45	Stand by

The value for "One of phases" is the reference value only.



2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL


Model	PJMA1500F-36																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+36V42A																																	
1.Graph																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>36.111</td><td>36.115</td> </tr> <tr> <td>100</td><td>36.112</td><td>36.116</td> </tr> <tr> <td>115</td><td>36.113</td><td>36.118</td> </tr> <tr> <td>200</td><td>36.113</td><td>36.119</td> </tr> <tr> <td>230</td><td>36.112</td><td>36.120</td> </tr> <tr> <td>264</td><td>36.113</td><td>36.119</td> </tr> <tr> <td>280</td><td>36.113</td><td>36.120</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	36.111	36.115	100	36.112	36.116	115	36.113	36.118	200	36.113	36.119	230	36.112	36.120	264	36.113	36.119	280	36.113	36.120	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	36.111	36.115																																
100	36.112	36.116																																
115	36.113	36.118																																
200	36.113	36.119																																
230	36.112	36.120																																
264	36.113	36.119																																
280	36.113	36.120																																
--	-	-																																
--	-	-																																
※1 : Load 80% ※2 : Load 90%																																		
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL

Model	PJMA1500F-36	Temperature	25°C	
Item	Load Regulation	Testing Circuitry	Figure A	
Object	+36V42A			
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 115V - - -○--- Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>			
	<p>Note: Slanted line shows the range of the rated load current.</p>			
Item	Ripple-Noise	Temperature	25°C	
Object	+36V42A	Testing Circuitry	Figure B	
1.Graph	<p>Input Voltage 115V Load 100%</p>  <p>20[mV/div]</p> <p>20[ms/div]</p>			

COSEL

Model	PJMA1500F-36
Item	Dynamic Load Response
Object	+36V42A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 115 V
Cycle 1000 msMin.Load (0A)↔
Load 100% (42A)

200 mV/div

10 ms/div

10 ms/div

Load 50% (21A)↔
Load 100% (42A)

100 mV/div

100 us/div


100 us/div

COSEL

Model	PJMA1500F-36
Item	Time Lapse Drift
Object	+36V42A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Time since start [H]	Output Voltage [V]
0.0	36.794
0.5	36.802
1.0	36.802
2.0	36.801
3.0	36.803
4.0	36.803
5.0	36.803
6.0	36.802
7.0	36.802
8.0	36.802

COSEL


Model	PJMA1500F-36	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time		
Object	+36V42A		

1.Graph



2.Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		674.0	61.0	735.0	58.8	47.2	
100 %		671.5	61.5	733.0	26.6	25.7	



COSEL

Model	PJMA1500F-36	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+36V42A																																		
1. Graph		2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>54</td><td>27</td></tr> <tr><td>100</td><td>56</td><td>28</td></tr> <tr><td>115</td><td>57</td><td>28</td></tr> <tr><td>200</td><td>62</td><td>31</td></tr> <tr><td>230</td><td>62</td><td>32</td></tr> <tr><td>264</td><td>62</td><td>32</td></tr> <tr><td>280</td><td>62</td><td>32</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	54	27	100	56	28	115	57	28	200	62	31	230	62	32	264	62	32	280	62	32	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	54	27																																	
100	56	28																																	
115	57	28																																	
200	62	31																																	
230	62	32																																	
264	62	32																																	
280	62	32																																	
--	-	-																																	
--	-	-																																	
			※1 : Load 80%																																
			※2 : Load 90%																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PJMA1500F-36	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+36V42A																																																					
1.Graph	<p>Graph showing Instantaneous Compensation Time [ms] vs Load Current [A] for three input voltages: 100V, 115V, and 230V. The Y-axis is logarithmic from 1 to 10000 ms. The X-axis is linear from 0 to 50 A. A slanted line indicates the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8.4</td><td>22</td><td>26</td><td>162</td></tr> <tr> <td>16.8</td><td>22</td><td>26</td><td>75</td></tr> <tr> <td>25.2</td><td>22</td><td>26</td><td>52</td></tr> <tr> <td>33.6</td><td>22</td><td>26</td><td>37</td></tr> <tr> <td>37.8</td><td>22</td><td>26</td><td>34</td></tr> <tr> <td>42.0</td><td>22</td><td>25</td><td>28</td></tr> <tr> <td>46.2</td><td>-</td><td>22</td><td>26</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	-	-	-	8.4	22	26	162	16.8	22	26	75	25.2	22	26	52	33.6	22	26	37	37.8	22	26	34	42.0	22	25	28	46.2	-	22	26	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
8.4	22	26	162																																																			
16.8	22	26	75																																																			
25.2	22	26	52																																																			
33.6	22	26	37																																																			
37.8	22	26	34																																																			
42.0	22	25	28																																																			
46.2	-	22	26																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					



Model	PJMA1500F-36	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+36V42A																																																									
1.Graph		2.Values																																																								
<p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>36.0</td><td>48.46</td><td>48.49</td><td>48.59</td></tr> <tr><td>34.2</td><td>48.68</td><td>48.66</td><td>48.78</td></tr> <tr><td>32.4</td><td>48.96</td><td>48.92</td><td>49.00</td></tr> <tr><td>28.8</td><td>49.50</td><td>49.49</td><td>49.63</td></tr> <tr><td>25.2</td><td>50.12</td><td>50.08</td><td>50.22</td></tr> <tr><td>21.6</td><td>50.83</td><td>50.84</td><td>50.88</td></tr> <tr><td>18.0</td><td>51.07</td><td>51.11</td><td>51.76</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	36.0	48.46	48.49	48.59	34.2	48.68	48.66	48.78	32.4	48.96	48.92	49.00	28.8	49.50	49.49	49.63	25.2	50.12	50.08	50.22	21.6	50.83	50.84	50.88	18.0	51.07	51.11	51.76	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																							
36.0	48.46	48.49	48.59																																																							
34.2	48.68	48.66	48.78																																																							
32.4	48.96	48.92	49.00																																																							
28.8	49.50	49.49	49.63																																																							
25.2	50.12	50.08	50.22																																																							
21.6	50.83	50.84	50.88																																																							
18.0	51.07	51.11	51.76																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
<p>Intermittent operation occurs when the output voltage is from 18V to 0V.</p>																																																										



Model	PJMA1500F-36	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+36V42A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 115V	Input Volt. 230V
-20	35.852	35.853	35.855
25	36.095	36.097	36.098
50	36.151	36.152	36.150

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A	
Object	+36V42A		

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	68	68
25	69	70
50	67	68

Item	Overvoltage Protection	Testing Circuitry Figure A	
Object	+36V42A		

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	46.34	46.40
25	48.09	48.09
50	49.14	49.14

COSEL




Figure A




Figure B




Figure C (IEC60601-1)