



EXTRA TEST DATA OF PLA50F-24


*Regulated DC Power Supply
Jul 20, 2021*

COSEL CO.,LTD.

CONTENTS



1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Overvoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Figure of Testing Circuitry	5

(Final Page 5)

COSEL

COSEL


Model	PLA50F-24	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object	_____		



COSEL

Model	PLA50F-24	Temperature	25°C
Item	Over Voltage Protection	Testing Circuitry	A
Object	_____	Input Voltage : 100V	


Output
Voltage
[5V/div]



Load : 0%
Overvoltage protection
value : 32.4V


Time
[40ms/div]

Output
Voltage
[5V/div]




Load : 100%
Overvoltage protection
value : 32.2V

Time
[20ms/div]



COSEL


Model	PLA50F-24	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object	_____	Load	: Short

Output Current
[2A/div]

Input Voltage : 100V

Short-circuit
current : 8A


ON Time : 178ms

Short circuit
period : 358msTime
[200ms/div]Output Current
[2A/div]

Input Voltage : 230V

Short-circuit
current : 8A

ON Time : 180ms

Short circuit
period : 362msTime
[200ms/div]




Figure A