

TEST DATA OF PLA600F-15

Regulated DC Power Supply
August 19, 2011

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Shintaro Oki
Shintaro Oki Design Engineer

COSEL CO.,LTD.

CONTENTS


1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	PLA600F-15																																																						
Item	Input Current (by Load Current)	Temperature	25°C																																																				
Object	—	Testing Circuitry	Figure A																																																				
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 115V - - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 115V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.143</td><td>0.155</td><td>0.278</td></tr> <tr><td>8</td><td>1.642</td><td>1.439</td><td>0.806</td></tr> <tr><td>16</td><td>2.975</td><td>2.584</td><td>1.369</td></tr> <tr><td>24</td><td>4.366</td><td>3.784</td><td>1.942</td></tr> <tr><td>32</td><td>5.807</td><td>5.014</td><td>2.528</td></tr> <tr><td>40</td><td>7.290</td><td>6.284</td><td>3.127</td></tr> <tr><td>44</td><td>-</td><td>6.912</td><td>3.440</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 115V [A]	Input Volt. 230V [A]	0	0.143	0.155	0.278	8	1.642	1.439	0.806	16	2.975	2.584	1.369	24	4.366	3.784	1.942	32	5.807	5.014	2.528	40	7.290	6.284	3.127	44	-	6.912	3.440	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	2.Values					
Load Current [A]	Input Volt. 100V [A]	Input Volt. 115V [A]	Input Volt. 230V [A]																																																				
0	0.143	0.155	0.278																																																				
8	1.642	1.439	0.806																																																				
16	2.975	2.584	1.369																																																				
24	4.366	3.784	1.942																																																				
32	5.807	5.014	2.528																																																				
40	7.290	6.284	3.127																																																				
44	-	6.912	3.440																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.143</td><td>0.155</td><td>0.278</td></tr> <tr><td>8</td><td>1.642</td><td>1.439</td><td>0.806</td></tr> <tr><td>16</td><td>2.975</td><td>2.584</td><td>1.369</td></tr> <tr><td>24</td><td>4.366</td><td>3.784</td><td>1.942</td></tr> <tr><td>32</td><td>5.807</td><td>5.014</td><td>2.528</td></tr> <tr><td>40</td><td>7.290</td><td>6.284</td><td>3.127</td></tr> <tr><td>44</td><td>-</td><td>6.912</td><td>3.440</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	0.143	0.155	0.278	8	1.642	1.439	0.806	16	2.975	2.584	1.369	24	4.366	3.784	1.942	32	5.807	5.014	2.528	40	7.290	6.284	3.127	44	-	6.912	3.440	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Current [A]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0	0.143	0.155	0.278																																																				
8	1.642	1.439	0.806																																																				
16	2.975	2.584	1.369																																																				
24	4.366	3.784	1.942																																																				
32	5.807	5.014	2.528																																																				
40	7.290	6.284	3.127																																																				
44	-	6.912	3.440																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																						


COSEL

Model	PLA600F-15																																																					
Item	Input Power (by Load Current)	Temperature	25°C																																																			
Object	—	Testing Circuitry	Figure A																																																			
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 115V - - -○- - Input Volt. 230V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 1000) against Load Current [A] on the X-axis (0 to 40). Three curves are shown for different input voltages: 100V (solid line with triangles), 115V (dashed line with squares), and 230V (dotted line with circles). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (10, 150) and ending at (40, 750), indicating the range of the rated load current.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>6.4</td><td>6.3</td><td>6.7</td></tr> <tr><td>8</td><td>156.4</td><td>155.6</td><td>153.5</td></tr> <tr><td>16</td><td>292.0</td><td>289.8</td><td>284.1</td></tr> <tr><td>24</td><td>432.2</td><td>429.0</td><td>418.3</td></tr> <tr><td>32</td><td>577.1</td><td>571.4</td><td>555.0</td></tr> <tr><td>40</td><td>726.0</td><td>717.9</td><td>695.0</td></tr> <tr><td>44</td><td>-</td><td>789.7</td><td>764.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	6.4	6.3	6.7	8	156.4	155.6	153.5	16	292.0	289.8	284.1	24	432.2	429.0	418.3	32	577.1	571.4	555.0	40	726.0	717.9	695.0	44	-	789.7	764.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	6.4	6.3	6.7																																																			
8	156.4	155.6	153.5																																																			
16	292.0	289.8	284.1																																																			
24	432.2	429.0	418.3																																																			
32	577.1	571.4	555.0																																																			
40	726.0	717.9	695.0																																																			
44	-	789.7	764.5																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PLA600F-15
Item	Efficiency (by Input Voltage)
Object	—

1. Graph



Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	81.4	81.4 ※1
100	82.3	82.3 ※2
115	82.9	82.9
200	84.5	85.2
230	84.8	85.6
264	85.0	86.0
280	85.1	86.1
--	-	-
--	-	-

※1: Load 80%

※2: Load 90%

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	PLA600F-15																																																					
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V 																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8</td><td>76.0</td><td>76.4</td><td>77.5</td></tr> <tr> <td>16</td><td>81.4</td><td>82.1</td><td>83.7</td></tr> <tr> <td>24</td><td>82.6</td><td>83.3</td><td>85.4</td></tr> <tr> <td>32</td><td>82.5</td><td>83.3</td><td>85.8</td></tr> <tr> <td>40</td><td>82.0</td><td>82.9</td><td>85.6</td></tr> <tr> <td>44</td><td>-</td><td>82.8</td><td>85.6</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	-	-	-	8	76.0	76.4	77.5	16	81.4	82.1	83.7	24	82.6	83.3	85.4	32	82.5	83.3	85.8	40	82.0	82.9	85.6	44	-	82.8	85.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
8	76.0	76.4	77.5																																																			
16	81.4	82.1	83.7																																																			
24	82.6	83.3	85.4																																																			
32	82.5	83.3	85.8																																																			
40	82.0	82.9	85.6																																																			
44	-	82.8	85.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PLA600F-15	Temperature Testing Circuitry	25°C Figure A																																
Item	Power Factor (by Input Voltage)																																		
Object	—																																		
1. Graph		2. Values																																	
<p>Legend: - - - □ - - - Load 50% — △ — Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>0.990</td><td>0.996 ※1</td> </tr> <tr> <td>100</td><td>0.988</td><td>0.995 ※2</td> </tr> <tr> <td>115</td><td>0.982</td><td>0.994</td> </tr> <tr> <td>200</td><td>0.942</td><td>0.976</td> </tr> <tr> <td>230</td><td>0.923</td><td>0.967</td> </tr> <tr> <td>264</td><td>0.894</td><td>0.947</td> </tr> <tr> <td>280</td><td>0.830</td><td>0.890</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.990	0.996 ※1	100	0.988	0.995 ※2	115	0.982	0.994	200	0.942	0.976	230	0.923	0.967	264	0.894	0.947	280	0.830	0.890	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
85	0.990	0.996 ※1																																	
100	0.988	0.995 ※2																																	
115	0.982	0.994																																	
200	0.942	0.976																																	
230	0.923	0.967																																	
264	0.894	0.947																																	
280	0.830	0.890																																	
--	-	-																																	
--	-	-																																	
			※1: Load 80% ※2: Load 90%																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PLA600F-15
Item	Power Factor (by Load Current)
Object	—


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	0.448	0.355	0.105
8	0.952	0.940	0.827
16	0.982	0.975	0.901
24	0.990	0.986	0.936
32	0.994	0.991	0.954
40	0.996	0.994	0.965
44	-	0.994	0.965
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.


COSEL

Model PLA600F-15


Temperature 25°C
Testing Circuitry Figure A

Item Inrush Current


Object



Input Voltage 115 V
Frequency 60 Hz
Load 100 %
Primary inrush current : 23.7 A
Secondary inrush current : 14.7 A



Input Voltage 230 V
Frequency 60 Hz
Load 100 %
Primary inrush current : 35.1 A
Secondary inrush current : 6.9 A





Model	PLA600F-15	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

[mA]

Standards		Input Volt.			Note
		100 [V]	115 [V]	240 [V]	
DEN-AN	Both phases	0.31	0.33	0.66	Operation
	One of phases	0.43	0.51	1.10	Stand by
IEC60950-1	Both phases	0.25	0.29	0.64	Operation
	One of phases	0.44	0.50	1.10	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL


Model PLA600F-15

Item Line Regulation

Object +15V40A

1. Graph

---□--- Load 50%
 —△— Load 100%



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
 Testing Circuitry Figure A


2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	15.013	15.007 ※1
100	15.013	15.004 ※2
115	15.013	15.003
200	15.012	15.002
230	15.012	15.002
264	15.012	15.001
280	15.012	15.001
--	-	-
--	-	-

※1: Load 80%

※2: Load 90%


Model	PLA600F-15	Temperature 25°C Testing Circuitry Figure A																																																	
Item	Load Regulation																																																		
Object	+15V40A																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V 																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>15.023</td><td>15.023</td><td>15.022</td></tr> <tr> <td>8</td><td>15.015</td><td>15.015</td><td>15.014</td></tr> <tr> <td>16</td><td>15.014</td><td>15.014</td><td>15.013</td></tr> <tr> <td>24</td><td>15.011</td><td>15.012</td><td>15.011</td></tr> <tr> <td>32</td><td>15.007</td><td>15.007</td><td>15.007</td></tr> <tr> <td>40</td><td>15.000</td><td>15.006</td><td>15.006</td></tr> <tr> <td>44</td><td>-</td><td>15.002</td><td>15.001</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	15.023	15.023	15.022	8	15.015	15.015	15.014	16	15.014	15.014	15.013	24	15.011	15.012	15.011	32	15.007	15.007	15.007	40	15.000	15.006	15.006	44	-	15.002	15.001	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																
0	15.023	15.023	15.022																																																
8	15.015	15.015	15.014																																																
16	15.014	15.014	15.013																																																
24	15.011	15.012	15.011																																																
32	15.007	15.007	15.007																																																
40	15.000	15.006	15.006																																																
44	-	15.002	15.001																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
Note:	Slanted line shows the range of the rated load current.																																																		

COSEL

COSEL

Model	PLA600F-15
Item	Ripple Voltage (by Load Current)
Object	+15V40A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0	30	30
6	25	20
13	20	20
19	20	20
26	25	20
32	25	20
38	25	25
40	25	25
44	30	30
--	-	-
--	-	-

T1: Due to AC Input Line
T2: Due to Switching




Fig. Complex Ripple Wave Form


COSEL

Model PLA600F-15

Item Ripple-Noise

Object +15V40A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0	60	60
6	55	55
13	55	55
19	55	55
26	55	55
32	60	60
38	70	70
40	75	75
44	85	85
--	-	-
--	-	-



T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL

Model	PLA600F-15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V40A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-20	45	45
-10	40	40
0	35	35
10	30	30
20	25	25
25	25	25
30	25	25
40	30	30
50	35	35
--	-	-
--	-	-

Note: In case of Input Volt. 100V, Load 90%.

Other case Load 100%.

<p>Model PLA600F-15</p> <p>Item Ambient Temperature Drift</p> <p>Object +15V40A</p> <p>1.Graph</p> <p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 115V ---○--- Input Volt. 230V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	<p>Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>15.110</td><td>15.094</td><td>15.093</td></tr> <tr><td>-10</td><td>15.112</td><td>15.098</td><td>15.098</td></tr> <tr><td>0</td><td>15.112</td><td>15.101</td><td>15.101</td></tr> <tr><td>10</td><td>15.112</td><td>15.103</td><td>15.102</td></tr> <tr><td>+ 20</td><td>15.113</td><td>15.104</td><td>15.103</td></tr> <tr><td>25</td><td>15.109</td><td>15.105</td><td>15.105</td></tr> <tr><td>30</td><td>15.110</td><td>15.107</td><td>15.106</td></tr> <tr><td>40</td><td>15.110</td><td>15.106</td><td>15.105</td></tr> <tr><td>50</td><td>15.105</td><td>15.103</td><td>15.104</td></tr> <tr><td>60</td><td>-</td><td>15.101</td><td>15.102</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>Note: In case of Input Volt. 100V, Load 90%. Other case Load 100%.</p>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	-20	15.110	15.094	15.093	-10	15.112	15.098	15.098	0	15.112	15.101	15.101	10	15.112	15.103	15.102	+ 20	15.113	15.104	15.103	25	15.109	15.105	15.105	30	15.110	15.107	15.106	40	15.110	15.106	15.105	50	15.105	15.103	15.104	60	-	15.101	15.102	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																			
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																	
-20	15.110	15.094	15.093																																																	
-10	15.112	15.098	15.098																																																	
0	15.112	15.101	15.101																																																	
10	15.112	15.103	15.102																																																	
+ 20	15.113	15.104	15.103																																																	
25	15.109	15.105	15.105																																																	
30	15.110	15.107	15.106																																																	
40	15.110	15.106	15.105																																																	
50	15.105	15.103	15.104																																																	
60	-	15.101	15.102																																																	
--	-	-	-																																																	



Model	PLA600F-15	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+15V40A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 115 - 264V

Load Current : 0 - 40A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	30	230	0	15.129		
Minimum Voltage	-20	230	40	15.093	±18	±0.1

COSEL

Model	PLA600F-15	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+15V40A																							
1.Graph		2.Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 230V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.192</td></tr> <tr><td>0.5</td><td>15.191</td></tr> <tr><td>1.0</td><td>15.191</td></tr> <tr><td>2.0</td><td>15.191</td></tr> <tr><td>3.0</td><td>15.191</td></tr> <tr><td>4.0</td><td>15.191</td></tr> <tr><td>5.0</td><td>15.191</td></tr> <tr><td>6.0</td><td>15.191</td></tr> <tr><td>7.0</td><td>15.191</td></tr> <tr><td>8.0</td><td>15.191</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.192	0.5	15.191	1.0	15.191	2.0	15.191	3.0	15.191	4.0	15.191	5.0	15.191	6.0	15.191	7.0	15.191	8.0	15.191
Time since start [H]	Output Voltage [V]																							
0.0	15.192																							
0.5	15.191																							
1.0	15.191																							
2.0	15.191																							
3.0	15.191																							
4.0	15.191																							
5.0	15.191																							
6.0	15.191																							
7.0	15.191																							
8.0	15.191																							

* The characteristic of AC115V is equal.

COSEL


Model PLA600F-15

Item Rise and Fall Time

Object +15V40A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

[ms]


Input Volt.	Time	Td	Tr	Ts	Th	Tf
115 V		159.5	33.5	193.0	29.5	9.0
230 V		135.5	33.5	169.0	35.0	9.0



COSEL

Model	PLA600F-15
Item	Hold-Up Time
Object	+15V40A

1.Graph


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	59	36 ※1
100	61	32 ※2
115	62	29
200	71	33
230	73	35
264	74	36
280	74	36
--	-	-
--	-	-

※1:Load 80%

※2:Load 90%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	PLA600F-15	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+15V40A																																																					
1. Graph		2. Values																																																				
<p>Graph showing Instantaneous Compensation Time [ms] vs Load Current [A]. The Y-axis is logarithmic from 1 to 10000 ms. The X-axis is linear from 0 to 40 A. Three curves are shown for Input Volt. 100V (solid line with triangles), Input Volt. 115V (dashed line with squares), and Input Volt. 230V (dash-dot line with circles). A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8</td><td>114</td><td>126</td><td>172</td></tr> <tr><td>16</td><td>39</td><td>40</td><td>88</td></tr> <tr><td>24</td><td>31</td><td>31</td><td>55</td></tr> <tr><td>32</td><td>27</td><td>28</td><td>43</td></tr> <tr><td>40</td><td>22</td><td>23</td><td>30</td></tr> <tr><td>44</td><td>-</td><td>20</td><td>26</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	-	-	-	8	114	126	172	16	39	40	88	24	31	31	55	32	27	28	43	40	22	23	30	44	-	20	26	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
8	114	126	172																																																			
16	39	40	88																																																			
24	31	31	55																																																			
32	27	28	43																																																			
40	22	23	30																																																			
44	-	20	26																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PLA600F-15
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V40A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	46	59
-10	46	58
0	46	58
10	46	59
20	46	59
25	46	59
30	46	59
40	47	60
50	47	61
60	47	66
—	-	-


COSEL

Model PLA600F-15

Item Overcurrent Protection

Object +15V40A

1. Graph



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
14.25	46.29	46.26
13.50	46.42	46.39
12.00	46.69	46.60
10.50	46.89	46.76
9.00	46.97	46.77
7.50	47.01	46.79
6.00	46.97	46.53
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	PLA600F-15
Item	Overvoltage Protection
Object	+15V40A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 115[V]	Input Volt. 230[V]
-20	18.80	18.80
-10	18.85	18.85
0	18.90	18.90
10	18.95	18.95
20	18.98	18.98
25	19.10	19.10
30	19.10	19.10
40	19.15	19.15
50	19.20	19.20
60	19.25	19.25
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C