



DATA SHEET		Date	28-Jun-10
Model	PMA100F-12	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	K.Takami



Frequency MHz	Harm	Line Phase	Reading dB(uV)		Factor dB	Level dB(uV)		Limit dB(uV)		Margin dB		Pass/ Fail	Remark
			QP	AV		QP	AV	QP	AV	QP	AV		
0.23708		VA	36.2	33	10.1	46.3	43.1	62.2	52.2	15.9	9.1	Pass	
0.15968		VB	39.5	25.1	10.2	49.7	35.3	65.5	55.5	15.8	20.2	Pass	
0.2356		VB	33.1	28	10.1	43.2	38.1	62.2	52.2	19	14.1	Pass	



Frequency MHz	Polarization	Stability	Reading dB(uV)		Space Loss dB	Level dB(mW)		Margin dB	Pass/Fail	Height cm	Angle deg	Remark
			QP	AV		QP	AV					
115.03	H	Stable	52.4	-19.8		32.6		40	7.4	Pass	150	162
129.502	H	Stable	51.6	-19.6		32		40	8	Pass	146	137

DATA SHEET

Model	Circuit used for measurement
Test	EMI Line conduction & Radiated emission

1. Line conduction



2. Radiated emission

