

TEST DATA OF SFS104812

Regulated DC Power Supply
Jan.9. 2004

Approved by : Isao Yasuda
Isao Yasuda Design Manager

Prepared by : Kenichi Tsukada
Kenichi Tsukada Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	SFS104812																																																																									
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																							
Object	—	—	—																																																																							
1.Graph	<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 100% (▲) Load 50% (■) Load 0% (○) <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>24</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>33</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>35</td><td>0.022</td><td>0.182</td><td>0.343</td></tr> <tr><td>36</td><td>0.022</td><td>0.179</td><td>0.336</td></tr> <tr><td>40</td><td>0.021</td><td>0.162</td><td>0.303</td></tr> <tr><td>48</td><td>0.020</td><td>0.138</td><td>0.254</td></tr> <tr><td>60</td><td>0.020</td><td>0.113</td><td>0.206</td></tr> <tr><td>70</td><td>0.020</td><td>0.100</td><td>0.180</td></tr> <tr><td>76</td><td>0.020</td><td>0.094</td><td>0.167</td></tr> <tr><td>80</td><td>0.020</td><td>0.091</td><td>0.160</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	8	0.000	0.000	0.000	16	0.000	0.000	0.000	24	0.000	0.000	0.000	33	0.000	0.000	0.000	35	0.022	0.182	0.343	36	0.022	0.179	0.336	40	0.021	0.162	0.303	48	0.020	0.138	0.254	60	0.020	0.113	0.206	70	0.020	0.100	0.180	76	0.020	0.094	0.167	80	0.020	0.091	0.160	—	-	-	-	—	-	-	-	—	-	-	-
Input Voltage [V]	Input Current [A]																																																																									
	Load 0%	Load 50%	Load 100%																																																																							
0	0.000	0.000	0.000																																																																							
8	0.000	0.000	0.000																																																																							
16	0.000	0.000	0.000																																																																							
24	0.000	0.000	0.000																																																																							
33	0.000	0.000	0.000																																																																							
35	0.022	0.182	0.343																																																																							
36	0.022	0.179	0.336																																																																							
40	0.021	0.162	0.303																																																																							
48	0.020	0.138	0.254																																																																							
60	0.020	0.113	0.206																																																																							
70	0.020	0.100	0.180																																																																							
76	0.020	0.094	0.167																																																																							
80	0.020	0.091	0.160																																																																							
—	-	-	-																																																																							
—	-	-	-																																																																							
—	-	-	-																																																																							

COSEL

Model	SFS104812	Temperature Testing Circuitry	25°C Figure A																																																				
Item	Input Current (by Load Current)																																																						
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - -○--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.022</td><td>0.020</td><td>0.020</td></tr> <tr><td>0.15</td><td>0.071</td><td>0.057</td><td>0.043</td></tr> <tr><td>0.30</td><td>0.123</td><td>0.096</td><td>0.068</td></tr> <tr><td>0.45</td><td>0.179</td><td>0.138</td><td>0.094</td></tr> <tr><td>0.60</td><td>0.228</td><td>0.174</td><td>0.117</td></tr> <tr><td>0.75</td><td>0.281</td><td>0.213</td><td>0.141</td></tr> <tr><td>0.90</td><td>0.336</td><td>0.254</td><td>0.167</td></tr> <tr><td>0.95</td><td>0.353</td><td>0.267</td><td>0.175</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0.00	0.022	0.020	0.020	0.15	0.071	0.057	0.043	0.30	0.123	0.096	0.068	0.45	0.179	0.138	0.094	0.60	0.228	0.174	0.117	0.75	0.281	0.213	0.141	0.90	0.336	0.254	0.167	0.95	0.353	0.267	0.175	2.Values																	
Load Current [A]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																																																				
0.00	0.022	0.020	0.020																																																				
0.15	0.071	0.057	0.043																																																				
0.30	0.123	0.096	0.068																																																				
0.45	0.179	0.138	0.094																																																				
0.60	0.228	0.174	0.117																																																				
0.75	0.281	0.213	0.141																																																				
0.90	0.336	0.254	0.167																																																				
0.95	0.353	0.267	0.175																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.022</td><td>0.020</td><td>0.020</td></tr> <tr><td>0.15</td><td>0.071</td><td>0.057</td><td>0.043</td></tr> <tr><td>0.30</td><td>0.123</td><td>0.096</td><td>0.068</td></tr> <tr><td>0.45</td><td>0.179</td><td>0.138</td><td>0.094</td></tr> <tr><td>0.60</td><td>0.228</td><td>0.174</td><td>0.117</td></tr> <tr><td>0.75</td><td>0.281</td><td>0.213</td><td>0.141</td></tr> <tr><td>0.90</td><td>0.336</td><td>0.254</td><td>0.167</td></tr> <tr><td>0.95</td><td>0.353</td><td>0.267</td><td>0.175</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.022	0.020	0.020	0.15	0.071	0.057	0.043	0.30	0.123	0.096	0.068	0.45	0.179	0.138	0.094	0.60	0.228	0.174	0.117	0.75	0.281	0.213	0.141	0.90	0.336	0.254	0.167	0.95	0.353	0.267	0.175	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Current [A]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0.00	0.022	0.020	0.020																																																				
0.15	0.071	0.057	0.043																																																				
0.30	0.123	0.096	0.068																																																				
0.45	0.179	0.138	0.094																																																				
0.60	0.228	0.174	0.117																																																				
0.75	0.281	0.213	0.141																																																				
0.90	0.336	0.254	0.167																																																				
0.95	0.353	0.267	0.175																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SFS104812		
Item	Input Power (by Load Current)	Temperature 25°C	Testing Circuitry Figure A
Object	_____	_____	_____
1.Graph	Input Volt. 36V Input Volt. 48V Input Volt. 76V	2.Values	
<p>Note: Slanted line shows the range of the rated load current.</p>			
Load Current [A]	Input Power [W] 36[V]	Input Power [W] 48[V]	Input Power [W] 76[V]
0.00	0.76	0.97	1.52
0.15	2.55	2.74	3.30
0.30	4.41	4.60	5.15
0.45	6.28	6.46	7.02
0.60	8.18	8.33	8.88
0.75	10.09	10.22	10.75
0.90	12.02	12.13	12.63
0.95	12.67	12.77	13.27
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	SFS104812	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	—																																		
1.Graph	<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency [%] (Load 50%)</th> <th>Efficiency [%] (Load 100%)</th> </tr> </thead> <tbody> <tr><td>34</td><td>84.5</td><td>85.5</td></tr> <tr><td>36</td><td>84.5</td><td>85.4</td></tr> <tr><td>40</td><td>84.0</td><td>88.0</td></tr> <tr><td>48</td><td>80.5</td><td>87.8</td></tr> <tr><td>55</td><td>77.5</td><td>84.7</td></tr> <tr><td>60</td><td>79.5</td><td>84.7</td></tr> <tr><td>70</td><td>77.4</td><td>82.8</td></tr> <tr><td>76</td><td>76.3</td><td>82.8</td></tr> <tr><td>78</td><td>75.5</td><td>81.0</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%] (Load 50%)	Efficiency [%] (Load 100%)	34	84.5	85.5	36	84.5	85.4	40	84.0	88.0	48	80.5	87.8	55	77.5	84.7	60	79.5	84.7	70	77.4	82.8	76	76.3	82.8	78	75.5	81.0		
Input Voltage [V]	Efficiency [%] (Load 50%)	Efficiency [%] (Load 100%)																																	
34	84.5	85.5																																	
36	84.5	85.4																																	
40	84.0	88.0																																	
48	80.5	87.8																																	
55	77.5	84.7																																	
60	79.5	84.7																																	
70	77.4	82.8																																	
76	76.3	82.8																																	
78	75.5	81.0																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>34</td><td>85.5</td><td>89.1</td></tr> <tr><td>36</td><td>85.4</td><td>89.3</td></tr> <tr><td>40</td><td>84.7</td><td>89.1</td></tr> <tr><td>48</td><td>82.8</td><td>88.4</td></tr> <tr><td>55</td><td>81.0</td><td>87.6</td></tr> <tr><td>60</td><td>79.7</td><td>87.0</td></tr> <tr><td>70</td><td>77.4</td><td>85.5</td></tr> <tr><td>76</td><td>76.3</td><td>84.8</td></tr> <tr><td>78</td><td>75.5</td><td>84.4</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	34	85.5	89.1	36	85.4	89.3	40	84.7	89.1	48	82.8	88.4	55	81.0	87.6	60	79.7	87.0	70	77.4	85.5	76	76.3	84.8	78	75.5	84.4
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
34	85.5	89.1																																	
36	85.4	89.3																																	
40	84.7	89.1																																	
48	82.8	88.4																																	
55	81.0	87.6																																	
60	79.7	87.0																																	
70	77.4	85.5																																	
76	76.3	84.8																																	
78	75.5	84.4																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	SFS104812
Item	Efficiency (by Load Current)
Object	

1. Graph

Load Current [A]	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
0.15	68.4	63.6	52.7
0.30	80.5	77.0	68.9
0.45	85.4	82.8	76.3
0.60	87.4	85.7	80.5
0.75	88.7	87.4	83.1
0.90	89.3	88.4	84.8
0.95	89.3	88.6	85.2

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.00	-	-	-
0.15	68.4	63.6	52.7
0.30	80.5	77.0	68.9
0.45	85.4	82.8	76.3
0.60	87.4	85.7	80.5
0.75	88.7	87.4	83.1
0.90	89.3	88.4	84.8
0.95	89.3	88.6	85.2
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model SFS104812

Item Line Regulation

Object +12V0.9A

1. Graph



Note: Slanted line shows the range of the rated input voltage.


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
34	12.069	11.964
36	12.097	12.012
40	12.090	12.018
48	12.073	12.005
55	12.067	12.000
60	12.066	11.998
70	12.072	11.996
76	12.079	11.997
78	12.081	11.997

COSEL

Model	SFS104812	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.9A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.191</td><td>12.172</td><td>12.162</td></tr> <tr><td>0.15</td><td>12.160</td><td>12.143</td><td>12.128</td></tr> <tr><td>0.30</td><td>12.125</td><td>12.104</td><td>12.109</td></tr> <tr><td>0.45</td><td>12.096</td><td>12.072</td><td>12.078</td></tr> <tr><td>0.60</td><td>12.070</td><td>12.048</td><td>12.043</td></tr> <tr><td>0.75</td><td>12.043</td><td>12.027</td><td>12.017</td></tr> <tr><td>0.90</td><td>12.012</td><td>12.006</td><td>11.997</td></tr> <tr><td>0.95</td><td>12.001</td><td>11.999</td><td>11.991</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	12.191	12.172	12.162	0.15	12.160	12.143	12.128	0.30	12.125	12.104	12.109	0.45	12.096	12.072	12.078	0.60	12.070	12.048	12.043	0.75	12.043	12.027	12.017	0.90	12.012	12.006	11.997	0.95	12.001	11.999	11.991	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	12.191	12.172	12.162																																																			
0.15	12.160	12.143	12.128																																																			
0.30	12.125	12.104	12.109																																																			
0.45	12.096	12.072	12.078																																																			
0.60	12.070	12.048	12.043																																																			
0.75	12.043	12.027	12.017																																																			
0.90	12.012	12.006	11.997																																																			
0.95	12.001	11.999	11.991																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL


Model	SFS104812																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+12V0.9A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 50 mV, and the X-axis ranges from 0.0 to 1.2 A. Two sets of data points are plotted: Input Volt. 36V (open circles) and Input Volt. 76V (open triangles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (36V)</th> <th>Ripple Voltage [mV] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>22</td><td>35</td></tr> <tr><td>0.18</td><td>22</td><td>35</td></tr> <tr><td>0.36</td><td>22</td><td>35</td></tr> <tr><td>0.54</td><td>22</td><td>35</td></tr> <tr><td>0.72</td><td>22</td><td>35</td></tr> <tr><td>0.90</td><td>22</td><td>35</td></tr> <tr><td>0.99</td><td>22</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (36V)	Ripple Voltage [mV] (76V)	0.00	22	35	0.18	22	35	0.36	22	35	0.54	22	35	0.72	22	35	0.90	22	35	0.99	22	35	--	-	-	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (36V)	Ripple Voltage [mV] (76V)																																						
0.00	22	35																																						
0.18	22	35																																						
0.36	22	35																																						
0.54	22	35																																						
0.72	22	35																																						
0.90	22	35																																						
0.99	22	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>22</td><td>35</td></tr> <tr><td>0.18</td><td>22</td><td>35</td></tr> <tr><td>0.36</td><td>22</td><td>35</td></tr> <tr><td>0.54</td><td>22</td><td>35</td></tr> <tr><td>0.72</td><td>22</td><td>35</td></tr> <tr><td>0.90</td><td>22</td><td>35</td></tr> <tr><td>0.99</td><td>22</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	22	35	0.18	22	35	0.36	22	35	0.54	22	35	0.72	22	35	0.90	22	35	0.99	22	35	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	22	35																																						
0.18	22	35																																						
0.36	22	35																																						
0.54	22	35																																						
0.72	22	35																																						
0.90	22	35																																						
0.99	22	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	SFS104812
Item	Ripple-Noise
Object	+12V0.9A

Temperature 25°C
 Testing Circuitry Figure C

1.Graph



Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.00	22	35
0.18	22	35
0.36	22	35
0.54	22	35
0.72	22	35
0.90	22	35
0.99	22	35
--	-	-
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

COSEL

Model	SFS104812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.9A

1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-50	30	30
-40	30	30
-20	27	27
0	25	25
25	22	22
85	22	22
90	22	22
--	--	--
--	--	--
--	--	--
--	--	--

COSEL

Model	SFS104812	Testing Circuitry Figure A		
Item	Ambient Temperature Drift			
Object	+12V0.9A			
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 	2.Values		
Ambient Temperature [°C]	Output Voltage [V]			
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	
-45	11.992	11.988	11.971	
-40	11.996	11.989	11.974	
-20	12.010	11.995	11.985	
0	12.022	12.004	11.997	
25	12.015	12.005	11.996	
50	11.975	12.003	11.988	
85	11.953	12.004	11.975	
90	11.951	12.002	11.971	
--	-	-	-	
--	-	-	-	
--	-	-	-	

Note: Slanted line shows the range of the rated ambient temperature.



Model	SFS104812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.9A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 ~ 85°C

Input Voltage : 36 ~ 76V

Load Current : 0 ~ 0.9A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	85	48	0	12.224	±136	±1.1
Minimum Voltage	85	36	0.9	11.952		

COSEL

Model	SFS104812
Item	Time Lapse Drift
Object	+12V0.9A

1.Graph


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	12.007
0.5	12.003
1.0	12.004
2.0	12.003
3.0	12.004
4.0	12.003
5.0	12.004
6.0	12.004
7.0	12.003
8.0	12.003

COSEL

Model SFS104812


Item Rise and Fall Time

Object +12V0.9A

Temperature 25°C
Testing Circuitry Figure A

1. Graph


Input Volt. 36 V



2. Values

[mS]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		58.8	0.8	59.6	0.3	1.3
100 %		58.8	0.8	59.6	0.3	0.8



Model	SFS104812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.9A

Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-45	32.2	32.2
-40	32.2	32.2
-20	32.4	32.4
0	32.4	32.6
25	32.6	32.6
50	32.6	32.8
85	32.8	32.8
90	32.8	32.8
--	-	-
--	-	-
--	-	-

COSEL

Model	SFS104812	Temperature 25°C Testing Circuitry Figure A																																																																					
Item	Overcurrent Protection																																																																						
Object	+12V0.9A																																																																						
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																																						
	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																						
	<p>When the output voltage fell to less than 10.8V, the unit shuts off the output by operating low voltage protection.</p>																																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>0.92</td><td>0.92</td><td>0.92</td></tr> <tr><td>11.4</td><td>1.07</td><td>1.08</td><td>1.14</td></tr> <tr><td>10.8</td><td>1.07</td><td>1.09</td><td>1.16</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	0.92	0.92	0.92	11.4	1.07	1.08	1.14	10.8	1.07	1.09	1.16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																				
12.0	0.92	0.92	0.92																																																																				
11.4	1.07	1.08	1.14																																																																				
10.8	1.07	1.09	1.16																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				
-	-	-	-																																																																				


COSEL

Model SFS104812

Item Overvoltage Protection

Object +12V0.9A

1.Graph ——▲— Input Volt. 48V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]		
	Input Volt. 48[V]	Input Volt.	Input Volt.
-40	16.14	-	-
25	15.97	-	-
85	15.79	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-




Figure A




Figure B (General Electric Characteristic)




Figure C (Ripple and Ripple noise Characteristic)