

TEST DATA OF SNDBS400B03

Regulated DC Power Supply
July 20, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

Model	SNDBS400B03																																																																																	
Item	Input Current (by Input Voltage)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Load 100% (solid line with triangles) Load 50% (dashed line with squares) Load 0% (dash-dot line with circles) <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>165</td><td>0.026</td><td>1.015</td><td>1.922</td></tr> <tr><td>170</td><td>0.026</td><td>0.980</td><td>1.908</td></tr> <tr><td>180</td><td>0.025</td><td>0.920</td><td>1.790</td></tr> <tr><td>200</td><td>0.025</td><td>0.821</td><td>1.643</td></tr> <tr><td>250</td><td>0.024</td><td>0.659</td><td>1.282</td></tr> <tr><td>280</td><td>0.022</td><td>0.592</td><td>1.173</td></tr> <tr><td>300</td><td>0.022</td><td>0.555</td><td>1.066</td></tr> <tr><td>350</td><td>0.022</td><td>0.482</td><td>0.916</td></tr> <tr><td>400</td><td>0.022</td><td>0.427</td><td>0.830</td></tr> <tr><td>420</td><td>0.021</td><td>0.409</td><td>0.769</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.000	0.000	0.000	165	0.026	1.015	1.922	170	0.026	0.980	1.908	180	0.025	0.920	1.790	200	0.025	0.821	1.643	250	0.024	0.659	1.282	280	0.022	0.592	1.173	300	0.022	0.555	1.066	350	0.022	0.482	0.916	400	0.022	0.427	0.830	420	0.021	0.409	0.769	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
50	0.000	0.000	0.000																																																																															
100	0.000	0.000	0.000																																																																															
150	0.000	0.000	0.000																																																																															
165	0.026	1.015	1.922																																																																															
170	0.026	0.980	1.908																																																																															
180	0.025	0.920	1.790																																																																															
200	0.025	0.821	1.643																																																																															
250	0.024	0.659	1.282																																																																															
280	0.022	0.592	1.173																																																																															
300	0.022	0.555	1.066																																																																															
350	0.022	0.482	0.916																																																																															
400	0.022	0.427	0.830																																																																															
420	0.021	0.409	0.769																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	SNDBS400B03																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 200V Input Volt. 280V Input Volt. 400V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.025</td><td>0.022</td><td>0.022</td></tr> <tr> <td>15</td><td>0.328</td><td>0.231</td><td>0.175</td></tr> <tr> <td>30</td><td>0.614</td><td>0.440</td><td>0.321</td></tr> <tr> <td>45</td><td>0.908</td><td>0.654</td><td>0.470</td></tr> <tr> <td>60</td><td>1.216</td><td>0.872</td><td>0.622</td></tr> <tr> <td>75</td><td>1.535</td><td>1.097</td><td>0.777</td></tr> <tr> <td>80</td><td>1.643</td><td>1.173</td><td>0.830</td></tr> <tr> <td>88</td><td>1.818</td><td>1.295</td><td>0.915</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	0.025	0.022	0.022	15	0.328	0.231	0.175	30	0.614	0.440	0.321	45	0.908	0.654	0.470	60	1.216	0.872	0.622	75	1.535	1.097	0.777	80	1.643	1.173	0.830	88	1.818	1.295	0.915	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	0.025	0.022	0.022																																																			
15	0.328	0.231	0.175																																																			
30	0.614	0.440	0.321																																																			
45	0.908	0.654	0.470																																																			
60	1.216	0.872	0.622																																																			
75	1.535	1.097	0.777																																																			
80	1.643	1.173	0.830																																																			
88	1.818	1.295	0.915																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model SNDBS400B03

Item Input Power (by Load Current)

Object _____

1. Graph

- △— Input Volt. 200V
- - □ - - Input Volt. 280V
- · ○ - - Input Volt. 400V




Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0	4.8	6.2	8.5
15	65.5	64.7	70.1
30	122.5	123.2	128.4
45	181.4	183.2	187.7
60	242.9	244.2	248.6
75	307.0	307.2	310.8
80	328.3	328.3	332.0
88	363.1	362.6	365.9
--	-	-	-
--	-	-	-
--	-	-	-


Model	SNDBS400B03																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>170</td><td>81.4</td><td>79.9</td></tr> <tr><td>180</td><td>81.9</td><td>80.3</td></tr> <tr><td>200</td><td>82.6</td><td>80.4</td></tr> <tr><td>240</td><td>82.3</td><td>80.5</td></tr> <tr><td>280</td><td>81.9</td><td>80.4</td></tr> <tr><td>320</td><td>81.3</td><td>80.2</td></tr> <tr><td>360</td><td>80.4</td><td>79.9</td></tr> <tr><td>400</td><td>79.5</td><td>79.5</td></tr> <tr><td>420</td><td>79.0</td><td>79.3</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	170	81.4	79.9	180	81.9	80.3	200	82.6	80.4	240	82.3	80.5	280	81.9	80.4	320	81.3	80.2	360	80.4	79.9	400	79.5	79.5	420	79.0	79.3
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
170	81.4	79.9																																
180	81.9	80.3																																
200	82.6	80.4																																
240	82.3	80.5																																
280	81.9	80.4																																
320	81.3	80.2																																
360	80.4	79.9																																
400	79.5	79.5																																
420	79.0	79.3																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	SNDBS400B03		
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A
Object	<hr/>		
1.Graph	<p>—△— Input Volt. 200V - - -□--- Input Volt. 280V - - -○--- Input Volt. 400V</p> 		
2.Values	Load Current [A]	Efficiency [%]	Efficiency [%]
		Input Volt. 200[V]	Input Volt. 280[V]
0		-	-
15		76.7	77.7
30		81.8	81.4
45		82.6	81.8
60		81.9	81.5
75		80.7	80.6
80		80.4	80.4
88		79.8	79.9
--		-	-
--		-	-
--		-	-

Note: Slanted line shows the range of the rated load current.

Model	SNDBS400B03																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+3.3V80A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>170</td><td>3.348</td><td>3.316</td></tr> <tr><td>180</td><td>3.348</td><td>3.316</td></tr> <tr><td>200</td><td>3.348</td><td>3.316</td></tr> <tr><td>240</td><td>3.349</td><td>3.316</td></tr> <tr><td>280</td><td>3.349</td><td>3.316</td></tr> <tr><td>320</td><td>3.349</td><td>3.315</td></tr> <tr><td>360</td><td>3.349</td><td>3.315</td></tr> <tr><td>400</td><td>3.349</td><td>3.315</td></tr> <tr><td>420</td><td>3.349</td><td>3.314</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	170	3.348	3.316	180	3.348	3.316	200	3.348	3.316	240	3.349	3.316	280	3.349	3.316	320	3.349	3.315	360	3.349	3.315	400	3.349	3.315	420	3.349	3.314
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
170	3.348	3.316																																
180	3.348	3.316																																
200	3.348	3.316																																
240	3.349	3.316																																
280	3.349	3.316																																
320	3.349	3.315																																
360	3.349	3.315																																
400	3.349	3.315																																
420	3.349	3.314																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	SNDBS400B03																																																					
Item	Load Regulation																																																					
Object	+3.3V80A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 200V Input Volt. 280V Input Volt. 400V 																																																					
	<p>Temperature 25°C Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3.380</td> <td>3.381</td> <td>3.381</td> </tr> <tr> <td>15</td> <td>3.369</td> <td>3.370</td> <td>3.370</td> </tr> <tr> <td>30</td> <td>3.357</td> <td>3.358</td> <td>3.358</td> </tr> <tr> <td>45</td> <td>3.345</td> <td>3.346</td> <td>3.346</td> </tr> <tr> <td>60</td> <td>3.333</td> <td>3.334</td> <td>3.333</td> </tr> <tr> <td>75</td> <td>3.321</td> <td>3.321</td> <td>3.321</td> </tr> <tr> <td>80</td> <td>3.317</td> <td>3.316</td> <td>3.315</td> </tr> <tr> <td>88</td> <td>3.310</td> <td>3.310</td> <td>3.309</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0	3.380	3.381	3.381	15	3.369	3.370	3.370	30	3.357	3.358	3.358	45	3.345	3.346	3.346	60	3.333	3.334	3.333	75	3.321	3.321	3.321	80	3.317	3.316	3.315	88	3.310	3.310	3.309	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0	3.380	3.381	3.381																																																			
15	3.369	3.370	3.370																																																			
30	3.357	3.358	3.358																																																			
45	3.345	3.346	3.346																																																			
60	3.333	3.334	3.333																																																			
75	3.321	3.321	3.321																																																			
80	3.317	3.316	3.315																																																			
88	3.310	3.310	3.309																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

COSEL


COSSEL

Model SNDBS400B03

Item Ripple Voltage (by Load Current)

Object +3.3V80A

1. Graph



Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values


Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	14	18
15	14	20
30	14	22
45	16	24
60	18	24
75	20	24
80	20	24
88	20	26
--	-	-
--	-	-
--	-	-

COSEL

Model	SNDBS400B03
Item	Ripple-Noise
Object	+3.3V80A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0	18	26
15	20	28
30	22	32
45	22	34
60	24	36
75	24	36
80	24	36
88	24	36
--	-	-
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SNDBS400B03
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V80A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.





Fig.Complex Ripple Noise Wave Form

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	20	24
-20	18	22
0	18	22
25	18	22
55	16	20
70	16	20
80	16	20
--	-	-
--	-	-
--	-	-
--	-	-



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-40	3.321	3.320	3.320
-20	3.321	3.321	3.320
0	3.321	3.321	3.320
15	3.318	3.318	3.317
25	3.316	3.316	3.315
40	3.313	3.313	3.313
55	3.310	3.310	3.309
70	3.304	3.304	3.303
80	3.301	3.301	3.300
90	3.295	3.294	3.293
--	-	-	-



Model	SNDBS400B03	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V80A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 80°C

Input Voltage : 200 - 400V

Load Current : 0 - 80A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	400	0	3.383	± 40	± 1.2
Minimum Voltage	80	400	80	3.303		

COSEL


Model	SNDBS400B03	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+3.3V80A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt: 280V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.319</td></tr> <tr><td>0.5</td><td>3.320</td></tr> <tr><td>1.0</td><td>3.321</td></tr> <tr><td>2.0</td><td>3.321</td></tr> <tr><td>3.0</td><td>3.321</td></tr> <tr><td>4.0</td><td>3.321</td></tr> <tr><td>5.0</td><td>3.321</td></tr> <tr><td>6.0</td><td>3.321</td></tr> <tr><td>7.0</td><td>3.321</td></tr> <tr><td>8.0</td><td>3.321</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.319	0.5	3.320	1.0	3.321	2.0	3.321	3.0	3.321	4.0	3.321	5.0	3.321	6.0	3.321	7.0	3.321	8.0	3.321
Time since start [H]	Output Voltage [V]																								
0.0	3.319																								
0.5	3.320																								
1.0	3.321																								
2.0	3.321																								
3.0	3.321																								
4.0	3.321																								
5.0	3.321																								
6.0	3.321																								
7.0	3.321																								
8.0	3.321																								

COSEL

Model	SNDBS400B03
Item	Rise and Fall Time
Object	+3.3V80A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		14.3	26.5	40.8	0.1	1.5	
100 %		14.3	27.0	41.3	0.1	0.7	



Model	SNDBS400B03
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V80A

Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	152	162
-20	151	162
0	151	162
15	150	162
25	150	162
40	150	162
55	150	162
70	149	162
80	149	162
90	148	162
--	-	-

COSEL

Model	SNDBS400B03					
Item	Overcurrent Protection					
Object	+3.3V80A					
1.Graph						
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 200V Input Volt. 280V Input Volt. 400V</p>						
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 2.31V to 0V.</p>						
Temperature 25°C Testing Circuitry Figure A						
2.Values						
Output Voltage [V]	Load Current [A]					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]			
3.14	93.63	94.09	96.14			
2.97	93.85	94.40	96.32			
2.64	94.51	94.86	96.93			
2.31	94.93	95.19	97.35			
--	-	-	-			
--	-	-	-			
--	-	-	-			
--	-	-	-			
--	-	-	-			
--	-	-	-			
--	-	-	-			
--	-	-	-			
--	-	-	-			

Model	SNDBS400B03																																						
Item	Overvoltage Protection																																						
Object	+3.3V80A																																						
1.Graph																																							
<p>The graph plots the operating point in Volts against ambient temperature in degrees Celsius. Two data series are shown: Input Volt. 200V (solid line with open triangle markers) and Input Volt. 400V (dashed line with open square markers). Both series show a slight decrease in operating point as ambient temperature increases from -40°C to 90°C. Slanted lines indicate the rated ambient temperature range for each input voltage.</p> <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>5.22</td><td>5.22</td></tr> <tr><td>-20</td><td>5.10</td><td>5.10</td></tr> <tr><td>0</td><td>4.98</td><td>4.98</td></tr> <tr><td>15</td><td>4.81</td><td>4.81</td></tr> <tr><td>25</td><td>4.81</td><td>4.81</td></tr> <tr><td>40</td><td>4.69</td><td>4.69</td></tr> <tr><td>55</td><td>4.63</td><td>4.63</td></tr> <tr><td>70</td><td>4.57</td><td>4.57</td></tr> <tr><td>80</td><td>4.54</td><td>4.54</td></tr> <tr><td>90</td><td>4.50</td><td>4.50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Volt. 200[V]	Input Volt. 400[V]	-40	5.22	5.22	-20	5.10	5.10	0	4.98	4.98	15	4.81	4.81	25	4.81	4.81	40	4.69	4.69	55	4.63	4.63	70	4.57	4.57	80	4.54	4.54	90	4.50	4.50	--	-	-		
Ambient Temperature [°C]	Input Volt. 200[V]	Input Volt. 400[V]																																					
-40	5.22	5.22																																					
-20	5.10	5.10																																					
0	4.98	4.98																																					
15	4.81	4.81																																					
25	4.81	4.81																																					
40	4.69	4.69																																					
55	4.63	4.63																																					
70	4.57	4.57																																					
80	4.54	4.54																																					
90	4.50	4.50																																					
--	-	-																																					
2.Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>5.22</td><td>5.22</td></tr> <tr><td>-20</td><td>5.10</td><td>5.10</td></tr> <tr><td>0</td><td>4.98</td><td>4.98</td></tr> <tr><td>15</td><td>4.81</td><td>4.81</td></tr> <tr><td>25</td><td>4.81</td><td>4.81</td></tr> <tr><td>40</td><td>4.69</td><td>4.69</td></tr> <tr><td>55</td><td>4.63</td><td>4.63</td></tr> <tr><td>70</td><td>4.57</td><td>4.57</td></tr> <tr><td>80</td><td>4.54</td><td>4.54</td></tr> <tr><td>90</td><td>4.50</td><td>4.50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	5.22	5.22	-20	5.10	5.10	0	4.98	4.98	15	4.81	4.81	25	4.81	4.81	40	4.69	4.69	55	4.63	4.63	70	4.57	4.57	80	4.54	4.54	90	4.50	4.50	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																						
	Input Volt. 200[V]	Input Volt. 400[V]																																					
-40	5.22	5.22																																					
-20	5.10	5.10																																					
0	4.98	4.98																																					
15	4.81	4.81																																					
25	4.81	4.81																																					
40	4.69	4.69																																					
55	4.63	4.63																																					
70	4.57	4.57																																					
80	4.54	4.54																																					
90	4.50	4.50																																					
--	-	-																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																							




Figure A

