

TEST DATA OF SNDBS700B24

Regulated DC Power Supply
July 9, 2012

Approved by :

Takahiro Yoneda

Takahiro Yoneda

Design Manager

Prepared by :

Satoshi Kinoshita

Satoshi Kinoshita

Design Engineer


COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage) · · · · ·	1
2. Input Current (by Load Current) · · · · ·	2
3. Input Power (by Load Current) · · · · ·	3
4. Efficiency (by Input Voltage) · · · · ·	4
5. Efficiency (by Load Current) · · · · ·	5
6. Line Regulation · · · · ·	6
7. Load Regulation · · · · ·	7
8. Dynamic Load Response · · · · ·	8
9. Ripple Voltage (by Load Current) · · · · ·	9
10. Ripple-Noise · · · · ·	10
11. Ripple Voltage (by Ambient Temperature) · · · · ·	11
12. Ambient Temperature Drift · · · · ·	12
13. Output Voltage Accuracy · · · · ·	13
14. Time Lapse Drift · · · · ·	14
15. Rise and Fall Time · · · · ·	15
16. Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17. Overcurrent Protection · · · · ·	17
18. Overvoltage Protection · · · · ·	18
19. Figure of Testing Circuitry · · · · ·	19

(Final Page 19)

Model	SNDBS700B24
Item	Input Current (by Input Voltage)
Object	—



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
50	0.000	0.000	0.000
100	0.000	0.000	0.000
150	0.003	0.003	0.003
170	0.003	0.003	0.003
180	0.003	0.003	0.003
190	0.019	2.020	4.065
200	0.018	1.922	3.852
250	0.015	1.546	3.092
280	0.014	1.388	2.758
300	0.013	1.299	2.587
350	0.012	1.126	2.230
400	0.011	0.997	1.956
420	0.011	0.954	1.876
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


COSEL

Model	SNDBS700B24																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	—	—	—																																																			
1. Graph		2. Values																																																				
<p>Graph showing Input Current [A] vs Load Current [A] for SNDBS700B24 at 25°C. The graph plots Input Current [A] on the y-axis (0.0 to 5.0) against Load Current [A] on the x-axis (0 to 30). Three curves are shown for Input Voltages: 200V (solid line with triangles), 280V (dashed line with squares), and 400V (dash-dot line with circles). A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.018</td> <td>0.014</td> <td>0.011</td> </tr> <tr> <td>4.0</td> <td>0.560</td> <td>0.402</td> <td>0.292</td> </tr> <tr> <td>8.0</td> <td>1.072</td> <td>0.782</td> <td>0.570</td> </tr> <tr> <td>12.0</td> <td>1.586</td> <td>1.150</td> <td>0.829</td> </tr> <tr> <td>16.0</td> <td>2.108</td> <td>1.521</td> <td>1.090</td> </tr> <tr> <td>20.0</td> <td>2.640</td> <td>1.900</td> <td>1.354</td> </tr> <tr> <td>24.0</td> <td>3.174</td> <td>2.278</td> <td>1.619</td> </tr> <tr> <td>28.0</td> <td>3.715</td> <td>2.660</td> <td>1.890</td> </tr> <tr> <td>29.0</td> <td>3.852</td> <td>2.758</td> <td>1.956</td> </tr> <tr> <td>31.9</td> <td>4.252</td> <td>3.040</td> <td>2.154</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	0.018	0.014	0.011	4.0	0.560	0.402	0.292	8.0	1.072	0.782	0.570	12.0	1.586	1.150	0.829	16.0	2.108	1.521	1.090	20.0	2.640	1.900	1.354	24.0	3.174	2.278	1.619	28.0	3.715	2.660	1.890	29.0	3.852	2.758	1.956	31.9	4.252	3.040	2.154	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.0	0.018	0.014	0.011																																																			
4.0	0.560	0.402	0.292																																																			
8.0	1.072	0.782	0.570																																																			
12.0	1.586	1.150	0.829																																																			
16.0	2.108	1.521	1.090																																																			
20.0	2.640	1.900	1.354																																																			
24.0	3.174	2.278	1.619																																																			
28.0	3.715	2.660	1.890																																																			
29.0	3.852	2.758	1.956																																																			
31.9	4.252	3.040	2.154																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNDBS700B24
Item	Input Power (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	3.4	3.6	4.1
4.0	111.7	112.4	116.5
8.0	213.8	218.9	227.6
12.0	316.8	321.8	331.7
16.0	421.0	425.5	436.0
20.0	527.0	531.0	541.0
24.0	634.0	637.0	647.0
28.0	742.0	745.0	755.0
29.0	770.0	772.0	781.0
31.9	850.0	851.0	860.0
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL


Model SNDBS700B24

Item Efficiency (by Input Voltage)

Object _____

1. Graph

--- □ --- Load 50%
 —△— Load 100%



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
195	90.6	89.8
200	90.6	89.8
240	90.1	89.8
280	89.5	89.6
320	88.8	89.2
360	88.1	88.9
400	87.2	88.6
420	86.8	88.1
--	-	-


Model	SNDBS700B24																																																					
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 200V Input Volt. 280V Input Volt. 400V 																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>4.0</td><td>85.6</td><td>85.1</td><td>82.2</td></tr> <tr> <td>8.0</td><td>89.3</td><td>87.3</td><td>83.9</td></tr> <tr> <td>12.0</td><td>90.4</td><td>89.0</td><td>86.3</td></tr> <tr> <td>16.0</td><td>90.6</td><td>89.7</td><td>87.5</td></tr> <tr> <td>20.0</td><td>90.6</td><td>89.9</td><td>88.3</td></tr> <tr> <td>24.0</td><td>90.4</td><td>89.9</td><td>88.6</td></tr> <tr> <td>28.0</td><td>90.0</td><td>89.7</td><td>88.5</td></tr> <tr> <td>29.0</td><td>89.8</td><td>89.6</td><td>88.6</td></tr> <tr> <td>31.9</td><td>89.5</td><td>89.4</td><td>88.5</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	-	-	-	4.0	85.6	85.1	82.2	8.0	89.3	87.3	83.9	12.0	90.4	89.0	86.3	16.0	90.6	89.7	87.5	20.0	90.6	89.9	88.3	24.0	90.4	89.9	88.6	28.0	90.0	89.7	88.5	29.0	89.8	89.6	88.6	31.9	89.5	89.4	88.5	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																			
0.0	-	-	-																																																			
4.0	85.6	85.1	82.2																																																			
8.0	89.3	87.3	83.9																																																			
12.0	90.4	89.0	86.3																																																			
16.0	90.6	89.7	87.5																																																			
20.0	90.6	89.9	88.3																																																			
24.0	90.4	89.9	88.6																																																			
28.0	90.0	89.7	88.5																																																			
29.0	89.8	89.6	88.6																																																			
31.9	89.5	89.4	88.5																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNDBS700B24																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+24V29A																																	
1.Graph																																		
		2.Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>24.098</td><td>24.081</td></tr> <tr><td>200</td><td>24.098</td><td>24.079</td></tr> <tr><td>240</td><td>24.099</td><td>24.079</td></tr> <tr><td>280</td><td>24.098</td><td>24.077</td></tr> <tr><td>320</td><td>24.098</td><td>24.076</td></tr> <tr><td>360</td><td>24.098</td><td>24.075</td></tr> <tr><td>400</td><td>24.097</td><td>24.074</td></tr> <tr><td>420</td><td>24.096</td><td>24.074</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	24.098	24.081	200	24.098	24.079	240	24.099	24.079	280	24.098	24.077	320	24.098	24.076	360	24.098	24.075	400	24.097	24.074	420	24.096	24.074	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
195	24.098	24.081																																
200	24.098	24.079																																
240	24.099	24.079																																
280	24.098	24.077																																
320	24.098	24.076																																
360	24.098	24.075																																
400	24.097	24.074																																
420	24.096	24.074																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	SNDBS700B24
Item	Load Regulation
Object	+24V29A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.0	24.112	24.112	24.108
4.0	24.107	24.108	24.106
8.0	24.102	24.103	24.102
12.0	24.097	24.098	24.097
16.0	24.093	24.094	24.092
20.0	24.089	24.089	24.087
24.0	24.084	24.084	24.081
28.0	24.079	24.079	24.076
29.0	24.079	24.077	24.074
31.9	24.075	24.073	24.069
--	-	-	-

COSEL

Model SNDBS700B24

Item Dynamic Load Response

Object +24V29A

Temperature
Testing Circuitry25°C
Figure AInput Volt. 280 V
Cycle 1000 ms

Load Current

29A/65μs

Min. Load (0A) ↔

Load 100% (29A)

500 mV/div

500 μs/div

5 ms/div

Min. Load (0A) ↔

Load 50% (14.5A)

500 mV/div

500 μs/div

5 ms/div

Load 10% (2.9A) ↔

Load 100% (29A)

500 mV/div

500 μs/div

5 ms/div

COSEL


Model SNDBS700B24

Item Ripple Voltage (by Load Current)

Object +24V29A

1. Graph

—△— Input Volt. 200V
 -·○- Input Volt. 400V

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.0	10	24
4.0	26	34
8.0	26	40
12.0	28	40
16.0	30	40
20.0	30	40
24.0	30	40
28.0	30	40
29.0	30	40
31.9	30	40
--	-	-

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	SNDBS700B24
Item	Ripple-Noise
Object	+24V29A

Temperature 25°C
 Testing Circuitry Figure B

1. Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 200 [V]	Input Volt. 400 [V]
0.0	28	32
4.0	34	48
8.0	38	50
12.0	40	50
16.0	44	50
20.0	50	56
24.0	50	58
28.0	50	60
29.0	50	60
31.9	50	60
--	-	-



Model	SNDBS700B24
Item	Ripple Voltage (by Ambient Temp.)
Object	+24V29A

1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.




Fig.Complex Ripple Noise Wave Form

Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	60	60
-20	40	40
0	34	34
25	30	30
55	30	30
70	30	30
80	30	30
95	40	40
--	-	-
--	-	-
--	-	-

Model SNDBS700B24 Item Ambient Temperature Drift Object +24V29A	Testing Circuitry Figure A																																																				
	2.Values																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>24.003</td><td>24.000</td><td>23.997</td></tr> <tr> <td>-20</td><td>24.041</td><td>24.038</td><td>24.034</td></tr> <tr> <td>0</td><td>24.067</td><td>24.064</td><td>24.060</td></tr> <tr> <td>10</td><td>24.076</td><td>24.074</td><td>24.070</td></tr> <tr> <td>25</td><td>24.079</td><td>24.077</td><td>24.074</td></tr> <tr> <td>40</td><td>24.078</td><td>24.075</td><td>24.071</td></tr> <tr> <td>50</td><td>24.076</td><td>24.074</td><td>24.072</td></tr> <tr> <td>70</td><td>24.061</td><td>24.059</td><td>24.057</td></tr> <tr> <td>95</td><td>24.067</td><td>24.066</td><td>24.070</td></tr> <tr> <td>100</td><td>24.067</td><td>24.066</td><td>24.070</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-40	24.003	24.000	23.997	-20	24.041	24.038	24.034	0	24.067	24.064	24.060	10	24.076	24.074	24.070	25	24.079	24.077	24.074	40	24.078	24.075	24.071	50	24.076	24.074	24.072	70	24.061	24.059	24.057	95	24.067	24.066	24.070	100	24.067	24.066	24.070	--	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																		
-40	24.003	24.000	23.997																																																		
-20	24.041	24.038	24.034																																																		
0	24.067	24.064	24.060																																																		
10	24.076	24.074	24.070																																																		
25	24.079	24.077	24.074																																																		
40	24.078	24.075	24.071																																																		
50	24.076	24.074	24.072																																																		
70	24.061	24.059	24.057																																																		
95	24.067	24.066	24.070																																																		
100	24.067	24.066	24.070																																																		
--	-	-	-																																																		
1.Graph	<p>The graph plots Output Voltage [V] on the Y-axis (23.80 to 24.50) against Ambient Temperature [°C] on the X-axis (-60 to 100). Three data series are shown for Input Volt. 200V (solid line with squares), Input Volt. 280V (dashed line with circles), and Input Volt. 400V (dotted line with triangles). All series show a slight increase in output voltage with increasing ambient temperature, staying within the respective rated ranges indicated by slanted lines.</p>																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																				



Model	SNDBS700B24	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+24V29A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 29A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	400	0	24.022	± 40	± 0.2
Minimum Voltage	-20	400	29	23.943		

COSEL

Model	SNDBS700B24
Item	Time Lapse Drift
Object	+24V29A

1. Graph



Temperature 25°C
Testing Circuitry Figure A

2. Values


Time since start [H]	Output Voltage [V]
0.0	24.090
0.5	24.073
1.0	24.074
2.0	24.074
3.0	24.075
4.0	24.075
5.0	24.075
6.0	24.075
7.0	24.075
8.0	24.075

COSEL

Model	SNDBS700B24
Item	Rise and Fall Time
Object	+24V29A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		60.3	35.8	96.1	0.7	15.9	
100 %		58.8	35.8	94.6	0.4	7.9	



<table border="1"> <tr><td>Model</td><td>SNDBS700B24</td></tr> <tr><td>Item</td><td>Minimum Input Voltage for Regulated Output Voltage</td></tr> <tr><td>Object</td><td>+24V29A</td></tr> </table>	Model	SNDBS700B24	Item	Minimum Input Voltage for Regulated Output Voltage	Object	+24V29A	Testing Circuitry Figure A	
Model	SNDBS700B24							
Item	Minimum Input Voltage for Regulated Output Voltage							
Object	+24V29A							
2.Values								
Ambient Temperature [°C]	Input Voltage [V]							
	Load 50%	Load 100%						
-40	160	160						
-20	160	160						
0	160	160						
10	159	160						
25	160	160						
40	160	160						
50	160	160						
70	159	160						
95	159	159						
100	158	159						
--	-	-						




Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	SNDBS700B24																																																																	
Item	Overcurrent Protection																																																																	
Object	+24V29A																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																	
	<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 19.2V to 0V.</p>																																																																	
Temperature Testing Circuitry	25°C Figure A																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>22.8</td><td>34.69</td><td>34.78</td><td>36.10</td></tr> <tr><td>21.6</td><td>34.75</td><td>34.94</td><td>36.47</td></tr> <tr><td>19.2</td><td>34.98</td><td>35.36</td><td>37.01</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	22.8	34.69	34.78	36.10	21.6	34.75	34.94	36.47	19.2	34.98	35.36	37.01	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																	
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																															
22.8	34.69	34.78	36.10																																																															
21.6	34.75	34.94	36.47																																																															
19.2	34.98	35.36	37.01																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															

Model	SNDBS700B24
Item	Overvoltage Protection
Object	+24V29A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 200[V]	Input Volt. 400[V]
-40	30.94	30.94
-20	30.94	30.94
0	31.05	31.05
10	31.05	31.05
25	31.05	31.05
40	31.05	31.05
50	31.05	31.05
70	31.17	31.17
95	31.16	31.16
100	31.16	31.16
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)