

TEST DATA OF SNDBS700B36

Regulated DC Power Supply
July 4, 2012

Approved by : Takahiro Lyoneda
Design Manager

Prepared by : Satoshi Kinoshita
Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1

2.Input Current (by Load Current) 2

3.Input Power (by Load Current) 3

4.Efficiency (by Input Voltage) 4

5.Efficiency (by Load Current) 5

6.Line Regulation 6

7.Load Regulation 7

8.Dynamic Load Response 8

9.Ripple Voltage (by Load Current) 9

10.Ripple-Noise 10

11.Ripple Voltage (by Ambient Temperature) 11

12.Ambient Temperature Drift 12

13.Output Voltage Accuracy 13

14.Time Lapse Drift 14

15.Rise and Fall Time 15

16.Minimum Input Voltage for Regulated Output Voltage 16

17.Overcurrent Protection 17

18.Overvoltage Protection 18

19.Figure of Testing Circuitry 19

(Final Page 19)



Model		SNDBS700B36		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object		_____																																																																																		
1.Graph			—△— Load 100% - - -□- - Load 50% - · - ○ - · - Load 0%																																																																																	
			2.Values																																																																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>170</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>180</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>190</td><td>0.025</td><td>2.038</td><td>4.100</td></tr> <tr><td>200</td><td>0.025</td><td>1.939</td><td>3.890</td></tr> <tr><td>250</td><td>0.022</td><td>1.562</td><td>3.130</td></tr> <tr><td>280</td><td>0.018</td><td>1.402</td><td>2.796</td></tr> <tr><td>300</td><td>0.018</td><td>1.313</td><td>2.626</td></tr> <tr><td>350</td><td>0.015</td><td>1.142</td><td>2.276</td></tr> <tr><td>400</td><td>0.013</td><td>1.009</td><td>1.998</td></tr> <tr><td>420</td><td>0.013</td><td>0.964</td><td>1.910</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.003	0.003	0.003	170	0.003	0.003	0.003	180	0.003	0.003	0.003	190	0.025	2.038	4.100	200	0.025	1.939	3.890	250	0.022	1.562	3.130	280	0.018	1.402	2.796	300	0.018	1.313	2.626	350	0.015	1.142	2.276	400	0.013	1.009	1.998	420	0.013	0.964	1.910	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0	0.000	0.000	0.000																																																																																	
50	0.000	0.000	0.000																																																																																	
100	0.000	0.000	0.000																																																																																	
150	0.003	0.003	0.003																																																																																	
170	0.003	0.003	0.003																																																																																	
180	0.003	0.003	0.003																																																																																	
190	0.025	2.038	4.100																																																																																	
200	0.025	1.939	3.890																																																																																	
250	0.022	1.562	3.130																																																																																	
280	0.018	1.402	2.796																																																																																	
300	0.018	1.313	2.626																																																																																	
350	0.015	1.142	2.276																																																																																	
400	0.013	1.009	1.998																																																																																	
420	0.013	0.964	1.910																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



<p>Model SNDBS700B36</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Input Current (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> —△— Input Volt. 200V - - - □ - - - Input Volt. 280V - · - ○ - · - - Input Volt. 400V </p> <p>Input Current [A]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.025</td><td>0.018</td><td>0.013</td></tr> <tr><td>3.00</td><td>0.617</td><td>0.464</td><td>0.347</td></tr> <tr><td>6.00</td><td>1.206</td><td>0.879</td><td>0.638</td></tr> <tr><td>9.00</td><td>1.789</td><td>1.297</td><td>0.935</td></tr> <tr><td>12.00</td><td>2.378</td><td>1.718</td><td>1.232</td></tr> <tr><td>15.00</td><td>2.974</td><td>2.146</td><td>1.534</td></tr> <tr><td>18.00</td><td>3.582</td><td>2.578</td><td>1.842</td></tr> <tr><td>19.50</td><td>3.890</td><td>2.796</td><td>1.998</td></tr> <tr><td>21.45</td><td>4.302</td><td>3.090</td><td>2.204</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	0.025	0.018	0.013	3.00	0.617	0.464	0.347	6.00	1.206	0.879	0.638	9.00	1.789	1.297	0.935	12.00	2.378	1.718	1.232	15.00	2.974	2.146	1.534	18.00	3.582	2.578	1.842	19.50	3.890	2.796	1.998	21.45	4.302	3.090	2.204	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																		
0.00	0.025	0.018	0.013																																																		
3.00	0.617	0.464	0.347																																																		
6.00	1.206	0.879	0.638																																																		
9.00	1.789	1.297	0.935																																																		
12.00	2.378	1.718	1.232																																																		
15.00	2.974	2.146	1.534																																																		
18.00	3.582	2.578	1.842																																																		
19.50	3.890	2.796	1.998																																																		
21.45	4.302	3.090	2.204																																																		
--	-	-	-																																																		
--	-	-	-																																																		




<p>Model SNDBS700B36</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Input Power (by Load Current)																																																				
Object																																																					
<p>1.Graph</p> <p> —△— Input Volt. 200V - - - □ - - - Input Volt. 280V - · - ○ - · - - Input Volt. 400V </p> <p>Input Power [W]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4.9</td><td>4.9</td><td>5.2</td></tr> <tr><td>3.00</td><td>123.1</td><td>129.8</td><td>138.5</td></tr> <tr><td>6.00</td><td>240.7</td><td>245.9</td><td>255.1</td></tr> <tr><td>9.00</td><td>357.4</td><td>362.6</td><td>373.0</td></tr> <tr><td>12.00</td><td>475.0</td><td>481.0</td><td>492.0</td></tr> <tr><td>15.00</td><td>594.0</td><td>600.0</td><td>613.0</td></tr> <tr><td>18.00</td><td>715.0</td><td>721.0</td><td>736.0</td></tr> <tr><td>19.50</td><td>777.0</td><td>782.0</td><td>798.0</td></tr> <tr><td>21.45</td><td>860.0</td><td>865.0</td><td>881.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	4.9	4.9	5.2	3.00	123.1	129.8	138.5	6.00	240.7	245.9	255.1	9.00	357.4	362.6	373.0	12.00	475.0	481.0	492.0	15.00	594.0	600.0	613.0	18.00	715.0	721.0	736.0	19.50	777.0	782.0	798.0	21.45	860.0	865.0	881.0	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																		
0.00	4.9	4.9	5.2																																																		
3.00	123.1	129.8	138.5																																																		
6.00	240.7	245.9	255.1																																																		
9.00	357.4	362.6	373.0																																																		
12.00	475.0	481.0	492.0																																																		
15.00	594.0	600.0	613.0																																																		
18.00	715.0	721.0	736.0																																																		
19.50	777.0	782.0	798.0																																																		
21.45	860.0	865.0	881.0																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



Model	SNDBS700B36
Item	Efficiency (by Input Voltage)
Object	

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.


2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
195	90.8	89.9
200	90.7	89.8
240	90.0	89.5
280	89.4	89.2
320	88.7	88.6
360	87.8	88.1
400	86.9	87.5
420	86.5	86.9
--	-	-



Model	SNDBS700B36
Item	Efficiency (by Load Current)
Object	_____

Temperature 25°C
Testing Circuitry Figure A



2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.00	-	-	-
3.00	87.7	83.2	78.0
6.00	89.5	87.6	84.5
9.00	90.4	89.1	86.6
12.00	90.6	89.5	87.5
15.00	90.5	89.6	87.7
18.00	90.2	89.5	87.6
19.50	89.8	89.2	87.5
21.45	89.5	89.0	87.3
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.



<p>Model SNDBS700B36</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Line Regulation</p>																																		
<p>Object +36V19.5A</p>																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>36.066</td><td>36.056</td></tr> <tr><td>200</td><td>36.066</td><td>36.054</td></tr> <tr><td>240</td><td>36.071</td><td>36.055</td></tr> <tr><td>280</td><td>36.070</td><td>36.052</td></tr> <tr><td>320</td><td>36.070</td><td>36.050</td></tr> <tr><td>360</td><td>36.070</td><td>36.049</td></tr> <tr><td>400</td><td>36.069</td><td>36.046</td></tr> <tr><td>420</td><td>36.068</td><td>36.044</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	36.066	36.056	200	36.066	36.054	240	36.071	36.055	280	36.070	36.052	320	36.070	36.050	360	36.070	36.049	400	36.069	36.046	420	36.068	36.044	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
195	36.066	36.056																																
200	36.066	36.054																																
240	36.071	36.055																																
280	36.070	36.052																																
320	36.070	36.050																																
360	36.070	36.049																																
400	36.069	36.046																																
420	36.068	36.044																																
--	-	-																																




Model	SNDBS700B36
Item	Load Regulation
Object	+36V19.5A

Temperature 25°C
Testing Circuitry Figure A

1.Graph

- △— Input Volt. 200V
- Input Volt. 280V
- Input Volt. 400V



Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
0.00	36.082	36.084	36.079
3.00	36.078	36.080	36.075
6.00	36.073	36.075	36.071
9.00	36.069	36.070	36.066
12.00	36.064	36.065	36.060
15.00	36.059	36.059	36.053
18.00	36.055	36.054	36.046
19.50	36.054	36.052	36.046
21.45	36.049	36.046	36.036
--	-	-	-
--	-	-	-




Model	SNDBS700B36	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+36V19.5A		


Input Volt. 280 V
 Cycle 1000 ms




Min. Load (0A) ←→
 Load 100% (19.5A)



Min. Load (0A) ←→
 Load 50% (9.75A)



Load 10% (1.95A) ←→
 Load 100% (19.5A)





Model		SNDBS700B36		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		+36V19.5A																																									
1.Graph			2.Values																																								
<p> —△— Input Volt. 200V - - ○ - - Input Volt. 400V </p> <p> Y-axis: Ripple Voltage [mV] (0 to 400) X-axis: Load Current [A] (0 to 24) </p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>28</td></tr> <tr><td>3.00</td><td>26</td><td>36</td></tr> <tr><td>6.00</td><td>30</td><td>56</td></tr> <tr><td>9.00</td><td>32</td><td>58</td></tr> <tr><td>12.00</td><td>34</td><td>58</td></tr> <tr><td>15.00</td><td>36</td><td>58</td></tr> <tr><td>18.00</td><td>38</td><td>58</td></tr> <tr><td>19.50</td><td>38</td><td>58</td></tr> <tr><td>21.45</td><td>38</td><td>58</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	10	28	3.00	26	36	6.00	30	56	9.00	32	58	12.00	34	58	15.00	36	58	18.00	38	58	19.50	38	58	21.45	38	58	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 200 [V]	Input Volt. 400 [V]																																									
0.00	10	28																																									
3.00	26	36																																									
6.00	30	56																																									
9.00	32	58																																									
12.00	34	58																																									
15.00	36	58																																									
18.00	38	58																																									
19.50	38	58																																									
21.45	38	58																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																											




<p>Model SNDBS700B36</p> <p>Item Ripple-Noise</p> <p>Object +36V19.5A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 200V</p> <p>- - -○- - - Input Volt. 400V</p> </div> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>30</td><td>70</td></tr> <tr><td>3.00</td><td>40</td><td>60</td></tr> <tr><td>6.00</td><td>40</td><td>68</td></tr> <tr><td>9.00</td><td>50</td><td>68</td></tr> <tr><td>12.00</td><td>50</td><td>70</td></tr> <tr><td>15.00</td><td>52</td><td>74</td></tr> <tr><td>18.00</td><td>54</td><td>74</td></tr> <tr><td>19.50</td><td>54</td><td>74</td></tr> <tr><td>21.45</td><td>54</td><td>74</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	30	70	3.00	40	60	6.00	40	68	9.00	50	68	12.00	50	70	15.00	52	74	18.00	54	74	19.50	54	74	21.45	54	74	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0.00	30	70																																						
3.00	40	60																																						
6.00	40	68																																						
9.00	50	68																																						
12.00	50	70																																						
15.00	52	74																																						
18.00	54	74																																						
19.50	54	74																																						
21.45	54	74																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model	SNDBS700B36
Item	Ripple Voltage (by Ambient Temp.)
Object	+36V19.5A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	110	110
-20	72	68
0	38	42
25	38	42
55	38	42
70	38	42
80	40	42
95	42	42
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.




Fig.Complex Ripple Noise Wave Form




Model	SNDBS700B36
Item	Ambient Temperature Drift
Object	+36V19.5A

Testing Circuitry Figure A

1. Graph

- △— Input Volt. 200V
- Input Volt. 280V
- Input Volt. 400V



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]
-40	35.974	35.971	35.964
-20	36.008	36.003	35.997
0	36.034	36.030	36.024
10	36.045	36.042	36.036
25	36.054	36.052	36.046
40	36.055	36.052	36.047
50	36.057	36.053	36.049
70	36.053	36.052	36.050
95	36.086	36.086	36.038
100	36.107	36.108	36.037
--	-	-	-



COSEL		
Model	SNDBS700B36	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+36V19.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 19.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	400	0	36.143	±64	±0.2
Minimum Voltage	-20	400	19.5	36.016		




COSEL																								
Model	SNDBS700B36																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+36V19.5A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 280V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>36.065</td></tr> <tr><td>0.5</td><td>36.036</td></tr> <tr><td>1.0</td><td>36.036</td></tr> <tr><td>2.0</td><td>36.036</td></tr> <tr><td>3.0</td><td>36.037</td></tr> <tr><td>4.0</td><td>36.037</td></tr> <tr><td>5.0</td><td>36.038</td></tr> <tr><td>6.0</td><td>36.038</td></tr> <tr><td>7.0</td><td>36.039</td></tr> <tr><td>8.0</td><td>36.039</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	36.065	0.5	36.036	1.0	36.036	2.0	36.036	3.0	36.037	4.0	36.037	5.0	36.038	6.0	36.038	7.0	36.039	8.0	36.039
Time since start [H]	Output Voltage [V]																							
0.0	36.065																							
0.5	36.036																							
1.0	36.036																							
2.0	36.036																							
3.0	36.037																							
4.0	36.037																							
5.0	36.038																							
6.0	36.038																							
7.0	36.039																							
8.0	36.039																							



Model	SNDBS700B36	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+36V19.5A		


1. Graph



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	61.0	37.8	98.8	1.2	26.1
100 %	61.0	37.8	98.8	0.6	12.8

[ms]






Model	SNDBS700B36
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+36V19.5A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	165	170
-20	165	170
0	165	170
10	165	170
25	165	170
40	164	170
50	164	170
70	162	169
95	160	168
100	160	168
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



<p>Model SNDBS700B36</p> <p>Item Overcurrent Protection</p> <p>Object +36V19.5A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1.Graph</p> <p> Input Volt. 200V Input Volt. 280V Input Volt. 400V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 21.6V to 0V.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>34.2</td> <td>22.86</td> <td>23.13</td> <td>24.49</td> </tr> <tr> <td>32.4</td> <td>22.95</td> <td>23.31</td> <td>24.74</td> </tr> <tr> <td>28.8</td> <td>23.26</td> <td>23.75</td> <td>25.21</td> </tr> <tr> <td>25.2</td> <td>23.62</td> <td>24.53</td> <td>25.77</td> </tr> <tr> <td>21.6</td> <td>24.05</td> <td>25.17</td> <td>26.79</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	34.2	22.86	23.13	24.49	32.4	22.95	23.31	24.74	28.8	23.26	23.75	25.21	25.2	23.62	24.53	25.77	21.6	24.05	25.17	26.79	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																						
34.2	22.86	23.13	24.49																																																						
32.4	22.95	23.31	24.74																																																						
28.8	23.26	23.75	25.21																																																						
25.2	23.62	24.53	25.77																																																						
21.6	24.05	25.17	26.79																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						



Model		SNDBS700B36	Testing Circuitry Figure A																																						
Item		Overvoltage Protection																																							
Object		+36V19.5A																																							
1.Graph		<p> \triangle Input Volt. 200V \square Input Volt. 400V </p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p>	2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>44.88</td><td>44.77</td></tr> <tr><td>-20</td><td>44.94</td><td>44.94</td></tr> <tr><td>0</td><td>44.94</td><td>44.94</td></tr> <tr><td>10</td><td>44.93</td><td>44.93</td></tr> <tr><td>25</td><td>44.93</td><td>44.93</td></tr> <tr><td>40</td><td>44.93</td><td>44.93</td></tr> <tr><td>50</td><td>44.93</td><td>44.93</td></tr> <tr><td>70</td><td>44.93</td><td>44.93</td></tr> <tr><td>95</td><td>44.93</td><td>44.93</td></tr> <tr><td>100</td><td>44.87</td><td>44.93</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	44.88	44.77	-20	44.94	44.94	0	44.94	44.94	10	44.93	44.93	25	44.93	44.93	40	44.93	44.93	50	44.93	44.93	70	44.93	44.93	95	44.93	44.93	100	44.87	44.93	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 200[V]	Input Volt. 400[V]																																							
-40	44.88	44.77																																							
-20	44.94	44.94																																							
0	44.94	44.94																																							
10	44.93	44.93																																							
25	44.93	44.93																																							
40	44.93	44.93																																							
50	44.93	44.93																																							
70	44.93	44.93																																							
95	44.93	44.93																																							
100	44.87	44.93																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									




Figure A




Figure B (Ripple and Ripple noise Characteristic)