

TEST DATA OF SNDHS100A05

Regulated DC Power Supply
April 9, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)


COSEL

Model	SNDHS100A05	Temperature Testing Circuitry	25°C Figure A																																																																															
Item	Input Current (by Input Voltage)																																																																																	
Object	+5V20A																																																																																	
1.Graph		2.Values																																																																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>40</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>45</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.035</td><td>1.232</td><td>2.452</td></tr> <tr><td>55</td><td>0.032</td><td>1.110</td><td>2.194</td></tr> <tr><td>60</td><td>0.032</td><td>1.013</td><td>2.060</td></tr> <tr><td>66</td><td>0.032</td><td>0.923</td><td>1.801</td></tr> <tr><td>80</td><td>0.031</td><td>0.770</td><td>1.486</td></tr> <tr><td>95</td><td>0.031</td><td>0.646</td><td>1.246</td></tr> <tr><td>110</td><td>0.031</td><td>0.544</td><td>1.098</td></tr> <tr><td>125</td><td>0.031</td><td>0.483</td><td>0.933</td></tr> <tr><td>140</td><td>0.031</td><td>0.435</td><td>0.834</td></tr> <tr><td>160</td><td>0.031</td><td>0.385</td><td>0.763</td></tr> <tr><td>170</td><td>0.030</td><td>0.365</td><td>0.692</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	40	0.000	0.000	0.000	45	0.000	0.000	0.000	50	0.035	1.232	2.452	55	0.032	1.110	2.194	60	0.032	1.013	2.060	66	0.032	0.923	1.801	80	0.031	0.770	1.486	95	0.031	0.646	1.246	110	0.031	0.544	1.098	125	0.031	0.483	0.933	140	0.031	0.435	0.834	160	0.031	0.385	0.763	170	0.030	0.365	0.692	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
40	0.000	0.000	0.000																																																																															
45	0.000	0.000	0.000																																																																															
50	0.035	1.232	2.452																																																																															
55	0.032	1.110	2.194																																																																															
60	0.032	1.013	2.060																																																																															
66	0.032	0.923	1.801																																																																															
80	0.031	0.770	1.486																																																																															
95	0.031	0.646	1.246																																																																															
110	0.031	0.544	1.098																																																																															
125	0.031	0.483	0.933																																																																															
140	0.031	0.435	0.834																																																																															
160	0.031	0.385	0.763																																																																															
170	0.030	0.365	0.692																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	SNDHS100A05	Temperature 25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry Figure A																																																			
Object	+5V20A																																																				
1.Graph																																																					
<p style="text-align: center;"> —△— Input Volt. 60V ---□--- Input Volt. 110V ---○--- Input Volt. 160V </p> <p>The graph plots Input Current [A] on the Y-axis (0.0 to 4.0) against Load Current [A] on the X-axis (0 to 20). Three curves are shown for input voltages of 60V, 110V, and 160V. The 60V curve (triangles) is the steepest, followed by 110V (squares), and 160V (circles). A slanted line is drawn through the origin, representing the rated load current range.</p>																																																					
2.Values																																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.032</td><td>0.031</td><td>0.031</td></tr> <tr><td>4</td><td>0.438</td><td>0.227</td><td>0.164</td></tr> <tr><td>8</td><td>0.819</td><td>0.438</td><td>0.313</td></tr> <tr><td>12</td><td>1.216</td><td>0.652</td><td>0.460</td></tr> <tr><td>16</td><td>1.630</td><td>0.871</td><td>0.609</td></tr> <tr><td>20</td><td>2.060</td><td>1.098</td><td>0.763</td></tr> <tr><td>22</td><td>2.290</td><td>1.216</td><td>0.841</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0	0.032	0.031	0.031	4	0.438	0.227	0.164	8	0.819	0.438	0.313	12	1.216	0.652	0.460	16	1.630	0.871	0.609	20	2.060	1.098	0.763	22	2.290	1.216	0.841	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																		
0	0.032	0.031	0.031																																																		
4	0.438	0.227	0.164																																																		
8	0.819	0.438	0.313																																																		
12	1.216	0.652	0.460																																																		
16	1.630	0.871	0.609																																																		
20	2.060	1.098	0.763																																																		
22	2.290	1.216	0.841																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

COSEL

Model	SNDHS100A05	Temperature Testing Circuitry	25°C Figure A																																																	
Item	Input Power (by Load Current)																																																			
Object	+5V20A																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 60V - - - □ - - Input Volt. 110V - - ○ - - Input Volt. 160V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 150) against Load Current [A] on the X-axis (0 to 20). Three curves are shown for input voltages of 60V, 110V, and 160V. The 60V curve starts at (0,0) and ends at approximately (20, 135). The 110V curve starts at (0,0) and ends at approximately (20, 125). The 160V curve starts at (0,0) and ends at approximately (20, 115). A slanted line is drawn through the origin, passing through the points (12, 72.8), (16, 97.4), and (20, 123.6), representing the rated load current range.</p>																																																				
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>2.0</td> <td>3.4</td> <td>4.9</td> </tr> <tr> <td>4</td> <td>26.2</td> <td>25.0</td> <td>26.2</td> </tr> <tr> <td>8</td> <td>49.0</td> <td>48.0</td> <td>50.0</td> </tr> <tr> <td>12</td> <td>72.8</td> <td>71.5</td> <td>73.4</td> </tr> <tr> <td>16</td> <td>97.4</td> <td>95.6</td> <td>97.3</td> </tr> <tr> <td>20</td> <td>123.6</td> <td>120.5</td> <td>121.7</td> </tr> <tr> <td>22</td> <td>137.1</td> <td>133.3</td> <td>134.3</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0	2.0	3.4	4.9	4	26.2	25.0	26.2	8	49.0	48.0	50.0	12	72.8	71.5	73.4	16	97.4	95.6	97.3	20	123.6	120.5	121.7	22	137.1	133.3	134.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																			
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																	
0	2.0	3.4	4.9																																																	
4	26.2	25.0	26.2																																																	
8	49.0	48.0	50.0																																																	
12	72.8	71.5	73.4																																																	
16	97.4	95.6	97.3																																																	
20	123.6	120.5	121.7																																																	
22	137.1	133.3	134.3																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	


Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNDHS100A05
Item	Efficiency (by Input Voltage)
Object	+5V20A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
56	83.6	81.4
60	83.6	81.7
66	83.6	82.0
80	82.7	82.0
95	82.8	82.2
110	85.2	83.7
125	84.3	83.4
140	83.6	83.3
160	82.6	83.0
170	81.9	82.8

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	SNDHS100A05	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+5V20A																																																					
1.Graph	<p>—△— Input Volt. 60V - - □ - - Input Volt. 110V - - ○ - - Input Volt. 160V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [60V] (%)</th> <th>Efficiency [110V] (%)</th> <th>Efficiency [160V] (%)</th> </tr> </thead> <tbody> <tr><td>5</td><td>79</td><td>80</td><td>79</td></tr> <tr><td>10</td><td>83</td><td>84</td><td>82</td></tr> <tr><td>15</td><td>82</td><td>83</td><td>81</td></tr> <tr><td>20</td><td>80</td><td>81</td><td>79</td></tr> </tbody> </table>			Load Current [A]	Efficiency [60V] (%)	Efficiency [110V] (%)	Efficiency [160V] (%)	5	79	80	79	10	83	84	82	15	82	83	81	20	80	81	79																															
Load Current [A]	Efficiency [60V] (%)	Efficiency [110V] (%)	Efficiency [160V] (%)																																																			
5	79	80	79																																																			
10	83	84	82																																																			
15	82	83	81																																																			
20	80	81	79																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4</td><td>78.0</td><td>81.9</td><td>78.0</td></tr> <tr><td>8</td><td>83.1</td><td>84.8</td><td>81.5</td></tr> <tr><td>12</td><td>83.7</td><td>85.2</td><td>83.0</td></tr> <tr><td>16</td><td>83.2</td><td>84.7</td><td>83.3</td></tr> <tr><td>20</td><td>81.7</td><td>83.8</td><td>83.0</td></tr> <tr><td>22</td><td>81.0</td><td>83.3</td><td>82.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0	-	-	-	4	78.0	81.9	78.0	8	83.1	84.8	81.5	12	83.7	85.2	83.0	16	83.2	84.7	83.3	20	81.7	83.8	83.0	22	81.0	83.3	82.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
0	-	-	-																																																			
4	78.0	81.9	78.0																																																			
8	83.1	84.8	81.5																																																			
12	83.7	85.2	83.0																																																			
16	83.2	84.7	83.3																																																			
20	81.7	83.8	83.0																																																			
22	81.0	83.3	82.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNDHS100A05
Item	Line Regulation
Object	+5V20A

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
56	5.091	5.062
60	5.091	5.062
66	5.091	5.062
80	5.091	5.062
95	5.091	5.062
110	5.091	5.061
125	5.091	5.061
140	5.091	5.061
160	5.091	5.061
170	5.091	5.062

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model SNDHS100A05

Item Load Regulation

Object +5V20A

1.Graph

—△— Input Volt. 60V
 - - -□- - Input Volt. 110V
 - - ○ - - Input Volt. 160V




Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]
0	5.122	5.123	5.123
4	5.109	5.109	5.110
8	5.097	5.097	5.097
12	5.085	5.085	5.086
16	5.074	5.074	5.074
20	5.062	5.062	5.062
22	5.056	5.056	5.056
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model	SNDHS100A05	Temperature Testing Circuitry	25°C Figure B																																						
Item	Ripple Voltage (by Load Current)																																								
Object	+5V20A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 60V</th> <th>Input Volt. 160V</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>4</td><td>10</td><td>15</td></tr> <tr><td>8</td><td>10</td><td>15</td></tr> <tr><td>12</td><td>10</td><td>15</td></tr> <tr><td>16</td><td>10</td><td>15</td></tr> <tr><td>20</td><td>10</td><td>15</td></tr> <tr><td>22</td><td>10</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 60V	Input Volt. 160V	0	5	5	4	10	15	8	10	15	12	10	15	16	10	15	20	10	15	22	10	20	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 60V	Input Volt. 160V																																							
0	5	5																																							
4	10	15																																							
8	10	15																																							
12	10	15																																							
16	10	15																																							
20	10	15																																							
22	10	20																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									

Model	SNDHS100A05	Temperature Testing Circuitry	25°C Figure B																																						
Item	Ripple-Noise																																								
Object	+5V20A																																								
1. Graph																																									
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 300 mV, and the X-axis ranges from 0 to 20 A. Two curves are plotted: one for Input Volt. 60V (solid line with triangle markers) and one for Input Volt. 160V (dashed line with circle markers). Both curves show an increase in Ripple Voltage as Load Current increases. A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 60V)</th> <th>Ripple Voltage [mV] (Input Volt. 160V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>15</td><td>20</td></tr> <tr><td>4</td><td>25</td><td>30</td></tr> <tr><td>8</td><td>35</td><td>45</td></tr> <tr><td>12</td><td>45</td><td>50</td></tr> <tr><td>16</td><td>60</td><td>55</td></tr> <tr><td>20</td><td>90</td><td>85</td></tr> <tr><td>22</td><td>100</td><td>100</td></tr> </tbody> </table>				Load Current [A]	Ripple Voltage [mV] (Input Volt. 60V)	Ripple Voltage [mV] (Input Volt. 160V)	0	15	20	4	25	30	8	35	45	12	45	50	16	60	55	20	90	85	22	100	100														
Load Current [A]	Ripple Voltage [mV] (Input Volt. 60V)	Ripple Voltage [mV] (Input Volt. 160V)																																							
0	15	20																																							
4	25	30																																							
8	35	45																																							
12	45	50																																							
16	60	55																																							
20	90	85																																							
22	100	100																																							
2. Values																																									
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 60 [V]</th> <th>Input Volt. 160 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>15</td><td>20</td></tr> <tr><td>4</td><td>25</td><td>30</td></tr> <tr><td>8</td><td>35</td><td>45</td></tr> <tr><td>12</td><td>45</td><td>50</td></tr> <tr><td>16</td><td>60</td><td>55</td></tr> <tr><td>20</td><td>90</td><td>85</td></tr> <tr><td>22</td><td>100</td><td>100</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Ripple-Noise [mV]		Input Volt. 60 [V]	Input Volt. 160 [V]	0	15	20	4	25	30	8	35	45	12	45	50	16	60	55	20	90	85	22	100	100	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 60 [V]	Input Volt. 160 [V]																																							
0	15	20																																							
4	25	30																																							
8	35	45																																							
12	45	50																																							
16	60	55																																							
20	90	85																																							
22	100	100																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																									

Model	SNDHS100A05
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V20A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	40	45
-20	25	30
0	20	20
25	20	20
40	15	20
55	20	20
70	20	20
80	20	20
95	20	20
100	20	20
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL

Model	SNDHS100A05	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+5V20A																																																						
1.Graph	<p>—▲— Input Volt. 60V - - - □ - - Input Volt. 110V - - ○ - - Input Volt. 160V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td> <td>5.075</td> <td>5.075</td> <td>5.074</td> </tr> <tr> <td>-20</td> <td>5.069</td> <td>5.068</td> <td>5.067</td> </tr> <tr> <td>0</td> <td>5.064</td> <td>5.063</td> <td>5.063</td> </tr> <tr> <td>25</td> <td>5.062</td> <td>5.062</td> <td>5.062</td> </tr> <tr> <td>40</td> <td>5.061</td> <td>5.061</td> <td>5.061</td> </tr> <tr> <td>55</td> <td>5.059</td> <td>5.058</td> <td>5.058</td> </tr> <tr> <td>70</td> <td>5.055</td> <td>5.055</td> <td>5.054</td> </tr> <tr> <td>80</td> <td>5.052</td> <td>5.052</td> <td>5.052</td> </tr> <tr> <td>95</td> <td>5.048</td> <td>5.048</td> <td>5.047</td> </tr> <tr> <td>100</td> <td>5.048</td> <td>5.048</td> <td>5.047</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	-40	5.075	5.075	5.074	-20	5.069	5.068	5.067	0	5.064	5.063	5.063	25	5.062	5.062	5.062	40	5.061	5.061	5.061	55	5.059	5.058	5.058	70	5.055	5.055	5.054	80	5.052	5.052	5.052	95	5.048	5.048	5.047	100	5.048	5.048	5.047	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																				
-40	5.075	5.075	5.074																																																				
-20	5.069	5.068	5.067																																																				
0	5.064	5.063	5.063																																																				
25	5.062	5.062	5.062																																																				
40	5.061	5.061	5.061																																																				
55	5.059	5.058	5.058																																																				
70	5.055	5.055	5.054																																																				
80	5.052	5.052	5.052																																																				
95	5.048	5.048	5.047																																																				
100	5.048	5.048	5.047																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.



Model	SNDHS100A05	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V20A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 60 - 160V

Load Current : 0 - 20A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	60	0	5.125	± 39	± 0.8
Minimum Voltage	95	160	20	5.047		

COSEL

Model	SNDHS100A05	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V20A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 110V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.062</td></tr> <tr><td>0.5</td><td>5.062</td></tr> <tr><td>1.0</td><td>5.062</td></tr> <tr><td>2.0</td><td>5.062</td></tr> <tr><td>3.0</td><td>5.062</td></tr> <tr><td>4.0</td><td>5.062</td></tr> <tr><td>5.0</td><td>5.062</td></tr> <tr><td>6.0</td><td>5.062</td></tr> <tr><td>7.0</td><td>5.062</td></tr> <tr><td>8.0</td><td>5.062</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.062	0.5	5.062	1.0	5.062	2.0	5.062	3.0	5.062	4.0	5.062	5.0	5.062	6.0	5.062	7.0	5.062	8.0	5.062
Time since start [H]	Output Voltage [V]																								
0.0	5.062																								
0.5	5.062																								
1.0	5.062																								
2.0	5.062																								
3.0	5.062																								
4.0	5.062																								
5.0	5.062																								
6.0	5.062																								
7.0	5.062																								
8.0	5.062																								

COSEL


Model SNDHS100A05

Item Rise and Fall Time

Object +5V20A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		39.8	17.0	56.8	4.9	10.8
100 %		40.0	17.8	57.8	2.5	5.7



COSEL


Model SNDHS100A05

Item Minimum Input Voltage
for Regulated Output Voltage

Object +5V20A

1. Graph

---□--- Load 50%
—△— Load 100%



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	45	47
-20	45	48
0	46	49
25	46	48
40	46	49
55	46	49
70	46	49
80	46	49
95	46	49
100	46	49
--	-	-

COSEL

Model	SNDHS100A05	Temperature Testing Circuitry	25°C Figure A																																																															
Item	Overcurrent Protection																																																																	
Object	+5V20A																																																																	
1.Graph	<p>— Input Volt. 60V — Input Volt. 110V - - - Input Volt. 160V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																																
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> <p>Intermittent operation occurs when the output voltage is from 3.5V to 0V.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>4.75</td><td>25.83</td><td>25.94</td><td>26.95</td></tr> <tr><td>4.50</td><td>25.79</td><td>26.14</td><td>26.94</td></tr> <tr><td>4.00</td><td>25.84</td><td>26.37</td><td>27.66</td></tr> <tr><td>3.50</td><td>25.97</td><td>26.93</td><td>27.23</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	4.75	25.83	25.94	26.95	4.50	25.79	26.14	26.94	4.00	25.84	26.37	27.66	3.50	25.97	26.93	27.23	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																																	
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																															
4.75	25.83	25.94	26.95																																																															
4.50	25.79	26.14	26.94																																																															
4.00	25.84	26.37	27.66																																																															
3.50	25.97	26.93	27.23																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															
--	-	-	-																																																															


COSEL

Model SNDHS100A05

Item Overvoltage Protection

Object +5V20A

1.Graph



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 60[V]	Input Volt. 160[V]
-40	6.97	6.97
-20	6.97	6.97
0	6.97	6.97
25	6.97	6.97
40	6.97	6.97
55	6.97	6.96
70	6.97	6.97
80	6.97	6.97
95	6.96	6.96
100	6.96	6.96
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)