

TEST DATA OF SNDHS100A15

Regulated DC Power Supply
April 9, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Ovvervoltage Protection	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	SNDHS100A15
Item	Input Current (by Input Voltage)
Object	+15V6.7A

1. Graph

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
40	0.000	0.000	0.000
45	0.000	0.000	0.000
50	0.002	0.002	0.002
51	0.044	1.158	2.246
55	0.043	1.063	2.136
60	0.042	0.971	1.960
66	0.041	0.880	1.760
80	0.039	0.724	1.441
95	0.038	0.610	1.209
110	0.037	0.531	1.053
125	0.037	0.472	0.925
140	0.036	0.426	0.828
160	0.036	0.379	0.733
170	0.035	0.360	0.690
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0	0.000	0.000	0.000
40	0.000	0.000	0.000
45	0.000	0.000	0.000
50	0.002	0.002	0.002
51	0.044	1.158	2.246
55	0.043	1.063	2.136
60	0.042	0.971	1.960
66	0.041	0.880	1.760
80	0.039	0.724	1.441
95	0.038	0.610	1.209
110	0.037	0.531	1.053
125	0.037	0.472	0.925
140	0.036	0.426	0.828
160	0.036	0.379	0.733
170	0.035	0.360	0.690
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	SNDHS100A15
Item	Input Current (by Load Current)
Object	+15V6.7A



Temperature 25°C
Testing Circuitry Figure A


2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]
0.00	0.042	0.037	0.036
1.00	0.332	0.173	0.132
2.00	0.603	0.332	0.242
3.00	0.879	0.480	0.345
4.00	1.160	0.631	0.448
5.00	1.450	0.784	0.553
6.00	1.745	0.942	0.658
6.70	1.960	1.053	0.733
7.37	2.170	1.159	0.804
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNDHS100A15
Item	Input Power (by Load Current)
Object	+15V6.7A



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]
0.00	2.5	4.1	5.7
1.00	19.9	19.1	21.1
2.00	36.1	36.4	38.6
3.00	52.5	52.7	55.0
4.00	69.4	69.3	71.5
5.00	86.7	86.0	88.2
6.00	104.4	103.3	105.1
6.70	117.2	115.6	117.1
7.37	129.7	127.3	128.5
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNDHS100A15
Item	Efficiency (by Input Voltage)
Object	+15V6.7A

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
56	87.0	86.3
60	87.4	87.0
66	87.8	87.8
80	88.3	88.4
95	88.3	88.7
110	87.5	88.5
125	86.7	88.2
140	85.7	88.0
160	84.3	87.4
170	83.5	87.1

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNDHS100A15	Temperature	25°C																																		
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																		
Object	+15V6.7A																																				
1.Graph		2.Values																																			
<p>The graph shows efficiency increasing with load current. At low currents, efficiency is lower for higher input voltages. A slanted line marks the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [60V] (%)</th> <th>Efficiency [110V] (%)</th> <th>Efficiency [160V] (%)</th> </tr> </thead> <tbody> <tr><td>1.00</td><td>76.9</td><td>80.2</td><td>72.5</td></tr> <tr><td>2.00</td><td>84.8</td><td>83.9</td><td>79.3</td></tr> <tr><td>3.00</td><td>87.3</td><td>87.0</td><td>83.4</td></tr> <tr><td>4.00</td><td>88.0</td><td>88.2</td><td>85.6</td></tr> <tr><td>5.00</td><td>88.1</td><td>88.8</td><td>86.6</td></tr> <tr><td>6.00</td><td>87.7</td><td>88.7</td><td>87.2</td></tr> <tr><td>6.70</td><td>87.3</td><td>88.5</td><td>87.4</td></tr> <tr><td>7.37</td><td>86.8</td><td>88.4</td><td>87.6</td></tr> </tbody> </table>		Load Current [A]	Efficiency [60V] (%)	Efficiency [110V] (%)	Efficiency [160V] (%)	1.00	76.9	80.2	72.5	2.00	84.8	83.9	79.3	3.00	87.3	87.0	83.4	4.00	88.0	88.2	85.6	5.00	88.1	88.8	86.6	6.00	87.7	88.7	87.2	6.70	87.3	88.5	87.4	7.37	86.8	88.4	87.6
Load Current [A]	Efficiency [60V] (%)	Efficiency [110V] (%)	Efficiency [160V] (%)																																		
1.00	76.9	80.2	72.5																																		
2.00	84.8	83.9	79.3																																		
3.00	87.3	87.0	83.4																																		
4.00	88.0	88.2	85.6																																		
5.00	88.1	88.8	86.6																																		
6.00	87.7	88.7	87.2																																		
6.70	87.3	88.5	87.4																																		
7.37	86.8	88.4	87.6																																		
<p>The graph shows efficiency increasing with load current. At low currents, efficiency is lower for higher input voltages. A slanted line marks the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [60V] (%)</th> <th>Efficiency [110V] (%)</th> <th>Efficiency [160V] (%)</th> </tr> </thead> <tbody> <tr><td>1.00</td><td>76.9</td><td>80.2</td><td>72.5</td></tr> <tr><td>2.00</td><td>84.8</td><td>83.9</td><td>79.3</td></tr> <tr><td>3.00</td><td>87.3</td><td>87.0</td><td>83.4</td></tr> <tr><td>4.00</td><td>88.0</td><td>88.2</td><td>85.6</td></tr> <tr><td>5.00</td><td>88.1</td><td>88.8</td><td>86.6</td></tr> <tr><td>6.00</td><td>87.7</td><td>88.7</td><td>87.2</td></tr> <tr><td>6.70</td><td>87.3</td><td>88.5</td><td>87.4</td></tr> <tr><td>7.37</td><td>86.8</td><td>88.4</td><td>87.6</td></tr> </tbody> </table>		Load Current [A]	Efficiency [60V] (%)	Efficiency [110V] (%)	Efficiency [160V] (%)	1.00	76.9	80.2	72.5	2.00	84.8	83.9	79.3	3.00	87.3	87.0	83.4	4.00	88.0	88.2	85.6	5.00	88.1	88.8	86.6	6.00	87.7	88.7	87.2	6.70	87.3	88.5	87.4	7.37	86.8	88.4	87.6
Load Current [A]	Efficiency [60V] (%)	Efficiency [110V] (%)	Efficiency [160V] (%)																																		
1.00	76.9	80.2	72.5																																		
2.00	84.8	83.9	79.3																																		
3.00	87.3	87.0	83.4																																		
4.00	88.0	88.2	85.6																																		
5.00	88.1	88.8	86.6																																		
6.00	87.7	88.7	87.2																																		
6.70	87.3	88.5	87.4																																		
7.37	86.8	88.4	87.6																																		
Note: Slanted line shows the range of the rated load current.																																					

COSEL

Model	SNDHS100A15	Temperature	25°C																																				
Item	Line Regulation	Testing Circuitry	Figure A																																				
Object	+15V6.7A																																						
1.Graph		2.Values																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>56</td><td>15.278</td><td>15.265</td></tr> <tr><td>60</td><td>15.278</td><td>15.265</td></tr> <tr><td>66</td><td>15.278</td><td>15.265</td></tr> <tr><td>80</td><td>15.278</td><td>15.266</td></tr> <tr><td>95</td><td>15.279</td><td>15.267</td></tr> <tr><td>110</td><td>15.280</td><td>15.268</td></tr> <tr><td>125</td><td>15.280</td><td>15.268</td></tr> <tr><td>140</td><td>15.281</td><td>15.269</td></tr> <tr><td>160</td><td>15.282</td><td>15.270</td></tr> <tr><td>170</td><td>15.282</td><td>15.270</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	56	15.278	15.265	60	15.278	15.265	66	15.278	15.265	80	15.278	15.266	95	15.279	15.267	110	15.280	15.268	125	15.280	15.268	140	15.281	15.269	160	15.282	15.270	170	15.282	15.270
Input Voltage [V]	Output Voltage [V]																																						
	Load 50%	Load 100%																																					
56	15.278	15.265																																					
60	15.278	15.265																																					
66	15.278	15.265																																					
80	15.278	15.266																																					
95	15.279	15.267																																					
110	15.280	15.268																																					
125	15.280	15.268																																					
140	15.281	15.269																																					
160	15.282	15.270																																					
170	15.282	15.270																																					
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																							


COSEL

Model	SNDHS100A15
Item	Load Regulation
Object	+15V6.7A
1.Graph	
<p style="text-align: center;"> △ Input Volt. 60V □ Input Volt. 110V ○ Input Volt. 160V </p>	
<p>Note: Slanted line shows the range of the rated load current.</p>	

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]
0.00	15.298	15.297	15.298
1.00	15.287	15.289	15.291
2.00	15.283	15.285	15.287
3.00	15.279	15.281	15.283
4.00	15.275	15.277	15.280
5.00	15.271	15.274	15.276
6.00	15.267	15.270	15.272
6.70	15.265	15.267	15.270
7.37	15.262	15.265	15.267
--	-	-	-
--	-	-	-


COSEL

COSEL

Model	SNDHS100A15
Item	Ripple Voltage (by Load Current)
Object	+15V6.7A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 60 [V]	Input Volt. 160 [V]
0.00	10	10
1.00	30	50
2.00	35	50
3.00	35	50
4.00	35	50
5.00	35	50
6.00	35	50
6.70	35	50
7.37	35	60
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig. Complex Ripple Wave Form

COSEL

Model	SNDHS100A15
Item	Ripple-Noise
Object	+15V6.7A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 60 [V]	Input Volt. 160 [V]
0.00	30	40
1.00	60	70
2.00	70	95
3.00	90	85
4.00	90	85
5.00	95	85
6.00	100	90
6.70	100	90
7.37	100	95
--	-	-
--	-	-





Fig.Complex Ripple Noise Wave Form

Model	SNDHS100A15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V6.7A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	80	85
-20	65	70
0	55	60
25	45	50
40	50	50
55	45	55
70	55	45
80	55	55
95	60	60
100	60	60
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL


Model SNDHS100A15

Item Ambient Temperature Drift

Object +15V6.7A

1. Graph

—△— Input Volt. 60V
 - - - □ - - Input Volt. 110V
 - - ○ - - Input Volt. 160V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]
-40	15.248	15.252	15.256
-20	15.268	15.271	15.276
0	15.272	15.275	15.279
25	15.271	15.274	15.276
40	15.275	15.277	15.279
55	15.282	15.285	15.286
70	15.279	15.282	15.283
80	15.276	15.279	15.281
95	15.270	15.273	15.274
100	15.268	15.270	15.271
--	-	-	-



Model	SNDHS100A15	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V6.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 60 - 160V

Load Current : 0 - 6.7A

* Output Voltage Accuracy = \pm (Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	60	0	15.318	± 25	± 0.2
Minimum Voltage	-20	60	6.7	15.268		

COSEL

Model	SNDHS100A15
Item	Time Lapse Drift
Object	+15V6.7A

1.Graph



Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.263
0.5	15.269
1.0	15.269
2.0	15.269
3.0	15.269
4.0	15.269
5.0	15.269
6.0	15.269
7.0	15.269
8.0	15.269

COSEL


Model SNDHS100A15

Item Rise and Fall Time

Temperature 25°C
Testing Circuitry Figure A


Object +15V6.7A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		20.0	5.0	25.0	6.0	24.9
100 %		20.0	5.8	25.8	3.0	13.0




COSEL

Model	SNDHS100A15
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V6.7A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	47	49
-20	47	49
0	47	49
25	48	51
40	48	50
55	48	50
70	48	50
80	47	50
95	47	50
100	47	50
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


COSEL

Model	SNDHS100A15	Temperature Testing Circuitry	25°C Figure A																																																											
Item	Overcurrent Protection																																																													
Object	+15V6.7A																																																													
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 60V Input Volt. 110V Input Volt. 160V</p>																																																													
Note:	<p>Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> <p>Intermittent operation occurs when the output voltage is from 8.5V to 0V.</p>																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>7.90</td><td>8.21</td><td>8.51</td></tr> <tr><td>13.5</td><td>7.97</td><td>8.26</td><td>8.58</td></tr> <tr><td>12.0</td><td>8.01</td><td>8.36</td><td>8.73</td></tr> <tr><td>10.5</td><td>8.07</td><td>8.49</td><td>8.71</td></tr> <tr><td>9.0</td><td>8.19</td><td>8.73</td><td>8.69</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	14.3	7.90	8.21	8.51	13.5	7.97	8.26	8.58	12.0	8.01	8.36	8.73	10.5	8.07	8.49	8.71	9.0	8.19	8.73	8.69	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																													
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																											
14.3	7.90	8.21	8.51																																																											
13.5	7.97	8.26	8.58																																																											
12.0	8.01	8.36	8.73																																																											
10.5	8.07	8.49	8.71																																																											
9.0	8.19	8.73	8.69																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											

COSEL

Model	SNDHS100A15
Item	Overshoot Protection
Object	+15V6.7A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 60[V]	Input Volt. 160[V]
-40	18.46	18.46
-20	18.75	18.75
0	19.04	19.04
25	19.39	19.39
40	19.57	19.57
55	19.75	19.75
70	19.86	19.86
80	20.04	20.04
95	20.16	20.16
100	20.21	20.22
--	-	-

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)