

# TEST DATA OF SNDHS100B15

Regulated DC Power Supply  
June 30, 2011

Approved by : Takahiro Yoneda  
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai  
Tadashi Arai Design Engineer

**COSEL CO.,LTD.**

CONTENTS

1.Input Current (by Input Voltage) . . . . . 1  
 2.Input Current (by Load Current) . . . . . 2  
 3.Input Power (by Load Current) . . . . . 3  
 4.Efficiency (by Input Voltage) . . . . . 4  
 5.Efficiency (by Load Current) . . . . . 5  
 6.Line Regulation . . . . . 6  
 7.Load Regulation . . . . . 7  
 8.Dynamic Load Response . . . . . 8  
 9.Ripple Voltage (by Load Current) . . . . . 9  
 10.Ripple-Noise . . . . . 10  
 11.Ripple Voltage (by Ambient Temperature) . . . . . 11  
 12.Ambient Temperature Drift . . . . . 12  
 13.Output Voltage Accuracy . . . . . 13  
 14.Time Lapse Drift . . . . . 14  
 15.Rise and Fall Time . . . . . 15  
 16.Minimum Input Voltage for Regulated Output Voltage . . . . . 16  
 17.Overcurrent Protection . . . . . 17  
 18.Overvoltage Protection . . . . . 18  
 19.Figure of Testing Circuitry . . . . . 19

(Final Page 19)



Model		SNDHS100B15		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object																																																																																				
1.Graph			2.Values																																																																																	
<p>Legend:          —△— Load 100%          - - -□- - - Load 50%          - · -○- · - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>100</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>170</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>180</td><td>0.036</td><td>0.336</td><td>0.625</td></tr> <tr><td>185</td><td>0.036</td><td>0.327</td><td>0.631</td></tr> <tr><td>200</td><td>0.036</td><td>0.301</td><td>0.581</td></tr> <tr><td>250</td><td>0.035</td><td>0.242</td><td>0.466</td></tr> <tr><td>280</td><td>0.035</td><td>0.218</td><td>0.417</td></tr> <tr><td>300</td><td>0.034</td><td>0.205</td><td>0.390</td></tr> <tr><td>350</td><td>0.034</td><td>0.180</td><td>0.338</td></tr> <tr><td>400</td><td>0.033</td><td>0.161</td><td>0.299</td></tr> <tr><td>420</td><td>0.033</td><td>0.155</td><td>0.286</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.000	0.000	0.000	100	0.000	0.000	0.000	150	0.000	0.000	0.000	170	0.003	0.003	0.003	180	0.036	0.336	0.625	185	0.036	0.327	0.631	200	0.036	0.301	0.581	250	0.035	0.242	0.466	280	0.035	0.218	0.417	300	0.034	0.205	0.390	350	0.034	0.180	0.338	400	0.033	0.161	0.299	420	0.033	0.155	0.286	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0	0.000	0.000	0.000																																																																																	
50	0.000	0.000	0.000																																																																																	
100	0.000	0.000	0.000																																																																																	
150	0.000	0.000	0.000																																																																																	
170	0.003	0.003	0.003																																																																																	
180	0.036	0.336	0.625																																																																																	
185	0.036	0.327	0.631																																																																																	
200	0.036	0.301	0.581																																																																																	
250	0.035	0.242	0.466																																																																																	
280	0.035	0.218	0.417																																																																																	
300	0.034	0.205	0.390																																																																																	
350	0.034	0.180	0.338																																																																																	
400	0.033	0.161	0.299																																																																																	
420	0.033	0.155	0.286																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		SNDHS100B15		Temperature	25°C																																																			
Item		Input Current (by Load Current)		Testing Circuitry	Figure A																																																			
Object																																																								
1.Graph		—△— Input Volt. 200V - - -□- - - Input Volt. 280V - · - ○ - · - - Input Volt. 400V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.036</td><td>0.035</td><td>0.034</td></tr> <tr><td>1.00</td><td>0.111</td><td>0.080</td><td>0.062</td></tr> <tr><td>2.00</td><td>0.195</td><td>0.143</td><td>0.108</td></tr> <tr><td>3.00</td><td>0.276</td><td>0.200</td><td>0.149</td></tr> <tr><td>4.00</td><td>0.359</td><td>0.258</td><td>0.189</td></tr> <tr><td>5.00</td><td>0.443</td><td>0.318</td><td>0.230</td></tr> <tr><td>6.00</td><td>0.528</td><td>0.378</td><td>0.271</td></tr> <tr><td>6.70</td><td>0.587</td><td>0.420</td><td>0.301</td></tr> <tr><td>7.37</td><td>0.645</td><td>0.461</td><td>0.330</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	0.036	0.035	0.034	1.00	0.111	0.080	0.062	2.00	0.195	0.143	0.108	3.00	0.276	0.200	0.149	4.00	0.359	0.258	0.189	5.00	0.443	0.318	0.230	6.00	0.528	0.378	0.271	6.70	0.587	0.420	0.301	7.37	0.645	0.461	0.330	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	0.036	0.035	0.034																																																					
1.00	0.111	0.080	0.062																																																					
2.00	0.195	0.143	0.108																																																					
3.00	0.276	0.200	0.149																																																					
4.00	0.359	0.258	0.189																																																					
5.00	0.443	0.318	0.230																																																					
6.00	0.528	0.378	0.271																																																					
6.70	0.587	0.420	0.301																																																					
7.37	0.645	0.461	0.330																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SNDHS100B15		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>---□--- Input Volt. 280V</p> <p>-·-○-·- Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>7.3</td><td>9.9</td><td>13.7</td></tr> <tr><td>1.00</td><td>22.3</td><td>22.4</td><td>25.1</td></tr> <tr><td>2.00</td><td>39.0</td><td>40.1</td><td>43.3</td></tr> <tr><td>3.00</td><td>55.1</td><td>56.2</td><td>59.5</td></tr> <tr><td>4.00</td><td>71.7</td><td>72.4</td><td>75.8</td></tr> <tr><td>5.00</td><td>88.5</td><td>89.0</td><td>92.0</td></tr> <tr><td>6.00</td><td>105.5</td><td>105.9</td><td>108.7</td></tr> <tr><td>6.70</td><td>117.5</td><td>117.8</td><td>120.6</td></tr> <tr><td>7.37</td><td>129.0</td><td>129.3</td><td>132.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	7.3	9.9	13.7	1.00	22.3	22.4	25.1	2.00	39.0	40.1	43.3	3.00	55.1	56.2	59.5	4.00	71.7	72.4	75.8	5.00	88.5	89.0	92.0	6.00	105.5	105.9	108.7	6.70	117.5	117.8	120.6	7.37	129.0	129.3	132.1	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	7.3	9.9	13.7																																																					
1.00	22.3	22.4	25.1																																																					
2.00	39.0	40.1	43.3																																																					
3.00	55.1	56.2	59.5																																																					
4.00	71.7	72.4	75.8																																																					
5.00	88.5	89.0	92.0																																																					
6.00	105.5	105.9	108.7																																																					
6.70	117.5	117.8	120.6																																																					
7.37	129.0	129.3	132.1																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDHS100B15		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object																																					
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>84.9</td><td>87.6</td></tr> <tr><td>200</td><td>85.0</td><td>87.7</td></tr> <tr><td>240</td><td>84.6</td><td>87.7</td></tr> <tr><td>280</td><td>83.8</td><td>87.4</td></tr> <tr><td>320</td><td>82.4</td><td>86.9</td></tr> <tr><td>360</td><td>80.8</td><td>86.2</td></tr> <tr><td>400</td><td>79.3</td><td>85.4</td></tr> <tr><td>420</td><td>78.5</td><td>84.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	84.9	87.6	200	85.0	87.7	240	84.6	87.7	280	83.8	87.4	320	82.4	86.9	360	80.8	86.2	400	79.3	85.4	420	78.5	84.9	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
195	84.9	87.6																																			
200	85.0	87.7																																			
240	84.6	87.7																																			
280	83.8	87.4																																			
320	82.4	86.9																																			
360	80.8	86.2																																			
400	79.3	85.4																																			
420	78.5	84.9																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		SNDHS100B15		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>- -□- - Input Volt. 280V</p> <p>-·-○-·- Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>70.4</td><td>70.1</td><td>62.6</td></tr> <tr><td>2.00</td><td>79.5</td><td>77.4</td><td>71.7</td></tr> <tr><td>3.00</td><td>84.1</td><td>82.5</td><td>77.9</td></tr> <tr><td>4.00</td><td>86.0</td><td>85.2</td><td>81.3</td></tr> <tr><td>5.00</td><td>86.9</td><td>86.5</td><td>83.6</td></tr> <tr><td>6.00</td><td>87.4</td><td>87.1</td><td>84.9</td></tr> <tr><td>6.70</td><td>87.6</td><td>87.4</td><td>85.4</td></tr> <tr><td>7.37</td><td>87.7</td><td>87.5</td><td>85.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	-	-	-	1.00	70.4	70.1	62.6	2.00	79.5	77.4	71.7	3.00	84.1	82.5	77.9	4.00	86.0	85.2	81.3	5.00	86.9	86.5	83.6	6.00	87.4	87.1	84.9	6.70	87.6	87.4	85.4	7.37	87.7	87.5	85.7	--	-	-	-	--	-	-	-		
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	-	-	-																																																					
1.00	70.4	70.1	62.6																																																					
2.00	79.5	77.4	71.7																																																					
3.00	84.1	82.5	77.9																																																					
4.00	86.0	85.2	81.3																																																					
5.00	86.9	86.5	83.6																																																					
6.00	87.4	87.1	84.9																																																					
6.70	87.6	87.4	85.4																																																					
7.37	87.7	87.5	85.7																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



<b>COSEL</b>																																			
Model	SNDHS100B15	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V6.7A																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>15.311</td><td>15.299</td></tr> <tr><td>200</td><td>15.312</td><td>15.299</td></tr> <tr><td>240</td><td>15.312</td><td>15.299</td></tr> <tr><td>280</td><td>15.313</td><td>15.301</td></tr> <tr><td>320</td><td>15.314</td><td>15.301</td></tr> <tr><td>360</td><td>15.314</td><td>15.302</td></tr> <tr><td>400</td><td>15.315</td><td>15.302</td></tr> <tr><td>420</td><td>15.315</td><td>15.302</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	15.311	15.299	200	15.312	15.299	240	15.312	15.299	280	15.313	15.301	320	15.314	15.301	360	15.314	15.302	400	15.315	15.302	420	15.315	15.302	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
195	15.311	15.299																																	
200	15.312	15.299																																	
240	15.312	15.299																																	
280	15.313	15.301																																	
320	15.314	15.301																																	
360	15.314	15.302																																	
400	15.315	15.302																																	
420	15.315	15.302																																	
--	-	-																																	



Model		SNDHS100B15		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+15V6.7A																																																						
1.Graph		—△— Input Volt. 200V ---□--- Input Volt. 280V -·-○-·- Input Volt. 400V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.325</td><td>15.325</td><td>15.326</td></tr> <tr><td>1.00</td><td>15.316</td><td>15.318</td><td>15.320</td></tr> <tr><td>2.00</td><td>15.312</td><td>15.314</td><td>15.316</td></tr> <tr><td>3.00</td><td>15.308</td><td>15.310</td><td>15.312</td></tr> <tr><td>4.00</td><td>15.304</td><td>15.307</td><td>15.309</td></tr> <tr><td>5.00</td><td>15.301</td><td>15.303</td><td>15.305</td></tr> <tr><td>6.00</td><td>15.297</td><td>15.299</td><td>15.301</td></tr> <tr><td>6.70</td><td>15.295</td><td>15.297</td><td>15.299</td></tr> <tr><td>7.37</td><td>15.292</td><td>15.295</td><td>15.296</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.00	15.325	15.325	15.326	1.00	15.316	15.318	15.320	2.00	15.312	15.314	15.316	3.00	15.308	15.310	15.312	4.00	15.304	15.307	15.309	5.00	15.301	15.303	15.305	6.00	15.297	15.299	15.301	6.70	15.295	15.297	15.299	7.37	15.292	15.295	15.296	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.00	15.325	15.325	15.326																																																					
1.00	15.316	15.318	15.320																																																					
2.00	15.312	15.314	15.316																																																					
3.00	15.308	15.310	15.312																																																					
4.00	15.304	15.307	15.309																																																					
5.00	15.301	15.303	15.305																																																					
6.00	15.297	15.299	15.301																																																					
6.70	15.295	15.297	15.299																																																					
7.37	15.292	15.295	15.296																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDHS100B15	
Item		Dynamic Load Response	
Object		+15V6.7A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 280 V  
 Cycle 1000 ms




Min. Load (0A) ↔  
 Load 100% (6.7A)

0.5 V/div




1ms/div




20ms/div

Min. Load (0A) ↔  
 Load 50% (3.35A)

0.5 V/div




1ms/div




20ms/div

Load 10% (0.67A) ↔  
 Load 100% (6.7A)

0.5 V/div



1ms/div



20ms/div



Model		SNDHS100B15		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		+15V6.7A																																									
1.Graph				2.Values																																							
<p>                     —△— Input Volt. 200V                      -·-○-·- Input Volt. 400V                 </p> <p>                     Measured by 100 MHz Oscilloscope.                      Ripple Voltage is shown as p-p in the figure below.                      Note: Slanted line shows the range of the rated load current.                 </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>1.00</td><td>30</td><td>40</td></tr> <tr><td>2.00</td><td>30</td><td>40</td></tr> <tr><td>3.00</td><td>35</td><td>45</td></tr> <tr><td>4.00</td><td>35</td><td>45</td></tr> <tr><td>5.00</td><td>35</td><td>45</td></tr> <tr><td>6.00</td><td>35</td><td>45</td></tr> <tr><td>6.70</td><td>35</td><td>50</td></tr> <tr><td>7.37</td><td>35</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	5	5	1.00	30	40	2.00	30	40	3.00	35	45	4.00	35	45	5.00	35	45	6.00	35	45	6.70	35	50	7.37	35	50	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 200 [V]	Input Volt. 400 [V]																																									
0.00	5	5																																									
1.00	30	40																																									
2.00	30	40																																									
3.00	35	45																																									
4.00	35	45																																									
5.00	35	45																																									
6.00	35	45																																									
6.70	35	50																																									
7.37	35	50																																									
--	-	-																																									
--	-	-																																									
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																											



Model		SNDHS100B15																																							
Item		Ripple-Noise																																							
Object		+15V6.7A																																							
1.Graph		2.Values																																							
<p>                     —△— Input Volt. 200V                      -·-○-·- Input Volt. 400V                 </p> <p>                     Measured by 100 MHz Oscilloscope.                      Ripple-Noise is shown as p-p in the figure below.                      Note: Slanted line shows the range of the rated load current.                 </p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>35</td><td>50</td></tr> <tr><td>1.00</td><td>50</td><td>70</td></tr> <tr><td>2.00</td><td>50</td><td>70</td></tr> <tr><td>3.00</td><td>50</td><td>85</td></tr> <tr><td>4.00</td><td>50</td><td>85</td></tr> <tr><td>5.00</td><td>50</td><td>80</td></tr> <tr><td>6.00</td><td>50</td><td>80</td></tr> <tr><td>6.70</td><td>50</td><td>80</td></tr> <tr><td>7.37</td><td>50</td><td>85</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.00	35	50	1.00	50	70	2.00	50	70	3.00	50	85	4.00	50	85	5.00	50	80	6.00	50	80	6.70	50	80	7.37	50	85	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 200 [V]	Input Volt. 400 [V]																																							
0.00	35	50																																							
1.00	50	70																																							
2.00	50	70																																							
3.00	50	85																																							
4.00	50	85																																							
5.00	50	80																																							
6.00	50	80																																							
6.70	50	80																																							
7.37	50	85																																							
--	-	-																																							
--	-	-																																							
<p>Fig.Complex Ripple Noise Wave Form</p>																																									



<b>Model</b>		SNDHS100B15		Testing Circuitry Figure B																																						
<b>Item</b>		Ripple Voltage (by Ambient Temp.)																																								
<b>Object</b>		+15V6.7A																																								
1.Graph			2.Values																																							
<p style="text-align: right;">                     ---□--- Load 50%                      —△— Load 100%                 </p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 280V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>50</td><td>50</td></tr> <tr><td>-20</td><td>50</td><td>55</td></tr> <tr><td>0</td><td>50</td><td>50</td></tr> <tr><td>25</td><td>40</td><td>40</td></tr> <tr><td>40</td><td>50</td><td>50</td></tr> <tr><td>55</td><td>50</td><td>50</td></tr> <tr><td>70</td><td>55</td><td>55</td></tr> <tr><td>85</td><td>55</td><td>55</td></tr> <tr><td>95</td><td>60</td><td>60</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-40	50	50	-20	50	55	0	50	50	25	40	40	40	50	50	55	50	50	70	55	55	85	55	55	95	60	60	--	-	-	--	-	-
			Ambient Temperature [°C]	Ripple Voltage [mV]																																						
Load 50%	Load 100%																																									
-40	50	50																																								
-20	50	55																																								
0	50	50																																								
25	40	40																																								
40	50	50																																								
55	50	50																																								
70	55	55																																								
85	55	55																																								
95	60	60																																								
--	-	-																																								
--	-	-																																								
Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.																																										



Model		SNDHS100B15		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+15V6.7A																																																						
1.Graph		<p>—△— Input Volt. 200V                  ---□--- Input Volt. 280V                  -·-○-·- Input Volt. 400V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>15.239</td><td>15.249</td><td>15.260</td></tr> <tr><td>-20</td><td>15.262</td><td>15.268</td><td>15.277</td></tr> <tr><td>0</td><td>15.278</td><td>15.282</td><td>15.287</td></tr> <tr><td>25</td><td>15.289</td><td>15.290</td><td>15.293</td></tr> <tr><td>40</td><td>15.291</td><td>15.292</td><td>15.293</td></tr> <tr><td>55</td><td>15.292</td><td>15.293</td><td>15.293</td></tr> <tr><td>70</td><td>15.286</td><td>15.286</td><td>15.285</td></tr> <tr><td>85</td><td>15.280</td><td>15.280</td><td>15.278</td></tr> <tr><td>95</td><td>15.275</td><td>15.275</td><td>15.273</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-40	15.239	15.249	15.260	-20	15.262	15.268	15.277	0	15.278	15.282	15.287	25	15.289	15.290	15.293	40	15.291	15.292	15.293	55	15.292	15.293	15.293	70	15.286	15.286	15.285	85	15.280	15.280	15.278	95	15.275	15.275	15.273	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
-40	15.239	15.249	15.260																																																					
-20	15.262	15.268	15.277																																																					
0	15.278	15.282	15.287																																																					
25	15.289	15.290	15.293																																																					
40	15.291	15.292	15.293																																																					
55	15.292	15.293	15.293																																																					
70	15.286	15.286	15.285																																																					
85	15.280	15.280	15.278																																																					
95	15.275	15.275	15.273																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								



<b>COSEL</b>		Testing Circuitry Figure A
Model	SNDHS100B15	
Item	Output Voltage Accuracy	
Object	+15V6.7A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 6.7A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	400	0	15.326	±32	±0.2
Minimum Voltage	-20	200	6.7	15.262		




<b>COSEL</b>																									
Model	SNDHS100B15	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V6.7A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt.    280V Load            100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.249</td></tr> <tr><td>0.5</td><td>15.250</td></tr> <tr><td>1.0</td><td>15.249</td></tr> <tr><td>2.0</td><td>15.249</td></tr> <tr><td>3.0</td><td>15.249</td></tr> <tr><td>4.0</td><td>15.250</td></tr> <tr><td>5.0</td><td>15.249</td></tr> <tr><td>6.0</td><td>15.249</td></tr> <tr><td>7.0</td><td>15.249</td></tr> <tr><td>8.0</td><td>15.249</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	15.249	0.5	15.250	1.0	15.249	2.0	15.249	3.0	15.249	4.0	15.250	5.0	15.249	6.0	15.249	7.0	15.249	8.0	15.249
Time since start [H]	Output Voltage [V]																								
0.0	15.249																								
0.5	15.250																								
1.0	15.249																								
2.0	15.249																								
3.0	15.249																								
4.0	15.250																								
5.0	15.249																								
6.0	15.249																								
7.0	15.249																								
8.0	15.249																								



Model	SNDHS100B15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V6.7A		


1. Graph

Input Volt. 280 V



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	19.0	3.8	22.8	2.4	23.0
100 %	19.3	5.0	24.3	1.2	11.9





<p>Model      SNDHS100B15</p> <p>Item        Minimum Input Voltage for Regulated Output Voltage</p> <p>Object      +15V6.7A</p>		<p>Testing Circuitry    Figure A</p>																																						
<p>1. Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>162</td><td>168</td></tr> <tr><td>-20</td><td>164</td><td>170</td></tr> <tr><td>0</td><td>165</td><td>172</td></tr> <tr><td>25</td><td>167</td><td>174</td></tr> <tr><td>40</td><td>168</td><td>175</td></tr> <tr><td>55</td><td>169</td><td>176</td></tr> <tr><td>70</td><td>168</td><td>175</td></tr> <tr><td>85</td><td>168</td><td>176</td></tr> <tr><td>95</td><td>167</td><td>175</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	162	168	-20	164	170	0	165	172	25	167	174	40	168	175	55	169	176	70	168	175	85	168	176	95	167	175	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	162	168																																						
-20	164	170																																						
0	165	172																																						
25	167	174																																						
40	168	175																																						
55	169	176																																						
70	168	175																																						
85	168	176																																						
95	167	175																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model      SNDHS100B15</p>		<p>Temperature      25°C</p>																																																								
<p>Item      Overcurrent Protection</p>		<p>Testing Circuitry      Figure A</p>																																																								
<p>Object      +15V6.7A</p>																																																										
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>— Input Volt. 200V</p> <p>— Input Volt. 280V</p> <p>— Input Volt. 400V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>8.55</td><td>8.75</td><td>9.19</td></tr> <tr><td>13.5</td><td>8.59</td><td>8.83</td><td>9.24</td></tr> <tr><td>12.0</td><td>8.70</td><td>8.97</td><td>9.25</td></tr> <tr><td>10.5</td><td>8.83</td><td>9.13</td><td>9.45</td></tr> <tr><td>9.0</td><td>8.97</td><td>9.19</td><td>9.42</td></tr> <tr><td>7.5</td><td>9.08</td><td>9.37</td><td>9.34</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	14.3	8.55	8.75	9.19	13.5	8.59	8.83	9.24	12.0	8.70	8.97	9.25	10.5	8.83	9.13	9.45	9.0	8.97	9.19	9.42	7.5	9.08	9.37	9.34	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																							
14.3	8.55	8.75	9.19																																																							
13.5	8.59	8.83	9.24																																																							
12.0	8.70	8.97	9.25																																																							
10.5	8.83	9.13	9.45																																																							
9.0	8.97	9.19	9.42																																																							
7.5	9.08	9.37	9.34																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
--	-	-	-																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										
<p>Intermittent operation occurs when the output voltage is from 7.5V to 0V.</p>																																																										



<b>COSEL</b>																																								
Model	SNDHS100B15																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+15V6.7A																																							
<p>1. Graph</p> <p style="text-align: center;">Load 0%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>18.56</td><td>18.56</td></tr> <tr><td>-20</td><td>18.74</td><td>18.74</td></tr> <tr><td>0</td><td>19.03</td><td>19.03</td></tr> <tr><td>25</td><td>19.38</td><td>19.38</td></tr> <tr><td>40</td><td>19.55</td><td>19.55</td></tr> <tr><td>55</td><td>19.73</td><td>19.73</td></tr> <tr><td>70</td><td>19.85</td><td>19.85</td></tr> <tr><td>85</td><td>20.14</td><td>20.14</td></tr> <tr><td>95</td><td>20.25</td><td>20.25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	18.56	18.56	-20	18.74	18.74	0	19.03	19.03	25	19.38	19.38	40	19.55	19.55	55	19.73	19.73	70	19.85	19.85	85	20.14	20.14	95	20.25	20.25	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 200[V]	Input Volt. 400[V]																																						
-40	18.56	18.56																																						
-20	18.74	18.74																																						
0	19.03	19.03																																						
25	19.38	19.38																																						
40	19.55	19.55																																						
55	19.73	19.73																																						
70	19.85	19.85																																						
85	20.14	20.14																																						
95	20.25	20.25																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								




Figure A




Figure B (Ripple and Ripple noise Characteristic)