

TEST DATA OF SNDHS200A15

Regulated DC Power Supply
April 10, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1

2.Input Current (by Load Current) 2

3.Input Power (by Load Current) 3

4.Efficiency (by Input Voltage) 4

5.Efficiency (by Load Current) 5

6.Line Regulation 6

7.Load Regulation 7

8.Dynamic Load Response 8

9.Ripple Voltage (by Load Current) 9

10.Ripple-Noise 10

11.Ripple Voltage (by Ambient Temperature) 11

12.Ambient Temperature Drift 12

13.Output Voltage Accuracy 13

14.Time Lapse Drift 14

15.Rise and Fall Time 15

16.Minimum Input Voltage for Regulated Output Voltage 16

17.Overcurrent Protection 17

18.Overvoltage Protection 18

19.Figure of Testing Circuitry 19

(Final Page 19)



Model		SNDHS200A15		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		+15V13.4A																																																																																		
1. Graph			2. Values																																																																																	
<p>Legend: —△— Load 100% - - - □ - - - Load 50% - · - ○ - · - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>40</td><td>0.009</td><td>0.008</td><td>0.008</td></tr> <tr><td>50</td><td>0.005</td><td>0.005</td><td>0.005</td></tr> <tr><td>55</td><td>0.004</td><td>0.004</td><td>0.004</td></tr> <tr><td>56</td><td>0.022</td><td>2.056</td><td>4.050</td></tr> <tr><td>60</td><td>0.019</td><td>1.900</td><td>3.914</td></tr> <tr><td>66</td><td>0.017</td><td>1.715</td><td>3.502</td></tr> <tr><td>80</td><td>0.015</td><td>1.421</td><td>2.883</td></tr> <tr><td>95</td><td>0.013</td><td>1.201</td><td>2.422</td></tr> <tr><td>110</td><td>0.011</td><td>1.043</td><td>2.110</td></tr> <tr><td>125</td><td>0.011</td><td>0.923</td><td>1.847</td></tr> <tr><td>140</td><td>0.010</td><td>0.829</td><td>1.649</td></tr> <tr><td>160</td><td>0.008</td><td>0.733</td><td>1.461</td></tr> <tr><td>170</td><td>0.007</td><td>0.694</td><td>1.381</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	40	0.009	0.008	0.008	50	0.005	0.005	0.005	55	0.004	0.004	0.004	56	0.022	2.056	4.050	60	0.019	1.900	3.914	66	0.017	1.715	3.502	80	0.015	1.421	2.883	95	0.013	1.201	2.422	110	0.011	1.043	2.110	125	0.011	0.923	1.847	140	0.010	0.829	1.649	160	0.008	0.733	1.461	170	0.007	0.694	1.381	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0	0.000	0.000	0.000																																																																																	
40	0.009	0.008	0.008																																																																																	
50	0.005	0.005	0.005																																																																																	
55	0.004	0.004	0.004																																																																																	
56	0.022	2.056	4.050																																																																																	
60	0.019	1.900	3.914																																																																																	
66	0.017	1.715	3.502																																																																																	
80	0.015	1.421	2.883																																																																																	
95	0.013	1.201	2.422																																																																																	
110	0.011	1.043	2.110																																																																																	
125	0.011	0.923	1.847																																																																																	
140	0.010	0.829	1.649																																																																																	
160	0.008	0.733	1.461																																																																																	
170	0.007	0.694	1.381																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		SNDHS200A15		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		+15V13.4A																																																						
1.Graph		—△— Input Volt. 60V - - - □ - - - Input Volt. 110V - · - ○ - · - - Input Volt. 160V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.019</td><td>0.011</td><td>0.008</td></tr> <tr><td>2.5</td><td>0.746</td><td>0.412</td><td>0.300</td></tr> <tr><td>5.0</td><td>1.436</td><td>0.790</td><td>0.562</td></tr> <tr><td>7.5</td><td>2.146</td><td>1.172</td><td>0.822</td></tr> <tr><td>10.0</td><td>2.878</td><td>1.562</td><td>1.089</td></tr> <tr><td>12.5</td><td>3.638</td><td>1.962</td><td>1.361</td></tr> <tr><td>13.4</td><td>3.914</td><td>2.110</td><td>1.461</td></tr> <tr><td>14.7</td><td>4.332</td><td>2.324</td><td>1.606</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	0.019	0.011	0.008	2.5	0.746	0.412	0.300	5.0	1.436	0.790	0.562	7.5	2.146	1.172	0.822	10.0	2.878	1.562	1.089	12.5	3.638	1.962	1.361	13.4	3.914	2.110	1.461	14.7	4.332	2.324	1.606	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	0.019	0.011	0.008																																																					
2.5	0.746	0.412	0.300																																																					
5.0	1.436	0.790	0.562																																																					
7.5	2.146	1.172	0.822																																																					
10.0	2.878	1.562	1.089																																																					
12.5	3.638	1.962	1.361																																																					
13.4	3.914	2.110	1.461																																																					
14.7	4.332	2.324	1.606																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SNDHS200A15		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		+15V13.4A																																																						
1.Graph		<p>—△— Input Volt. 60V</p> <p>---□--- Input Volt. 110V</p> <p>-·-○-·- Input Volt. 160V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.2</td><td>1.2</td><td>1.2</td></tr> <tr><td>2.5</td><td>44.7</td><td>45.3</td><td>48.0</td></tr> <tr><td>5.0</td><td>86.0</td><td>86.8</td><td>89.8</td></tr> <tr><td>7.5</td><td>128.7</td><td>128.8</td><td>131.4</td></tr> <tr><td>10.0</td><td>172.5</td><td>171.6</td><td>174.1</td></tr> <tr><td>12.5</td><td>217.8</td><td>215.7</td><td>217.7</td></tr> <tr><td>13.4</td><td>234.7</td><td>231.9</td><td>233.5</td></tr> <tr><td>14.7</td><td>259.5</td><td>255.3</td><td>256.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	1.2	1.2	1.2	2.5	44.7	45.3	48.0	5.0	86.0	86.8	89.8	7.5	128.7	128.8	131.4	10.0	172.5	171.6	174.1	12.5	217.8	215.7	217.7	13.4	234.7	231.9	233.5	14.7	259.5	255.3	256.7	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	1.2	1.2	1.2																																																					
2.5	44.7	45.3	48.0																																																					
5.0	86.0	86.8	89.8																																																					
7.5	128.7	128.8	131.4																																																					
10.0	172.5	171.6	174.1																																																					
12.5	217.8	215.7	217.7																																																					
13.4	234.7	231.9	233.5																																																					
14.7	259.5	255.3	256.7																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SNDHS200A15																																	
Item		Efficiency (by Input Voltage)																																	
Object		+15V13.4A																																	
1.Graph		2.Values																																	
<p>---□--- Load 50%</p> <p>—△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>56</td><td>89.1</td><td>86.9</td></tr> <tr><td>66</td><td>89.4</td><td>87.6</td></tr> <tr><td>80</td><td>90.2</td><td>88.2</td></tr> <tr><td>95</td><td>90.0</td><td>88.6</td></tr> <tr><td>110</td><td>89.7</td><td>88.8</td></tr> <tr><td>125</td><td>89.2</td><td>88.6</td></tr> <tr><td>140</td><td>88.7</td><td>88.6</td></tr> <tr><td>160</td><td>88.1</td><td>88.5</td></tr> <tr><td>170</td><td>87.2</td><td>88.0</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	56	89.1	86.9	66	89.4	87.6	80	90.2	88.2	95	90.0	88.6	110	89.7	88.8	125	89.2	88.6	140	88.7	88.6	160	88.1	88.5	170	87.2	88.0
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
56	89.1	86.9																																	
66	89.4	87.6																																	
80	90.2	88.2																																	
95	90.0	88.6																																	
110	89.7	88.8																																	
125	89.2	88.6																																	
140	88.7	88.6																																	
160	88.1	88.5																																	
170	87.2	88.0																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model		SNDHS200A15		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		+15V13.4A																																																						
1.Graph		—△— Input Volt. 60V - - - □ - - - Input Volt. 110V - · - ○ - · - - Input Volt. 160V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.5</td><td>85.8</td><td>84.8</td><td>80.0</td></tr> <tr><td>5.0</td><td>89.2</td><td>88.4</td><td>85.5</td></tr> <tr><td>7.5</td><td>89.4</td><td>89.3</td><td>87.6</td></tr> <tr><td>10.0</td><td>88.9</td><td>89.4</td><td>88.1</td></tr> <tr><td>12.5</td><td>88.0</td><td>88.9</td><td>88.0</td></tr> <tr><td>13.4</td><td>87.5</td><td>88.6</td><td>88.0</td></tr> <tr><td>14.7</td><td>86.9</td><td>88.3</td><td>87.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	-	-	-	2.5	85.8	84.8	80.0	5.0	89.2	88.4	85.5	7.5	89.4	89.3	87.6	10.0	88.9	89.4	88.1	12.5	88.0	88.9	88.0	13.4	87.5	88.6	88.0	14.7	86.9	88.3	87.8	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	-	-	-																																																					
2.5	85.8	84.8	80.0																																																					
5.0	89.2	88.4	85.5																																																					
7.5	89.4	89.3	87.6																																																					
10.0	88.9	89.4	88.1																																																					
12.5	88.0	88.9	88.0																																																					
13.4	87.5	88.6	88.0																																																					
14.7	86.9	88.3	87.8																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



<p>Model SNDHS200A15</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																			
<p>Item Line Regulation</p>																																					
<p>Object +15V13.4A</p>																																					
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50% —△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>56</td><td>15.321</td><td>15.316</td></tr> <tr><td>60</td><td>15.321</td><td>15.316</td></tr> <tr><td>66</td><td>15.321</td><td>15.316</td></tr> <tr><td>80</td><td>15.321</td><td>15.317</td></tr> <tr><td>95</td><td>15.321</td><td>15.316</td></tr> <tr><td>110</td><td>15.321</td><td>15.317</td></tr> <tr><td>125</td><td>15.321</td><td>15.317</td></tr> <tr><td>140</td><td>15.320</td><td>15.316</td></tr> <tr><td>160</td><td>15.320</td><td>15.317</td></tr> <tr><td>170</td><td>15.320</td><td>15.317</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	56	15.321	15.316	60	15.321	15.316	66	15.321	15.316	80	15.321	15.317	95	15.321	15.316	110	15.321	15.317	125	15.321	15.317	140	15.320	15.316	160	15.320	15.317	170	15.320	15.317
Input Voltage [V]	Output Voltage [V]																																				
	Load 50%	Load 100%																																			
56	15.321	15.316																																			
60	15.321	15.316																																			
66	15.321	15.316																																			
80	15.321	15.317																																			
95	15.321	15.316																																			
110	15.321	15.317																																			
125	15.321	15.317																																			
140	15.320	15.316																																			
160	15.320	15.317																																			
170	15.320	15.317																																			



Model		SNDHS200A15		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+15V13.4A																																																						
1.Graph		<p>—△— Input Volt. 60V</p> <p>---□--- Input Volt. 110V</p> <p>---○--- Input Volt. 160V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.329</td><td>15.329</td><td>15.328</td></tr> <tr><td>2.5</td><td>15.327</td><td>15.327</td><td>15.327</td></tr> <tr><td>5.0</td><td>15.326</td><td>15.326</td><td>15.326</td></tr> <tr><td>7.5</td><td>15.325</td><td>15.325</td><td>15.325</td></tr> <tr><td>10.0</td><td>15.324</td><td>15.324</td><td>15.324</td></tr> <tr><td>12.5</td><td>15.323</td><td>15.324</td><td>15.324</td></tr> <tr><td>13.4</td><td>15.324</td><td>15.324</td><td>15.323</td></tr> <tr><td>14.7</td><td>15.324</td><td>15.323</td><td>15.324</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.0	15.329	15.329	15.328	2.5	15.327	15.327	15.327	5.0	15.326	15.326	15.326	7.5	15.325	15.325	15.325	10.0	15.324	15.324	15.324	12.5	15.323	15.324	15.324	13.4	15.324	15.324	15.323	14.7	15.324	15.323	15.324	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.0	15.329	15.329	15.328																																																					
2.5	15.327	15.327	15.327																																																					
5.0	15.326	15.326	15.326																																																					
7.5	15.325	15.325	15.325																																																					
10.0	15.324	15.324	15.324																																																					
12.5	15.323	15.324	15.324																																																					
13.4	15.324	15.324	15.323																																																					
14.7	15.324	15.323	15.324																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDHS200A15	
Item		Dynamic Load Response	
Object		+15V/13.4A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 110 V
 Cycle 1000 ms




Min. Load (0A) ↔
 Load 100% (13.4A)

1 V/div




400µs/div




40ms/div

Min. Load (0A) ↔
 Load 50% (6.7A)

1 V/div




400µs/div




40ms/div

Load 10% (1.34A) ↔
 Load 100% (13.4A)

1 V/div



400µs/div




40ms/div

Model	SNDHS200A15
Item	Ripple Voltage (by Load Current)
Object	+15V13.4A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 60 [V]	Input Volt. 160 [V]
0.0	5	5
2.5	15	25
5.0	15	25
7.5	15	25
10.0	15	30
12.5	15	30
13.4	15	30
14.7	15	25
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig. Complex Ripple Wave Form

Model	SNDHS200A15
Item	Ripple-Noise
Object	+15V13.4A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 60 [V]	Input Volt. 160 [V]
0.0	5	15
2.5	15	30
5.0	20	35
7.5	20	35
10.0	20	35
12.5	20	35
13.4	20	35
14.7	20	35
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.





Fig. Complex Ripple Noise Wave Form

Model	SNDHS200A15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V13.4A

Testing Circuitry Figure B

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	55	55
-20	40	40
0	30	30
25	25	25
40	25	25
55	25	25
70	20	25
80	20	25
95	20	20
100	20	20
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form



Model		SNDHS200A15		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+15V13.4A																																																						
1.Graph		<p>—△— Input Volt. 60V</p> <p>---□--- Input Volt. 110V</p> <p>-·-○-·- Input Volt. 160V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>15.253</td><td>15.254</td><td>15.255</td></tr> <tr><td>-20</td><td>15.281</td><td>15.281</td><td>15.282</td></tr> <tr><td>0</td><td>15.300</td><td>15.301</td><td>15.301</td></tr> <tr><td>25</td><td>15.314</td><td>15.314</td><td>15.314</td></tr> <tr><td>40</td><td>15.318</td><td>15.319</td><td>15.318</td></tr> <tr><td>55</td><td>15.321</td><td>15.321</td><td>15.321</td></tr> <tr><td>70</td><td>15.324</td><td>15.324</td><td>15.324</td></tr> <tr><td>80</td><td>15.326</td><td>15.326</td><td>15.326</td></tr> <tr><td>95</td><td>15.328</td><td>15.328</td><td>15.328</td></tr> <tr><td>100</td><td>15.331</td><td>15.331</td><td>15.331</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	-40	15.253	15.254	15.255	-20	15.281	15.281	15.282	0	15.300	15.301	15.301	25	15.314	15.314	15.314	40	15.318	15.319	15.318	55	15.321	15.321	15.321	70	15.324	15.324	15.324	80	15.326	15.326	15.326	95	15.328	15.328	15.328	100	15.331	15.331	15.331	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
-40	15.253	15.254	15.255																																																					
-20	15.281	15.281	15.282																																																					
0	15.300	15.301	15.301																																																					
25	15.314	15.314	15.314																																																					
40	15.318	15.319	15.318																																																					
55	15.321	15.321	15.321																																																					
70	15.324	15.324	15.324																																																					
80	15.326	15.326	15.326																																																					
95	15.328	15.328	15.328																																																					
100	15.331	15.331	15.331																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								



COSEL		
Model	SNDHS200A15	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+15V13.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 60 - 160V

Load Current : 0 - 13.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	60	0	15.339	±29	±0.2
Minimum Voltage	-20	60	13.4	15.281		



COSEL																								
Model	SNDHS200A15																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+15V13.4A																							
<p>1. Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 110V Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.317</td></tr> <tr><td>0.5</td><td>15.318</td></tr> <tr><td>1.0</td><td>15.318</td></tr> <tr><td>2.0</td><td>15.319</td></tr> <tr><td>3.0</td><td>15.318</td></tr> <tr><td>4.0</td><td>15.319</td></tr> <tr><td>5.0</td><td>15.319</td></tr> <tr><td>6.0</td><td>15.319</td></tr> <tr><td>7.0</td><td>15.319</td></tr> <tr><td>8.0</td><td>15.319</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.317	0.5	15.318	1.0	15.318	2.0	15.319	3.0	15.318	4.0	15.319	5.0	15.319	6.0	15.319	7.0	15.319	8.0	15.319
Time since start [H]	Output Voltage [V]																							
0.0	15.317																							
0.5	15.318																							
1.0	15.318																							
2.0	15.319																							
3.0	15.318																							
4.0	15.319																							
5.0	15.319																							
6.0	15.319																							
7.0	15.319																							
8.0	15.319																							




Model	SNDHS200A15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V13.4A		



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		52.5	3.3	55.8	3.3	18.8
100 %		52.5	3.8	56.3	1.6	9.6

[ms]





Model		SNDHS200A15																																							
Item		Minimum Input Voltage for Regulated Output Voltage																																							
Object		+15V13.4A																																							
1.Graph		Testing Circuitry Figure A																																							
<p>1. Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p> <p style="text-align: center;">Ambient Temperature [°C]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>52</td><td>54</td></tr> <tr><td>-20</td><td>51</td><td>54</td></tr> <tr><td>0</td><td>52</td><td>54</td></tr> <tr><td>25</td><td>52</td><td>55</td></tr> <tr><td>40</td><td>52</td><td>55</td></tr> <tr><td>55</td><td>52</td><td>55</td></tr> <tr><td>70</td><td>52</td><td>55</td></tr> <tr><td>80</td><td>52</td><td>55</td></tr> <tr><td>95</td><td>52</td><td>55</td></tr> <tr><td>100</td><td>52</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	52	54	-20	51	54	0	52	54	25	52	55	40	52	55	55	52	55	70	52	55	80	52	55	95	52	55	100	52	55	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-40	52	54																																							
-20	51	54																																							
0	52	54																																							
25	52	55																																							
40	52	55																																							
55	52	55																																							
70	52	55																																							
80	52	55																																							
95	52	55																																							
100	52	55																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									



<p>Model SNDHS200A15</p>		<p>Temperature 25°C</p>																																																												
<p>Item Overcurrent Protection</p>		<p>Testing Circuitry Figure A</p>																																																												
<p>Object +15V13.4A</p>																																																														
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>————— Input Volt. 60V</p> <p>————— Input Volt. 110V</p> <p>————— Input Volt. 160V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>16.71</td><td>16.82</td><td>17.12</td></tr> <tr><td>13.5</td><td>16.67</td><td>17.34</td><td>17.21</td></tr> <tr><td>12.0</td><td>16.99</td><td>17.91</td><td>17.67</td></tr> <tr><td>10.5</td><td>17.68</td><td>17.72</td><td>18.35</td></tr> <tr><td>9.0</td><td>17.88</td><td>18.82</td><td>18.86</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	14.3	16.71	16.82	17.12	13.5	16.67	17.34	17.21	12.0	16.99	17.91	17.67	10.5	17.68	17.72	18.35	9.0	17.88	18.82	18.86	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																													
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																											
14.3	16.71	16.82	17.12																																																											
13.5	16.67	17.34	17.21																																																											
12.0	16.99	17.91	17.67																																																											
10.5	17.68	17.72	18.35																																																											
9.0	17.88	18.82	18.86																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
--	-	-	-																																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> <p>Intermittent operation occurs when the output voltage is from 9V to 0V.</p>																																																														



Model		SNDHS200A15																																							
Item		Overvoltage Protection																																							
Object		+15V13.4A																																							
1.Graph		Testing Circuitry Figure A																																							
<p>—△— Input Volt. 60V ---□--- Input Volt. 160V</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>		2.Values																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>18.69</td><td>18.69</td></tr> <tr><td>-20</td><td>18.69</td><td>18.69</td></tr> <tr><td>0</td><td>18.75</td><td>18.75</td></tr> <tr><td>25</td><td>18.75</td><td>18.75</td></tr> <tr><td>40</td><td>18.75</td><td>18.75</td></tr> <tr><td>55</td><td>18.75</td><td>18.75</td></tr> <tr><td>70</td><td>18.75</td><td>18.75</td></tr> <tr><td>80</td><td>18.75</td><td>18.75</td></tr> <tr><td>95</td><td>18.75</td><td>18.75</td></tr> <tr><td>100</td><td>18.75</td><td>18.75</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 60[V]	Input Volt. 160[V]	-40	18.69	18.69	-20	18.69	18.69	0	18.75	18.75	25	18.75	18.75	40	18.75	18.75	55	18.75	18.75	70	18.75	18.75	80	18.75	18.75	95	18.75	18.75	100	18.75	18.75	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 60[V]	Input Volt. 160[V]																																							
-40	18.69	18.69																																							
-20	18.69	18.69																																							
0	18.75	18.75																																							
25	18.75	18.75																																							
40	18.75	18.75																																							
55	18.75	18.75																																							
70	18.75	18.75																																							
80	18.75	18.75																																							
95	18.75	18.75																																							
100	18.75	18.75																																							
--	-	-																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)