

TEST DATA OF SNDHS250B12

Regulated DC Power Supply
June 18, 2011

Approved by: Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by: Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1
 2.Input Current (by Load Current) 2
 3.Input Power (by Load Current) 3
 4.Efficiency (by Input Voltage) 4
 5.Efficiency (by Load Current) 5
 6.Line Regulation 6
 7.Load Regulation 7
 8.Dynamic Load Response 8
 9.Ripple Voltage (by Load Current) 9
 10.Ripple-Noise 10
 11.Ripple Voltage (by Ambient Temperature) 11
 12.Ambient Temperature Drift 12
 13.Output Voltage Accuracy 13
 14.Time Lapse Drift 14
 15.Rise and Fall Time 15
 16.Minimum Input Voltage for Regulated Output Voltage 16
 17.Overcurrent Protection 17
 18.Overvoltage Protection 18
 19.Figure of Testing Circuitry 19

(Final Page 19)



Model		SNDHS250B12		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			2.Values																																																																																	
<p>Legend: —△— Load 100% - - -□- - Load 50% - · -○- - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.004</td><td>0.004</td><td>0.000</td></tr> <tr><td>100</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>170</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>180</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>190</td><td>0.008</td><td>0.763</td><td>1.542</td></tr> <tr><td>195</td><td>0.008</td><td>0.740</td><td>1.504</td></tr> <tr><td>200</td><td>0.008</td><td>0.718</td><td>1.463</td></tr> <tr><td>250</td><td>0.008</td><td>0.571</td><td>1.159</td></tr> <tr><td>280</td><td>0.008</td><td>0.512</td><td>1.037</td></tr> <tr><td>300</td><td>0.008</td><td>0.479</td><td>0.967</td></tr> <tr><td>350</td><td>0.008</td><td>0.414</td><td>0.831</td></tr> <tr><td>400</td><td>0.009</td><td>0.366</td><td>0.730</td></tr> <tr><td>410</td><td>0.009</td><td>0.357</td><td>0.713</td></tr> <tr><td>420</td><td>0.009</td><td>0.350</td><td>0.697</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.004	0.004	0.000	100	0.002	0.002	0.002	150	0.000	0.000	0.000	170	0.000	0.000	0.000	180	0.000	0.000	0.000	190	0.008	0.763	1.542	195	0.008	0.740	1.504	200	0.008	0.718	1.463	250	0.008	0.571	1.159	280	0.008	0.512	1.037	300	0.008	0.479	0.967	350	0.008	0.414	0.831	400	0.009	0.366	0.730	410	0.009	0.357	0.713	420	0.009	0.350	0.697	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0	0.000	0.000	0.000																																																																																	
50	0.004	0.004	0.000																																																																																	
100	0.002	0.002	0.002																																																																																	
150	0.000	0.000	0.000																																																																																	
170	0.000	0.000	0.000																																																																																	
180	0.000	0.000	0.000																																																																																	
190	0.008	0.763	1.542																																																																																	
195	0.008	0.740	1.504																																																																																	
200	0.008	0.718	1.463																																																																																	
250	0.008	0.571	1.159																																																																																	
280	0.008	0.512	1.037																																																																																	
300	0.008	0.479	0.967																																																																																	
350	0.008	0.414	0.831																																																																																	
400	0.009	0.366	0.730																																																																																	
410	0.009	0.357	0.713																																																																																	
420	0.009	0.350	0.697																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		SNDHS250B12		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>- - -□- - Input Volt. 280V</p> <p>- · -○- · - Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.008</td> <td>0.008</td> <td>0.009</td> </tr> <tr> <td>4.0</td> <td>0.286</td> <td>0.204</td> <td>0.146</td> </tr> <tr> <td>8.5</td> <td>0.584</td> <td>0.416</td> <td>0.299</td> </tr> <tr> <td>12.5</td> <td>0.856</td> <td>0.609</td> <td>0.433</td> </tr> <tr> <td>17.0</td> <td>1.173</td> <td>0.832</td> <td>0.588</td> </tr> <tr> <td>21.0</td> <td>1.465</td> <td>1.036</td> <td>0.730</td> </tr> <tr> <td>23.1</td> <td>1.622</td> <td>1.146</td> <td>0.806</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	0.008	0.008	0.009	4.0	0.286	0.204	0.146	8.5	0.584	0.416	0.299	12.5	0.856	0.609	0.433	17.0	1.173	0.832	0.588	21.0	1.465	1.036	0.730	23.1	1.622	1.146	0.806	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	0.008	0.008	0.009																																																					
4.0	0.286	0.204	0.146																																																					
8.5	0.584	0.416	0.299																																																					
12.5	0.856	0.609	0.433																																																					
17.0	1.173	0.832	0.588																																																					
21.0	1.465	1.036	0.730																																																					
23.1	1.622	1.146	0.806																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDHS250B12		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>---□--- Input Volt. 280V</p> <p>-·-○-·- Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.6</td><td>2.2</td><td>3.5</td></tr> <tr><td>4.0</td><td>57.2</td><td>57.1</td><td>58.4</td></tr> <tr><td>8.5</td><td>116.9</td><td>116.7</td><td>119.8</td></tr> <tr><td>12.5</td><td>171.1</td><td>170.6</td><td>173.4</td></tr> <tr><td>17.0</td><td>234.5</td><td>232.9</td><td>235.4</td></tr> <tr><td>21.0</td><td>292.8</td><td>290.4</td><td>292.3</td></tr> <tr><td>23.1</td><td>324.2</td><td>320.9</td><td>322.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	1.6	2.2	3.5	4.0	57.2	57.1	58.4	8.5	116.9	116.7	119.8	12.5	171.1	170.6	173.4	17.0	234.5	232.9	235.4	21.0	292.8	290.4	292.3	23.1	324.2	320.9	322.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	1.6	2.2	3.5																																																					
4.0	57.2	57.1	58.4																																																					
8.5	116.9	116.7	119.8																																																					
12.5	171.1	170.6	173.4																																																					
17.0	234.5	232.9	235.4																																																					
21.0	292.8	290.4	292.3																																																					
23.1	324.2	320.9	322.6																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDHS250B12																																	
Item		Efficiency (by Input Voltage)																																	
Object		Temperature 25°C Testing Circuitry Figure A																																	
1.Graph		2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td> <td>89.3</td> <td>87.8</td> </tr> <tr> <td>200</td> <td>89.6</td> <td>88.0</td> </tr> <tr> <td>240</td> <td>90.4</td> <td>88.8</td> </tr> <tr> <td>280</td> <td>90.0</td> <td>88.8</td> </tr> <tr> <td>320</td> <td>89.5</td> <td>88.8</td> </tr> <tr> <td>360</td> <td>88.8</td> <td>88.6</td> </tr> <tr> <td>400</td> <td>88.2</td> <td>88.3</td> </tr> <tr> <td>420</td> <td>87.8</td> <td>88.1</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	89.3	87.8	200	89.6	88.0	240	90.4	88.8	280	90.0	88.8	320	89.5	88.8	360	88.8	88.6	400	88.2	88.3	420	87.8	88.1	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
195	89.3	87.8																																	
200	89.6	88.0																																	
240	90.4	88.8																																	
280	90.0	88.8																																	
320	89.5	88.8																																	
360	88.8	88.6																																	
400	88.2	88.3																																	
420	87.8	88.1																																	
--	-	-																																	



Model		SNDHS250B12		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			2.Values																																																					
<p> —△— Input Volt. 200V - - □ - - Input Volt. 280V - · ○ - · Input Volt. 400V </p> <p>Efficiency [%]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.0</td> <td>86.2</td> <td>86.4</td> <td>84.5</td> </tr> <tr> <td>8.5</td> <td>89.4</td> <td>89.6</td> <td>87.3</td> </tr> <tr> <td>12.5</td> <td>89.7</td> <td>89.9</td> <td>88.5</td> </tr> <tr> <td>17.0</td> <td>89.0</td> <td>89.6</td> <td>88.6</td> </tr> <tr> <td>21.0</td> <td>88.1</td> <td>88.8</td> <td>88.3</td> </tr> <tr> <td>23.1</td> <td>87.5</td> <td>88.4</td> <td>88.0</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	-	-	-	4.0	86.2	86.4	84.5	8.5	89.4	89.6	87.3	12.5	89.7	89.9	88.5	17.0	89.0	89.6	88.6	21.0	88.1	88.8	88.3	23.1	87.5	88.4	88.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	-	-	-																																																					
4.0	86.2	86.4	84.5																																																					
8.5	89.4	89.6	87.3																																																					
12.5	89.7	89.9	88.5																																																					
17.0	89.0	89.6	88.6																																																					
21.0	88.1	88.8	88.3																																																					
23.1	87.5	88.4	88.0																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



<p>Model SNDHS250B12</p>		<p>Temperature 25°C</p>																																	
<p>Item Line Regulation</p>		<p>Testing Circuitry Figure A</p>																																	
<p>Object +12V21A</p>																																			
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>12.285</td><td>12.283</td></tr> <tr><td>200</td><td>12.285</td><td>12.284</td></tr> <tr><td>240</td><td>12.285</td><td>12.284</td></tr> <tr><td>280</td><td>12.285</td><td>12.285</td></tr> <tr><td>320</td><td>12.285</td><td>12.286</td></tr> <tr><td>360</td><td>12.285</td><td>12.286</td></tr> <tr><td>400</td><td>12.285</td><td>12.288</td></tr> <tr><td>420</td><td>12.286</td><td>12.288</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	12.285	12.283	200	12.285	12.284	240	12.285	12.284	280	12.285	12.285	320	12.285	12.286	360	12.285	12.286	400	12.285	12.288	420	12.286	12.288	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
195	12.285	12.283																																	
200	12.285	12.284																																	
240	12.285	12.284																																	
280	12.285	12.285																																	
320	12.285	12.286																																	
360	12.285	12.286																																	
400	12.285	12.288																																	
420	12.286	12.288																																	
--	-	-																																	



Model		SNDHS250B12		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+12V21A																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>---□--- Input Volt. 280V</p> <p>-·-○-·- Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.292</td><td>12.293</td><td>12.294</td></tr> <tr><td>4.0</td><td>12.291</td><td>12.292</td><td>12.292</td></tr> <tr><td>8.5</td><td>12.290</td><td>12.290</td><td>12.291</td></tr> <tr><td>12.5</td><td>12.289</td><td>12.290</td><td>12.290</td></tr> <tr><td>17.0</td><td>12.288</td><td>12.288</td><td>12.289</td></tr> <tr><td>21.0</td><td>12.287</td><td>12.288</td><td>12.288</td></tr> <tr><td>23.1</td><td>12.287</td><td>12.287</td><td>12.288</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	12.292	12.293	12.294	4.0	12.291	12.292	12.292	8.5	12.290	12.290	12.291	12.5	12.289	12.290	12.290	17.0	12.288	12.288	12.289	21.0	12.287	12.288	12.288	23.1	12.287	12.287	12.288	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	12.292	12.293	12.294																																																					
4.0	12.291	12.292	12.292																																																					
8.5	12.290	12.290	12.291																																																					
12.5	12.289	12.290	12.290																																																					
17.0	12.288	12.288	12.289																																																					
21.0	12.287	12.288	12.288																																																					
23.1	12.287	12.287	12.288																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDHS250B12	
Item		Dynamic Load Response	
Object		+12V21A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 280 V
Cycle 1000 ms




Min. Load (0A) ←→
Load 100% (21A)

0.5 V/div




400us/div




40ms/div

Min. Load (0A) ←→
Load 50% (10.5A)

0.5 V/div




400us/div




40ms/div

Load 10% (2.1A) ←→
Load 100% (21A)

0.5 V/div



400us/div



40ms/div



Model		SNDHS250B12		Temperature 25°C Testing Circuitry Figure B																																						
Item		Ripple Voltage (by Load Current)																																								
Object		+12V21A																																								
1.Graph			2.Values																																							
<p>—△— Input Volt. 200V - - ○ - - Input Volt. 400V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>4.0</td><td>20</td><td>30</td></tr> <tr><td>8.5</td><td>20</td><td>30</td></tr> <tr><td>12.5</td><td>20</td><td>30</td></tr> <tr><td>17.0</td><td>20</td><td>30</td></tr> <tr><td>21.0</td><td>20</td><td>30</td></tr> <tr><td>23.1</td><td>20</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.0	5	5	4.0	20	30	8.5	20	30	12.5	20	30	17.0	20	30	21.0	20	30	23.1	20	30	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																									
	Input Volt. 200 [V]	Input Volt. 400 [V]																																								
0.0	5	5																																								
4.0	20	30																																								
8.5	20	30																																								
12.5	20	30																																								
17.0	20	30																																								
21.0	20	30																																								
23.1	20	30																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
--	-	-																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																										
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																										

<p>Model SNDHS250B12</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +12V21A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 200V -·-○-·- Input Volt. 400V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>4.0</td><td>30</td><td>35</td></tr> <tr><td>8.5</td><td>30</td><td>40</td></tr> <tr><td>12.5</td><td>25</td><td>40</td></tr> <tr><td>17.0</td><td>30</td><td>40</td></tr> <tr><td>21.0</td><td>25</td><td>40</td></tr> <tr><td>23.1</td><td>25</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.0	20	20	4.0	30	35	8.5	30	40	12.5	25	40	17.0	30	40	21.0	25	40	23.1	25	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0.0	20	20																																						
4.0	30	35																																						
8.5	30	40																																						
12.5	25	40																																						
17.0	30	40																																						
21.0	25	40																																						
23.1	25	40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								



COSEL																																								
Model	DHS250B12																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+12V21A																																							
<p>1.Graph</p> <p style="text-align: center;">Input Volt. 280V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>55</td><td>55</td></tr> <tr><td>-20</td><td>35</td><td>40</td></tr> <tr><td>0</td><td>30</td><td>30</td></tr> <tr><td>25</td><td>25</td><td>25</td></tr> <tr><td>40</td><td>25</td><td>25</td></tr> <tr><td>55</td><td>25</td><td>25</td></tr> <tr><td>70</td><td>25</td><td>25</td></tr> <tr><td>85</td><td>25</td><td>25</td></tr> <tr><td>95</td><td>25</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-40	55	55	-20	35	40	0	30	30	25	25	25	40	25	25	55	25	25	70	25	25	85	25	25	95	25	25	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-40	55	55																																						
-20	35	40																																						
0	30	30																																						
25	25	25																																						
40	25	25																																						
55	25	25																																						
70	25	25																																						
85	25	25																																						
95	25	25																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model		SNDHS250B12		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+12V21A																																																						
1.Graph		<p> —△— Input Volt. 200V - - - □ - - - Input Volt. 280V · · · ○ · · · Input Volt. 400V </p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>12.239</td><td>12.241</td><td>12.242</td></tr> <tr><td>-20</td><td>12.256</td><td>12.257</td><td>12.258</td></tr> <tr><td>0</td><td>12.269</td><td>12.270</td><td>12.271</td></tr> <tr><td>25</td><td>12.285</td><td>12.285</td><td>12.285</td></tr> <tr><td>40</td><td>12.287</td><td>12.287</td><td>12.287</td></tr> <tr><td>55</td><td>12.291</td><td>12.292</td><td>12.291</td></tr> <tr><td>70</td><td>12.286</td><td>12.286</td><td>12.287</td></tr> <tr><td>85</td><td>12.286</td><td>12.286</td><td>12.287</td></tr> <tr><td>95</td><td>12.289</td><td>12.289</td><td>12.290</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-40	12.239	12.241	12.242	-20	12.256	12.257	12.258	0	12.269	12.270	12.271	25	12.285	12.285	12.285	40	12.287	12.287	12.287	55	12.291	12.292	12.291	70	12.286	12.286	12.287	85	12.286	12.286	12.287	95	12.289	12.289	12.290	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
-40	12.239	12.241	12.242																																																					
-20	12.256	12.257	12.258																																																					
0	12.269	12.270	12.271																																																					
25	12.285	12.285	12.285																																																					
40	12.287	12.287	12.287																																																					
55	12.291	12.292	12.291																																																					
70	12.286	12.286	12.287																																																					
85	12.286	12.286	12.287																																																					
95	12.289	12.289	12.290																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								



COSEL		
Model	SNDHS250B12	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V21A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 21A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	200	0	12.297	±21	±0.2
Minimum Voltage	-20	200	21	12.256		




COSEL																									
Model	SNDHS250B12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V21A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 280V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.285</td></tr> <tr><td>0.5</td><td>12.291</td></tr> <tr><td>1.0</td><td>12.291</td></tr> <tr><td>2.0</td><td>12.291</td></tr> <tr><td>3.0</td><td>12.291</td></tr> <tr><td>4.0</td><td>12.291</td></tr> <tr><td>5.0</td><td>12.291</td></tr> <tr><td>6.0</td><td>12.291</td></tr> <tr><td>7.0</td><td>12.291</td></tr> <tr><td>8.0</td><td>12.291</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.285	0.5	12.291	1.0	12.291	2.0	12.291	3.0	12.291	4.0	12.291	5.0	12.291	6.0	12.291	7.0	12.291	8.0	12.291
Time since start [H]	Output Voltage [V]																								
0.0	12.285																								
0.5	12.291																								
1.0	12.291																								
2.0	12.291																								
3.0	12.291																								
4.0	12.291																								
5.0	12.291																								
6.0	12.291																								
7.0	12.291																								
8.0	12.291																								



Model	SNDHS250B12	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V21A		

1. Graph


Input Volt. 280 V



2. Values

[ms]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	53.0	2.5	55.5	1.0	9.4
100 %	53.0	2.3	55.3	0.5	4.9





COSEL																																								
Model	SNDHS250B12																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V21A																																							
1. Graph		2. Values																																						
<div style="text-align: right; margin-bottom: 10px;"> ---□--- Load 50% —△— Load 100% </div>		<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>171</td><td>177</td></tr> <tr><td>-20</td><td>172</td><td>178</td></tr> <tr><td>0</td><td>172</td><td>180</td></tr> <tr><td>25</td><td>171</td><td>179</td></tr> <tr><td>40</td><td>171</td><td>179</td></tr> <tr><td>55</td><td>171</td><td>180</td></tr> <tr><td>70</td><td>172</td><td>180</td></tr> <tr><td>85</td><td>172</td><td>181</td></tr> <tr><td>95</td><td>172</td><td>181</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	171	177	-20	172	178	0	172	180	25	171	179	40	171	179	55	171	180	70	172	180	85	172	181	95	172	181	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	171	177																																						
-20	172	178																																						
0	172	180																																						
25	171	179																																						
40	171	179																																						
55	171	180																																						
70	172	180																																						
85	172	181																																						
95	172	181																																						
--	-	-																																						
--	-	-																																						
Note: Slanted line shows the range of the rated ambient temperature.																																								



<p>Model SNDHS250B12</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																							
<p>Item Overcurrent Protection</p>																																																									
<p>Object +12V21A</p>																																																									
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>————— Input Volt. 200V</p> <p>————— Input Volt. 280V</p> <p>————— Input Volt. 400V</p> </div> <div> </div> </div> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 6V to 0V.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr> <td>11.4</td> <td>25.52</td> <td>25.90</td> <td>25.80</td> </tr> <tr> <td>10.8</td> <td>25.72</td> <td>25.95</td> <td>26.15</td> </tr> <tr> <td>9.6</td> <td>26.14</td> <td>26.34</td> <td>26.47</td> </tr> <tr> <td>8.4</td> <td>26.39</td> <td>26.71</td> <td>26.69</td> </tr> <tr> <td>7.2</td> <td>26.73</td> <td>27.09</td> <td>27.02</td> </tr> <tr> <td>6.0</td> <td>27.28</td> <td>27.47</td> <td>27.37</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	11.4	25.52	25.90	25.80	10.8	25.72	25.95	26.15	9.6	26.14	26.34	26.47	8.4	26.39	26.71	26.69	7.2	26.73	27.09	27.02	6.0	27.28	27.47	27.37	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																						
11.4	25.52	25.90	25.80																																																						
10.8	25.72	25.95	26.15																																																						
9.6	26.14	26.34	26.47																																																						
8.4	26.39	26.71	26.69																																																						
7.2	26.73	27.09	27.02																																																						
6.0	27.28	27.47	27.37																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						
--	-	-	-																																																						



Model		SNDHS250B12																																							
Item		Overvoltage Protection																																							
Object		+12V21A																																							
1.Graph		Testing Circuitry Figure A																																							
<p>—△— Input Volt. 200V ---□--- Input Volt. 400V</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>		2.Values																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>14.88</td><td>14.88</td></tr> <tr><td>-20</td><td>14.88</td><td>14.88</td></tr> <tr><td>0</td><td>14.88</td><td>14.88</td></tr> <tr><td>25</td><td>14.94</td><td>14.94</td></tr> <tr><td>40</td><td>14.94</td><td>14.94</td></tr> <tr><td>55</td><td>14.94</td><td>14.94</td></tr> <tr><td>70</td><td>14.94</td><td>14.94</td></tr> <tr><td>85</td><td>14.94</td><td>14.94</td></tr> <tr><td>95</td><td>14.93</td><td>14.93</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	14.88	14.88	-20	14.88	14.88	0	14.88	14.88	25	14.94	14.94	40	14.94	14.94	55	14.94	14.94	70	14.94	14.94	85	14.94	14.94	95	14.93	14.93	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 200[V]	Input Volt. 400[V]																																							
-40	14.88	14.88																																							
-20	14.88	14.88																																							
0	14.88	14.88																																							
25	14.94	14.94																																							
40	14.94	14.94																																							
55	14.94	14.94																																							
70	14.94	14.94																																							
85	14.94	14.94																																							
95	14.93	14.93																																							
--	-	-																																							
--	-	-																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)