

TEST DATA OF SNDHS250B28

Regulated DC Power Supply
June 18, 2011

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai
Tadashi Arai Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1

2.Input Current (by Load Current) 2

3.Input Power (by Load Current) 3

4.Efficiency (by Input Voltage) 4

5.Efficiency (by Load Current) 5

6.Line Regulation 6

7.Load Regulation 7

8.Dynamic Load Response 8

9.Ripple Voltage (by Load Current) 9

10.Ripple-Noise 10

11.Ripple Voltage (by Ambient Temperature) 11

12.Ambient Temperature Drift 12

13.Output Voltage Accuracy 13

14.Time Lapse Drift 14

15.Rise and Fall Time 15

16.Minimum Input Voltage for Regulated Output Voltage 16

17.Overcurrent Protection 17

18.Overvoltage Protection 18

19.Figure of Testing Circuitry 19

(Final Page 19)



Model		SNDHS250B28		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object																																																																																				
1.Graph			2.Values																																																																																	
<p>Legend: —△— Load 100% - - -□- - - Load 50% - · -○- · - - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>50</td><td>0.004</td><td>0.004</td><td>0.000</td></tr> <tr><td>100</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>150</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>170</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>180</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>190</td><td>0.006</td><td>0.740</td><td>1.481</td></tr> <tr><td>195</td><td>0.006</td><td>0.718</td><td>1.440</td></tr> <tr><td>200</td><td>0.006</td><td>0.698</td><td>1.401</td></tr> <tr><td>250</td><td>0.006</td><td>0.557</td><td>1.113</td></tr> <tr><td>280</td><td>0.006</td><td>0.501</td><td>0.998</td></tr> <tr><td>300</td><td>0.006</td><td>0.470</td><td>0.933</td></tr> <tr><td>350</td><td>0.006</td><td>0.408</td><td>0.806</td></tr> <tr><td>400</td><td>0.006</td><td>0.362</td><td>0.710</td></tr> <tr><td>410</td><td>0.006</td><td>0.354</td><td>0.694</td></tr> <tr><td>420</td><td>0.006</td><td>0.346</td><td>0.679</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	50	0.004	0.004	0.000	100	0.002	0.002	0.002	150	0.000	0.000	0.000	170	0.000	0.000	0.000	180	0.000	0.000	0.000	190	0.006	0.740	1.481	195	0.006	0.718	1.440	200	0.006	0.698	1.401	250	0.006	0.557	1.113	280	0.006	0.501	0.998	300	0.006	0.470	0.933	350	0.006	0.408	0.806	400	0.006	0.362	0.710	410	0.006	0.354	0.694	420	0.006	0.346	0.679	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0	0.000	0.000	0.000																																																																																	
50	0.004	0.004	0.000																																																																																	
100	0.002	0.002	0.002																																																																																	
150	0.000	0.000	0.000																																																																																	
170	0.000	0.000	0.000																																																																																	
180	0.000	0.000	0.000																																																																																	
190	0.006	0.740	1.481																																																																																	
195	0.006	0.718	1.440																																																																																	
200	0.006	0.698	1.401																																																																																	
250	0.006	0.557	1.113																																																																																	
280	0.006	0.501	0.998																																																																																	
300	0.006	0.470	0.933																																																																																	
350	0.006	0.408	0.806																																																																																	
400	0.006	0.362	0.710																																																																																	
410	0.006	0.354	0.694																																																																																	
420	0.006	0.346	0.679																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		SNDHS250B28		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>- -□- - Input Volt. 280V</p> <p>- -○- - Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.005</td><td>0.006</td><td>0.006</td></tr> <tr><td>2.0</td><td>0.323</td><td>0.229</td><td>0.165</td></tr> <tr><td>3.5</td><td>0.548</td><td>0.394</td><td>0.286</td></tr> <tr><td>5.5</td><td>0.853</td><td>0.610</td><td>0.439</td></tr> <tr><td>7.0</td><td>1.086</td><td>0.775</td><td>0.554</td></tr> <tr><td>9.0</td><td>1.403</td><td>0.998</td><td>0.710</td></tr> <tr><td>9.9</td><td>1.550</td><td>1.100</td><td>0.781</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	0.005	0.006	0.006	2.0	0.323	0.229	0.165	3.5	0.548	0.394	0.286	5.5	0.853	0.610	0.439	7.0	1.086	0.775	0.554	9.0	1.403	0.998	0.710	9.9	1.550	1.100	0.781	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Input Current [A]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	0.005	0.006	0.006																																																					
2.0	0.323	0.229	0.165																																																					
3.5	0.548	0.394	0.286																																																					
5.5	0.853	0.610	0.439																																																					
7.0	1.086	0.775	0.554																																																					
9.0	1.403	0.998	0.710																																																					
9.9	1.550	1.100	0.781																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SNDHS250B28		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>---□--- Input Volt. 280V</p> <p>-·-○-·- Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.1</td><td>1.6</td><td>2.5</td></tr> <tr><td>2.0</td><td>64.6</td><td>64.1</td><td>66.1</td></tr> <tr><td>3.5</td><td>109.7</td><td>110.4</td><td>114.6</td></tr> <tr><td>5.5</td><td>170.5</td><td>171.0</td><td>175.6</td></tr> <tr><td>7.0</td><td>217.2</td><td>217.1</td><td>221.8</td></tr> <tr><td>9.0</td><td>280.6</td><td>279.6</td><td>284.2</td></tr> <tr><td>9.9</td><td>309.8</td><td>308.2</td><td>312.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	1.1	1.6	2.5	2.0	64.6	64.1	66.1	3.5	109.7	110.4	114.6	5.5	170.5	171.0	175.6	7.0	217.2	217.1	221.8	9.0	280.6	279.6	284.2	9.9	309.8	308.2	312.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	1.1	1.6	2.5																																																					
2.0	64.6	64.1	66.1																																																					
3.5	109.7	110.4	114.6																																																					
5.5	170.5	171.0	175.6																																																					
7.0	217.2	217.1	221.8																																																					
9.0	280.6	279.6	284.2																																																					
9.9	309.8	308.2	312.7																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDHS250B28		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object																																					
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>195</td> <td>89.7</td> <td>89.5</td> </tr> <tr> <td>200</td> <td>90.0</td> <td>89.8</td> </tr> <tr> <td>240</td> <td>90.4</td> <td>90.5</td> </tr> <tr> <td>280</td> <td>89.7</td> <td>90.1</td> </tr> <tr> <td>320</td> <td>88.8</td> <td>89.8</td> </tr> <tr> <td>360</td> <td>87.9</td> <td>89.2</td> </tr> <tr> <td>400</td> <td>86.9</td> <td>88.7</td> </tr> <tr> <td>420</td> <td>86.5</td> <td>88.4</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	195	89.7	89.5	200	90.0	89.8	240	90.4	90.5	280	89.7	90.1	320	88.8	89.8	360	87.9	89.2	400	86.9	88.7	420	86.5	88.4	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
195	89.7	89.5																																			
200	90.0	89.8																																			
240	90.4	90.5																																			
280	89.7	90.1																																			
320	88.8	89.8																																			
360	87.9	89.2																																			
400	86.9	88.7																																			
420	86.5	88.4																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		SNDHS250B28		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>- -□- - Input Volt. 280V</p> <p>- ·○- · Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.0</td><td>86.7</td><td>87.4</td><td>84.8</td></tr> <tr><td>3.5</td><td>89.4</td><td>88.8</td><td>85.5</td></tr> <tr><td>5.5</td><td>90.3</td><td>90.1</td><td>87.7</td></tr> <tr><td>7.0</td><td>90.3</td><td>90.3</td><td>88.4</td></tr> <tr><td>9.0</td><td>89.8</td><td>90.1</td><td>88.7</td></tr> <tr><td>9.9</td><td>89.5</td><td>89.9</td><td>88.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	-	-	-	2.0	86.7	87.4	84.8	3.5	89.4	88.8	85.5	5.5	90.3	90.1	87.7	7.0	90.3	90.3	88.4	9.0	89.8	90.1	88.7	9.9	89.5	89.9	88.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	-	-	-																																																					
2.0	86.7	87.4	84.8																																																					
3.5	89.4	88.8	85.5																																																					
5.5	90.3	90.1	87.7																																																					
7.0	90.3	90.3	88.4																																																					
9.0	89.8	90.1	88.7																																																					
9.9	89.5	89.9	88.7																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SNDHS250B28		Temperature 25°C																																	
Item		Line Regulation		Testing Circuitry Figure A																																	
Object		+28V9A																																			
1. Graph				2. Values																																	
<p>---□--- Load 50% —△— Load 100%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>195</td><td>28.015</td><td>28.013</td></tr> <tr><td>200</td><td>28.015</td><td>28.013</td></tr> <tr><td>240</td><td>28.014</td><td>28.013</td></tr> <tr><td>280</td><td>28.014</td><td>28.013</td></tr> <tr><td>320</td><td>28.013</td><td>28.014</td></tr> <tr><td>360</td><td>28.013</td><td>28.014</td></tr> <tr><td>400</td><td>28.013</td><td>28.015</td></tr> <tr><td>420</td><td>28.013</td><td>28.015</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	195	28.015	28.013	200	28.015	28.013	240	28.014	28.013	280	28.014	28.013	320	28.013	28.014	360	28.013	28.014	400	28.013	28.015	420	28.013	28.015	--	-	-
Input Voltage [V]	Output Voltage [V]																																				
	Load 50%	Load 100%																																			
195	28.015	28.013																																			
200	28.015	28.013																																			
240	28.014	28.013																																			
280	28.014	28.013																																			
320	28.013	28.014																																			
360	28.013	28.014																																			
400	28.013	28.015																																			
420	28.013	28.015																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		SNDHS250B28		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+28V9A																																																						
1.Graph		—△— Input Volt. 200V - - - □ - - - Input Volt. 280V - · - ○ - · - - Input Volt. 400V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>27.999</td><td>28.001</td><td>28.004</td></tr> <tr><td>2.0</td><td>27.999</td><td>28.002</td><td>28.004</td></tr> <tr><td>3.5</td><td>27.999</td><td>28.002</td><td>28.004</td></tr> <tr><td>5.5</td><td>28.000</td><td>28.002</td><td>28.005</td></tr> <tr><td>7.0</td><td>28.000</td><td>28.003</td><td>28.005</td></tr> <tr><td>9.0</td><td>28.001</td><td>28.003</td><td>28.005</td></tr> <tr><td>9.9</td><td>28.001</td><td>28.004</td><td>28.006</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	0.0	27.999	28.001	28.004	2.0	27.999	28.002	28.004	3.5	27.999	28.002	28.004	5.5	28.000	28.002	28.005	7.0	28.000	28.003	28.005	9.0	28.001	28.003	28.005	9.9	28.001	28.004	28.006	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
0.0	27.999	28.001	28.004																																																					
2.0	27.999	28.002	28.004																																																					
3.5	27.999	28.002	28.004																																																					
5.5	28.000	28.002	28.005																																																					
7.0	28.000	28.003	28.005																																																					
9.0	28.001	28.003	28.005																																																					
9.9	28.001	28.004	28.006																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDHS250B28	
Item		Dynamic Load Response	
Object		+28V9A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 280 V
 Cycle 1000 ms




Min. Load (0A) \longleftrightarrow
 Load 100% (9A)

0.5 V/div




1ms/div




40ms/div

Min. Load (0A) \longleftrightarrow
 Load 50% (4.5A)

0.5 V/div




1ms/div




40ms/div

Load 10% (0.9A) \longleftrightarrow
 Load 100% (9A)

0.5 V/div



1ms/div



40ms/div



Model		SNDHS250B28		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		+28V9A																																									
1.Graph				2.Values																																							
<p> </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>2.0</td><td>25</td><td>30</td></tr> <tr><td>3.5</td><td>25</td><td>40</td></tr> <tr><td>5.5</td><td>25</td><td>40</td></tr> <tr><td>7.0</td><td>25</td><td>40</td></tr> <tr><td>9.0</td><td>25</td><td>40</td></tr> <tr><td>9.9</td><td>25</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.0	5	5	2.0	25	30	3.5	25	40	5.5	25	40	7.0	25	40	9.0	25	40	9.9	25	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 200 [V]	Input Volt. 400 [V]																																									
0.0	5	5																																									
2.0	25	30																																									
3.5	25	40																																									
5.5	25	40																																									
7.0	25	40																																									
9.0	25	40																																									
9.9	25	40																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																											



<p>Model SNDHS250B28</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +28V9A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 200V - -○- - Input Volt. 400V</p> </div> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 200 [V]</th> <th>Input Volt. 400 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>2.0</td><td>30</td><td>40</td></tr> <tr><td>3.5</td><td>35</td><td>45</td></tr> <tr><td>5.5</td><td>35</td><td>50</td></tr> <tr><td>7.0</td><td>35</td><td>50</td></tr> <tr><td>9.0</td><td>30</td><td>50</td></tr> <tr><td>9.9</td><td>35</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 200 [V]	Input Volt. 400 [V]	0.0	15	20	2.0	30	40	3.5	35	45	5.5	35	50	7.0	35	50	9.0	30	50	9.9	35	50	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 200 [V]	Input Volt. 400 [V]																																						
0.0	15	20																																						
2.0	30	40																																						
3.5	35	45																																						
5.5	35	50																																						
7.0	35	50																																						
9.0	30	50																																						
9.9	35	50																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p style="text-align: center;">Ripple Noise[mVp-p]</p> <p style="text-align: center;">Fig.Complex Ripple Noise Wave Form</p>																																								



Model		SNDHS250B28		Testing Circuitry Figure B																																						
Item		Ripple Voltage (by Ambient Temp.)																																								
Object		+28V9A																																								
1.Graph			2.Values																																							
<p style="text-align: center;">Input Volt. 280V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>80</td><td>80</td></tr> <tr><td>-20</td><td>60</td><td>60</td></tr> <tr><td>0</td><td>40</td><td>40</td></tr> <tr><td>25</td><td>30</td><td>30</td></tr> <tr><td>40</td><td>30</td><td>30</td></tr> <tr><td>55</td><td>30</td><td>30</td></tr> <tr><td>70</td><td>30</td><td>30</td></tr> <tr><td>85</td><td>30</td><td>30</td></tr> <tr><td>95</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-40	80	80	-20	60	60	0	40	40	25	30	30	40	30	30	55	30	30	70	30	30	85	30	30	95	30	30	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																									
	Load 50%	Load 100%																																								
-40	80	80																																								
-20	60	60																																								
0	40	40																																								
25	30	30																																								
40	30	30																																								
55	30	30																																								
70	30	30																																								
85	30	30																																								
95	30	30																																								
--	-	-																																								
--	-	-																																								
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																										



Model		SNDHS250B28		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+28V9A																																																						
1.Graph		<p>—△— Input Volt. 200V</p> <p>---□--- Input Volt. 280V</p> <p>-·-○-·- Input Volt. 400V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>27.933</td><td>27.935</td><td>27.939</td></tr> <tr><td>-20</td><td>27.978</td><td>27.979</td><td>27.982</td></tr> <tr><td>0</td><td>28.018</td><td>28.019</td><td>28.021</td></tr> <tr><td>25</td><td>28.046</td><td>28.046</td><td>28.048</td></tr> <tr><td>40</td><td>28.054</td><td>28.054</td><td>28.055</td></tr> <tr><td>55</td><td>28.055</td><td>28.055</td><td>28.055</td></tr> <tr><td>70</td><td>28.051</td><td>28.051</td><td>28.051</td></tr> <tr><td>85</td><td>28.051</td><td>28.052</td><td>28.053</td></tr> <tr><td>95</td><td>28.047</td><td>28.048</td><td>28.050</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	-40	27.933	27.935	27.939	-20	27.978	27.979	27.982	0	28.018	28.019	28.021	25	28.046	28.046	28.048	40	28.054	28.054	28.055	55	28.055	28.055	28.055	70	28.051	28.051	28.051	85	28.051	28.052	28.053	95	28.047	28.048	28.050	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																					
-40	27.933	27.935	27.939																																																					
-20	27.978	27.979	27.982																																																					
0	28.018	28.019	28.021																																																					
25	28.046	28.046	28.048																																																					
40	28.054	28.054	28.055																																																					
55	28.055	28.055	28.055																																																					
70	28.051	28.051	28.051																																																					
85	28.051	28.052	28.053																																																					
95	28.047	28.048	28.050																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature.																																																								



COSEL		Testing Circuitry Figure A
Model	SNDHS250B28	
Item	Output Voltage Accuracy	
Object	+28V9A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 200 - 400V

Load Current : 0 - 9A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	400	9	28.055	±39	±0.1
Minimum Voltage	-20	200	0	27.977		




COSEL																									
Model	SNDHS250B28	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+28V9A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 280V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>28.006</td></tr> <tr><td>0.5</td><td>28.016</td></tr> <tr><td>1.0</td><td>28.016</td></tr> <tr><td>2.0</td><td>28.016</td></tr> <tr><td>3.0</td><td>28.016</td></tr> <tr><td>4.0</td><td>28.016</td></tr> <tr><td>5.0</td><td>28.016</td></tr> <tr><td>6.0</td><td>28.016</td></tr> <tr><td>7.0</td><td>28.016</td></tr> <tr><td>8.0</td><td>28.016</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	28.006	0.5	28.016	1.0	28.016	2.0	28.016	3.0	28.016	4.0	28.016	5.0	28.016	6.0	28.016	7.0	28.016	8.0	28.016
Time since start [H]	Output Voltage [V]																								
0.0	28.006																								
0.5	28.016																								
1.0	28.016																								
2.0	28.016																								
3.0	28.016																								
4.0	28.016																								
5.0	28.016																								
6.0	28.016																								
7.0	28.016																								
8.0	28.016																								



Model		SNDHS250B28	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+28V9A		


1. Graph

Input Volt. 280 V



2. Values



Load	Time	Td	Tr	Ts	Th	Tf
50 %		53.5	3.8	57.3	1.4	17.9
100 %		53.5	4.0	57.5	0.7	9.1





COSEL																																								
Model	SNDHS250B28																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+28V9A																																							
<p>1. Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>172</td><td>176</td></tr> <tr><td>-20</td><td>171</td><td>175</td></tr> <tr><td>0</td><td>171</td><td>176</td></tr> <tr><td>25</td><td>171</td><td>176</td></tr> <tr><td>40</td><td>171</td><td>176</td></tr> <tr><td>55</td><td>171</td><td>177</td></tr> <tr><td>70</td><td>170</td><td>177</td></tr> <tr><td>85</td><td>170</td><td>177</td></tr> <tr><td>95</td><td>171</td><td>178</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	172	176	-20	171	175	0	171	176	25	171	176	40	171	176	55	171	177	70	170	177	85	170	177	95	171	178	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	172	176																																						
-20	171	175																																						
0	171	176																																						
25	171	176																																						
40	171	176																																						
55	171	177																																						
70	170	177																																						
85	170	177																																						
95	171	178																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model		SNDHS250B28		Temperature 25°C																																																								
Item		Overcurrent Protection		Testing Circuitry Figure A																																																								
Object		+28V9A																																																										
1.Graph		<p>  </p>		2.Values																																																								
				<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 280[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>26.6</td><td>12.33</td><td>12.35</td><td>12.36</td></tr> <tr><td>25.2</td><td>12.25</td><td>12.30</td><td>12.31</td></tr> <tr><td>22.4</td><td>12.57</td><td>12.65</td><td>12.55</td></tr> <tr><td>19.6</td><td>12.71</td><td>12.82</td><td>12.70</td></tr> <tr><td>16.8</td><td>12.84</td><td>12.97</td><td>12.79</td></tr> <tr><td>14.0</td><td>12.96</td><td>13.08</td><td>12.77</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]	26.6	12.33	12.35	12.36	25.2	12.25	12.30	12.31	22.4	12.57	12.65	12.55	19.6	12.71	12.82	12.70	16.8	12.84	12.97	12.79	14.0	12.96	13.08	12.77	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 200[V]	Input Volt. 280[V]	Input Volt. 400[V]																																																									
26.6	12.33	12.35	12.36																																																									
25.2	12.25	12.30	12.31																																																									
22.4	12.57	12.65	12.55																																																									
19.6	12.71	12.82	12.70																																																									
16.8	12.84	12.97	12.79																																																									
14.0	12.96	13.08	12.77																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
--	-	-	-																																																									
<p>Note: Slanted line shows the range of the rated load current.</p>																																																												
<p>Intermittent operation occurs when the output voltage is from 14V to 0V.</p>																																																												



Model		SNDHS250B28																																							
Item		Overvoltage Protection																																							
Object		+28V9A																																							
1.Graph		Testing Circuitry Figure A																																							
<p>—△— Input Volt. 200V ---□--- Input Volt. 400V</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>		2.Values																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 200[V]</th> <th>Input Volt. 400[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>34.36</td><td>34.36</td></tr> <tr><td>-20</td><td>34.48</td><td>34.48</td></tr> <tr><td>0</td><td>34.48</td><td>34.48</td></tr> <tr><td>25</td><td>34.59</td><td>34.59</td></tr> <tr><td>40</td><td>34.59</td><td>34.59</td></tr> <tr><td>55</td><td>34.59</td><td>34.59</td></tr> <tr><td>70</td><td>34.59</td><td>34.59</td></tr> <tr><td>85</td><td>34.59</td><td>34.59</td></tr> <tr><td>95</td><td>34.59</td><td>34.59</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 200[V]	Input Volt. 400[V]	-40	34.36	34.36	-20	34.48	34.48	0	34.48	34.48	25	34.59	34.59	40	34.59	34.59	55	34.59	34.59	70	34.59	34.59	85	34.59	34.59	95	34.59	34.59	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 200[V]	Input Volt. 400[V]																																							
-40	34.36	34.36																																							
-20	34.48	34.48																																							
0	34.48	34.48																																							
25	34.59	34.59																																							
40	34.59	34.59																																							
55	34.59	34.59																																							
70	34.59	34.59																																							
85	34.59	34.59																																							
95	34.59	34.59																																							
--	-	-																																							
--	-	-																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)