

# TEST DATA OF SNDHS50A15

Regulated DC Power Supply  
April 8, 2012

Approved by : Takahiro Yoneda  
Takahiro Yoneda Design Manager

Prepared by : Tadashi Arai  
Tadashi Arai Design Engineer

**COSEL CO.,LTD.**

CONTENTS

1.Input Current (by Input Voltage) . . . . . 1

2.Input Current (by Load Current) . . . . . 2

3.Input Power (by Load Current) . . . . . 3

4.Efficiency (by Input Voltage) . . . . . 4

5.Efficiency (by Load Current) . . . . . 5

6.Line Regulation . . . . . 6

7.Load Regulation . . . . . 7

8.Dynamic Load Response . . . . . 8

9.Ripple Voltage (by Load Current) . . . . . 9

10.Ripple-Noise . . . . . 10

11.Ripple Voltage (by Ambient Temperature) . . . . . 11

12.Ambient Temperature Drift . . . . . 12

13.Output Voltage Accuracy . . . . . 13

14.Time Lapse Drift . . . . . 14

15.Rise and Fall Time . . . . . 15

16.Minimum Input Voltage for Regulated Output Voltage . . . . . 16

17.Overcurrent Protection . . . . . 17

18.Overvoltage Protection . . . . . 18

19.Figure of Testing Circuitry . . . . . 19

(Final Page 19)



Model		SNDHS50A15		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		+15V3.4A																																																																																		
<p>1.Graph</p> <p> <span style="display: inline-block; width: 1em; border-bottom: 1px solid black; margin-right: 0.5em;"></span> <span style="display: inline-block; width: 1em; border-bottom: 1px dashed black; margin-right: 0.5em;"></span> <span style="display: inline-block; width: 1em; border-bottom: 1px dash-dot black; margin-right: 0.5em;"></span> </p> <p> <span style="display: inline-block; width: 1em; border-bottom: 1px solid black; margin-right: 0.5em;"></span> <span style="font-size: 0.8em;">△</span> Load 100%  <span style="display: inline-block; width: 1em; border-bottom: 1px dashed black; margin-right: 0.5em;"></span> <span style="font-size: 0.8em;">□</span> Load 50%  <span style="display: inline-block; width: 1em; border-bottom: 1px dash-dot black; margin-right: 0.5em;"></span> <span style="font-size: 0.8em;">○</span> Load 0%                 </p> <p style="margin-top: 10px;">Note: Slanted line shows the range of the rated input voltage.</p>				<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>40</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>45</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>50</td><td>0.035</td><td>0.626</td><td>1.182</td></tr> <tr><td>55</td><td>0.033</td><td>0.557</td><td>1.085</td></tr> <tr><td>60</td><td>0.032</td><td>0.506</td><td>0.995</td></tr> <tr><td>66</td><td>0.032</td><td>0.458</td><td>0.892</td></tr> <tr><td>80</td><td>0.031</td><td>0.380</td><td>0.738</td></tr> <tr><td>95</td><td>0.031</td><td>0.326</td><td>0.625</td></tr> <tr><td>110</td><td>0.030</td><td>0.287</td><td>0.549</td></tr> <tr><td>125</td><td>0.030</td><td>0.257</td><td>0.486</td></tr> <tr><td>140</td><td>0.030</td><td>0.234</td><td>0.438</td></tr> <tr><td>160</td><td>0.030</td><td>0.211</td><td>0.392</td></tr> <tr><td>170</td><td>0.030</td><td>0.202</td><td>0.370</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	40	0.000	0.000	0.000	45	0.002	0.002	0.002	50	0.035	0.626	1.182	55	0.033	0.557	1.085	60	0.032	0.506	0.995	66	0.032	0.458	0.892	80	0.031	0.380	0.738	95	0.031	0.326	0.625	110	0.030	0.287	0.549	125	0.030	0.257	0.486	140	0.030	0.234	0.438	160	0.030	0.211	0.392	170	0.030	0.202	0.370	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0	0.000	0.000	0.000																																																																																	
40	0.000	0.000	0.000																																																																																	
45	0.002	0.002	0.002																																																																																	
50	0.035	0.626	1.182																																																																																	
55	0.033	0.557	1.085																																																																																	
60	0.032	0.506	0.995																																																																																	
66	0.032	0.458	0.892																																																																																	
80	0.031	0.380	0.738																																																																																	
95	0.031	0.326	0.625																																																																																	
110	0.030	0.287	0.549																																																																																	
125	0.030	0.257	0.486																																																																																	
140	0.030	0.234	0.438																																																																																	
160	0.030	0.211	0.392																																																																																	
170	0.030	0.202	0.370																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	



Model		SNDHS50A15		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		+15V3.4A																																																						
1.Graph		<p>—△— Input Volt. 60V</p> <p>- - □ - - Input Volt. 110V</p> <p>- · - ○ - · - Input Volt. 160V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.032</td><td>0.030</td><td>0.030</td></tr> <tr><td>0.60</td><td>0.208</td><td>0.122</td><td>0.094</td></tr> <tr><td>1.20</td><td>0.372</td><td>0.213</td><td>0.160</td></tr> <tr><td>1.80</td><td>0.538</td><td>0.303</td><td>0.223</td></tr> <tr><td>2.40</td><td>0.707</td><td>0.394</td><td>0.286</td></tr> <tr><td>3.00</td><td>0.878</td><td>0.487</td><td>0.350</td></tr> <tr><td>3.40</td><td>0.995</td><td>0.549</td><td>0.392</td></tr> <tr><td>3.74</td><td>1.096</td><td>0.602</td><td>0.429</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	0.032	0.030	0.030	0.60	0.208	0.122	0.094	1.20	0.372	0.213	0.160	1.80	0.538	0.303	0.223	2.40	0.707	0.394	0.286	3.00	0.878	0.487	0.350	3.40	0.995	0.549	0.392	3.74	1.096	0.602	0.429	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.00	0.032	0.030	0.030																																																					
0.60	0.208	0.122	0.094																																																					
1.20	0.372	0.213	0.160																																																					
1.80	0.538	0.303	0.223																																																					
2.40	0.707	0.394	0.286																																																					
3.00	0.878	0.487	0.350																																																					
3.40	0.995	0.549	0.392																																																					
3.74	1.096	0.602	0.429																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDHS50A15		Temperature 25°C																																																				
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																				
Object		+15V3.4A																																																						
1.Graph		<p>—△— Input Volt. 60V</p> <p>- -□- - Input Volt. 110V</p> <p>- ··○·· Input Volt. 160V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.92</td><td>3.35</td><td>4.83</td></tr> <tr><td>0.60</td><td>12.48</td><td>13.47</td><td>15.12</td></tr> <tr><td>1.20</td><td>22.26</td><td>23.43</td><td>25.62</td></tr> <tr><td>1.80</td><td>32.21</td><td>33.33</td><td>35.64</td></tr> <tr><td>2.40</td><td>42.31</td><td>43.35</td><td>45.72</td></tr> <tr><td>3.00</td><td>52.61</td><td>53.50</td><td>55.95</td></tr> <tr><td>3.40</td><td>59.60</td><td>60.40</td><td>62.78</td></tr> <tr><td>3.74</td><td>65.60</td><td>66.20</td><td>68.61</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	1.92	3.35	4.83	0.60	12.48	13.47	15.12	1.20	22.26	23.43	25.62	1.80	32.21	33.33	35.64	2.40	42.31	43.35	45.72	3.00	52.61	53.50	55.95	3.40	59.60	60.40	62.78	3.74	65.60	66.20	68.61	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.00	1.92	3.35	4.83																																																					
0.60	12.48	13.47	15.12																																																					
1.20	22.26	23.43	25.62																																																					
1.80	32.21	33.33	35.64																																																					
2.40	42.31	43.35	45.72																																																					
3.00	52.61	53.50	55.95																																																					
3.40	59.60	60.40	62.78																																																					
3.74	65.60	66.20	68.61																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model		SNDHS50A15		Temperature 25°C																																				
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																				
Object		+15V3.4A																																						
1. Graph			2. Values																																					
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>56</td><td>84.8</td><td>86.3</td></tr> <tr><td>60</td><td>85.3</td><td>87.1</td></tr> <tr><td>66</td><td>85.8</td><td>87.9</td></tr> <tr><td>80</td><td>85.4</td><td>87.9</td></tr> <tr><td>95</td><td>83.9</td><td>87.2</td></tr> <tr><td>110</td><td>82.4</td><td>86.3</td></tr> <tr><td>125</td><td>80.8</td><td>85.5</td></tr> <tr><td>140</td><td>79.2</td><td>84.6</td></tr> <tr><td>160</td><td>77.0</td><td>83.1</td></tr> <tr><td>170</td><td>75.9</td><td>82.5</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	56	84.8	86.3	60	85.3	87.1	66	85.8	87.9	80	85.4	87.9	95	83.9	87.2	110	82.4	86.3	125	80.8	85.5	140	79.2	84.6	160	77.0	83.1	170	75.9	82.5
Input Voltage [V]	Efficiency [%]																																							
	Load 50%	Load 100%																																						
56	84.8	86.3																																						
60	85.3	87.1																																						
66	85.8	87.9																																						
80	85.4	87.9																																						
95	83.9	87.2																																						
110	82.4	86.3																																						
125	80.8	85.5																																						
140	79.2	84.6																																						
160	77.0	83.1																																						
170	75.9	82.5																																						
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																								



Model		SNDHS50A15		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		+15V3.4A																																																						
1.Graph			2.Values																																																					
<p>                 —△— Input Volt. 60V                  - - □ - - Input Volt. 110V                  - - ○ - - Input Volt. 160V             </p> <p>Efficiency [%]</p> <p>Load Current [A]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.60</td><td>73.9</td><td>68.6</td><td>61.2</td></tr> <tr><td>1.20</td><td>82.7</td><td>78.7</td><td>72.0</td></tr> <tr><td>1.80</td><td>85.7</td><td>82.9</td><td>77.6</td></tr> <tr><td>2.40</td><td>87.0</td><td>84.9</td><td>80.5</td></tr> <tr><td>3.00</td><td>87.4</td><td>86.0</td><td>82.2</td></tr> <tr><td>3.40</td><td>87.4</td><td>86.3</td><td>83.0</td></tr> <tr><td>3.74</td><td>87.3</td><td>86.6</td><td>83.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	-	-	-	0.60	73.9	68.6	61.2	1.20	82.7	78.7	72.0	1.80	85.7	82.9	77.6	2.40	87.0	84.9	80.5	3.00	87.4	86.0	82.2	3.40	87.4	86.3	83.0	3.74	87.3	86.6	83.6	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.00	-	-	-																																																					
0.60	73.9	68.6	61.2																																																					
1.20	82.7	78.7	72.0																																																					
1.80	85.7	82.9	77.6																																																					
2.40	87.0	84.9	80.5																																																					
3.00	87.4	86.0	82.2																																																					
3.40	87.4	86.3	83.0																																																					
3.74	87.3	86.6	83.6																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDHS50A15		Temperature 25°C Testing Circuitry Figure A																																			
Item		Line Regulation																																					
Object		+15V3.4A																																					
1.Graph				2.Values																																			
<p>Legend:          - - - □ - - - Load 50%          — — — △ — — — Load 100%</p>																																							
<p>Note: Slanted line shows the range of the rated input voltage.</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>56</td><td>15.294</td><td>15.287</td></tr> <tr><td>60</td><td>15.294</td><td>15.287</td></tr> <tr><td>66</td><td>15.294</td><td>15.287</td></tr> <tr><td>80</td><td>15.294</td><td>15.288</td></tr> <tr><td>95</td><td>15.295</td><td>15.288</td></tr> <tr><td>110</td><td>15.295</td><td>15.289</td></tr> <tr><td>125</td><td>15.296</td><td>15.290</td></tr> <tr><td>140</td><td>15.297</td><td>15.291</td></tr> <tr><td>160</td><td>15.298</td><td>15.293</td></tr> <tr><td>170</td><td>15.299</td><td>15.293</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	56	15.294	15.287	60	15.294	15.287	66	15.294	15.287	80	15.294	15.288	95	15.295	15.288	110	15.295	15.289	125	15.296	15.290	140	15.297	15.291	160	15.298	15.293	170	15.299	15.293
Input Voltage [V]	Output Voltage [V]																																						
	Load 50%	Load 100%																																					
56	15.294	15.287																																					
60	15.294	15.287																																					
66	15.294	15.287																																					
80	15.294	15.288																																					
95	15.295	15.288																																					
110	15.295	15.289																																					
125	15.296	15.290																																					
140	15.297	15.291																																					
160	15.298	15.293																																					
170	15.299	15.293																																					



Model		SNDHS50A15		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+15V3.4A																																																						
1.Graph		<p>—△— Input Volt. 60V</p> <p>- - -□- - - Input Volt. 110V</p> <p>- · - ○ - · - - Input Volt. 160V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.308</td><td>15.306</td><td>15.307</td></tr> <tr><td>0.60</td><td>15.297</td><td>15.299</td><td>15.301</td></tr> <tr><td>1.20</td><td>15.295</td><td>15.297</td><td>15.299</td></tr> <tr><td>1.80</td><td>15.292</td><td>15.295</td><td>15.297</td></tr> <tr><td>2.40</td><td>15.290</td><td>15.292</td><td>15.296</td></tr> <tr><td>3.00</td><td>15.287</td><td>15.291</td><td>15.294</td></tr> <tr><td>3.40</td><td>15.286</td><td>15.289</td><td>15.293</td></tr> <tr><td>3.74</td><td>15.285</td><td>15.288</td><td>15.292</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	0.00	15.308	15.306	15.307	0.60	15.297	15.299	15.301	1.20	15.295	15.297	15.299	1.80	15.292	15.295	15.297	2.40	15.290	15.292	15.296	3.00	15.287	15.291	15.294	3.40	15.286	15.289	15.293	3.74	15.285	15.288	15.292	--	-	-	-	--	-	-	-	--	-	-	-		
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																					
0.00	15.308	15.306	15.307																																																					
0.60	15.297	15.299	15.301																																																					
1.20	15.295	15.297	15.299																																																					
1.80	15.292	15.295	15.297																																																					
2.40	15.290	15.292	15.296																																																					
3.00	15.287	15.291	15.294																																																					
3.40	15.286	15.289	15.293																																																					
3.74	15.285	15.288	15.292																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDHS50A15	
Item		Dynamic Load Response	
Object		+15V3.4A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 110 V  
 Cycle 1000 ms




Min. Load (0A) ←→  
 Load 100% (3.4A)

1 V/div




400µs/div




10ms/div

Min. Load (0A) ←→  
 Load 50% (1.7A)

1 V/div




400µs/div




10ms/div

Load 10% (0.34A) ←→  
 Load 100% (3.4A)

1 V/div



400µs/div



10ms/div




Model		SNDHS50A15		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		+15V3.4A																																									
1.Graph				2.Values																																							
<p>                     —△— Input Volt. 60V                      - - ○ - - Input Volt. 160V                 </p>				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 60 [V]</th> <th>Input Volt. 160 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.60</td><td>35</td><td>50</td></tr> <tr><td>1.20</td><td>35</td><td>50</td></tr> <tr><td>1.80</td><td>35</td><td>50</td></tr> <tr><td>2.40</td><td>35</td><td>50</td></tr> <tr><td>3.00</td><td>35</td><td>50</td></tr> <tr><td>3.40</td><td>35</td><td>50</td></tr> <tr><td>3.74</td><td>35</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 60 [V]	Input Volt. 160 [V]	0.00	10	10	0.60	35	50	1.20	35	50	1.80	35	50	2.40	35	50	3.00	35	50	3.40	35	50	3.74	35	50	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 60 [V]	Input Volt. 160 [V]																																									
0.00	10	10																																									
0.60	35	50																																									
1.20	35	50																																									
1.80	35	50																																									
2.40	35	50																																									
3.00	35	50																																									
3.40	35	50																																									
3.74	35	50																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope.                      Ripple Voltage is shown as p-p in the figure below.                      Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																											

Model		SNDHS50A15		Temperature 25°C																																							
Item		Ripple-Noise		Testing Circuitry Figure B																																							
Object		+15V3.4A																																									
1. Graph				2. Values																																							
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 60 [V]</th> <th>Input Volt. 160 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>25</td></tr> <tr><td>0.60</td><td>40</td><td>65</td></tr> <tr><td>1.20</td><td>40</td><td>70</td></tr> <tr><td>1.80</td><td>40</td><td>70</td></tr> <tr><td>2.40</td><td>45</td><td>70</td></tr> <tr><td>3.00</td><td>45</td><td>70</td></tr> <tr><td>3.40</td><td>45</td><td>70</td></tr> <tr><td>3.74</td><td>45</td><td>70</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 60 [V]	Input Volt. 160 [V]	0.00	10	25	0.60	40	65	1.20	40	70	1.80	40	70	2.40	45	70	3.00	45	70	3.40	45	70	3.74	45	70	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																										
	Input Volt. 60 [V]	Input Volt. 160 [V]																																									
0.00	10	25																																									
0.60	40	65																																									
1.20	40	70																																									
1.80	40	70																																									
2.40	45	70																																									
3.00	45	70																																									
3.40	45	70																																									
3.74	45	70																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope.                  Ripple-Noise is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Fig. Complex Ripple Noise Wave Form</p>																																											

Model	SNDHS50A15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V3.4A

Testing Circuitry Figure B

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	55	55
-20	55	55
0	55	60
25	55	60
40	60	60
55	70	65
70	70	65
80	70	70
95	70	70
100	70	70
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form



Model		SNDHS50A15		Testing Circuitry Figure A																																																		
Item		Ambient Temperature Drift																																																				
Object		+15V3.4A																																																				
1.Graph		<p>                 —△— Input Volt. 60V                  - - - □ - - - Input Volt. 110V                  - · - ○ - · - - Input Volt. 160V             </p>		2.Values																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>15.222</td><td>15.226</td><td>15.235</td></tr> <tr><td>-20</td><td>15.249</td><td>15.252</td><td>15.259</td></tr> <tr><td>0</td><td>15.265</td><td>15.268</td><td>15.273</td></tr> <tr><td>25</td><td>15.284</td><td>15.287</td><td>15.291</td></tr> <tr><td>40</td><td>15.289</td><td>15.292</td><td>15.295</td></tr> <tr><td>55</td><td>15.288</td><td>15.291</td><td>15.294</td></tr> <tr><td>70</td><td>15.291</td><td>15.294</td><td>15.295</td></tr> <tr><td>80</td><td>15.289</td><td>15.292</td><td>15.293</td></tr> <tr><td>95</td><td>15.289</td><td>15.292</td><td>15.293</td></tr> <tr><td>100</td><td>15.289</td><td>15.292</td><td>15.293</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	-40	15.222	15.226	15.235	-20	15.249	15.252	15.259	0	15.265	15.268	15.273	25	15.284	15.287	15.291	40	15.289	15.292	15.295	55	15.288	15.291	15.294	70	15.291	15.294	15.295	80	15.289	15.292	15.293	95	15.289	15.292	15.293	100	15.289	15.292	15.293	--	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																			
-40	15.222	15.226	15.235																																																			
-20	15.249	15.252	15.259																																																			
0	15.265	15.268	15.273																																																			
25	15.284	15.287	15.291																																																			
40	15.289	15.292	15.295																																																			
55	15.288	15.291	15.294																																																			
70	15.291	15.294	15.295																																																			
80	15.289	15.292	15.293																																																			
95	15.289	15.292	15.293																																																			
100	15.289	15.292	15.293																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



<b>COSEL</b>		Testing Circuitry Figure A
Model	SNDHS50A15	
Item	Output Voltage Accuracy	
Object	+15V3.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 60 - 160V

Load Current : 0 - 3.4A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	110	0	15.315	±33	±0.2
Minimum Voltage	-20	60	3.4	15.249		




<b>COSEL</b>																								
Model	SNDHS50A15	Temperature 25°C Testing Circuitry Figure A																						
Item	Time Lapse Drift																							
Object	+15V3.4A																							
1.Graph		2.Values																						
<p style="text-align: center;">Time [H]</p> <p>Input Volt. 110V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.284</td></tr> <tr><td>0.5</td><td>15.288</td></tr> <tr><td>1.0</td><td>15.289</td></tr> <tr><td>2.0</td><td>15.289</td></tr> <tr><td>3.0</td><td>15.289</td></tr> <tr><td>4.0</td><td>15.289</td></tr> <tr><td>5.0</td><td>15.289</td></tr> <tr><td>6.0</td><td>15.289</td></tr> <tr><td>7.0</td><td>15.289</td></tr> <tr><td>8.0</td><td>15.289</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.284	0.5	15.288	1.0	15.289	2.0	15.289	3.0	15.289	4.0	15.289	5.0	15.289	6.0	15.289	7.0	15.289	8.0	15.289
Time since start [H]	Output Voltage [V]																							
0.0	15.284																							
0.5	15.288																							
1.0	15.289																							
2.0	15.289																							
3.0	15.289																							
4.0	15.289																							
5.0	15.289																							
6.0	15.289																							
7.0	15.289																							
8.0	15.289																							



Model	SNDHS50A15	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V3.4A		


1. Graph

Input Volt. 110 V



2. Values


		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
	50 %	19.8	6.8	26.6	10.9	46.8
	100 %	19.8	9.5	29.3	5.5	23.9





Model	SNDHS50A15	Testing Circuitry Figure A
Item	Minimum Input Voltage for Regulated Output Voltage	
Object	+15V3.4A	

1. Graph





Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	46	48
-20	47	48
0	47	49
25	47	49
40	48	50
55	47	50
70	47	49
80	47	49
95	47	49
100	47	49
--	-	-



Model		SNDHS50A15		Temperature 25°C																																																												
Item		Overcurrent Protection		Testing Circuitry Figure A																																																												
Object		+15V3.4A																																																														
1.Graph		<p>  </p>		2.Values																																																												
				<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 110[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr> <td>14.3</td> <td>4.33</td> <td>4.50</td> <td>4.61</td> </tr> <tr> <td>13.5</td> <td>4.35</td> <td>4.53</td> <td>4.62</td> </tr> <tr> <td>12.0</td> <td>4.38</td> <td>4.57</td> <td>4.62</td> </tr> <tr> <td>10.5</td> <td>4.42</td> <td>4.67</td> <td>4.59</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]	14.3	4.33	4.50	4.61	13.5	4.35	4.53	4.62	12.0	4.38	4.57	4.62	10.5	4.42	4.67	4.59	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Output Voltage [V]	Load Current [A]																																																															
	Input Volt. 60[V]	Input Volt. 110[V]	Input Volt. 160[V]																																																													
14.3	4.33	4.50	4.61																																																													
13.5	4.35	4.53	4.62																																																													
12.0	4.38	4.57	4.62																																																													
10.5	4.42	4.67	4.59																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
--	-	-	-																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> <p>Intermittent operation occurs when the output voltage is from 10V to 0V.</p>																																																																



Model		SNDHS50A15																																							
Item		Overvoltage Protection																																							
Object		+15V3.4A																																							
1.Graph		Testing Circuitry Figure A																																							
<p>—△— Input Volt. 60V                  ---□--- Input Volt. 160V</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>		2.Values																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 60[V]</th> <th>Input Volt. 160[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>18.45</td><td>18.45</td></tr> <tr><td>-20</td><td>18.75</td><td>18.75</td></tr> <tr><td>0</td><td>19.04</td><td>19.04</td></tr> <tr><td>25</td><td>19.39</td><td>19.39</td></tr> <tr><td>40</td><td>19.57</td><td>19.57</td></tr> <tr><td>55</td><td>19.75</td><td>19.75</td></tr> <tr><td>70</td><td>19.86</td><td>19.87</td></tr> <tr><td>80</td><td>20.04</td><td>20.04</td></tr> <tr><td>95</td><td>20.16</td><td>20.27</td></tr> <tr><td>100</td><td>20.20</td><td>20.36</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 60[V]	Input Volt. 160[V]	-40	18.45	18.45	-20	18.75	18.75	0	19.04	19.04	25	19.39	19.39	40	19.57	19.57	55	19.75	19.75	70	19.86	19.87	80	20.04	20.04	95	20.16	20.27	100	20.20	20.36	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 60[V]	Input Volt. 160[V]																																							
-40	18.45	18.45																																							
-20	18.75	18.75																																							
0	19.04	19.04																																							
25	19.39	19.39																																							
40	19.57	19.57																																							
55	19.75	19.75																																							
70	19.86	19.87																																							
80	20.04	20.04																																							
95	20.16	20.27																																							
100	20.20	20.36																																							
--	-	-																																							




Figure A




Figure B (Ripple and Ripple noise Characteristic)