



# TEST DATA OF SNDPF1000

(200V INPUT)

Regulated DC Power Supply  
July 9, 2012

Approved by :

*Takahiro Yoneda*

Takahiro Yoneda

Design Manager

Prepared by :

*Satoshi Kinoshita*

Satoshi Kinoshita

Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ambient Temperature Drift . . . . .	13
14. Output Voltage Accuracy . . . . .	14
15. Time Lapse Drift . . . . .	15
16. Rise and Fall Time . . . . .	16
17. Minimum Input Voltage for Regulated Output Voltage . . . . .	17
18. Overvoltage Protection . . . . .	18
19. Figure of Testing Circuitry . . . . .	19

(Final Page 19)

# COSEL

Model	SNDPF1000	Temperature Testing Circuitry	25°C Figure A																														
Item	Input Current (by Load Power)																																
Object	_____																																
1.Graph		2.Values																															
<p>—△— Input Volt. 170V        - - -□- - Input Volt. 200V        - - -○- - Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Power [W]</th> <th>Input Current [A] (170V)</th> <th>Input Current [A] (200V)</th> <th>Input Current [A] (264V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.683</td><td>0.803</td><td>1.067</td></tr> <tr><td>300</td><td>2.097</td><td>1.888</td><td>1.844</td></tr> <tr><td>600</td><td>3.877</td><td>3.387</td><td>2.976</td></tr> <tr><td>900</td><td>5.722</td><td>4.925</td><td>4.309</td></tr> <tr><td>1200</td><td>7.558</td><td>6.492</td><td>5.743</td></tr> <tr><td>1500</td><td>9.409</td><td>8.049</td><td>7.084</td></tr> <tr><td>1650</td><td>10.338</td><td>8.829</td><td>7.738</td></tr> </tbody> </table>		Load Power [W]	Input Current [A] (170V)	Input Current [A] (200V)	Input Current [A] (264V)	0	0.683	0.803	1.067	300	2.097	1.888	1.844	600	3.877	3.387	2.976	900	5.722	4.925	4.309	1200	7.558	6.492	5.743	1500	9.409	8.049	7.084	1650	10.338	8.829	7.738
Load Power [W]	Input Current [A] (170V)	Input Current [A] (200V)	Input Current [A] (264V)																														
0	0.683	0.803	1.067																														
300	2.097	1.888	1.844																														
600	3.877	3.387	2.976																														
900	5.722	4.925	4.309																														
1200	7.558	6.492	5.743																														
1500	9.409	8.049	7.084																														
1650	10.338	8.829	7.738																														
<p>Input Current [A]</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Power [W]</th> <th>Input Current [A] (170V)</th> <th>Input Current [A] (200V)</th> <th>Input Current [A] (264V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.683</td><td>0.803</td><td>1.067</td></tr> <tr><td>300</td><td>2.097</td><td>1.888</td><td>1.844</td></tr> <tr><td>600</td><td>3.877</td><td>3.387</td><td>2.976</td></tr> <tr><td>900</td><td>5.722</td><td>4.925</td><td>4.309</td></tr> <tr><td>1200</td><td>7.558</td><td>6.492</td><td>5.743</td></tr> <tr><td>1500</td><td>9.409</td><td>8.049</td><td>7.084</td></tr> <tr><td>1650</td><td>10.338</td><td>8.829</td><td>7.738</td></tr> </tbody> </table>		Load Power [W]	Input Current [A] (170V)	Input Current [A] (200V)	Input Current [A] (264V)	0	0.683	0.803	1.067	300	2.097	1.888	1.844	600	3.877	3.387	2.976	900	5.722	4.925	4.309	1200	7.558	6.492	5.743	1500	9.409	8.049	7.084	1650	10.338	8.829	7.738
Load Power [W]	Input Current [A] (170V)	Input Current [A] (200V)	Input Current [A] (264V)																														
0	0.683	0.803	1.067																														
300	2.097	1.888	1.844																														
600	3.877	3.387	2.976																														
900	5.722	4.925	4.309																														
1200	7.558	6.492	5.743																														
1500	9.409	8.049	7.084																														
1650	10.338	8.829	7.738																														
<p>Note: Slanted line shows the range of the rated load current.</p>																																	

# COSEL

Model	SNDPF1000	Temperature Testing Circuitry	25°C Figure A																																																		
Item	Input Power (by Load Power)																																																				
Object	—																																																				
1. Graph		—△— Input Volt. 170V - -□--- Input Volt. 200V - -○--- Input Volt. 264V																																																			
			2. Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>9</td><td>10</td><td>15</td></tr> <tr><td>300</td><td>322</td><td>321</td><td>318</td></tr> <tr><td>600</td><td>633</td><td>630</td><td>623</td></tr> <tr><td>900</td><td>947</td><td>940</td><td>928</td></tr> <tr><td>1200</td><td>1261</td><td>1251</td><td>1237</td></tr> <tr><td>1500</td><td>1575</td><td>1563</td><td>1546</td></tr> <tr><td>1650</td><td>1733</td><td>1719</td><td>1700</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Power [W]	Input Power [W]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	9	10	15	300	322	321	318	600	633	630	623	900	947	940	928	1200	1261	1251	1237	1500	1575	1563	1546	1650	1733	1719	1700	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Power [W]		Input Power [W]																																																			
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																		
0	9	10	15																																																		
300	322	321	318																																																		
600	633	630	623																																																		
900	947	940	928																																																		
1200	1261	1251	1237																																																		
1500	1575	1563	1546																																																		
1650	1733	1719	1700																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	SNDPF1000	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	—																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>94.4</td><td>94.6</td></tr> <tr><td>170</td><td>95.0</td><td>95.2</td></tr> <tr><td>180</td><td>95.3</td><td>95.6</td></tr> <tr><td>200</td><td>95.6</td><td>96.0</td></tr> <tr><td>220</td><td>96.1</td><td>96.5</td></tr> <tr><td>240</td><td>96.2</td><td>96.7</td></tr> <tr><td>255</td><td>96.4</td><td>96.9</td></tr> <tr><td>264</td><td>96.7</td><td>97.1</td></tr> <tr><td>280</td><td>96.8</td><td>96.8</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	150	94.4	94.6	170	95.0	95.2	180	95.3	95.6	200	95.6	96.0	220	96.1	96.5	240	96.2	96.7	255	96.4	96.9	264	96.7	97.1	280	96.8	96.8
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
150	94.4	94.6																																	
170	95.0	95.2																																	
180	95.3	95.6																																	
200	95.6	96.0																																	
220	96.1	96.5																																	
240	96.2	96.7																																	
255	96.4	96.9																																	
264	96.7	97.1																																	
280	96.8	96.8																																	

Note: Slanted line shows the range of the rated input voltage.

# COSEL

Model	SNDPF1000	Temperature	25°C																																																			
Item	Efficiency (by Load Power)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Efficiency [%]</p> <p>Load Power [W]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 170V</li> <li>Input Volt. 200V</li> <li>Input Volt. 264V</li> </ul>		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>170[V]</th> <th>200[V]</th> <th>264[V]</th> </tr> </thead> <tbody> <tr><td>300</td><td>93.1</td><td>93.5</td><td>94.4</td></tr> <tr><td>600</td><td>94.8</td><td>95.3</td><td>96.3</td></tr> <tr><td>900</td><td>95.0</td><td>95.8</td><td>97.0</td></tr> <tr><td>1200</td><td>95.2</td><td>95.9</td><td>97.0</td></tr> <tr><td>1500</td><td>95.2</td><td>96.0</td><td>97.1</td></tr> <tr><td>1650</td><td>95.2</td><td>96.0</td><td>97.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Power [W]	Efficiency [%]			170[V]	200[V]	264[V]	300	93.1	93.5	94.4	600	94.8	95.3	96.3	900	95.0	95.8	97.0	1200	95.2	95.9	97.0	1500	95.2	96.0	97.1	1650	95.2	96.0	97.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Power [W]	Efficiency [%]																																																					
	170[V]	200[V]	264[V]																																																			
300	93.1	93.5	94.4																																																			
600	94.8	95.3	96.3																																																			
900	95.0	95.8	97.0																																																			
1200	95.2	95.9	97.0																																																			
1500	95.2	96.0	97.1																																																			
1650	95.2	96.0	97.1																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	SNDPF1000	Temperature	25°C																															
Item	Power Factor (by Input Voltage)	Testing Circuitry	Figure A																															
Object	—	2.Values																																
1.Graph	<p>Power Factor</p> <p>Load 50%</p> <p>Load 100%</p> <p>Input Voltage [V]</p>																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>0.982</td><td>0.991</td></tr> <tr><td>170</td><td>0.971</td><td>0.985</td></tr> <tr><td>180</td><td>0.964</td><td>0.982</td></tr> <tr><td>200</td><td>0.948</td><td>0.972</td></tr> <tr><td>220</td><td>0.921</td><td>0.956</td></tr> <tr><td>240</td><td>0.891</td><td>0.925</td></tr> <tr><td>255</td><td>0.834</td><td>0.887</td></tr> <tr><td>264</td><td>0.822</td><td>0.830</td></tr> <tr><td>280</td><td>0.427</td><td>0.511</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	150	0.982	0.991	170	0.971	0.985	180	0.964	0.982	200	0.948	0.972	220	0.921	0.956	240	0.891	0.925	255	0.834	0.887	264	0.822	0.830	280	0.427	0.511
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
150	0.982	0.991																																
170	0.971	0.985																																
180	0.964	0.982																																
200	0.948	0.972																																
220	0.921	0.956																																
240	0.891	0.925																																
255	0.834	0.887																																
264	0.822	0.830																																
280	0.427	0.511																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		


# COSEL

Model	SNDPF1000	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Power Factor (by Load Power)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 170V        - -□--- Input Volt. 200V        - -○--- Input Volt. 264V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Power [W]</th> <th>170V PF</th> <th>200V PF</th> <th>264V PF</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.90</td><td>-</td><td>-</td></tr> <tr><td>200</td><td>-</td><td>0.85</td><td>-</td></tr> <tr><td>400</td><td>-</td><td>0.88</td><td>-</td></tr> <tr><td>600</td><td>0.95</td><td>0.92</td><td>0.80</td></tr> <tr><td>800</td><td>0.96</td><td>0.93</td><td>0.81</td></tr> <tr><td>1000</td><td>0.97</td><td>0.94</td><td>0.82</td></tr> <tr><td>1200</td><td>0.97</td><td>0.94</td><td>0.82</td></tr> <tr><td>1400</td><td>0.98</td><td>0.95</td><td>0.83</td></tr> <tr><td>1600</td><td>0.98</td><td>0.95</td><td>0.83</td></tr> <tr><td>1800</td><td>0.98</td><td>0.95</td><td>0.83</td></tr> </tbody> </table>	Load Power [W]	170V PF	200V PF	264V PF	0	0.90	-	-	200	-	0.85	-	400	-	0.88	-	600	0.95	0.92	0.80	800	0.96	0.93	0.81	1000	0.97	0.94	0.82	1200	0.97	0.94	0.82	1400	0.98	0.95	0.83	1600	0.98	0.95	0.83	1800	0.98	0.95	0.83	2.Values								
Load Power [W]	170V PF	200V PF	264V PF																																																			
0	0.90	-	-																																																			
200	-	0.85	-																																																			
400	-	0.88	-																																																			
600	0.95	0.92	0.80																																																			
800	0.96	0.93	0.81																																																			
1000	0.97	0.94	0.82																																																			
1200	0.97	0.94	0.82																																																			
1400	0.98	0.95	0.83																																																			
1600	0.98	0.95	0.83																																																			
1800	0.98	0.95	0.83																																																			
	<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>300</td><td>0.903</td><td>0.849</td><td>0.653</td></tr> <tr><td>600</td><td>0.960</td><td>0.930</td><td>0.793</td></tr> <tr><td>900</td><td>0.973</td><td>0.954</td><td>0.816</td></tr> <tr><td>1200</td><td>0.981</td><td>0.964</td><td>0.816</td></tr> <tr><td>1500</td><td>0.985</td><td>0.971</td><td>0.826</td></tr> <tr><td>1650</td><td>0.986</td><td>0.973</td><td>0.832</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Power [W]	Power Factor			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	300	0.903	0.849	0.653	600	0.960	0.930	0.793	900	0.973	0.954	0.816	1200	0.981	0.964	0.816	1500	0.985	0.971	0.826	1650	0.986	0.973	0.832	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Power [W]	Power Factor																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
300	0.903	0.849	0.653																																																			
600	0.960	0.930	0.793																																																			
900	0.973	0.954	0.816																																																			
1200	0.981	0.964	0.816																																																			
1500	0.985	0.971	0.826																																																			
1650	0.986	0.973	0.832																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	SNDPF1000	Temperature Testing Circuitry	25°C
Item	Inrush Current	Circuitry	Figure A
Object	—		




Input Voltage 200 V

Frequency 60 Hz

Load 0 %

Primary inrush current 38.9 A

Secondary inrush current 41.1 A



Note: The current of the input surge to a built-in noise filter (0.2ms or less) is excluded.



Model	SNDPF1000	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A)DEN-AN	-	-	-
(B)IEC60950-1	-	-	-

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 240 [V]	Input Volt. 264 [V]
(B)IEC60950-1	0.17	0.26	0.29

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

# COSEL

Model	SNDPF1000	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+360V 1500W																																		
1.Graph			2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50%    —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>150</td><td>375.378</td><td>373.191</td></tr> <tr><td>170</td><td>375.956</td><td>374.451</td></tr> <tr><td>180</td><td>376.172</td><td>374.775</td></tr> <tr><td>200</td><td>376.505</td><td>375.521</td></tr> <tr><td>220</td><td>376.741</td><td>375.912</td></tr> <tr><td>240</td><td>376.907</td><td>376.298</td></tr> <tr><td>255</td><td>377.067</td><td>376.554</td></tr> <tr><td>264</td><td>377.089</td><td>376.829</td></tr> <tr><td>280</td><td>378.098</td><td>377.528</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	150	375.378	373.191	170	375.956	374.451	180	376.172	374.775	200	376.505	375.521	220	376.741	375.912	240	376.907	376.298	255	377.067	376.554	264	377.089	376.829	280	378.098	377.528
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
150	375.378	373.191																																	
170	375.956	374.451																																	
180	376.172	374.775																																	
200	376.505	375.521																																	
220	376.741	375.912																																	
240	376.907	376.298																																	
255	377.067	376.554																																	
264	377.089	376.829																																	
280	378.098	377.528																																	

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	SNDPF1000	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+360V 1500W																																																					
1.Graph		—△— Input Volt. 170V - -□--- Input Volt. 200V - -○--- Input Volt. 264V																																																				
			2.Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>377.573</td><td>377.711</td><td>377.844</td></tr> <tr> <td>300</td><td>376.880</td><td>377.168</td><td>377.499</td></tr> <tr> <td>600</td><td>376.285</td><td>376.748</td><td>377.231</td></tr> <tr> <td>900</td><td>375.651</td><td>376.306</td><td>377.043</td></tr> <tr> <td>1200</td><td>374.991</td><td>375.870</td><td>376.918</td></tr> <tr> <td>1500</td><td>374.451</td><td>375.521</td><td>376.829</td></tr> <tr> <td>1650</td><td>374.014</td><td>375.203</td><td>376.634</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Power [W]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	0	377.573	377.711	377.844	300	376.880	377.168	377.499	600	376.285	376.748	377.231	900	375.651	376.306	377.043	1200	374.991	375.870	376.918	1500	374.451	375.521	376.829	1650	374.014	375.203	376.634	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Power [W]	Output Voltage [V]																																																					
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																			
0	377.573	377.711	377.844																																																			
300	376.880	377.168	377.499																																																			
600	376.285	376.748	377.231																																																			
900	375.651	376.306	377.043																																																			
1200	374.991	375.870	376.918																																																			
1500	374.451	375.521	376.829																																																			
1650	374.014	375.203	376.634																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**


Model	SNDPF1000	Temperature Testing Circuitry	25°C
Item	Dynamic Load Response		Figure A
Object	+360V 1500W		

Input Volt. 200 V  
 Cycle 1000 ms




Min. Load (0W) ↔

Load 100% (1500W)



50 V/div


50 ms/div



50 ms/div


Min. Load (0W) ↔

Load 50% (750W)



50 V/div

50 ms/div




50 ms/div

# COSEL

Model	SNDPF1000
Item	Ripple Voltage (by Load Current)
Object	+360V1500W

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Load Power [W]	Ripple Voltage [mV]	
	Input Volt. 170 [V]	Input Volt. 264 [V]
0	0.2	0.4
300	5.4	6.4
600	9.6	12.0
900	14.0	19.0
1200	17.0	23.0
1500	20.0	28.0
1650	22.0	32.0
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line  
T2: Due to Switching





Fig. Complex Ripple Wave Form

**COSEL**

Model	SNDPF1000	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+360V 1500W																																																						
1.Graph	<p style="text-align: center;"> <span style="color: black;">— △ —</span> Input Volt. 170V  <span style="color: gray;">--- □ ---</span> Input Volt. 200V  <span style="color: gray;">--- ○ ---</span> Input Volt. 264V         </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	2.Values																																																					
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 170[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 264[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>374.023</td><td>374.941</td><td>375.936</td></tr> <tr><td>-20</td><td>374.157</td><td>375.105</td><td>376.199</td></tr> <tr><td>0</td><td>374.301</td><td>375.306</td><td>376.471</td></tr> <tr><td>25</td><td>374.451</td><td>375.521</td><td>376.829</td></tr> <tr><td>40</td><td>374.430</td><td>375.543</td><td>376.909</td></tr> <tr><td>55</td><td>374.367</td><td>375.531</td><td>376.970</td></tr> <tr><td>70</td><td>374.275</td><td>375.496</td><td>377.028</td></tr> <tr><td>80</td><td>374.274</td><td>375.536</td><td>377.141</td></tr> <tr><td>90</td><td>374.254</td><td>375.556</td><td>377.193</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]	-40	374.023	374.941	375.936	-20	374.157	375.105	376.199	0	374.301	375.306	376.471	25	374.451	375.521	376.829	40	374.430	375.543	376.909	55	374.367	375.531	376.970	70	374.275	375.496	377.028	80	374.274	375.536	377.141	90	374.254	375.556	377.193	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 170[V]	Input Volt. 200[V]	Input Volt. 264[V]																																																				
-40	374.023	374.941	375.936																																																				
-20	374.157	375.105	376.199																																																				
0	374.301	375.306	376.471																																																				
25	374.451	375.521	376.829																																																				
40	374.430	375.543	376.909																																																				
55	374.367	375.531	376.970																																																				
70	374.275	375.496	377.028																																																				
80	374.274	375.536	377.141																																																				
90	374.254	375.556	377.193																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.



Model	SNDPF1000	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+360V 1500W	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 80°C

Input Voltage : 170 - 264V

Load Current : 0 - 1500W

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [V]	Ration [%]
Maximum Voltage	80	264	0	378.320	$\pm 2$	$\pm 0.1$
Minimum Voltage	-20	170	4.17	374.157		

**COSEL**

Model	SNDPF1000
Item	Time Lapse Drift
Object	+360V 1500W

Temperature 25°C  
Testing Circuitry Figure A


1.Graph



Input Volt. 200V  
Load 100%

2.Values

Time since start [H]	Output Voltage [V]
0.0	375.124
0.5	375.420
1.0	375.420
2.0	375.422
3.0	375.410
4.0	375.412
5.0	375.411
6.0	375.410
7.0	375.411
8.0	375.408


**COSEL**

**COSEL**

Model	SNDPF1000
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+360V 1500W

## 1.Graph

---□--- Load 50%  
—△— Load 100%



Testing Circuitry Figure A

## 2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	79	80
-20	77	80
0	76	81
25	73	83
40	72	84
55	70	88
70	69	92
80	68	94
90	68	95
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	SNDPF1000
Item	Overvoltage Protection
Object	+360V1500W

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 170[V]	Input Volt. 264[V]
-40	436.0	436.2
-20	435.3	435.3
0	435.0	435.1
25	434.5	434.5
40	434.1	434.2
55	433.8	433.7
70	433.4	433.3
80	433.3	433.2
90	433.1	433.0
--	-	-
--	-	-

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950-1 )