

TEST DATA OF SNDPF1000

(100V INPUT)

Regulated DC Power Supply
July 5, 2012

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ambient Temperature Drift	13
14. Output Voltage Accuracy	14
15. Time Lapse Drift	15
16. Rise and Fall Time	16
17. Minimum Input Voltage for Regulated Output Voltage	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)



Model		SNDPF1000		Temperature 25°C																																																				
Item		Input Current (by Load Power)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 85V</p> <p>---□--- Input Volt. 100V</p> <p>-·-○-·- Input Volt. 132V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.380</td><td>0.418</td><td>0.547</td></tr> <tr><td>50</td><td>0.889</td><td>0.782</td><td>0.740</td></tr> <tr><td>150</td><td>2.113</td><td>1.782</td><td>1.431</td></tr> <tr><td>300</td><td>4.001</td><td>3.338</td><td>2.560</td></tr> <tr><td>450</td><td>5.897</td><td>4.980</td><td>3.763</td></tr> <tr><td>600</td><td>7.737</td><td>6.562</td><td>4.942</td></tr> <tr><td>750</td><td>9.731</td><td>8.198</td><td>6.153</td></tr> <tr><td>850</td><td>11.017</td><td>9.234</td><td>6.945</td></tr> <tr><td>1000</td><td>12.901</td><td>10.903</td><td>8.137</td></tr> <tr><td>1100</td><td>14.292</td><td>12.023</td><td>8.953</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Power [W]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.380	0.418	0.547	50	0.889	0.782	0.740	150	2.113	1.782	1.431	300	4.001	3.338	2.560	450	5.897	4.980	3.763	600	7.737	6.562	4.942	750	9.731	8.198	6.153	850	11.017	9.234	6.945	1000	12.901	10.903	8.137	1100	14.292	12.023	8.953	--	-	-	-		
Load Power [W]	Input Current [A]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0	0.380	0.418	0.547																																																					
50	0.889	0.782	0.740																																																					
150	2.113	1.782	1.431																																																					
300	4.001	3.338	2.560																																																					
450	5.897	4.980	3.763																																																					
600	7.737	6.562	4.942																																																					
750	9.731	8.198	6.153																																																					
850	11.017	9.234	6.945																																																					
1000	12.901	10.903	8.137																																																					
1100	14.292	12.023	8.953																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDPF1000		Temperature 25°C																																																				
Item		Input Power (by Load Power)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 85V - - - □ - - - Input Volt. 100V - · - ○ - · - - Input Volt. 132V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>13</td><td>14</td><td>9</td></tr> <tr><td>50</td><td>67</td><td>66</td><td>65</td></tr> <tr><td>150</td><td>173</td><td>171</td><td>171</td></tr> <tr><td>300</td><td>333</td><td>328</td><td>326</td></tr> <tr><td>450</td><td>495</td><td>490</td><td>483</td></tr> <tr><td>600</td><td>653</td><td>650</td><td>641</td></tr> <tr><td>750</td><td>822</td><td>813</td><td>800</td></tr> <tr><td>850</td><td>932</td><td>917</td><td>905</td></tr> <tr><td>1000</td><td>1092</td><td>1084</td><td>1064</td></tr> <tr><td>1100</td><td>1208</td><td>1196</td><td>1171</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Power [W]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	13	14	9	50	67	66	65	150	173	171	171	300	333	328	326	450	495	490	483	600	653	650	641	750	822	813	800	850	932	917	905	1000	1092	1084	1064	1100	1208	1196	1171	--	-	-	-
Load Power [W]	Input Power [W]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
0	13	14	9																																																					
50	67	66	65																																																					
150	173	171	171																																																					
300	333	328	326																																																					
450	495	490	483																																																					
600	653	650	641																																																					
750	822	813	800																																																					
850	932	917	905																																																					
1000	1092	1084	1064																																																					
1100	1208	1196	1171																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																								



Model		SNDPF1000		Temperature 25°C																																	
Item		Efficiency (by Input Voltage)		Testing Circuitry Figure A																																	
Object		_____																																			
1.Graph				2.Values																																	
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>80</td><td>91.4</td><td>90.6</td></tr> <tr><td>85</td><td>91.3</td><td>91.5</td></tr> <tr><td>90</td><td>91.8</td><td>91.7</td></tr> <tr><td>100</td><td>92.0</td><td>92.2</td></tr> <tr><td>110</td><td>91.8</td><td>93.2</td></tr> <tr><td>120</td><td>92.6</td><td>93.3</td></tr> <tr><td>132</td><td>93.4</td><td>94.0</td></tr> <tr><td>140</td><td>93.5</td><td>94.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	80	91.4	90.6	85	91.3	91.5	90	91.8	91.7	100	92.0	92.2	110	91.8	93.2	120	92.6	93.3	132	93.4	94.0	140	93.5	94.2	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
80	91.4	90.6																																			
85	91.3	91.5																																			
90	91.8	91.7																																			
100	92.0	92.2																																			
110	91.8	93.2																																			
120	92.6	93.3																																			
132	93.4	94.0																																			
140	93.5	94.2																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		SNDPF1000		Temperature 25°C																																																				
Item		Efficiency (by Load Power)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 85V - - - □ - - - Input Volt. 100V - · - ○ - · - - Input Volt. 132V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>50</td><td>74.7</td><td>75.3</td><td>76.2</td></tr> <tr><td>150</td><td>86.9</td><td>87.5</td><td>87.8</td></tr> <tr><td>300</td><td>90.0</td><td>91.4</td><td>92.0</td></tr> <tr><td>450</td><td>91.0</td><td>91.8</td><td>93.2</td></tr> <tr><td>600</td><td>91.9</td><td>92.3</td><td>93.6</td></tr> <tr><td>750</td><td>91.2</td><td>92.3</td><td>93.8</td></tr> <tr><td>850</td><td>91.2</td><td>92.7</td><td>94.0</td></tr> <tr><td>1000</td><td>91.5</td><td>92.2</td><td>94.0</td></tr> <tr><td>1100</td><td>91.0</td><td>92.0</td><td>93.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Power [W]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	50	74.7	75.3	76.2	150	86.9	87.5	87.8	300	90.0	91.4	92.0	450	91.0	91.8	93.2	600	91.9	92.3	93.6	750	91.2	92.3	93.8	850	91.2	92.7	94.0	1000	91.5	92.2	94.0	1100	91.0	92.0	93.9	--	-	-	-	--	-	-	-		
Load Power [W]	Efficiency [%]																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
50	74.7	75.3	76.2																																																					
150	86.9	87.5	87.8																																																					
300	90.0	91.4	92.0																																																					
450	91.0	91.8	93.2																																																					
600	91.9	92.3	93.6																																																					
750	91.2	92.3	93.8																																																					
850	91.2	92.7	94.0																																																					
1000	91.5	92.2	94.0																																																					
1100	91.0	92.0	93.9																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDPF1000		Temperature 25°C																																	
Item		Power Factor (by Input Voltage)		Testing Circuitry Figure A																																	
Object																																					
1.Graph			2.Values																																		
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>0.991</td> <td>0.992</td> </tr> <tr> <td>85</td> <td>0.990</td> <td>0.998</td> </tr> <tr> <td>90</td> <td>0.989</td> <td>0.997</td> </tr> <tr> <td>100</td> <td>0.987</td> <td>0.995</td> </tr> <tr> <td>110</td> <td>0.984</td> <td>0.994</td> </tr> <tr> <td>120</td> <td>0.986</td> <td>0.992</td> </tr> <tr> <td>132</td> <td>0.978</td> <td>0.991</td> </tr> <tr> <td>140</td> <td>0.972</td> <td>0.989</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.991	0.992	85	0.990	0.998	90	0.989	0.997	100	0.987	0.995	110	0.984	0.994	120	0.986	0.992	132	0.978	0.991	140	0.972	0.989	--	-	-
Input Voltage [V]	Power Factor																																				
	Load 50%	Load 100%																																			
80	0.991	0.992																																			
85	0.990	0.998																																			
90	0.989	0.997																																			
100	0.987	0.995																																			
110	0.984	0.994																																			
120	0.986	0.992																																			
132	0.978	0.991																																			
140	0.972	0.989																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		SNDPF1000		Temperature 25°C																																																				
Item		Power Factor (by Load Power)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 85V - - - □ - - - Input Volt. 100V - · - ○ - · - - Input Volt. 132V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>50</td><td>0.885</td><td>0.850</td><td>0.668</td></tr> <tr><td>150</td><td>0.961</td><td>0.962</td><td>0.905</td></tr> <tr><td>300</td><td>0.980</td><td>0.984</td><td>0.966</td></tr> <tr><td>450</td><td>0.987</td><td>0.984</td><td>0.972</td></tr> <tr><td>600</td><td>0.993</td><td>0.990</td><td>0.982</td></tr> <tr><td>750</td><td>0.994</td><td>0.991</td><td>0.985</td></tr> <tr><td>850</td><td>0.996</td><td>0.993</td><td>0.987</td></tr> <tr><td>1000</td><td>0.996</td><td>0.995</td><td>0.991</td></tr> <tr><td>1100</td><td>0.995</td><td>0.995</td><td>0.991</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Power [W]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	50	0.885	0.850	0.668	150	0.961	0.962	0.905	300	0.980	0.984	0.966	450	0.987	0.984	0.972	600	0.993	0.990	0.982	750	0.994	0.991	0.985	850	0.996	0.993	0.987	1000	0.996	0.995	0.991	1100	0.995	0.995	0.991	--	-	-	-	--	-	-	-
Load Power [W]	Power Factor																																																							
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
50	0.885	0.850	0.668																																																					
150	0.961	0.962	0.905																																																					
300	0.980	0.984	0.966																																																					
450	0.987	0.984	0.972																																																					
600	0.993	0.990	0.982																																																					
750	0.994	0.991	0.985																																																					
850	0.996	0.993	0.987																																																					
1000	0.996	0.995	0.991																																																					
1100	0.995	0.995	0.991																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								




Model		SNDPF1000	Temperature 25°C Testing Circuitry Figure A
Item		Inrush Current	
Object		_____	



Input Voltage 100 V
 Frequency 60 Hz
 Load 0 %

Primary inrush current 18.9 A
 Secondary inrush current 20.1 A



Note: The current of the input surge to a built-in noise filter (0.2ms or less) is excluded.



COSEL		
Model	SNDPF1000	Temperature 25°C Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

1.Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.08	0.09	0.12
(B)IEC60950-1	0.08	0.09	0.12

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 240 [V]	Input Volt. 264 [V]
(B)IEC60950-1	-	-	-


2.Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



Model	SNDPF1000	Temperature	25°C
Item	Line Regulation	Testing Circuitry	Figure A
Object	+360V 1000W		

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	371.339	365.332
85	372.044	367.044
90	372.654	368.365
100	373.717	370.150
110	374.421	371.601
120	374.960	372.643
132	375.503	373.615
140	375.771	374.136
--	-	-




<p>Model SNDPF1000</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Load Regulation																																																				
Object	+360V 1000W																																																				
<p>1.Graph</p> <p> —△— Input Volt. 85V ---□--- Input Volt. 100V -·-○-·- Input Volt. 132V </p> <p>Output Voltage [V]</p> <p>Load Power [W]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Power [W]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>376.707</td><td>377.018</td><td>377.369</td></tr> <tr><td>50</td><td>376.100</td><td>376.585</td><td>377.081</td></tr> <tr><td>150</td><td>375.194</td><td>375.903</td><td>376.714</td></tr> <tr><td>300</td><td>373.854</td><td>374.942</td><td>376.199</td></tr> <tr><td>450</td><td>372.386</td><td>373.972</td><td>375.679</td></tr> <tr><td>600</td><td>370.955</td><td>372.890</td><td>375.091</td></tr> <tr><td>750</td><td>369.505</td><td>371.909</td><td>374.567</td></tr> <tr><td>850</td><td>368.570</td><td>371.191</td><td>374.200</td></tr> <tr><td>1000</td><td>367.044</td><td>370.150</td><td>373.615</td></tr> <tr><td>1100</td><td>365.813</td><td>369.385</td><td>373.177</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Power [W]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	376.707	377.018	377.369	50	376.100	376.585	377.081	150	375.194	375.903	376.714	300	373.854	374.942	376.199	450	372.386	373.972	375.679	600	370.955	372.890	375.091	750	369.505	371.909	374.567	850	368.570	371.191	374.200	1000	367.044	370.150	373.615	1100	365.813	369.385	373.177	--	-	-	-
Load Power [W]	Output Voltage [V]																																																				
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																		
0	376.707	377.018	377.369																																																		
50	376.100	376.585	377.081																																																		
150	375.194	375.903	376.714																																																		
300	373.854	374.942	376.199																																																		
450	372.386	373.972	375.679																																																		
600	370.955	372.890	375.091																																																		
750	369.505	371.909	374.567																																																		
850	368.570	371.191	374.200																																																		
1000	367.044	370.150	373.615																																																		
1100	365.813	369.385	373.177																																																		
--	-	-	-																																																		




Model	SNDPF1000	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+360V 1000W		


Input Volt. 100 V
 Cycle 1000 ms



Min. Load (0A) ←→
 Load 100% (1000W)




50 ms/div




50 ms/div

Min. Load (0A) ←→
 Load 50% (500W)



50 ms/div




50 ms/div



Model	SNDPF1000
Item	Ripple Voltage (by Load Current)
Object	+360V1000W

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Power [W]	Ripple Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0	0.2	0.2
150	2.8	3.0
300	4.4	4.8
450	6.4	6.8
600	8.0	8.8
750	10.0	10.4
850	10.8	11.6
1000	12.8	13.6
1100	14.0	14.4
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
Ripple Voltage is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.




Fig. Complex Ripple Wave Form




Model	SNDPF1000
Item	Ambient Temperature Drift
Object	+360V 1000W

Testing Circuitry Figure A

1. Graph

—△— Input Volt. 85V
 - - - □ - - - Input Volt. 100V
 - · - ○ - · - - Input Volt. 132V



2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-40	367.730	370.415	373.317
-20	367.750	370.427	373.437
0	367.591	370.389	373.542
25	367.044	370.150	373.615
40	366.872	370.032	373.561
55	366.467	369.764	373.462
70	365.999	369.503	373.397
80	365.706	369.355	373.375
90	365.437	369.214	373.374
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL		Testing Circuitry Figure A
Model	SNDPF1000	
Item	Output Voltage Accuracy	
Object	+360V 1000W	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 80°C

Input Voltage : 85 - 132V

Load Current : 0 - 1000W

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [V]	Ration [%]
Maximum Voltage	80	132	0	377.633	±6	±0.1
Minimum Voltage	80	85	2.78	365.706		




COSEL																								
Model	SNDPF1000																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+360V 1000W																							
<p>1. Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>370.125</td></tr> <tr><td>0.5</td><td>376.875</td></tr> <tr><td>1.0</td><td>376.875</td></tr> <tr><td>2.0</td><td>376.867</td></tr> <tr><td>3.0</td><td>376.869</td></tr> <tr><td>4.0</td><td>376.871</td></tr> <tr><td>5.0</td><td>376.869</td></tr> <tr><td>6.0</td><td>376.871</td></tr> <tr><td>7.0</td><td>376.872</td></tr> <tr><td>8.0</td><td>376.870</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	370.125	0.5	376.875	1.0	376.875	2.0	376.867	3.0	376.869	4.0	376.871	5.0	376.869	6.0	376.871	7.0	376.872	8.0	376.870
Time since start [H]	Output Voltage [V]																							
0.0	370.125																							
0.5	376.875																							
1.0	376.875																							
2.0	376.867																							
3.0	376.869																							
4.0	376.871																							
5.0	376.869																							
6.0	376.871																							
7.0	376.872																							
8.0	376.870																							



Model	SNDPF1000	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+360V 1000W		


1. Graph

Input Volt. 100 V



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
	50 %	3.0	201.0	204.0	174.0	491.0
	100 %	2.6	201.4	204.0	85.0	285.0






COSEL																																								
Model	SNDPF1000	Testing Circuitry Figure A																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+360V 1000W																																							
<p>1. Graph</p> <p style="text-align: center;">Ambient Temperature [°C]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>79</td><td>79</td></tr> <tr><td>-20</td><td>77</td><td>78</td></tr> <tr><td>0</td><td>76</td><td>76</td></tr> <tr><td>25</td><td>74</td><td>74</td></tr> <tr><td>40</td><td>72</td><td>73</td></tr> <tr><td>55</td><td>71</td><td>72</td></tr> <tr><td>70</td><td>69</td><td>71</td></tr> <tr><td>80</td><td>68</td><td>70</td></tr> <tr><td>90</td><td>67</td><td>69</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	79	79	-20	77	78	0	76	76	25	74	74	40	72	73	55	71	72	70	69	71	80	68	70	90	67	69	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	79	79																																						
-20	77	78																																						
0	76	76																																						
25	74	74																																						
40	72	73																																						
55	71	72																																						
70	69	71																																						
80	68	70																																						
90	67	69																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model	SNDPF1000
Item	Oversvoltage Protection
Object	+360V1000W

Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 85[V]	Input Volt. 132[V]
-40	436.0	435.5
-20	435.3	435.3
0	435.2	435.0
25	434.5	434.7
40	434.2	434.2
55	433.6	433.6
70	433.5	433.5
80	433.4	433.4
90	433.3	433.3
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)