

TEST DATA OF SNTUNS100F05

Regulated DC Power Supply

July 23, 2013

Approved by : Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita Design Engineer
Satoshi Kinoshita

CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - ○- Input Volt. 230V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.109</td><td>0.169</td><td>0.194</td></tr> <tr><td>2.0</td><td>0.202</td><td>0.184</td><td>0.219</td></tr> <tr><td>4.0</td><td>0.309</td><td>0.221</td><td>0.240</td></tr> <tr><td>8.0</td><td>0.541</td><td>0.327</td><td>0.313</td></tr> <tr><td>12.0</td><td>0.784</td><td>0.437</td><td>0.406</td></tr> <tr><td>16.0</td><td>1.030</td><td>0.549</td><td>0.504</td></tr> <tr><td>20.0</td><td>1.289</td><td>0.669</td><td>0.608</td></tr> <tr><td>22.0</td><td>1.424</td><td>0.729</td><td>0.662</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.109	0.169	0.194	2.0	0.202	0.184	0.219	4.0	0.309	0.221	0.240	8.0	0.541	0.327	0.313	12.0	0.784	0.437	0.406	16.0	1.030	0.549	0.504	20.0	1.289	0.669	0.608	22.0	1.424	0.729	0.662	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.109	0.169	0.194																																																			
2.0	0.202	0.184	0.219																																																			
4.0	0.309	0.221	0.240																																																			
8.0	0.541	0.327	0.313																																																			
12.0	0.784	0.437	0.406																																																			
16.0	1.030	0.549	0.504																																																			
20.0	1.289	0.669	0.608																																																			
22.0	1.424	0.729	0.662																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□-- Input Volt. 200V - - ○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7.0</td><td>7.6</td><td>7.7</td></tr> <tr><td>5.0</td><td>25.0</td><td>26.0</td><td>26.5</td></tr> <tr><td>10.0</td><td>52.0</td><td>53.0</td><td>53.5</td></tr> <tr><td>15.0</td><td>79.0</td><td>80.0</td><td>80.5</td></tr> <tr><td>20.0</td><td>106.0</td><td>107.0</td><td>107.5</td></tr> <tr><td>22.0</td><td>120.0</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0.0	7.0	7.6	7.7	5.0	25.0	26.0	26.5	10.0	52.0	53.0	53.5	15.0	79.0	80.0	80.5	20.0	106.0	107.0	107.5	22.0	120.0	-	-																							
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																			
0.0	7.0	7.6	7.7																																																			
5.0	25.0	26.0	26.5																																																			
10.0	52.0	53.0	53.5																																																			
15.0	79.0	80.0	80.5																																																			
20.0	106.0	107.0	107.5																																																			
22.0	120.0	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7.0</td><td>7.6</td><td>7.7</td></tr> <tr><td>2.0</td><td>17.9</td><td>18.3</td><td>18.4</td></tr> <tr><td>4.0</td><td>29.0</td><td>29.0</td><td>29.1</td></tr> <tr><td>8.0</td><td>52.3</td><td>51.5</td><td>51.5</td></tr> <tr><td>12.0</td><td>76.3</td><td>74.5</td><td>74.4</td></tr> <tr><td>16.0</td><td>101.2</td><td>98.1</td><td>97.9</td></tr> <tr><td>20.0</td><td>127.3</td><td>122.6</td><td>122.2</td></tr> <tr><td>22.0</td><td>140.8</td><td>135.3</td><td>134.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	7.0	7.6	7.7	2.0	17.9	18.3	18.4	4.0	29.0	29.0	29.1	8.0	52.3	51.5	51.5	12.0	76.3	74.5	74.4	16.0	101.2	98.1	97.9	20.0	127.3	122.6	122.2	22.0	140.8	135.3	134.8	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	7.0	7.6	7.7																																																			
2.0	17.9	18.3	18.4																																																			
4.0	29.0	29.0	29.1																																																			
8.0	52.3	51.5	51.5																																																			
12.0	76.3	74.5	74.4																																																			
16.0	101.2	98.1	97.9																																																			
20.0	127.3	122.6	122.2																																																			
22.0	140.8	135.3	134.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																													
Item	Efficiency (by Input Voltage)																															
Object	—																															
1. Graph			2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (44 to 100) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing from approximately 77% at 80V to about 81% at 280V. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>80</td><td>77.6</td><td>77.3</td></tr> <tr><td>85</td><td>78.1</td><td>78.0</td></tr> <tr><td>100</td><td>79.1</td><td>79.6</td></tr> <tr><td>120</td><td>79.8</td><td>80.9</td></tr> <tr><td>200</td><td>80.5</td><td>82.6</td></tr> <tr><td>230</td><td>80.5</td><td>82.8</td></tr> <tr><td>264</td><td>80.8</td><td>83.1</td></tr> <tr><td>280</td><td>81.6</td><td>82.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	80	77.6	77.3	85	78.1	78.0	100	79.1	79.6	120	79.8	80.9	200	80.5	82.6	230	80.5	82.8	264	80.8	83.1	280	81.6	82.9	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																														
80	77.6	77.3																														
85	78.1	78.0																														
100	79.1	79.6																														
120	79.8	80.9																														
200	80.5	82.6																														
230	80.5	82.8																														
264	80.8	83.1																														
280	81.6	82.9																														
--	-	-																														
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [Efficiency %]</th> <th>200V [Efficiency %]</th> <th>230V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>2.0</td><td>56.6</td><td>55.4</td><td>55.2</td></tr> <tr><td>4.0</td><td>69.7</td><td>69.7</td><td>69.4</td></tr> <tr><td>8.0</td><td>77.3</td><td>78.5</td><td>78.5</td></tr> <tr><td>12.0</td><td>79.6</td><td>81.5</td><td>81.6</td></tr> <tr><td>16.0</td><td>80.0</td><td>82.5</td><td>82.7</td></tr> <tr><td>20.0</td><td>79.6</td><td>82.6</td><td>82.8</td></tr> <tr><td>22.0</td><td>79.1</td><td>82.3</td><td>82.6</td></tr> </tbody> </table>			Load Current [A]	100V [Efficiency %]	200V [Efficiency %]	230V [Efficiency %]	2.0	56.6	55.4	55.2	4.0	69.7	69.7	69.4	8.0	77.3	78.5	78.5	12.0	79.6	81.5	81.6	16.0	80.0	82.5	82.7	20.0	79.6	82.6	82.8	22.0	79.1	82.3	82.6																			
Load Current [A]	100V [Efficiency %]	200V [Efficiency %]	230V [Efficiency %]																																																			
2.0	56.6	55.4	55.2																																																			
4.0	69.7	69.7	69.4																																																			
8.0	77.3	78.5	78.5																																																			
12.0	79.6	81.5	81.6																																																			
16.0	80.0	82.5	82.7																																																			
20.0	79.6	82.6	82.8																																																			
22.0	79.1	82.3	82.6																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.0</td><td>56.6</td><td>55.4</td><td>55.2</td></tr> <tr><td>4.0</td><td>69.7</td><td>69.7</td><td>69.4</td></tr> <tr><td>8.0</td><td>77.3</td><td>78.5</td><td>78.5</td></tr> <tr><td>12.0</td><td>79.6</td><td>81.5</td><td>81.6</td></tr> <tr><td>16.0</td><td>80.0</td><td>82.5</td><td>82.7</td></tr> <tr><td>20.0</td><td>79.6</td><td>82.6</td><td>82.8</td></tr> <tr><td>22.0</td><td>79.1</td><td>82.3</td><td>82.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	2.0	56.6	55.4	55.2	4.0	69.7	69.7	69.4	8.0	77.3	78.5	78.5	12.0	79.6	81.5	81.6	16.0	80.0	82.5	82.7	20.0	79.6	82.6	82.8	22.0	79.1	82.3	82.6	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
2.0	56.6	55.4	55.2																																																			
4.0	69.7	69.7	69.4																																																			
8.0	77.3	78.5	78.5																																																			
12.0	79.6	81.5	81.6																																																			
16.0	80.0	82.5	82.7																																																			
20.0	79.6	82.6	82.8																																																			
22.0	79.1	82.3	82.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																
Item	Power Factor (by Input Voltage)																																		
Object	—																																		
1. Graph			2. Values																																
<p>Graph showing Power Factor vs Input Voltage for SNTUNS100F05 at 25°C. The Y-axis is Power Factor (0.4 to 1.0) and the X-axis is Input Voltage [V] (50 to 300). Two curves are shown: Load 50% (dashed line with squares) and Load 100% (solid line with triangles). Both curves show a decreasing trend as input voltage increases. A slanted line indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>0.982</td> <td>0.994</td> </tr> <tr> <td>85</td> <td>0.979</td> <td>0.992</td> </tr> <tr> <td>100</td> <td>0.968</td> <td>0.988</td> </tr> <tr> <td>120</td> <td>0.950</td> <td>0.979</td> </tr> <tr> <td>200</td> <td>0.826</td> <td>0.917</td> </tr> <tr> <td>230</td> <td>0.761</td> <td>0.874</td> </tr> <tr> <td>264</td> <td>0.675</td> <td>0.818</td> </tr> <tr> <td>280</td> <td>0.437</td> <td>0.677</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.982	0.994	85	0.979	0.992	100	0.968	0.988	120	0.950	0.979	200	0.826	0.917	230	0.761	0.874	264	0.675	0.818	280	0.437	0.677	--	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
80	0.982	0.994																																	
85	0.979	0.992																																	
100	0.968	0.988																																	
120	0.950	0.979																																	
200	0.826	0.917																																	
230	0.761	0.874																																	
264	0.675	0.818																																	
280	0.437	0.677																																	
--	-	-																																	




Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																																				
Item	Power Factor (by Load Current)																																																						
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor (100V)</th> <th>Power Factor (200V)</th> <th>Power Factor (230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.644</td><td>-</td><td>-</td></tr> <tr><td>2.0</td><td>0.887</td><td>-</td><td>-</td></tr> <tr><td>4.0</td><td>0.938</td><td>-</td><td>-</td></tr> <tr><td>8.0</td><td>0.967</td><td>0.787</td><td>0.714</td></tr> <tr><td>12.0</td><td>0.973</td><td>0.853</td><td>0.797</td></tr> <tr><td>16.0</td><td>0.983</td><td>0.893</td><td>0.844</td></tr> <tr><td>20.0</td><td>0.988</td><td>0.917</td><td>0.874</td></tr> <tr><td>22.0</td><td>0.989</td><td>0.928</td><td>0.886</td></tr> </tbody> </table>				Load Current [A]	Power Factor (100V)	Power Factor (200V)	Power Factor (230V)	0.0	0.644	-	-	2.0	0.887	-	-	4.0	0.938	-	-	8.0	0.967	0.787	0.714	12.0	0.973	0.853	0.797	16.0	0.983	0.893	0.844	20.0	0.988	0.917	0.874	22.0	0.989	0.928	0.886															
Load Current [A]	Power Factor (100V)	Power Factor (200V)	Power Factor (230V)																																																				
0.0	0.644	-	-																																																				
2.0	0.887	-	-																																																				
4.0	0.938	-	-																																																				
8.0	0.967	0.787	0.714																																																				
12.0	0.973	0.853	0.797																																																				
16.0	0.983	0.893	0.844																																																				
20.0	0.988	0.917	0.874																																																				
22.0	0.989	0.928	0.886																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.644</td><td>0.224</td><td>0.173</td></tr> <tr><td>2.0</td><td>0.887</td><td>0.497</td><td>0.366</td></tr> <tr><td>4.0</td><td>0.938</td><td>0.656</td><td>0.528</td></tr> <tr><td>8.0</td><td>0.967</td><td>0.787</td><td>0.714</td></tr> <tr><td>12.0</td><td>0.973</td><td>0.853</td><td>0.797</td></tr> <tr><td>16.0</td><td>0.983</td><td>0.893</td><td>0.844</td></tr> <tr><td>20.0</td><td>0.988</td><td>0.917</td><td>0.874</td></tr> <tr><td>22.0</td><td>0.989</td><td>0.928</td><td>0.886</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.644	0.224	0.173	2.0	0.887	0.497	0.366	4.0	0.938	0.656	0.528	8.0	0.967	0.787	0.714	12.0	0.973	0.853	0.797	16.0	0.983	0.893	0.844	20.0	0.988	0.917	0.874	22.0	0.989	0.928	0.886	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	0.644	0.224	0.173																																																				
2.0	0.887	0.497	0.366																																																				
4.0	0.938	0.656	0.528																																																				
8.0	0.967	0.787	0.714																																																				
12.0	0.973	0.853	0.797																																																				
16.0	0.983	0.893	0.844																																																				
20.0	0.988	0.917	0.874																																																				
22.0	0.989	0.928	0.886																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	





Model	SNTUNS100F05	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
IEC60950-1	Both phases	0.18	0.38	0.50	Operation
	One of phases	0.32	0.74	0.96	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+5V20A																																	
1. Graph		2. Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>5.061</td> <td>5.059</td> </tr> <tr> <td>85</td> <td>5.061</td> <td>5.059</td> </tr> <tr> <td>100</td> <td>5.062</td> <td>5.059</td> </tr> <tr> <td>120</td> <td>5.062</td> <td>5.059</td> </tr> <tr> <td>200</td> <td>5.062</td> <td>5.059</td> </tr> <tr> <td>230</td> <td>5.062</td> <td>5.059</td> </tr> <tr> <td>264</td> <td>5.062</td> <td>5.059</td> </tr> <tr> <td>280</td> <td>5.062</td> <td>5.060</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	80	5.061	5.059	85	5.061	5.059	100	5.062	5.059	120	5.062	5.059	200	5.062	5.059	230	5.062	5.059	264	5.062	5.059	280	5.062	5.060	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
80	5.061	5.059																																
85	5.061	5.059																																
100	5.062	5.059																																
120	5.062	5.059																																
200	5.062	5.059																																
230	5.062	5.059																																
264	5.062	5.059																																
280	5.062	5.060																																
--	-	-																																

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+5V20A																																																				
1.Graph	<p>—▲— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.065</td><td>5.066</td><td>5.066</td></tr> <tr><td>2.0</td><td>5.065</td><td>5.065</td><td>5.065</td></tr> <tr><td>4.0</td><td>5.064</td><td>5.064</td><td>5.064</td></tr> <tr><td>8.0</td><td>5.063</td><td>5.063</td><td>5.063</td></tr> <tr><td>12.0</td><td>5.061</td><td>5.061</td><td>5.062</td></tr> <tr><td>16.0</td><td>5.060</td><td>5.060</td><td>5.060</td></tr> <tr><td>20.0</td><td>5.059</td><td>5.059</td><td>5.059</td></tr> <tr><td>22.0</td><td>5.058</td><td>5.058</td><td>5.058</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	5.065	5.066	5.066	2.0	5.065	5.065	5.065	4.0	5.064	5.064	5.064	8.0	5.063	5.063	5.063	12.0	5.061	5.061	5.062	16.0	5.060	5.060	5.060	20.0	5.059	5.059	5.059	22.0	5.058	5.058	5.058	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	5.065	5.066	5.066																																																		
2.0	5.065	5.065	5.065																																																		
4.0	5.064	5.064	5.064																																																		
8.0	5.063	5.063	5.063																																																		
12.0	5.061	5.061	5.062																																																		
16.0	5.060	5.060	5.060																																																		
20.0	5.059	5.059	5.059																																																		
22.0	5.058	5.058	5.058																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL

Model	SNTUNS100F05	Temperature	25°C																																					
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure C																																					
Object	+5V20A																																							
1. Graph			2. Values																																					
<p>—△— Input Volt. 100V -○- Input Volt. 200V</p>																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>30</td><td>30</td></tr> <tr><td>2.0</td><td>28</td><td>28</td></tr> <tr><td>4.0</td><td>28</td><td>28</td></tr> <tr><td>8.0</td><td>28</td><td>26</td></tr> <tr><td>12.0</td><td>28</td><td>26</td></tr> <tr><td>16.0</td><td>28</td><td>26</td></tr> <tr><td>20.0</td><td>28</td><td>28</td></tr> <tr><td>22.0</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	30	30	2.0	28	28	4.0	28	28	8.0	28	26	12.0	28	26	16.0	28	26	20.0	28	28	22.0	30	30	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.0	30	30																																						
2.0	28	28																																						
4.0	28	28																																						
8.0	28	26																																						
12.0	28	26																																						
16.0	28	26																																						
20.0	28	28																																						
22.0	30	30																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>T1: Due to AC Input Line T2: Due to Switching</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL


Model	SNTUNS100F05	Temperature Testing Circuitry 25°C Figure C																																						
Item	Ripple-Noise																																							
Object	+5V20A																																							
1. Graph		2. Values																																						
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The graph shows two horizontal lines at approximately 40 mV for both input voltages, indicating low noise levels across the load current range. A slanted line indicates the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>36</td><td>34</td></tr> <tr><td>2</td><td>34</td><td>34</td></tr> <tr><td>4</td><td>34</td><td>34</td></tr> <tr><td>8</td><td>34</td><td>34</td></tr> <tr><td>12</td><td>34</td><td>34</td></tr> <tr><td>16</td><td>34</td><td>34</td></tr> <tr><td>20</td><td>34</td><td>36</td></tr> <tr><td>22</td><td>36</td><td>36</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0	36	34	2	34	34	4	34	34	8	34	34	12	34	34	16	34	34	20	34	36	22	36	36	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0	36	34																																						
2	34	34																																						
4	34	34																																						
8	34	34																																						
12	34	34																																						
16	34	34																																						
20	34	36																																						
22	36	36																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>Diagram illustrating a Complex Ripple Wave Form. The diagram shows a waveform with two distinct components: T1 (Due to AC Input Line) and T2 (Due to Switching). The total Ripple-Noise is indicated as [mVp-p].</p>																																						
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	SNTUNS100F05
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V20A

1. Graph

--□-- Input Volt. 100V
—△— Input Volt. 200V



Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	120	105
-20	80	75
-10	60	60
0	40	40
25	30	30
50	30	30
70	30	30
85	30	30
95	30	30
100	30	30
--	-	-

COSEL

Model	SNTUNS100F05
Item	Ambient Temperature Drift
Object	+5V20A
1. Graph	
<p style="text-align: center;"> —△— Input Volt. 100V ---□--- Input Volt. 200V ---○--- Input Volt. 230V </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	
Note: Slanted line shows the range of the rated ambient temperature.	

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-30	5.046	5.046	5.046
-20	5.048	5.048	5.048
-10	5.049	5.049	5.049
0	5.051	5.051	5.051
25	5.059	5.059	5.059
50	5.066	5.067	5.067
70	5.072	5.072	5.072
85	5.074	5.074	5.074
95	5.076	5.076	5.076
100	5.076	5.076	5.076
--	-	-	-



Model	SNTUNS100F05	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+5V20A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 85 - 264V

Load Current : 0 - 20A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	95	200	0	5.079	± 16	± 0.3
Minimum Voltage	-20	85	20	5.048		

COSEL

Model	SNTUNS100F05
Item	Time Lapse Drift
Object	+5V20A

1.Graph



* The characteristic of AC200V is equal.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Time since start [H]	Output Voltage [V]
0.0	5.057
0.5	5.061
1.0	5.061
2.0	5.061
3.0	5.061
4.0	5.061
5.0	5.061
6.0	5.061
7.0	5.061
8.0	5.061

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry Object	25°C Figure A
Item	Rise and Fall Time		
Object	+5V20A		


1. Graph



2. Values

[ms]

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		140.0	1.5	141.5	25.6	1.8
200 V		54.0	1.5	55.5	25.5	1.9



COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time																																		
Object	+5V20A																																		
1. Graph			2. Values																																
<p>Hold-Up Time [ms]</p> <p>Input Voltage [V]</p> <p>Legend: --- □--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>80</td><td>51</td><td>26</td></tr> <tr><td>85</td><td>51</td><td>26</td></tr> <tr><td>100</td><td>51</td><td>26</td></tr> <tr><td>120</td><td>51</td><td>26</td></tr> <tr><td>200</td><td>51</td><td>26</td></tr> <tr><td>230</td><td>51</td><td>26</td></tr> <tr><td>264</td><td>51</td><td>26</td></tr> <tr><td>280</td><td>52</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	51	26	85	51	26	100	51	26	120	51	26	200	51	26	230	51	26	264	51	26	280	52	25	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
80	51	26																																	
85	51	26																																	
100	51	26																																	
120	51	26																																	
200	51	26																																	
230	51	26																																	
264	51	26																																	
280	52	25																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+5V20A																																																					
1.Graph	<p>—△— Input Volt. 100V - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.0</td><td>200</td><td>200</td><td>200</td></tr> <tr><td>4.0</td><td>117</td><td>117</td><td>117</td></tr> <tr><td>8.0</td><td>63</td><td>62</td><td>62</td></tr> <tr><td>12.0</td><td>42</td><td>42</td><td>42</td></tr> <tr><td>16.0</td><td>31</td><td>32</td><td>31</td></tr> <tr><td>20.0</td><td>24</td><td>25</td><td>24</td></tr> <tr><td>22.0</td><td>22</td><td>22</td><td>22</td></tr> </tbody> </table>			Load Current [A]	100V [ms]	200V [ms]	230V [ms]	0.0	-	-	-	2.0	200	200	200	4.0	117	117	117	8.0	63	62	62	12.0	42	42	42	16.0	31	32	31	20.0	24	25	24	22.0	22	22	22															
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																			
0.0	-	-	-																																																			
2.0	200	200	200																																																			
4.0	117	117	117																																																			
8.0	63	62	62																																																			
12.0	42	42	42																																																			
16.0	31	32	31																																																			
20.0	24	25	24																																																			
22.0	22	22	22																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.0</td><td>200</td><td>200</td><td>200</td></tr> <tr><td>4.0</td><td>117</td><td>117</td><td>117</td></tr> <tr><td>8.0</td><td>63</td><td>62</td><td>62</td></tr> <tr><td>12.0</td><td>42</td><td>42</td><td>42</td></tr> <tr><td>16.0</td><td>31</td><td>32</td><td>31</td></tr> <tr><td>20.0</td><td>24</td><td>25</td><td>24</td></tr> <tr><td>22.0</td><td>22</td><td>22</td><td>22</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	2.0	200	200	200	4.0	117	117	117	8.0	63	62	62	12.0	42	42	42	16.0	31	32	31	20.0	24	25	24	22.0	22	22	22	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
2.0	200	200	200																																																			
4.0	117	117	117																																																			
8.0	63	62	62																																																			
12.0	42	42	42																																																			
16.0	31	32	31																																																			
20.0	24	25	24																																																			
22.0	22	22	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNTUNS100F05
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V20A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	69	67
-20	68	67
-10	68	67
0	68	67
25	67	67
50	69	70
70	70	72
85	69	70
95	72	73
100	74	75
--	-	-

COSEL

Model	SNTUNS100F05	Temperature Testing Circuitry	25°C Figure A																																												
Item	Overcurrent Protection																																														
Object	+5V20A																																														
1. Graph			2. Values																																												
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>20.78</td><td>20.70</td></tr> <tr><td>4.75</td><td>24.20</td><td>24.20</td></tr> <tr><td>4.50</td><td>24.55</td><td>24.54</td></tr> <tr><td>4.00</td><td>25.38</td><td>25.36</td></tr> <tr><td>3.50</td><td>26.20</td><td>26.18</td></tr> <tr><td>3.00</td><td>27.12</td><td>27.11</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 200[V]	5.00	20.78	20.70	4.75	24.20	24.20	4.50	24.55	24.54	4.00	25.38	25.36	3.50	26.20	26.18	3.00	27.12	27.11	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																														
	Input Volt. 100[V]	Input Volt. 200[V]																																													
5.00	20.78	20.70																																													
4.75	24.20	24.20																																													
4.50	24.55	24.54																																													
4.00	25.38	25.36																																													
3.50	26.20	26.18																																													
3.00	27.12	27.11																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNTUNS100F05																																								
Item	Overvoltage Protection	Testing Circuitry Figure A																																							
Object	+5V20A																																								
1.Graph			2.Values																																						
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p>			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>6.77</td><td>6.77</td></tr> <tr><td>-20</td><td>6.77</td><td>6.77</td></tr> <tr><td>-10</td><td>6.78</td><td>6.78</td></tr> <tr><td>0</td><td>6.78</td><td>6.78</td></tr> <tr><td>25</td><td>6.78</td><td>6.78</td></tr> <tr><td>50</td><td>6.79</td><td>6.79</td></tr> <tr><td>70</td><td>6.79</td><td>6.80</td></tr> <tr><td>85</td><td>6.79</td><td>6.79</td></tr> <tr><td>95</td><td>6.79</td><td>6.79</td></tr> <tr><td>100</td><td>6.79</td><td>6.79</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 200[V]	-30	6.77	6.77	-20	6.77	6.77	-10	6.78	6.78	0	6.78	6.78	25	6.78	6.78	50	6.79	6.79	70	6.79	6.80	85	6.79	6.79	95	6.79	6.79	100	6.79	6.79	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 100[V]	Input Volt. 200[V]																																							
-30	6.77	6.77																																							
-20	6.77	6.77																																							
-10	6.78	6.78																																							
0	6.78	6.78																																							
25	6.78	6.78																																							
50	6.79	6.79																																							
70	6.79	6.80																																							
85	6.79	6.79																																							
95	6.79	6.79																																							
100	6.79	6.79																																							
--	-	-																																							

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (IEC60950-1)




Figure C