

TEST DATA OF SNTUNS50F12

Regulated DC Power Supply

July 23, 2013

Approved by : Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	—																																																					
1. Graph		2. Values																																																				
<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.036</td><td>0.064</td><td>0.073</td></tr> <tr> <td>0.4</td><td>0.087</td><td>0.081</td><td>0.096</td></tr> <tr> <td>0.8</td><td>0.142</td><td>0.096</td><td>0.110</td></tr> <tr> <td>1.6</td><td>0.258</td><td>0.146</td><td>0.139</td></tr> <tr> <td>2.4</td><td>0.373</td><td>0.199</td><td>0.182</td></tr> <tr> <td>3.2</td><td>0.486</td><td>0.253</td><td>0.228</td></tr> <tr> <td>4.0</td><td>0.606</td><td>0.309</td><td>0.277</td></tr> <tr> <td>4.2</td><td>0.636</td><td>0.323</td><td>0.289</td></tr> <tr> <td>4.6</td><td>0.698</td><td>0.352</td><td>0.314</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.036	0.064	0.073	0.4	0.087	0.081	0.096	0.8	0.142	0.096	0.110	1.6	0.258	0.146	0.139	2.4	0.373	0.199	0.182	3.2	0.486	0.253	0.228	4.0	0.606	0.309	0.277	4.2	0.636	0.323	0.289	4.6	0.698	0.352	0.314	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.036	0.064	0.073																																																			
0.4	0.087	0.081	0.096																																																			
0.8	0.142	0.096	0.110																																																			
1.6	0.258	0.146	0.139																																																			
2.4	0.373	0.199	0.182																																																			
3.2	0.486	0.253	0.228																																																			
4.0	0.606	0.309	0.277																																																			
4.2	0.636	0.323	0.289																																																			
4.6	0.698	0.352	0.314																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A																																															
Item	Input Power (by Load Current)																																																	
Object	_____																																																	
1. Graph		2. Values																																																
<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.71</td><td>1.63</td><td>1.64</td></tr> <tr><td>0.4</td><td>7.82</td><td>7.90</td><td>7.90</td></tr> <tr><td>0.8</td><td>13.41</td><td>13.54</td><td>13.54</td></tr> <tr><td>1.6</td><td>24.71</td><td>24.55</td><td>24.61</td></tr> <tr><td>2.4</td><td>36.28</td><td>35.56</td><td>35.59</td></tr> <tr><td>3.2</td><td>47.69</td><td>46.40</td><td>46.40</td></tr> <tr><td>4.0</td><td>59.72</td><td>57.60</td><td>57.50</td></tr> <tr><td>4.2</td><td>62.81</td><td>60.50</td><td>60.40</td></tr> <tr><td>4.6</td><td>69.03</td><td>66.30</td><td>66.10</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	1.71	1.63	1.64	0.4	7.82	7.90	7.90	0.8	13.41	13.54	13.54	1.6	24.71	24.55	24.61	2.4	36.28	35.56	35.59	3.2	47.69	46.40	46.40	4.0	59.72	57.60	57.50	4.2	62.81	60.50	60.40	4.6	69.03	66.30	66.10	--	-	-	-	--	-	-	-		
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																															
0.0	1.71	1.63	1.64																																															
0.4	7.82	7.90	7.90																																															
0.8	13.41	13.54	13.54																																															
1.6	24.71	24.55	24.61																																															
2.4	36.28	35.56	35.59																																															
3.2	47.69	46.40	46.40																																															
4.0	59.72	57.60	57.50																																															
4.2	62.81	60.50	60.40																																															
4.6	69.03	66.30	66.10																																															
--	-	-	-																																															
--	-	-	-																																															
<p>Note: Slanted line shows the range of the rated load current.</p>																																																		

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry 25°C Figure A																													
Item	Efficiency (by Input Voltage)																														
Object	—																														
1. Graph		2. Values																													
<p>The graph plots Efficiency [%] on the y-axis (44 to 100) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>80</td><td>78.3</td><td>78.1</td></tr> <tr><td>85</td><td>78.7</td><td>78.9</td></tr> <tr><td>100</td><td>79.6</td><td>80.5</td></tr> <tr><td>120</td><td>80.2</td><td>81.7</td></tr> <tr><td>200</td><td>80.8</td><td>83.5</td></tr> <tr><td>230</td><td>80.7</td><td>83.7</td></tr> <tr><td>264</td><td>80.9</td><td>83.8</td></tr> <tr><td>280</td><td>82.1</td><td>84.0</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	80	78.3	78.1	85	78.7	78.9	100	79.6	80.5	120	80.2	81.7	200	80.8	83.5	230	80.7	83.7	264	80.9	83.8	280	82.1	84.0	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																													
80	78.3	78.1																													
85	78.7	78.9																													
100	79.6	80.5																													
120	80.2	81.7																													
200	80.8	83.5																													
230	80.7	83.7																													
264	80.9	83.8																													
280	82.1	84.0																													
--	-	-																													

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1. Graph		2. Values																																																				
<p>The graph plots Efficiency [%] on the y-axis (44 to 100) against Load Current [A] on the x-axis (0.0 to 5.0). Three data series are shown: Input Volt. 100V (solid line with open triangle markers), Input Volt. 200V (dashed line with open square markers), and Input Volt. 230V (dash-dot line with open circle markers). All series show an upward trend. A slanted line is drawn through the data points, indicating the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.4</td><td>61.6</td><td>61.0</td><td>61.0</td></tr> <tr><td>0.8</td><td>71.9</td><td>71.2</td><td>71.2</td></tr> <tr><td>1.6</td><td>78.0</td><td>78.6</td><td>78.4</td></tr> <tr><td>2.4</td><td>79.7</td><td>81.3</td><td>81.2</td></tr> <tr><td>3.2</td><td>80.7</td><td>83.0</td><td>82.9</td></tr> <tr><td>4.0</td><td>80.6</td><td>83.5</td><td>83.7</td></tr> <tr><td>4.2</td><td>80.5</td><td>83.5</td><td>83.7</td></tr> <tr><td>4.6</td><td>80.2</td><td>83.5</td><td>83.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.4	61.6	61.0	61.0	0.8	71.9	71.2	71.2	1.6	78.0	78.6	78.4	2.4	79.7	81.3	81.2	3.2	80.7	83.0	82.9	4.0	80.6	83.5	83.7	4.2	80.5	83.5	83.7	4.6	80.2	83.5	83.7	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
0.4	61.6	61.0	61.0																																																			
0.8	71.9	71.2	71.2																																																			
1.6	78.0	78.6	78.4																																																			
2.4	79.7	81.3	81.2																																																			
3.2	80.7	83.0	82.9																																																			
4.0	80.6	83.5	83.7																																																			
4.2	80.5	83.5	83.7																																																			
4.6	80.2	83.5	83.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL




Model	SNTUNS50F12																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line with squares) Load 100% (solid line with triangles) 																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>0.981</td><td>0.995</td></tr> <tr> <td>85</td><td>0.978</td><td>0.992</td></tr> <tr> <td>100</td><td>0.968</td><td>0.988</td></tr> <tr> <td>120</td><td>0.964</td><td>0.989</td></tr> <tr> <td>200</td><td>0.878</td><td>0.937</td></tr> <tr> <td>230</td><td>0.837</td><td>0.910</td></tr> <tr> <td>264</td><td>0.691</td><td>0.867</td></tr> <tr> <td>280</td><td>0.511</td><td>0.771</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	80	0.981	0.995	85	0.978	0.992	100	0.968	0.988	120	0.964	0.989	200	0.878	0.937	230	0.837	0.910	264	0.691	0.867	280	0.511	0.771	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
80	0.981	0.995																																
85	0.978	0.992																																
100	0.968	0.988																																
120	0.964	0.989																																
200	0.878	0.937																																
230	0.837	0.910																																
264	0.691	0.867																																
280	0.511	0.771																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.475</td><td>0.127</td><td>0.097</td></tr> <tr><td>0.4</td><td>0.896</td><td>0.490</td><td>0.359</td></tr> <tr><td>0.8</td><td>0.944</td><td>0.709</td><td>0.536</td></tr> <tr><td>1.6</td><td>0.959</td><td>0.844</td><td>0.772</td></tr> <tr><td>2.4</td><td>0.972</td><td>0.892</td><td>0.852</td></tr> <tr><td>3.2</td><td>0.981</td><td>0.919</td><td>0.885</td></tr> <tr><td>4.0</td><td>0.987</td><td>0.932</td><td>0.904</td></tr> <tr><td>4.2</td><td>0.988</td><td>0.937</td><td>0.910</td></tr> <tr><td>4.6</td><td>0.990</td><td>0.942</td><td>0.916</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.475	0.127	0.097	0.4	0.896	0.490	0.359	0.8	0.944	0.709	0.536	1.6	0.959	0.844	0.772	2.4	0.972	0.892	0.852	3.2	0.981	0.919	0.885	4.0	0.987	0.932	0.904	4.2	0.988	0.937	0.910	4.6	0.990	0.942	0.916	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.475	0.127	0.097																																																			
0.4	0.896	0.490	0.359																																																			
0.8	0.944	0.709	0.536																																																			
1.6	0.959	0.844	0.772																																																			
2.4	0.972	0.892	0.852																																																			
3.2	0.981	0.919	0.885																																																			
4.0	0.987	0.932	0.904																																																			
4.2	0.988	0.937	0.910																																																			
4.6	0.990	0.942	0.916																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	—	





Model	SNTUNS50F12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
IEC60950-1	Both phases	0.18	0.38	0.46	Operation
	One of phases	0.32	0.72	0.90	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+12V4.2A																																		
1.Graph			2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line) Load 100% (Solid line) 			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td> <td>12.049</td> <td>12.043</td> </tr> <tr> <td>85</td> <td>12.049</td> <td>12.044</td> </tr> <tr> <td>100</td> <td>12.050</td> <td>12.044</td> </tr> <tr> <td>120</td> <td>12.050</td> <td>12.044</td> </tr> <tr> <td>200</td> <td>12.049</td> <td>12.044</td> </tr> <tr> <td>230</td> <td>12.050</td> <td>12.044</td> </tr> <tr> <td>264</td> <td>12.050</td> <td>12.044</td> </tr> <tr> <td>280</td> <td>12.050</td> <td>12.045</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	80	12.049	12.043	85	12.049	12.044	100	12.050	12.044	120	12.050	12.044	200	12.049	12.044	230	12.050	12.044	264	12.050	12.044	280	12.050	12.045	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
80	12.049	12.043																																	
85	12.049	12.044																																	
100	12.050	12.044																																	
120	12.050	12.044																																	
200	12.049	12.044																																	
230	12.050	12.044																																	
264	12.050	12.044																																	
280	12.050	12.045																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A																																																		
Item	Load Regulation																																																				
Object	+12V4.2A																																																				
1. Graph		—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○- - Input Volt. 230V																																																			
			2. Values																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>12.055</td> <td>12.055</td> <td>12.056</td> </tr> <tr> <td>0.4</td> <td>12.054</td> <td>12.054</td> <td>12.055</td> </tr> <tr> <td>0.8</td> <td>12.053</td> <td>12.053</td> <td>12.054</td> </tr> <tr> <td>1.6</td> <td>12.051</td> <td>12.051</td> <td>12.051</td> </tr> <tr> <td>2.4</td> <td>12.048</td> <td>12.049</td> <td>12.049</td> </tr> <tr> <td>3.2</td> <td>12.047</td> <td>12.047</td> <td>12.047</td> </tr> <tr> <td>4.0</td> <td>12.044</td> <td>12.044</td> <td>12.045</td> </tr> <tr> <td>4.2</td> <td>12.044</td> <td>12.044</td> <td>12.044</td> </tr> <tr> <td>4.6</td> <td>12.043</td> <td>12.043</td> <td>12.043</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	12.055	12.055	12.056	0.4	12.054	12.054	12.055	0.8	12.053	12.053	12.054	1.6	12.051	12.051	12.051	2.4	12.048	12.049	12.049	3.2	12.047	12.047	12.047	4.0	12.044	12.044	12.045	4.2	12.044	12.044	12.044	4.6	12.043	12.043	12.043	--	-	-	-	--	-	-	-		
Load Current [A]		Output Voltage [V]																																																			
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	12.055	12.055	12.056																																																		
0.4	12.054	12.054	12.055																																																		
0.8	12.053	12.053	12.054																																																		
1.6	12.051	12.051	12.051																																																		
2.4	12.048	12.049	12.049																																																		
3.2	12.047	12.047	12.047																																																		
4.0	12.044	12.044	12.045																																																		
4.2	12.044	12.044	12.044																																																		
4.6	12.043	12.043	12.043																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL

Model	SNTUNS50F12																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure C																																						
Object	+12V4.2A																																							
1.Graph																																								
<p style="text-align: center;"> Input Volt. 100V Input Volt. 200V </p>																																								
2.Values																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>34</td><td>44</td></tr> <tr><td>0.4</td><td>24</td><td>30</td></tr> <tr><td>0.8</td><td>26</td><td>32</td></tr> <tr><td>1.6</td><td>30</td><td>32</td></tr> <tr><td>2.4</td><td>44</td><td>48</td></tr> <tr><td>3.2</td><td>28</td><td>30</td></tr> <tr><td>4.0</td><td>38</td><td>40</td></tr> <tr><td>4.2</td><td>40</td><td>42</td></tr> <tr><td>4.6</td><td>46</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	34	44	0.4	24	30	0.8	26	32	1.6	30	32	2.4	44	48	3.2	28	30	4.0	38	40	4.2	40	42	4.6	46	50	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.0	34	44																																						
0.4	24	30																																						
0.8	26	32																																						
1.6	30	32																																						
2.4	44	48																																						
3.2	28	30																																						
4.0	38	40																																						
4.2	40	42																																						
4.6	46	50																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								


COSEL

Model	SNTUNS50F12	Temperature Testing Circuitry 25°C Figure C																																						
Item	Ripple-Noise																																							
Object	+12V4.2A																																							
1.Graph		2.Values																																						
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The graph shows two curves: one for Input Volt. 100V (solid line with open circles) and one for Input Volt. 200V (dashed line with open circles). The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.0 to 5.0 A. A slanted line indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>40</td><td>46</td></tr> <tr><td>0.4</td><td>32</td><td>36</td></tr> <tr><td>0.8</td><td>32</td><td>36</td></tr> <tr><td>1.6</td><td>36</td><td>38</td></tr> <tr><td>2.4</td><td>50</td><td>56</td></tr> <tr><td>3.2</td><td>38</td><td>38</td></tr> <tr><td>4.0</td><td>46</td><td>48</td></tr> <tr><td>4.2</td><td>48</td><td>50</td></tr> <tr><td>4.6</td><td>58</td><td>56</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	40	46	0.4	32	36	0.8	32	36	1.6	36	38	2.4	50	56	3.2	38	38	4.0	46	48	4.2	48	50	4.6	58	56	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.0	40	46																																						
0.4	32	36																																						
0.8	32	36																																						
1.6	36	38																																						
2.4	50	56																																						
3.2	38	38																																						
4.0	46	48																																						
4.2	48	50																																						
4.6	58	56																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>Diagram illustrating a Complex Ripple Wave Form. The diagram shows a waveform with two types of noise components: T1 (due to AC Input Line) and T2 (due to Switching). The total noise is labeled as Ripple-Noise [mVp-p].</p>																																						
<p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	SNTUNS50F12	Testing Circuitry Figure C																													
Item	Ripple Voltage (by Ambient Temp.)																														
Object	+12V4.2A																														
1. Graph		2. Values																													
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C] for SNTUNS50F12 at +12V4.2A load. The graph shows two data series: Input Volt. 100V (dashed line with square markers) and Input Volt. 200V (solid line with triangle markers). Both series show a decrease in ripple voltage as ambient temperature increases from -40°C to 100°C. A slanted line indicates the rated ambient temperature range.</p> <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>-40</td><td>110</td><td>110</td></tr> <tr><td>-20</td><td>80</td><td>80</td></tr> <tr><td>0</td><td>55</td><td>60</td></tr> <tr><td>25</td><td>40</td><td>45</td></tr> <tr><td>50</td><td>30</td><td>35</td></tr> <tr><td>70</td><td>30</td><td>30</td></tr> <tr><td>85</td><td>30</td><td>30</td></tr> <tr><td>95</td><td>30</td><td>30</td></tr> <tr><td>100</td><td>30</td><td>30</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	-40	110	110	-20	80	80	0	55	60	25	40	45	50	30	35	70	30	30	85	30	30	95	30	30	100	30	30
Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																													
-40	110	110																													
-20	80	80																													
0	55	60																													
25	40	45																													
50	30	35																													
70	30	30																													
85	30	30																													
95	30	30																													
100	30	30																													
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																															

COSEL

Model	SNTUNS50F12	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+12V4.2A																																																						
1.Graph	<p style="text-align: center;"> Input Volt. 100V Input Volt. 200V Input Volt. 230V </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>12.004</td> <td>12.004</td> <td>12.005</td> </tr> <tr> <td>-20</td> <td>12.014</td> <td>12.015</td> <td>12.015</td> </tr> <tr> <td>-10</td> <td>12.024</td> <td>12.024</td> <td>12.024</td> </tr> <tr> <td>0</td> <td>12.032</td> <td>12.033</td> <td>12.033</td> </tr> <tr> <td>25</td> <td>12.044</td> <td>12.044</td> <td>12.044</td> </tr> <tr> <td>50</td> <td>12.062</td> <td>12.061</td> <td>12.062</td> </tr> <tr> <td>70</td> <td>12.066</td> <td>12.066</td> <td>12.066</td> </tr> <tr> <td>85</td> <td>12.064</td> <td>12.064</td> <td>12.064</td> </tr> <tr> <td>95</td> <td>12.063</td> <td>12.062</td> <td>12.063</td> </tr> <tr> <td>100</td> <td>12.062</td> <td>12.062</td> <td>12.062</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-30	12.004	12.004	12.005	-20	12.014	12.015	12.015	-10	12.024	12.024	12.024	0	12.032	12.033	12.033	25	12.044	12.044	12.044	50	12.062	12.061	12.062	70	12.066	12.066	12.066	85	12.064	12.064	12.064	95	12.063	12.062	12.063	100	12.062	12.062	12.062	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
-30	12.004	12.004	12.005																																																				
-20	12.014	12.015	12.015																																																				
-10	12.024	12.024	12.024																																																				
0	12.032	12.033	12.033																																																				
25	12.044	12.044	12.044																																																				
50	12.062	12.061	12.062																																																				
70	12.066	12.066	12.066																																																				
85	12.064	12.064	12.064																																																				
95	12.063	12.062	12.063																																																				
100	12.062	12.062	12.062																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated ambient temperature.



Model	SNTUNS50F12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V4.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 95°C

Input Voltage : 85 - 264V

Load Current : 0 - 4.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	70	264	0	12.080	±33	±0.3
Minimum Voltage	-20	85	4.2	12.014		



Model	SNTUNS50F12
Item	Time Lapse Drift
Object	+12V4.2A

1.Graph



Temperature 25°C
Testing Circuitry Figure A

2.Values


Time since start [H]	Output Voltage [V]
0.0	12.039
0.5	12.046
1.0	12.046
2.0	12.047
3.0	12.047
4.0	12.047
5.0	12.047
6.0	12.048
7.0	12.048
8.0	12.048

* The characteristic of AC200V is equal.

COSEL


Model	SNTUNS50F12	Temperature Testing Circuitry	25°C Figure A
Item	Rise and Fall Time		
Object	+12V4.2A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		94.5	3.5	98.0	26.3	38.3	
200 V		37.8	3.5	41.3	25.8	38.8	



COSEL

Model	SNTUNS50F12	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+12V4.2A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>92</td><td>19</td></tr> <tr> <td>85</td><td>92</td><td>19</td></tr> <tr> <td>100</td><td>92</td><td>19</td></tr> <tr> <td>120</td><td>92</td><td>19</td></tr> <tr> <td>200</td><td>92</td><td>19</td></tr> <tr> <td>230</td><td>92</td><td>19</td></tr> <tr> <td>264</td><td>91</td><td>18</td></tr> <tr> <td>280</td><td>91</td><td>18</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	92	19	85	92	19	100	92	19	120	92	19	200	92	19	230	92	19	264	91	18	280	91	18	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
80	92	19																																	
85	92	19																																	
100	92	19																																	
120	92	19																																	
200	92	19																																	
230	92	19																																	
264	91	18																																	
280	91	18																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	SNTUNS50F12	Temperature 25°C Testing Circuitry Figure A		
Item	Instantaneous Interruption Compensation			
Object	+12V4.2A			
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V <p>Y-axis: Instantaneous Compensation Time [ms]</p> <p>X-axis: Load Current [A]</p>	2.Values		
Note:	Slanted line shows the range of the rated load current.			

COSEL


<p>Model SNTUNS50F12</p> <p>Item Minimum Input Voltage for Regulated Output Voltage</p> <p>Object +12V4.2A</p>	<p>Testing Circuitry Figure A</p>																																						
<p>1. Graph</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line with open squares) Load 100% (Solid line with solid triangles) 	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>56</td> <td>58</td> </tr> <tr> <td>-20</td> <td>57</td> <td>59</td> </tr> <tr> <td>-10</td> <td>57</td> <td>59</td> </tr> <tr> <td>0</td> <td>57</td> <td>60</td> </tr> <tr> <td>25</td> <td>59</td> <td>62</td> </tr> <tr> <td>50</td> <td>59</td> <td>60</td> </tr> <tr> <td>70</td> <td>58</td> <td>60</td> </tr> <tr> <td>85</td> <td>57</td> <td>59</td> </tr> <tr> <td>95</td> <td>57</td> <td>59</td> </tr> <tr> <td>100</td> <td>57</td> <td>59</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-30	56	58	-20	57	59	-10	57	59	0	57	60	25	59	62	50	59	60	70	58	60	85	57	59	95	57	59	100	57	59	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-30	56	58																																					
-20	57	59																																					
-10	57	59																																					
0	57	60																																					
25	59	62																																					
50	59	60																																					
70	58	60																																					
85	57	59																																					
95	57	59																																					
100	57	59																																					
--	-	-																																					

Model	SNTUNS50F12	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Overcurrent Protection																																																						
Object	+12V4.2A																																																						
1. Graph		2. Values																																																					
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p> <table border="1"> <thead> <tr> <th>Output Voltage [V]</th> <th>Load Current [A] (Input Volt. 100[V])</th> <th>Load Current [A] (Input Volt. 200[V])</th> </tr> </thead> <tbody> <tr><td>12</td><td>4.65</td><td>4.89</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A] (Input Volt. 100[V])	Load Current [A] (Input Volt. 200[V])	12	4.65	4.89	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A] (Input Volt. 100[V])	Load Current [A] (Input Volt. 200[V])																																																					
12	4.65	4.89																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
--	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when the output voltage is from 12V to 0V.</p>																																																							

COSEL

Model	SNTUNS50F12
Item	Overvoltage Protection
Object	+12V4.2A

1.Graph




Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-30	15.19	15.19
-20	15.19	15.19
-10	15.19	15.19
0	15.26	15.26
25	15.26	15.26
50	15.26	15.26
70	15.26	15.26
85	15.26	15.25
95	15.25	15.25
100	15.25	15.25
--	-	-

COSEL



Data Acquisition/Control Unit

Figure A




Figure B (IEC60950-1)




Figure C