



DATA SHEET		Date	01-Nov-11
Model	SPLFA150F-12	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	T.MIYAKE




Frequency MHz	Line Phase	Reading dB(μV)		Factor dB	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/ Fail	Remark
		QP	AV		QP	AV	QP	AV	QP	AV		
0.17423	VB	36.0	31.2	10.2	46.2	41.4	64.8	54.8	18.6	13.4	Pass	
0.17775	VA	37.6	32.7	10.2	47.8	42.9	64.6	54.6	16.8	11.7	Pass	
14.56810	VB	27.1	21.4	10.6	37.7	32.0	60.0	50.0	22.3	18.0	Pass	
14.56965	VA	33.3	26.0	10.7	44.0	36.7	60.0	50.0	16.0	13.3	Pass	
21.42830	VB	27.8	24.5	10.9	38.7	35.4	60.0	50.0	21.3	14.6	Pass	
21.43400	VA	26.8	22.7	11.0	37.8	33.7	60.0	50.0	22.2	16.3	Pass	



Frequency MHz	Polariz ation	Reading dB(μV)		Space Loss dB	Level dB(mW)		Limit dB(mW)	Margin dB	Pass/ Fail	Height cm	Angle deg	Remark
		QP	AV		QP	AV						
54.57000	V	59.2	-25.4		33.8	40.0	40.0	6.2	Pass	118	296	
114.45400	V	46.6	-19.8		26.8	40.0	40.0	13.2	Pass	106	126	
182.24800	H	48.6	-22.3		26.3	40.0	40.0	13.7	Pass	153	142	
183.26400	V	46.5	-22.3		24.2	40.0	40.0	15.8	Pass	101	76	

DATA SHEET		Date	01-Nov-11
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	45 %RH
		Tested by	T.MIYAKE

1. Line conduction



2. Radiated emission

