



DATA SHEET				Date	25-May-11
Model	SPLFA30F-12			Temp.	25 degreeC
Test	EMI			Humid.	40 %RH
	Line conduction & Radiated emission			Tested by	H.Kitamura




Frequency MHz	Line Phas	Reading dB(μV)		Factor dB	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/ Fail	Remark
		QP	AV		QP	AV	QP	AV	QP	AV		
0.51799	VA	31.2	28.2	10.1	41.3	38.3	56	46	14.7	7.7	Pass	
6.23638	VA	28.4	25	10.3	38.7	35.3	60	50	21.3	14.7	Pass	
18.06445	VA	24.1	19.5	10.9	35	30.4	60	50	25	19.6	Pass	



Frequency MHz	Polarization	Reading dB(μV)		Space Loss dB	Level dB(mW)		Limit dB(mW)	Margin dB	Pass/ Fail	Height cm	Angle deg	Remark
		QP	AV		QP	AV						
121	V	48.2	-19.5		28.7		50	21.3	Pass	159	18	
170.6	H	52.1	-22		30.1		50	19.9	Pass	159	185	

DATA SHEET		Date	25-May-11
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	H.Kitamura

1. Line conduction



2. Radiated emission

