



DATA SHEET				Date	17-May-11
Model	SPLFA50F-24			Temp.	25 degreeC
Test	EMI			Humid.	40 %RH
	Line conduction & Radiated emission			Tested by	H.Kitamura




Frequency MHz	Line Phas	Reading dB(uV)		Factor dB	Level dB(uV)		Limit dB(uV)		Margin dB		Pass/ Fail	Remark
		QP	AV		QP	AV	QP	AV	QP	AV		
0.17126	VA	33.9	26.9	10.2	44.1	37.1	64.9	54.9	20.8	17.8	Pass	
22.3862	VA	19.5	18.3	11	30.5	29.3	60	50	29.5	20.7	Pass	
23.14775	VA	20.3	18	11	31.3	29	60	50	28.7	21	Pass	



Frequency MHz	Polarization	Reading dB(uV)		Space Loss dB	Level dB(mW)		Margin dB	Pass/ Fail	Height cm	Angle deg	Remark
		QP	AV		QP	AV					
38.921	V	59.2		-18	41.2	50	8.8	Pass	106	5	

DATA SHEET		Date	17-May-11
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI	Humid.	40 %RH
	Line conduction & Radiated emission	Tested by	H.Kitamura

1. Line conduction



2. Radiated emission

