

TEST DATA OF STMGFS152412

Regulated DC Power Supply
January 28, 2013

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple Voltage (by Load Current)	8
9.Ripple-Noise	9
10.Ripple Voltage (by Ambient Temperature)	10
11.Ambient Temperature Drift	11
12.Output Voltage Accuracy	12
13.Time Lapse Drift	13
14.Rise and Fall Time	14
15.Minimum Input Voltage for Regulated Output Voltage	15
16.Overcurrent Protection	16
17.Figure of Testing Circuitry	17

(Final Page 17)



Model		STMGFS152412		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object		_____																																																																																		
1.Graph			—△— Load 100% - - □ - - Load 50% - - ○ - - Load 0%	2.Values																																																																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.001</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.002</td><td>0.001</td><td>0.001</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>7.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.003</td></tr> <tr><td>8.1</td><td>0.089</td><td>1.117</td><td>0.002</td></tr> <tr><td>8.3</td><td>0.088</td><td>1.087</td><td>2.198</td></tr> <tr><td>8.5</td><td>0.086</td><td>1.059</td><td>2.166</td></tr> <tr><td>9.0</td><td>0.082</td><td>0.999</td><td>2.034</td></tr> <tr><td>12.0</td><td>0.068</td><td>0.748</td><td>1.475</td></tr> <tr><td>18.0</td><td>0.053</td><td>0.499</td><td>0.976</td></tr> <tr><td>24.0</td><td>0.045</td><td>0.380</td><td>0.736</td></tr> <tr><td>36.0</td><td>0.035</td><td>0.259</td><td>0.497</td></tr> <tr><td>40.0</td><td>0.033</td><td>0.236</td><td>0.447</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.001	0.000	0.000	4.0	0.002	0.001	0.001	6.0	0.002	0.002	0.002	7.0	0.002	0.002	0.002	8.0	0.002	0.002	0.003	8.1	0.089	1.117	0.002	8.3	0.088	1.087	2.198	8.5	0.086	1.059	2.166	9.0	0.082	0.999	2.034	12.0	0.068	0.748	1.475	18.0	0.053	0.499	0.976	24.0	0.045	0.380	0.736	36.0	0.035	0.259	0.497	40.0	0.033	0.236	0.447	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
2.0	0.001	0.000	0.000																																																																																	
4.0	0.002	0.001	0.001																																																																																	
6.0	0.002	0.002	0.002																																																																																	
7.0	0.002	0.002	0.002																																																																																	
8.0	0.002	0.002	0.003																																																																																	
8.1	0.089	1.117	0.002																																																																																	
8.3	0.088	1.087	2.198																																																																																	
8.5	0.086	1.059	2.166																																																																																	
9.0	0.082	0.999	2.034																																																																																	
12.0	0.068	0.748	1.475																																																																																	
18.0	0.053	0.499	0.976																																																																																	
24.0	0.045	0.380	0.736																																																																																	
36.0	0.035	0.259	0.497																																																																																	
40.0	0.033	0.236	0.447																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model		STMGFS152412		Temperature 25°C																																																																														
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 9V ---□--- Input Volt. 12V -·*·- Input Volt. 18V -·○·- Input Volt. 24V -·◇·- Input Volt. 36V 		2.Values																																																																														
<p style="font-size: small;">Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.082</td><td>0.068</td><td>0.053</td><td>0.045</td><td>0.035</td></tr> <tr><td>0.26</td><td>0.439</td><td>0.336</td><td>0.230</td><td>0.177</td><td>0.124</td></tr> <tr><td>0.52</td><td>0.807</td><td>0.609</td><td>0.408</td><td>0.311</td><td>0.214</td></tr> <tr><td>0.78</td><td>1.197</td><td>0.888</td><td>0.592</td><td>0.449</td><td>0.306</td></tr> <tr><td>1.04</td><td>1.599</td><td>1.201</td><td>0.781</td><td>0.587</td><td>0.400</td></tr> <tr><td>1.30</td><td>2.034</td><td>1.475</td><td>0.976</td><td>0.736</td><td>0.497</td></tr> <tr><td>1.43</td><td>2.228</td><td>1.631</td><td>1.073</td><td>0.802</td><td>0.544</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.082	0.068	0.053	0.045	0.035	0.26	0.439	0.336	0.230	0.177	0.124	0.52	0.807	0.609	0.408	0.311	0.214	0.78	1.197	0.888	0.592	0.449	0.306	1.04	1.599	1.201	0.781	0.587	0.400	1.30	2.034	1.475	0.976	0.736	0.497	1.43	2.228	1.631	1.073	0.802	0.544	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	0.082	0.068	0.053	0.045	0.035																																																																													
0.26	0.439	0.336	0.230	0.177	0.124																																																																													
0.52	0.807	0.609	0.408	0.311	0.214																																																																													
0.78	1.197	0.888	0.592	0.449	0.306																																																																													
1.04	1.599	1.201	0.781	0.587	0.400																																																																													
1.30	2.034	1.475	0.976	0.736	0.497																																																																													
1.43	2.228	1.631	1.073	0.802	0.544																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



<p>Model STMGFS152412</p>		<p>Temperature 25°C</p>																																																																														
<p>Item Input Power (by Load Current)</p>		<p>Testing Circuitry Figure A</p>																																																																														
<p>Object _____</p>																																																																																
<p>1.Graph</p> <p> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V </p> <p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.74</td><td>0.82</td><td>0.95</td><td>1.08</td><td>1.27</td></tr> <tr><td>0.26</td><td>3.95</td><td>4.01</td><td>4.12</td><td>4.24</td><td>4.45</td></tr> <tr><td>0.52</td><td>7.28</td><td>7.29</td><td>7.35</td><td>7.44</td><td>7.69</td></tr> <tr><td>0.78</td><td>10.76</td><td>10.66</td><td>10.68</td><td>10.74</td><td>11.01</td></tr> <tr><td>1.04</td><td>14.42</td><td>14.17</td><td>14.06</td><td>14.12</td><td>14.38</td></tr> <tr><td>1.30</td><td>18.23</td><td>17.77</td><td>17.53</td><td>17.55</td><td>17.82</td></tr> <tr><td>1.43</td><td>20.14</td><td>19.60</td><td>19.30</td><td>19.25</td><td>19.52</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.74	0.82	0.95	1.08	1.27	0.26	3.95	4.01	4.12	4.24	4.45	0.52	7.28	7.29	7.35	7.44	7.69	0.78	10.76	10.66	10.68	10.74	11.01	1.04	14.42	14.17	14.06	14.12	14.38	1.30	18.23	17.77	17.53	17.55	17.82	1.43	20.14	19.60	19.30	19.25	19.52	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																															
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																											
0.00	0.74	0.82	0.95	1.08	1.27																																																																											
0.26	3.95	4.01	4.12	4.24	4.45																																																																											
0.52	7.28	7.29	7.35	7.44	7.69																																																																											
0.78	10.76	10.66	10.68	10.74	11.01																																																																											
1.04	14.42	14.17	14.06	14.12	14.38																																																																											
1.30	18.23	17.77	17.53	17.55	17.82																																																																											
1.43	20.14	19.60	19.30	19.25	19.52																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											



<p>Model STMGFS152412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Efficiency (by Input Voltage)</p>																																		
<p>Object _____</p>																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>87.0</td><td>85.5</td></tr> <tr><td>9.0</td><td>87.2</td><td>86.1</td></tr> <tr><td>12.0</td><td>87.8</td><td>88.4</td></tr> <tr><td>15.0</td><td>87.8</td><td>89.4</td></tr> <tr><td>18.0</td><td>87.5</td><td>89.7</td></tr> <tr><td>24.0</td><td>86.6</td><td>89.7</td></tr> <tr><td>30.0</td><td>85.3</td><td>89.2</td></tr> <tr><td>36.0</td><td>84.3</td><td>88.3</td></tr> <tr><td>40.0</td><td>83.4</td><td>87.6</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	87.0	85.5	9.0	87.2	86.1	12.0	87.8	88.4	15.0	87.8	89.4	18.0	87.5	89.7	24.0	86.6	89.7	30.0	85.3	89.2	36.0	84.3	88.3	40.0	83.4	87.6
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	87.0	85.5																																
9.0	87.2	86.1																																
12.0	87.8	88.4																																
15.0	87.8	89.4																																
18.0	87.5	89.7																																
24.0	86.6	89.7																																
30.0	85.3	89.2																																
36.0	84.3	88.3																																
40.0	83.4	87.6																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



Model		STMGFS152412		Temperature 25°C																																																																														
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																																														
Object																																																																																		
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 9V ---□--- Input Volt. 12V ---*--- Input Volt. 18V ---○--- Input Volt. 24V ---◇--- Input Volt. 36V 		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.26</td><td>79.6</td><td>78.5</td><td>76.3</td><td>74.2</td><td>70.5</td></tr> <tr><td>0.52</td><td>86.4</td><td>86.3</td><td>85.6</td><td>84.5</td><td>81.8</td></tr> <tr><td>0.78</td><td>87.7</td><td>88.5</td><td>88.4</td><td>87.8</td><td>85.7</td></tr> <tr><td>1.04</td><td>87.2</td><td>88.8</td><td>89.5</td><td>89.1</td><td>87.5</td></tr> <tr><td>1.30</td><td>86.1</td><td>88.4</td><td>89.7</td><td>89.6</td><td>88.3</td></tr> <tr><td>1.43</td><td>85.8</td><td>88.2</td><td>89.6</td><td>89.9</td><td>88.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	-	-	0.26	79.6	78.5	76.3	74.2	70.5	0.52	86.4	86.3	85.6	84.5	81.8	0.78	87.7	88.5	88.4	87.8	85.7	1.04	87.2	88.8	89.5	89.1	87.5	1.30	86.1	88.4	89.7	89.6	88.3	1.43	85.8	88.2	89.6	89.9	88.6	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.26	79.6	78.5	76.3	74.2	70.5																																																																													
0.52	86.4	86.3	85.6	84.5	81.8																																																																													
0.78	87.7	88.5	88.4	87.8	85.7																																																																													
1.04	87.2	88.8	89.5	89.1	87.5																																																																													
1.30	86.1	88.4	89.7	89.6	88.3																																																																													
1.43	85.8	88.2	89.6	89.9	88.6																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



COSEL																																		
Model	STMGFS152412	Temperature 25°C Testing Circuitry Figure A																																
Item	Line Regulation																																	
Object	+12V1.3A																																	
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>12.071</td><td>12.072</td></tr> <tr><td>9.0</td><td>12.071</td><td>12.073</td></tr> <tr><td>12.0</td><td>12.071</td><td>12.073</td></tr> <tr><td>15.0</td><td>12.071</td><td>12.073</td></tr> <tr><td>18.0</td><td>12.071</td><td>12.073</td></tr> <tr><td>24.0</td><td>12.071</td><td>12.073</td></tr> <tr><td>30.0</td><td>12.072</td><td>12.073</td></tr> <tr><td>36.0</td><td>12.072</td><td>12.073</td></tr> <tr><td>40.0</td><td>12.072</td><td>12.073</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	12.071	12.072	9.0	12.071	12.073	12.0	12.071	12.073	15.0	12.071	12.073	18.0	12.071	12.073	24.0	12.071	12.073	30.0	12.072	12.073	36.0	12.072	12.073	40.0	12.072	12.073
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8.5	12.071	12.072																																
9.0	12.071	12.073																																
12.0	12.071	12.073																																
15.0	12.071	12.073																																
18.0	12.071	12.073																																
24.0	12.071	12.073																																
30.0	12.072	12.073																																
36.0	12.072	12.073																																
40.0	12.072	12.073																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model STMGFS152412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																																													
<p>Item Load Regulation</p>																																																																															
<p>Object +12V1.3A</p>																																																																															
<p>1.Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>---*--- Input Volt. 18V</p> <p>---○--- Input Volt. 24V</p> <p>---◇--- Input Volt. 36V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.080</td><td>12.079</td><td>12.079</td><td>12.078</td><td>12.078</td></tr> <tr><td>0.26</td><td>12.079</td><td>12.078</td><td>12.078</td><td>12.078</td><td>12.077</td></tr> <tr><td>0.52</td><td>12.078</td><td>12.077</td><td>12.077</td><td>12.076</td><td>12.076</td></tr> <tr><td>0.78</td><td>12.076</td><td>12.076</td><td>12.076</td><td>12.075</td><td>12.075</td></tr> <tr><td>1.04</td><td>12.075</td><td>12.075</td><td>12.075</td><td>12.074</td><td>12.074</td></tr> <tr><td>1.30</td><td>12.074</td><td>12.074</td><td>12.073</td><td>12.073</td><td>12.073</td></tr> <tr><td>1.43</td><td>12.073</td><td>12.073</td><td>12.073</td><td>12.072</td><td>12.073</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	12.080	12.079	12.079	12.078	12.078	0.26	12.079	12.078	12.078	12.078	12.077	0.52	12.078	12.077	12.077	12.076	12.076	0.78	12.076	12.076	12.076	12.075	12.075	1.04	12.075	12.075	12.075	12.074	12.074	1.30	12.074	12.074	12.073	12.073	12.073	1.43	12.073	12.073	12.073	12.072	12.073	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																														
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																										
0.00	12.080	12.079	12.079	12.078	12.078																																																																										
0.26	12.079	12.078	12.078	12.078	12.077																																																																										
0.52	12.078	12.077	12.077	12.076	12.076																																																																										
0.78	12.076	12.076	12.076	12.075	12.075																																																																										
1.04	12.075	12.075	12.075	12.074	12.074																																																																										
1.30	12.074	12.074	12.073	12.073	12.073																																																																										
1.43	12.073	12.073	12.073	12.072	12.073																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																															



<p>Model STMGFS152412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple Voltage (by Load Current)</p>																																								
<p>Object +12V1.3A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 9V -·-○-·- Input Volt. 36V</p> </div> <p style="text-align: center;">Ripple Voltage [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>0.26</td><td>15</td><td>15</td></tr> <tr><td>0.52</td><td>15</td><td>15</td></tr> <tr><td>0.78</td><td>15</td><td>15</td></tr> <tr><td>1.04</td><td>15</td><td>20</td></tr> <tr><td>1.30</td><td>20</td><td>20</td></tr> <tr><td>1.43</td><td>20</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	15	15	0.26	15	15	0.52	15	15	0.78	15	15	1.04	15	20	1.30	20	20	1.43	20	20	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.00	15	15																																						
0.26	15	15																																						
0.52	15	15																																						
0.78	15	15																																						
1.04	15	20																																						
1.30	20	20																																						
1.43	20	20																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p style="text-align: center;">Fig.Complex Ripple Wave Form</p>																																								




<p>Model STMGFS152412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +12V1.3A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 9V -·-○-·- Input Volt. 36V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>20</td></tr> <tr><td>0.26</td><td>25</td><td>25</td></tr> <tr><td>0.52</td><td>30</td><td>30</td></tr> <tr><td>0.78</td><td>30</td><td>30</td></tr> <tr><td>1.04</td><td>30</td><td>30</td></tr> <tr><td>1.30</td><td>35</td><td>40</td></tr> <tr><td>1.43</td><td>35</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	20	20	0.26	25	25	0.52	30	30	0.78	30	30	1.04	30	30	1.30	35	40	1.43	35	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.00	20	20																																						
0.26	25	25																																						
0.52	30	30																																						
0.78	30	30																																						
1.04	30	30																																						
1.30	35	40																																						
1.43	35	40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model	STMGFS152412	Testing Circuitry Figure B
Item	Ripple Voltage (by Ambient Temp.)	
Object	+12V1.3A	

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	30	30
-20	25	25
0	25	25
25	20	20
60	20	20
65	20	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.
 Note: Slanted line shows the range of the rated ambient temperature.




Fig.Complex Ripple Noise Wave Form



<p>Model STMGFS152412</p> <p>Item Ambient Temperature Drift</p> <p>Object +12V1.3A</p>		<p>Testing Circuitry Figure A</p>																																																																													
<p>1. Graph</p> <p> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>12.005</td><td>12.006</td><td>12.007</td><td>12.007</td><td>12.008</td></tr> <tr><td>-20</td><td>12.033</td><td>12.034</td><td>12.035</td><td>12.035</td><td>12.035</td></tr> <tr><td>0</td><td>12.054</td><td>12.055</td><td>12.056</td><td>12.056</td><td>12.056</td></tr> <tr><td>10</td><td>12.063</td><td>12.064</td><td>12.064</td><td>12.064</td><td>12.065</td></tr> <tr><td>25</td><td>12.072</td><td>12.073</td><td>12.073</td><td>12.074</td><td>12.073</td></tr> <tr><td>30</td><td>12.075</td><td>12.076</td><td>12.076</td><td>12.076</td><td>12.076</td></tr> <tr><td>40</td><td>12.080</td><td>12.081</td><td>12.081</td><td>12.081</td><td>12.081</td></tr> <tr><td>50</td><td>12.084</td><td>12.084</td><td>12.085</td><td>12.085</td><td>12.085</td></tr> <tr><td>60</td><td>12.086</td><td>12.086</td><td>12.087</td><td>12.087</td><td>12.087</td></tr> <tr><td>65</td><td>12.087</td><td>12.087</td><td>12.087</td><td>12.087</td><td>12.087</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-40	12.005	12.006	12.007	12.007	12.008	-20	12.033	12.034	12.035	12.035	12.035	0	12.054	12.055	12.056	12.056	12.056	10	12.063	12.064	12.064	12.064	12.065	25	12.072	12.073	12.073	12.074	12.073	30	12.075	12.076	12.076	12.076	12.076	40	12.080	12.081	12.081	12.081	12.081	50	12.084	12.084	12.085	12.085	12.085	60	12.086	12.086	12.087	12.087	12.087	65	12.087	12.087	12.087	12.087	12.087	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																														
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																										
-40	12.005	12.006	12.007	12.007	12.008																																																																										
-20	12.033	12.034	12.035	12.035	12.035																																																																										
0	12.054	12.055	12.056	12.056	12.056																																																																										
10	12.063	12.064	12.064	12.064	12.065																																																																										
25	12.072	12.073	12.073	12.074	12.073																																																																										
30	12.075	12.076	12.076	12.076	12.076																																																																										
40	12.080	12.081	12.081	12.081	12.081																																																																										
50	12.084	12.084	12.085	12.085	12.085																																																																										
60	12.086	12.086	12.087	12.087	12.087																																																																										
65	12.087	12.087	12.087	12.087	12.087																																																																										
--	-	-	-	-	-																																																																										



COSEL		
Model	STMGFS152412	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V1.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 9 - 36V

Load Current : 0 - 1.3A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	9	0	12.092	±30	±0.3
Minimum Voltage	-20	9	1.3	12.033		




COSEL																									
Model	STMGFS152412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V1.3A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.067</td></tr> <tr><td>0.5</td><td>12.075</td></tr> <tr><td>1.0</td><td>12.075</td></tr> <tr><td>2.0</td><td>12.075</td></tr> <tr><td>3.0</td><td>12.075</td></tr> <tr><td>4.0</td><td>12.075</td></tr> <tr><td>5.0</td><td>12.075</td></tr> <tr><td>6.0</td><td>12.076</td></tr> <tr><td>7.0</td><td>12.075</td></tr> <tr><td>8.0</td><td>12.075</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.067	0.5	12.075	1.0	12.075	2.0	12.075	3.0	12.075	4.0	12.075	5.0	12.075	6.0	12.076	7.0	12.075	8.0	12.075
Time since start [H]	Output Voltage [V]																								
0.0	12.067																								
0.5	12.075																								
1.0	12.075																								
2.0	12.075																								
3.0	12.075																								
4.0	12.075																								
5.0	12.075																								
6.0	12.076																								
7.0	12.075																								
8.0	12.075																								



Model	STMGFS152412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V1.3A		


1. Graph

Input Volt. 24 V



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	0.7	6.7	7.4	0.3	2.3
100 %	0.7	6.7	7.4	0.2	1.2





COSEL																																								
Model	STMGFS152412																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V1.3A																																							
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>8.0</td><td>8.2</td></tr> <tr><td>-20</td><td>8.1</td><td>8.3</td></tr> <tr><td>0</td><td>8.1</td><td>8.2</td></tr> <tr><td>10</td><td>8.1</td><td>8.3</td></tr> <tr><td>25</td><td>8.1</td><td>8.2</td></tr> <tr><td>30</td><td>8.1</td><td>8.3</td></tr> <tr><td>40</td><td>8.1</td><td>8.3</td></tr> <tr><td>50</td><td>8.1</td><td>8.3</td></tr> <tr><td>60</td><td>8.1</td><td>8.2</td></tr> <tr><td>65</td><td>8.2</td><td>8.2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	8.0	8.2	-20	8.1	8.3	0	8.1	8.2	10	8.1	8.3	25	8.1	8.2	30	8.1	8.3	40	8.1	8.3	50	8.1	8.3	60	8.1	8.2	65	8.2	8.2	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	8.0	8.2																																						
-20	8.1	8.3																																						
0	8.1	8.2																																						
10	8.1	8.3																																						
25	8.1	8.2																																						
30	8.1	8.3																																						
40	8.1	8.3																																						
50	8.1	8.3																																						
60	8.1	8.2																																						
65	8.2	8.2																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



COSEL																																																																																					
Model	STMGFS152412	Temperature 25°C Testing Circuitry Figure A																																																																																			
Item	Overcurrent Protection																																																																																				
Object	+12V1.3A																																																																																				
1.Graph	<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> <p>—△ Input Volt. 9V</p> <p>—□ Input Volt. 12V</p> <p>—* Input Volt. 18V</p> <p>—○ Input Volt. 24V</p> <p>—◇ Input Volt. 36V</p> </div> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>	2.Values																																																																																			
		<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>12.0</td> <td>1.652</td> <td>1.798</td> <td>1.921</td> <td>1.939</td> <td>1.799</td> </tr> <tr> <td>11.4</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>10.8</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>9.6</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>8.4</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>7.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>6.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.8</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3.6</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.4</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.2</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.0	1.652	1.798	1.921	1.939	1.799	11.4	-	-	-	-	-	10.8	-	-	-	-	-	9.6	-	-	-	-	-	8.4	-	-	-	-	-	7.2	-	-	-	-	-	6.0	-	-	-	-	-	4.8	-	-	-	-	-	3.6	-	-	-	-	-	2.4	-	-	-	-	-	1.2	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																
12.0	1.652	1.798	1.921	1.939	1.799																																																																																
11.4	-	-	-	-	-																																																																																
10.8	-	-	-	-	-																																																																																
9.6	-	-	-	-	-																																																																																
8.4	-	-	-	-	-																																																																																
7.2	-	-	-	-	-																																																																																
6.0	-	-	-	-	-																																																																																
4.8	-	-	-	-	-																																																																																
3.6	-	-	-	-	-																																																																																
2.4	-	-	-	-	-																																																																																
1.2	-	-	-	-	-																																																																																
0.0	-	-	-	-	-																																																																																




Figure A




Figure B (Ripple and Ripple noise Characteristic)