

# TEST DATA OF STMGFS154812

Regulated DC Power Supply  
January 26, 2013

Approved by : Takahiro Yoneda  
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita  
Satoshi Kinoshita Design Engineer

**COSEL CO.,LTD.**

CONTENTS

1.Input Current (by Input Voltage) . . . . . 1  
 2.Input Current (by Load Current) . . . . . 2  
 3.Input Power (by Load Current) . . . . . 3  
 4.Efficiency (by Input Voltage) . . . . . 4  
 5.Efficiency (by Load Current) . . . . . 5  
 6.Line Regulation . . . . . 6  
 7.Load Regulation . . . . . 7  
 8.Ripple Voltage (by Load Current) . . . . . 8  
 9.Ripple-Noise . . . . . 9  
 10.Ripple Voltage (by Ambient Temperature) . . . . . 10  
 11.Ambient Temperature Drift . . . . . 11  
 12.Output Voltage Accuracy . . . . . 12  
 13.Time Lapse Drift . . . . . 13  
 14.Rise and Fall Time . . . . . 14  
 15.Minimum Input Voltage for Regulated Output Voltage . . . . . 15  
 16.Overcurrent Protection . . . . . 16  
 17.Figure of Testing Circuitry . . . . . 17

(Final Page 17)



Model		STMGFS154812		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			—△— Load 100% - - -□- - Load 50% - - -○- - Load 0%																																																																																	
			2.Values																																																																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>10.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.039</td><td>0.540</td><td>1.092</td></tr> <tr><td>17.0</td><td>0.038</td><td>0.524</td><td>1.057</td></tr> <tr><td>17.5</td><td>0.037</td><td>0.507</td><td>1.025</td></tr> <tr><td>18.0</td><td>0.037</td><td>0.493</td><td>0.997</td></tr> <tr><td>24.0</td><td>0.031</td><td>0.368</td><td>0.733</td></tr> <tr><td>36.0</td><td>0.024</td><td>0.248</td><td>0.486</td></tr> <tr><td>48.0</td><td>0.021</td><td>0.188</td><td>0.365</td></tr> <tr><td>76.0</td><td>0.016</td><td>0.123</td><td>0.235</td></tr> <tr><td>80.0</td><td>0.016</td><td>0.118</td><td>0.224</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.002	0.002	0.002	10.0	0.002	0.002	0.002	15.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.5	0.039	0.540	1.092	17.0	0.038	0.524	1.057	17.5	0.037	0.507	1.025	18.0	0.037	0.493	0.997	24.0	0.031	0.368	0.733	36.0	0.024	0.248	0.486	48.0	0.021	0.188	0.365	76.0	0.016	0.123	0.235	80.0	0.016	0.118	0.224	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
5.0	0.002	0.002	0.002																																																																																	
10.0	0.002	0.002	0.002																																																																																	
15.0	0.002	0.002	0.002																																																																																	
16.0	0.002	0.002	0.002																																																																																	
16.5	0.039	0.540	1.092																																																																																	
17.0	0.038	0.524	1.057																																																																																	
17.5	0.037	0.507	1.025																																																																																	
18.0	0.037	0.493	0.997																																																																																	
24.0	0.031	0.368	0.733																																																																																	
36.0	0.024	0.248	0.486																																																																																	
48.0	0.021	0.188	0.365																																																																																	
76.0	0.016	0.123	0.235																																																																																	
80.0	0.016	0.118	0.224																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model		STMGFS154812		Temperature 25°C																																																																														
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 18V</li> <li>- - -□- - - Input Volt. 24V</li> <li>- · · * · · - · · Input Volt. 36V</li> <li>- · · ○ · · - · · Input Volt. 48V</li> <li>- - ◇ - - Input Volt. 76V</li> </ul>		2.Values																																																																														
<p>Input Current [A]</p> <p style="text-align: center;">Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.037</td><td>0.031</td><td>0.024</td><td>0.021</td><td>0.016</td></tr> <tr><td>0.26</td><td>0.216</td><td>0.164</td><td>0.113</td><td>0.087</td><td>0.058</td></tr> <tr><td>0.52</td><td>0.398</td><td>0.301</td><td>0.203</td><td>0.154</td><td>0.101</td></tr> <tr><td>0.78</td><td>0.595</td><td>0.441</td><td>0.295</td><td>0.223</td><td>0.145</td></tr> <tr><td>1.04</td><td>0.789</td><td>0.585</td><td>0.390</td><td>0.294</td><td>0.190</td></tr> <tr><td>1.30</td><td>0.997</td><td>0.733</td><td>0.486</td><td>0.365</td><td>0.235</td></tr> <tr><td>1.43</td><td>1.102</td><td>0.816</td><td>0.535</td><td>0.401</td><td>0.258</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.037	0.031	0.024	0.021	0.016	0.26	0.216	0.164	0.113	0.087	0.058	0.52	0.398	0.301	0.203	0.154	0.101	0.78	0.595	0.441	0.295	0.223	0.145	1.04	0.789	0.585	0.390	0.294	0.190	1.30	0.997	0.733	0.486	0.365	0.235	1.43	1.102	0.816	0.535	0.401	0.258	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
		Load Current [A]	Input Current [A]																																																																															
			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																											
		0.00	0.037	0.031	0.024	0.021	0.016																																																																											
		0.26	0.216	0.164	0.113	0.087	0.058																																																																											
		0.52	0.398	0.301	0.203	0.154	0.101																																																																											
		0.78	0.595	0.441	0.295	0.223	0.145																																																																											
		1.04	0.789	0.585	0.390	0.294	0.190																																																																											
		1.30	0.997	0.733	0.486	0.365	0.235																																																																											
		1.43	1.102	0.816	0.535	0.401	0.258																																																																											
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated load current.																																																																																		



Model		STMGFS154812		Temperature 25°C																																																																														
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p>                 —△— Input Volt. 18V                  ---□--- Input Volt. 24V                  ---*--- Input Volt. 36V                  ---○--- Input Volt. 48V                  ---◇--- Input Volt. 76V             </p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.66</td><td>0.74</td><td>0.88</td><td>0.99</td><td>1.23</td></tr> <tr><td>0.26</td><td>3.86</td><td>3.92</td><td>4.05</td><td>4.16</td><td>4.44</td></tr> <tr><td>0.52</td><td>7.17</td><td>7.19</td><td>7.28</td><td>7.40</td><td>7.71</td></tr> <tr><td>0.78</td><td>10.62</td><td>10.55</td><td>10.60</td><td>10.70</td><td>11.04</td></tr> <tr><td>1.04</td><td>14.21</td><td>14.03</td><td>13.99</td><td>14.08</td><td>14.44</td></tr> <tr><td>1.30</td><td>17.91</td><td>17.61</td><td>17.43</td><td>17.48</td><td>17.86</td></tr> <tr><td>1.43</td><td>19.82</td><td>19.44</td><td>19.20</td><td>19.21</td><td>19.60</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.66	0.74	0.88	0.99	1.23	0.26	3.86	3.92	4.05	4.16	4.44	0.52	7.17	7.19	7.28	7.40	7.71	0.78	10.62	10.55	10.60	10.70	11.04	1.04	14.21	14.03	13.99	14.08	14.44	1.30	17.91	17.61	17.43	17.48	17.86	1.43	19.82	19.44	19.20	19.21	19.60	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Input Power [W]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	0.66	0.74	0.88	0.99	1.23																																																																													
0.26	3.86	3.92	4.05	4.16	4.44																																																																													
0.52	7.17	7.19	7.28	7.40	7.71																																																																													
0.78	10.62	10.55	10.60	10.70	11.04																																																																													
1.04	14.21	14.03	13.99	14.08	14.44																																																																													
1.30	17.91	17.61	17.43	17.48	17.86																																																																													
1.43	19.82	19.44	19.20	19.21	19.60																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



<b>COSEL</b>																																			
Model	STMGFS154812	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>88.4</td><td>87.0</td></tr> <tr><td>18</td><td>88.6</td><td>87.8</td></tr> <tr><td>24</td><td>88.8</td><td>89.4</td></tr> <tr><td>30</td><td>88.5</td><td>89.8</td></tr> <tr><td>36</td><td>88.1</td><td>90.2</td></tr> <tr><td>48</td><td>87.0</td><td>90.0</td></tr> <tr><td>60</td><td>85.8</td><td>89.3</td></tr> <tr><td>76</td><td>84.1</td><td>88.1</td></tr> <tr><td>80</td><td>83.7</td><td>87.7</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	88.4	87.0	18	88.6	87.8	24	88.8	89.4	30	88.5	89.8	36	88.1	90.2	48	87.0	90.0	60	85.8	89.3	76	84.1	88.1	80	83.7	87.7
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
17	88.4	87.0																																	
18	88.6	87.8																																	
24	88.8	89.4																																	
30	88.5	89.8																																	
36	88.1	90.2																																	
48	87.0	90.0																																	
60	85.8	89.3																																	
76	84.1	88.1																																	
80	83.7	87.7																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Model		STMGFS154812		Temperature 25°C																																																																														
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																																														
Object																																																																																		
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 18V</li> <li>- - -□- - - Input Volt. 24V</li> <li>- · · * · · - - Input Volt. 36V</li> <li>- · · ○ · · - - Input Volt. 48V</li> <li>- - ◇ - - Input Volt. 76V</li> </ul>		2.Values																																																																														
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.26</td><td>81.4</td><td>80.0</td><td>77.7</td><td>75.6</td><td>70.8</td></tr> <tr><td>0.52</td><td>87.8</td><td>87.5</td><td>86.4</td><td>85.2</td><td>81.7</td></tr> <tr><td>0.78</td><td>88.9</td><td>89.4</td><td>89.1</td><td>88.3</td><td>85.5</td></tr> <tr><td>1.04</td><td>88.6</td><td>89.8</td><td>90.0</td><td>89.5</td><td>87.2</td></tr> <tr><td>1.30</td><td>87.8</td><td>89.4</td><td>90.2</td><td>90.0</td><td>88.1</td></tr> <tr><td>1.43</td><td>87.3</td><td>89.0</td><td>90.1</td><td>90.1</td><td>88.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	-	-	0.26	81.4	80.0	77.7	75.6	70.8	0.52	87.8	87.5	86.4	85.2	81.7	0.78	88.9	89.4	89.1	88.3	85.5	1.04	88.6	89.8	90.0	89.5	87.2	1.30	87.8	89.4	90.2	90.0	88.1	1.43	87.3	89.0	90.1	90.1	88.3	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.26	81.4	80.0	77.7	75.6	70.8																																																																													
0.52	87.8	87.5	86.4	85.2	81.7																																																																													
0.78	88.9	89.4	89.1	88.3	85.5																																																																													
1.04	88.6	89.8	90.0	89.5	87.2																																																																													
1.30	87.8	89.4	90.2	90.0	88.1																																																																													
1.43	87.3	89.0	90.1	90.1	88.3																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



<p>Model      STMGFS154812</p>		<p>Temperature      25°C Testing Circuitry    Figure A</p>																																
<p>Item      Line Regulation</p>																																		
<p>Object    +12V1.3A</p>																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p style="text-align: center;">Input Voltage [V]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>12.078</td><td>12.079</td></tr> <tr><td>18</td><td>12.078</td><td>12.080</td></tr> <tr><td>24</td><td>12.078</td><td>12.080</td></tr> <tr><td>30</td><td>12.079</td><td>12.080</td></tr> <tr><td>36</td><td>12.079</td><td>12.080</td></tr> <tr><td>48</td><td>12.079</td><td>12.080</td></tr> <tr><td>60</td><td>12.079</td><td>12.080</td></tr> <tr><td>76</td><td>12.079</td><td>12.080</td></tr> <tr><td>80</td><td>12.079</td><td>12.080</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	12.078	12.079	18	12.078	12.080	24	12.078	12.080	30	12.079	12.080	36	12.079	12.080	48	12.079	12.080	60	12.079	12.080	76	12.079	12.080	80	12.079	12.080
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
17	12.078	12.079																																
18	12.078	12.080																																
24	12.078	12.080																																
30	12.079	12.080																																
36	12.079	12.080																																
48	12.079	12.080																																
60	12.079	12.080																																
76	12.079	12.080																																
80	12.079	12.080																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model      STMGFS154812</p> <p>Item        Load Regulation</p> <p>Object      +12V1.3A</p>		<p>Temperature      25°C</p> <p>Testing Circuitry    Figure A</p>																																																																													
<p>1. Graph</p> <p>—△— Input Volt. 18V</p> <p>---□--- Input Volt. 24V</p> <p>---*--- Input Volt. 36V</p> <p>---○--- Input Volt. 48V</p> <p>---◇--- Input Volt. 76V</p>	<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.087</td><td>12.086</td><td>12.086</td><td>12.086</td><td>12.085</td></tr> <tr><td>0.26</td><td>12.085</td><td>12.085</td><td>12.085</td><td>12.084</td><td>12.084</td></tr> <tr><td>0.52</td><td>12.084</td><td>12.084</td><td>12.084</td><td>12.084</td><td>12.083</td></tr> <tr><td>0.78</td><td>12.083</td><td>12.082</td><td>12.083</td><td>12.082</td><td>12.082</td></tr> <tr><td>1.04</td><td>12.082</td><td>12.081</td><td>12.081</td><td>12.081</td><td>12.081</td></tr> <tr><td>1.30</td><td>12.079</td><td>12.080</td><td>12.080</td><td>12.080</td><td>12.080</td></tr> <tr><td>1.43</td><td>12.079</td><td>12.079</td><td>12.079</td><td>12.079</td><td>12.079</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	12.087	12.086	12.086	12.086	12.085	0.26	12.085	12.085	12.085	12.084	12.084	0.52	12.084	12.084	12.084	12.084	12.083	0.78	12.083	12.082	12.083	12.082	12.082	1.04	12.082	12.081	12.081	12.081	12.081	1.30	12.079	12.080	12.080	12.080	12.080	1.43	12.079	12.079	12.079	12.079	12.079	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																														
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																										
0.00	12.087	12.086	12.086	12.086	12.085																																																																										
0.26	12.085	12.085	12.085	12.084	12.084																																																																										
0.52	12.084	12.084	12.084	12.084	12.083																																																																										
0.78	12.083	12.082	12.083	12.082	12.082																																																																										
1.04	12.082	12.081	12.081	12.081	12.081																																																																										
1.30	12.079	12.080	12.080	12.080	12.080																																																																										
1.43	12.079	12.079	12.079	12.079	12.079																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																															



<p><b>Model</b>      STMGFS154812</p> <p><b>Item</b>        Ripple Voltage (by Load Current)</p> <p><b>Object</b>       +12V1.3A</p>		<p>Temperature      25°C</p> <p>Testing Circuitry   Figure B</p>																																						
<p>1. Graph</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>—△—      Input Volt.    18V</p> <p>- - -○- - -    Input Volt.    76V</p> </div> <div style="text-align: center;"> </div> </div>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>15</td></tr> <tr><td>0.260</td><td>10</td><td>15</td></tr> <tr><td>0.520</td><td>10</td><td>15</td></tr> <tr><td>0.780</td><td>10</td><td>15</td></tr> <tr><td>1.040</td><td>10</td><td>15</td></tr> <tr><td>1.300</td><td>15</td><td>15</td></tr> <tr><td>1.430</td><td>15</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.000	10	15	0.260	10	15	0.520	10	15	0.780	10	15	1.040	10	15	1.300	15	15	1.430	15	15	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.000	10	15																																						
0.260	10	15																																						
0.520	10	15																																						
0.780	10	15																																						
1.040	10	15																																						
1.300	15	15																																						
1.430	15	15																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.                  Ripple Voltage is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																								




<p>Model      STMGFS154812</p> <p>Item        Ripple-Noise</p> <p>Object     +12V1.3A</p>		<p>Temperature      25°C</p> <p>Testing Circuitry   Figure B</p>																																						
<p>1.Graph</p> <div style="text-align: right;"> <p>—△—      Input Volt.    18V</p> <p>-·-○-·-    Input Volt.    76V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <div style="text-align: center;"> <p>Ripple Noise[mVp-p]</p> </div> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>20</td></tr> <tr><td>0.26</td><td>25</td><td>25</td></tr> <tr><td>0.52</td><td>30</td><td>30</td></tr> <tr><td>0.78</td><td>30</td><td>30</td></tr> <tr><td>1.04</td><td>40</td><td>40</td></tr> <tr><td>1.30</td><td>40</td><td>40</td></tr> <tr><td>1.43</td><td>45</td><td>45</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	20	20	0.26	25	25	0.52	30	30	0.78	30	30	1.04	40	40	1.30	40	40	1.43	45	45	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	20	20																																						
0.26	25	25																																						
0.52	30	30																																						
0.78	30	30																																						
1.04	40	40																																						
1.30	40	40																																						
1.43	45	45																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



Model	STMGFS154812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1.3A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	30	30
-20	25	20
0	15	20
25	15	15
60	15	15
65	15	15
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.





Fig.Complex Ripple Noise Wave Form



Model	STMGFS154812
Item	Ambient Temperature Drift
Object	+12V1.3A

Testing Circuitry Figure A

1. Graph
- △— Input Volt. 18V
  - Input Volt. 24V
  - \*--- Input Volt. 36V
  - Input Volt. 48V
  - ◇--- Input Volt. 76V



Load 100%

Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-40	12.022	12.023	12.024	12.024	12.025
-20	12.045	12.046	12.047	12.047	12.047
0	12.062	12.063	12.063	12.063	12.064
10	12.069	12.070	12.070	12.071	12.070
25	12.079	12.080	12.080	12.080	12.080
30	12.079	12.080	12.080	12.080	12.080
40	12.083	12.084	12.084	12.084	12.084
50	12.087	12.088	12.088	12.088	12.088
60	12.089	12.089	12.090	12.090	12.090
65	12.089	12.089	12.089	12.089	12.089
--	-	-	-	-	-



<b>COSEL</b>		Testing Circuitry Figure A
Model	STMGFS154812	
Item	Output Voltage Accuracy	
Object	+12V1.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 18 - 76V

Load Current : 0 - 1.3A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	18	0	12.096	±26	±0.2
Minimum Voltage	-20	18	1.3	12.045		



<b>COSEL</b>																									
Model	STMGFS154812	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V1.3A																								
1.Graph		2.Values																							
<p style="text-align: center;">Time [H]</p> <p>Input Volt.     48V Load             100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.074</td></tr> <tr><td>0.5</td><td>12.080</td></tr> <tr><td>1.0</td><td>12.080</td></tr> <tr><td>2.0</td><td>12.080</td></tr> <tr><td>3.0</td><td>12.080</td></tr> <tr><td>4.0</td><td>12.080</td></tr> <tr><td>5.0</td><td>12.080</td></tr> <tr><td>6.0</td><td>12.081</td></tr> <tr><td>7.0</td><td>12.081</td></tr> <tr><td>8.0</td><td>12.081</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.074	0.5	12.080	1.0	12.080	2.0	12.080	3.0	12.080	4.0	12.080	5.0	12.080	6.0	12.081	7.0	12.081	8.0	12.081
Time since start [H]	Output Voltage [V]																								
0.0	12.074																								
0.5	12.080																								
1.0	12.080																								
2.0	12.080																								
3.0	12.080																								
4.0	12.080																								
5.0	12.080																								
6.0	12.081																								
7.0	12.081																								
8.0	12.081																								




Model	STMGFS154812	Temperature 25°C Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+12V1.3A	
1.Graph		



2.Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.0	6.4	7.4	0.2	2.6
100 %		1.0	6.6	7.6	0.2	1.3

[ms]





<p>Model      STMGFS154812</p> <p>Item        Minimum Input Voltage for Regulated Output Voltage</p> <p>Object      +12V1.3A</p>		<p>Testing Circuitry    Figure A</p>																																						
<p>1. Graph</p> <p style="text-align: center;"> <span style="margin-right: 20px;">---□--- Load 50%</span>  <span>—△— Load 100%</span> </p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-40</td><td>16.0</td><td>16.1</td></tr> <tr><td>-20</td><td>16.0</td><td>16.1</td></tr> <tr><td>0</td><td>16.0</td><td>16.1</td></tr> <tr><td>10</td><td>16.0</td><td>16.1</td></tr> <tr><td>25</td><td>16.0</td><td>16.1</td></tr> <tr><td>30</td><td>16.0</td><td>16.1</td></tr> <tr><td>40</td><td>16.0</td><td>16.1</td></tr> <tr><td>50</td><td>16.0</td><td>16.1</td></tr> <tr><td>60</td><td>16.2</td><td>16.1</td></tr> <tr><td>65</td><td>16.0</td><td>16.1</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-40	16.0	16.1	-20	16.0	16.1	0	16.0	16.1	10	16.0	16.1	25	16.0	16.1	30	16.0	16.1	40	16.0	16.1	50	16.0	16.1	60	16.2	16.1	65	16.0	16.1	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-40	16.0	16.1																																						
-20	16.0	16.1																																						
0	16.0	16.1																																						
10	16.0	16.1																																						
25	16.0	16.1																																						
30	16.0	16.1																																						
40	16.0	16.1																																						
50	16.0	16.1																																						
60	16.2	16.1																																						
65	16.0	16.1																																						
--	-	-																																						



<p><b>Model</b>      STMGFS154812</p>		<p>Temperature      25°C Testing Circuitry    Figure A</p>																																																																																			
<p><b>Item</b>        Overcurrent Protection</p>																																																																																					
<p><b>Object</b>      +12V1.3A</p>																																																																																					
<p>1. Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>—△ Input Volt. 18V</p> <p>—□ Input Volt. 24V</p> <p>—* Input Volt. 36V</p> <p>—○ Input Volt. 48V</p> <p>—◇ Input Volt. 76V</p> </div> </div>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>1.614</td><td>1.759</td><td>1.902</td><td>1.943</td><td>1.881</td></tr> <tr><td>11.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.8</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.6</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.8</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.6</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	1.614	1.759	1.902	1.943	1.881	11.4	-	-	-	-	-	10.8	-	-	-	-	-	9.6	-	-	-	-	-	8.4	-	-	-	-	-	7.2	-	-	-	-	-	6.0	-	-	-	-	-	4.8	-	-	-	-	-	3.6	-	-	-	-	-	2.4	-	-	-	-	-	1.2	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																																
12.0	1.614	1.759	1.902	1.943	1.881																																																																																
11.4	-	-	-	-	-																																																																																
10.8	-	-	-	-	-																																																																																
9.6	-	-	-	-	-																																																																																
8.4	-	-	-	-	-																																																																																
7.2	-	-	-	-	-																																																																																
6.0	-	-	-	-	-																																																																																
4.8	-	-	-	-	-																																																																																
3.6	-	-	-	-	-																																																																																
2.4	-	-	-	-	-																																																																																
1.2	-	-	-	-	-																																																																																
0.0	-	-	-	-	-																																																																																
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																																																					




Figure A




Figure B (Ripple and Ripple noise Characteristic)