

TEST DATA OF STMGFS304815

Regulated DC Power Supply
February 2, 2013

Approved by :

Takahiro Yoneda

Takahiro Yoneda

Design Manager

Prepared by :

Satoshi Kinoshita

Satoshi Kinoshita

Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple Voltage (by Load Current)	8
9.Ripple-Noise	9
10.Ripple Voltage (by Ambient Temperature)	10
11.Ambient Temperature Drift	11
12.Output Voltage Accuracy	12
13.Time Lapse Drift	13
14.Rise and Fall Time	14
15.Minimum Input Voltage for Regulated Output Voltage	15
16.Overcurrent Protection	16
17.Overvoltage Protection	17
18.Figure of Testing Circuitry	18

(Final Page 18)


COSEL

Model	STMGFS304815	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object																																																																																		
1.Graph	<p>—△— Load 100%</p> <p>- - □ - - Load 50%</p> <p>- - ○ - - Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.002</td><td>0.001</td><td>0.001</td></tr> <tr><td>10.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.050</td><td>1.001</td><td>2.018</td></tr> <tr><td>17.0</td><td>0.048</td><td>1.001</td><td>1.968</td></tr> <tr><td>17.5</td><td>0.046</td><td>0.946</td><td>1.909</td></tr> <tr><td>18.0</td><td>0.046</td><td>0.920</td><td>1.847</td></tr> <tr><td>24.0</td><td>0.041</td><td>0.693</td><td>1.383</td></tr> <tr><td>36.0</td><td>0.035</td><td>0.471</td><td>0.931</td></tr> <tr><td>48.0</td><td>0.033</td><td>0.362</td><td>0.705</td></tr> <tr><td>76.0</td><td>0.033</td><td>0.245</td><td>0.464</td></tr> <tr><td>80.0</td><td>0.033</td><td>0.235</td><td>0.443</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.0	0.000	0.000	0.000	5.0	0.002	0.001	0.001	10.0	0.002	0.002	0.002	15.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.5	0.050	1.001	2.018	17.0	0.048	1.001	1.968	17.5	0.046	0.946	1.909	18.0	0.046	0.920	1.847	24.0	0.041	0.693	1.383	36.0	0.035	0.471	0.931	48.0	0.033	0.362	0.705	76.0	0.033	0.245	0.464	80.0	0.033	0.235	0.443	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-					
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																															
0.0	0.000	0.000	0.000																																																																															
5.0	0.002	0.001	0.001																																																																															
10.0	0.002	0.002	0.002																																																																															
15.0	0.002	0.002	0.002																																																																															
16.0	0.002	0.002	0.002																																																																															
16.5	0.050	1.001	2.018																																																																															
17.0	0.048	1.001	1.968																																																																															
17.5	0.046	0.946	1.909																																																																															
18.0	0.046	0.920	1.847																																																																															
24.0	0.041	0.693	1.383																																																																															
36.0	0.035	0.471	0.931																																																																															
48.0	0.033	0.362	0.705																																																																															
76.0	0.033	0.245	0.464																																																																															
80.0	0.033	0.235	0.443																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.002</td><td>0.001</td><td>0.001</td></tr> <tr><td>10.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.050</td><td>1.001</td><td>2.018</td></tr> <tr><td>17.0</td><td>0.048</td><td>1.001</td><td>1.968</td></tr> <tr><td>17.5</td><td>0.046</td><td>0.946</td><td>1.909</td></tr> <tr><td>18.0</td><td>0.046</td><td>0.920</td><td>1.847</td></tr> <tr><td>24.0</td><td>0.041</td><td>0.693</td><td>1.383</td></tr> <tr><td>36.0</td><td>0.035</td><td>0.471</td><td>0.931</td></tr> <tr><td>48.0</td><td>0.033</td><td>0.362</td><td>0.705</td></tr> <tr><td>76.0</td><td>0.033</td><td>0.245</td><td>0.464</td></tr> <tr><td>80.0</td><td>0.033</td><td>0.235</td><td>0.443</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.002	0.001	0.001	10.0	0.002	0.002	0.002	15.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.5	0.050	1.001	2.018	17.0	0.048	1.001	1.968	17.5	0.046	0.946	1.909	18.0	0.046	0.920	1.847	24.0	0.041	0.693	1.383	36.0	0.035	0.471	0.931	48.0	0.033	0.362	0.705	76.0	0.033	0.245	0.464	80.0	0.033	0.235	0.443	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
5.0	0.002	0.001	0.001																																																																															
10.0	0.002	0.002	0.002																																																																															
15.0	0.002	0.002	0.002																																																																															
16.0	0.002	0.002	0.002																																																																															
16.5	0.050	1.001	2.018																																																																															
17.0	0.048	1.001	1.968																																																																															
17.5	0.046	0.946	1.909																																																																															
18.0	0.046	0.920	1.847																																																																															
24.0	0.041	0.693	1.383																																																																															
36.0	0.035	0.471	0.931																																																																															
48.0	0.033	0.362	0.705																																																																															
76.0	0.033	0.245	0.464																																																																															
80.0	0.033	0.235	0.443																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	STMGFS304815	Temperature 25°C	Testing Circuitry	Figure A					
Item	Input Current (by Load Current)								
Object	—								
1.Graph	—△— Input Volt. 18V ---□--- Input Volt. 24V -·*--- Input Volt. 36V —○--- Input Volt. 48V ---◇--- Input Volt. 76V	2.Values							
				Load Current [A]	Input Current [A]				
				18[V]	24[V]	36[V]	48[V]	76[V]	
				0.0	0.046	0.041	0.035	0.033	0.032
				0.4	0.390	0.301	0.209	0.164	0.116
				0.8	0.741	0.563	0.386	0.297	0.203
				1.2	1.102	0.828	0.563	0.431	0.289
				1.6	1.465	1.111	0.742	0.566	0.376
				2.0	1.847	1.383	0.931	0.705	0.464
				2.2	2.044	1.527	1.019	0.773	0.509
				--	-	-	-	-	-
				--	-	-	-	-	-
				--	-	-	-	-	-
				--	-	-	-	-	-
				--	-	-	-	-	-





Note: Slanted line shows the range of the rated load current.

COSEL

Model	STMGFS304815	Temperature 25°C																																																																													
Item	Input Power (by Load Current)	Testing Circuitry Figure A																																																																													
Object	—	—																																																																													
1.Graph	<p>—△— Input Volt. 18V</p> <p>---□--- Input Volt. 24V</p> <p>---*--- Input Volt. 36V</p> <p>---○--- Input Volt. 48V</p> <p>---◇--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>18[V] [W]</th> <th>24[V] [W]</th> <th>36[V] [W]</th> <th>48[V] [W]</th> <th>76[V] [W]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.85</td><td>0.99</td><td>1.28</td><td>1.59</td><td>2.44</td></tr> <tr><td>0.4</td><td>7.04</td><td>7.19</td><td>7.51</td><td>7.85</td><td>8.85</td></tr> <tr><td>0.8</td><td>13.34</td><td>13.48</td><td>13.84</td><td>14.23</td><td>15.40</td></tr> <tr><td>1.2</td><td>19.82</td><td>19.89</td><td>20.22</td><td>20.62</td><td>21.93</td></tr> <tr><td>1.6</td><td>26.44</td><td>26.45</td><td>26.73</td><td>27.13</td><td>28.50</td></tr> <tr><td>2.0</td><td>33.26</td><td>33.16</td><td>33.34</td><td>33.74</td><td>35.22</td></tr> <tr><td>2.2</td><td>36.77</td><td>36.58</td><td>36.74</td><td>37.14</td><td>38.65</td></tr> </tbody> </table>	Load Current [A]	18[V] [W]	24[V] [W]	36[V] [W]	48[V] [W]	76[V] [W]	0.0	0.85	0.99	1.28	1.59	2.44	0.4	7.04	7.19	7.51	7.85	8.85	0.8	13.34	13.48	13.84	14.23	15.40	1.2	19.82	19.89	20.22	20.62	21.93	1.6	26.44	26.45	26.73	27.13	28.50	2.0	33.26	33.16	33.34	33.74	35.22	2.2	36.77	36.58	36.74	37.14	38.65																														
Load Current [A]	18[V] [W]	24[V] [W]	36[V] [W]	48[V] [W]	76[V] [W]																																																																										
0.0	0.85	0.99	1.28	1.59	2.44																																																																										
0.4	7.04	7.19	7.51	7.85	8.85																																																																										
0.8	13.34	13.48	13.84	14.23	15.40																																																																										
1.2	19.82	19.89	20.22	20.62	21.93																																																																										
1.6	26.44	26.45	26.73	27.13	28.50																																																																										
2.0	33.26	33.16	33.34	33.74	35.22																																																																										
2.2	36.77	36.58	36.74	37.14	38.65																																																																										
2.Values																																																																															
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.85</td><td>0.99</td><td>1.28</td><td>1.59</td><td>2.44</td></tr> <tr><td>0.4</td><td>7.04</td><td>7.19</td><td>7.51</td><td>7.85</td><td>8.85</td></tr> <tr><td>0.8</td><td>13.34</td><td>13.48</td><td>13.84</td><td>14.23</td><td>15.40</td></tr> <tr><td>1.2</td><td>19.82</td><td>19.89</td><td>20.22</td><td>20.62</td><td>21.93</td></tr> <tr><td>1.6</td><td>26.44</td><td>26.45</td><td>26.73</td><td>27.13</td><td>28.50</td></tr> <tr><td>2.0</td><td>33.26</td><td>33.16</td><td>33.34</td><td>33.74</td><td>35.22</td></tr> <tr><td>2.2</td><td>36.77</td><td>36.58</td><td>36.74</td><td>37.14</td><td>38.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.85	0.99	1.28	1.59	2.44	0.4	7.04	7.19	7.51	7.85	8.85	0.8	13.34	13.48	13.84	14.23	15.40	1.2	19.82	19.89	20.22	20.62	21.93	1.6	26.44	26.45	26.73	27.13	28.50	2.0	33.26	33.16	33.34	33.74	35.22	2.2	36.77	36.58	36.74	37.14	38.65	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																														
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																										
0.0	0.85	0.99	1.28	1.59	2.44																																																																										
0.4	7.04	7.19	7.51	7.85	8.85																																																																										
0.8	13.34	13.48	13.84	14.23	15.40																																																																										
1.2	19.82	19.89	20.22	20.62	21.93																																																																										
1.6	26.44	26.45	26.73	27.13	28.50																																																																										
2.0	33.26	33.16	33.34	33.74	35.22																																																																										
2.2	36.77	36.58	36.74	37.14	38.65																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										

Note: Slanted line shows the range of the rated load current.

COSEL

COSEL


Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0.0	-	-	-	-	-
0.4	85.8	84.0	80.4	76.9	68.3
0.8	90.6	89.6	87.3	84.9	78.5
1.2	91.6	91.2	89.7	87.9	82.7
1.6	91.5	91.4	90.5	89.1	84.8
2.0	90.6	91.1	90.6	89.6	85.8
2.2	90.4	90.9	90.5	89.5	86.0
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Model	STMGFS304815
Item	Line Regulation
Object	+15V2A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	15.086	15.089
18	15.086	15.089
24	15.086	15.089
30	15.086	15.089
36	15.086	15.089
48	15.086	15.089
60	15.086	15.089
76	15.086	15.089
80	15.086	15.089

COSEL


Model	STMGFS304815	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Load Regulation																																																																																		
Object	+15V2A																																																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.096</td><td>15.095</td><td>15.095</td><td>15.095</td><td>15.095</td></tr> <tr><td>0.4</td><td>15.095</td><td>15.094</td><td>15.094</td><td>15.094</td><td>15.094</td></tr> <tr><td>0.8</td><td>15.094</td><td>15.093</td><td>15.093</td><td>15.093</td><td>15.093</td></tr> <tr><td>1.2</td><td>15.092</td><td>15.092</td><td>15.091</td><td>15.092</td><td>15.091</td></tr> <tr><td>1.6</td><td>15.091</td><td>15.091</td><td>15.091</td><td>15.090</td><td>15.090</td></tr> <tr><td>2.0</td><td>15.089</td><td>15.089</td><td>15.089</td><td>15.089</td><td>15.089</td></tr> <tr><td>2.2</td><td>15.089</td><td>15.089</td><td>15.089</td><td>15.088</td><td>15.089</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	15.096	15.095	15.095	15.095	15.095	0.4	15.095	15.094	15.094	15.094	15.094	0.8	15.094	15.093	15.093	15.093	15.093	1.2	15.092	15.092	15.091	15.092	15.091	1.6	15.091	15.091	15.091	15.090	15.090	2.0	15.089	15.089	15.089	15.089	15.089	2.2	15.089	15.089	15.089	15.088	15.089	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
0.0	15.096	15.095	15.095	15.095	15.095																																																																														
0.4	15.095	15.094	15.094	15.094	15.094																																																																														
0.8	15.094	15.093	15.093	15.093	15.093																																																																														
1.2	15.092	15.092	15.091	15.092	15.091																																																																														
1.6	15.091	15.091	15.091	15.090	15.090																																																																														
2.0	15.089	15.089	15.089	15.089	15.089																																																																														
2.2	15.089	15.089	15.089	15.088	15.089																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Note:	Slanted line shows the range of the rated load current.																																																																																		

COSEL

Model	STMGFS304815
Item	Ripple Voltage (by Load Current)
Object	+15V2A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	40	50
0.4	40	50
0.8	40	50
1.2	40	50
1.6	40	50
2.0	40	50
2.2	40	50
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form


COSEL

Model	STMGFS304815	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+15V2A																																								
1.Graph	2.Values																																								
	<p>Y-axis: Ripple-Noise [mV] (0 to 150) X-axis: Load Current [A] (.0 to 2.0) Legend: Input Volt. 18V (solid line with triangle), Input Volt. 76V (dashed line with circle)</p>																																								
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>45</td><td>60</td></tr> <tr><td>0.4</td><td>45</td><td>60</td></tr> <tr><td>0.8</td><td>45</td><td>60</td></tr> <tr><td>1.2</td><td>45</td><td>60</td></tr> <tr><td>1.6</td><td>45</td><td>60</td></tr> <tr><td>2.0</td><td>45</td><td>65</td></tr> <tr><td>2.2</td><td>45</td><td>65</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	45	60	0.4	45	60	0.8	45	60	1.2	45	60	1.6	45	60	2.0	45	65	2.2	45	65	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 18 [V]	Input Volt. 76 [V]																																							
0.0	45	60																																							
0.4	45	60																																							
0.8	45	60																																							
1.2	45	60																																							
1.6	45	60																																							
2.0	45	65																																							
2.2	45	65																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
	<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
	<p>Y-axis: Ripple Noise[mVp-p]</p>																																								
	<p>Fig:Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	STMGFS304815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V2A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	75	80
-20	60	60
0	45	55
25	40	50
60	40	50
65	40	50
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-




Fig.Complex Ripple Noise Wave Form

Model	STMGFS304815
Item	Ambient Temperature Drift
Object	+15V2A
1.Graph	<p>—△— Input Volt. 18V - - □ - - Input Volt. 24V - - * - - Input Volt. 36V - - ○ - - Input Volt. 48V - - ♦ - - Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>
Note:	Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-40	15.028	15.028	15.028	15.029	15.030
-20	15.053	15.054	15.054	15.054	15.054
0	15.073	15.073	15.073	15.073	15.073
10	15.080	15.080	15.080	15.081	15.081
25	15.089	15.089	15.089	15.089	15.089
30	15.091	15.091	15.091	15.091	15.091
40	15.094	15.094	15.094	15.094	15.094
50	15.095	15.095	15.095	15.095	15.094
60	15.095	15.095	15.095	15.095	15.094
65	15.095	15.095	15.095	15.095	15.094
--	-	-	-	-	-



Model	STMGFS304815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 18 - 76V

Load Current : 0 - 2A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	18	0	15.103	± 25	± 0.2
Minimum Voltage	-20	18	2	15.053		

COSEL

Model	STMGFS304815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V2A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.081</td></tr> <tr><td>0.5</td><td>15.090</td></tr> <tr><td>1.0</td><td>15.090</td></tr> <tr><td>2.0</td><td>15.091</td></tr> <tr><td>3.0</td><td>15.091</td></tr> <tr><td>4.0</td><td>15.091</td></tr> <tr><td>5.0</td><td>15.090</td></tr> <tr><td>6.0</td><td>15.091</td></tr> <tr><td>7.0</td><td>15.090</td></tr> <tr><td>8.0</td><td>15.091</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.081	0.5	15.090	1.0	15.090	2.0	15.091	3.0	15.091	4.0	15.091	5.0	15.090	6.0	15.091	7.0	15.090	8.0	15.091
Time since start [H]	Output Voltage [V]																								
0.0	15.081																								
0.5	15.090																								
1.0	15.090																								
2.0	15.091																								
3.0	15.091																								
4.0	15.091																								
5.0	15.090																								
6.0	15.091																								
7.0	15.090																								
8.0	15.091																								

COSEL


Model STMGFS304815

Item Rise and Fall Time

Object +15V2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.3	7.1	8.4	0.2	2.1	
100 %		1.3	7.2	8.5	0.2	1.0	



Model	STMGFS304815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	15.7	15.8
-20	15.7	15.8
0	15.9	16.0
10	15.9	16.0
25	15.9	16.0
30	15.9	16.0
40	15.9	16.0
50	15.9	16.0
60	15.9	16.0
65	15.9	15.9
--	-	-

COSEL

Model	STMGFS304815
Item	Overcurrent Protection
Object	+15V2A
1.Graph	
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>	


Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
15.0	2.578	2.742	2.855	2.856	2.622
14.3	-	-	-	-	-
13.5	-	-	-	-	-
12.0	-	-	-	-	-
10.5	-	-	-	-	-
9.0	-	-	-	-	-
7.5	-	-	-	-	-
6.0	-	-	-	-	-
4.5	-	-	-	-	-
3.0	-	-	-	-	-
1.5	-	-	-	-	-
0.0	-	-	-	-	-

Model	STMGFS304815
Item	Overvoltage Protection
Object	+15V2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-40	20.65	20.68
-20	20.97	20.93
0	21.14	21.21
25	21.19	21.58
60	21.66	22.11
65	21.80	22.19
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)