

TEST DATA OF STMGFW152415

Regulated DC Power Supply
January 26, 2013

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS


1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Ripple Voltage (by Load Current) · · · · ·	8
9.Ripple-Noise · · · · ·	10
10.Ripple Voltage (by Ambient Temperature) · · · · ·	12
11.Ambient Temperature Drift · · · · ·	13
12.Output Voltage Accuracy · · · · ·	14
13.Time Lapse Drift · · · · ·	15
14.Rise and Fall Time · · · · ·	16
15.Minimum Input Voltage for Regulated Output Voltage · · · · ·	18
16.Overcurrent Protection · · · · ·	19
17.Figure of Testing Circuitry · · · · ·	20

(Final Page 20)

Model	STMGFW152415																																																																																		
Item	Input Current (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																																																																	
Object	—																																																																																		
1.Graph	<p>Input Current [A]</p> <p>Input Voltage [V]</p>																																																																																		
	<p>—△— Load 100%</p> <p>- - □ - - Load 50%</p> <p>- - ○ - - Load 0%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.002</td></tr> <tr><td>7.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.3</td><td>0.057</td><td>1.048</td><td>0.391</td></tr> <tr><td>8.4</td><td>0.056</td><td>1.048</td><td>2.157</td></tr> <tr><td>8.5</td><td>0.055</td><td>1.026</td><td>2.114</td></tr> <tr><td>9.0</td><td>0.051</td><td>0.969</td><td>1.968</td></tr> <tr><td>12.0</td><td>0.040</td><td>0.727</td><td>1.450</td></tr> <tr><td>18.0</td><td>0.031</td><td>0.485</td><td>0.960</td></tr> <tr><td>24.0</td><td>0.023</td><td>0.364</td><td>0.717</td></tr> <tr><td>36.0</td><td>0.016</td><td>0.250</td><td>0.479</td></tr> <tr><td>40.0</td><td>0.015</td><td>0.230</td><td>0.437</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.000	0.000	0.002	7.0	0.002	0.002	0.002	8.0	0.002	0.002	0.002	8.3	0.057	1.048	0.391	8.4	0.056	1.048	2.157	8.5	0.055	1.026	2.114	9.0	0.051	0.969	1.968	12.0	0.040	0.727	1.450	18.0	0.031	0.485	0.960	24.0	0.023	0.364	0.717	36.0	0.016	0.250	0.479	40.0	0.015	0.230	0.437	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
2.0	0.000	0.000	0.000																																																																																
4.0	0.000	0.000	0.000																																																																																
6.0	0.000	0.000	0.002																																																																																
7.0	0.002	0.002	0.002																																																																																
8.0	0.002	0.002	0.002																																																																																
8.3	0.057	1.048	0.391																																																																																
8.4	0.056	1.048	2.157																																																																																
8.5	0.055	1.026	2.114																																																																																
9.0	0.051	0.969	1.968																																																																																
12.0	0.040	0.727	1.450																																																																																
18.0	0.031	0.485	0.960																																																																																
24.0	0.023	0.364	0.717																																																																																
36.0	0.016	0.250	0.479																																																																																
40.0	0.015	0.230	0.437																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

COSEL

Model	STMGFW152415	Temperature 25°C Testing Circuitry Figure A																																																																																
Item	Input Current (by Load Current)																																																																																	
Object	—																																																																																	
1.Graph	<p>—△— Input Volt. 9V - -□--- Input Volt. 12V - -*--- Input Volt. 18V - -○--- Input Volt. 24V - -◇--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> <th>24V [A]</th> <th>36V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.051</td><td>0.041</td><td>0.031</td><td>0.023</td><td>0.016</td></tr> <tr><td>20</td><td>0.426</td><td>0.312</td><td>0.214</td><td>0.161</td><td>0.117</td></tr> <tr><td>40</td><td>0.787</td><td>0.590</td><td>0.398</td><td>0.298</td><td>0.207</td></tr> <tr><td>60</td><td>1.162</td><td>0.872</td><td>0.580</td><td>0.441</td><td>0.293</td></tr> <tr><td>80</td><td>1.572</td><td>1.156</td><td>0.765</td><td>0.578</td><td>0.392</td></tr> <tr><td>100</td><td>1.968</td><td>1.450</td><td>0.960</td><td>0.717</td><td>0.479</td></tr> <tr><td>110</td><td>2.184</td><td>1.600</td><td>1.052</td><td>0.781</td><td>0.532</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	9V [A]	12V [A]	18V [A]	24V [A]	36V [A]	0	0.051	0.041	0.031	0.023	0.016	20	0.426	0.312	0.214	0.161	0.117	40	0.787	0.590	0.398	0.298	0.207	60	1.162	0.872	0.580	0.441	0.293	80	1.572	1.156	0.765	0.578	0.392	100	1.968	1.450	0.960	0.717	0.479	110	2.184	1.600	1.052	0.781	0.532	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ration [%]	9V [A]	12V [A]	18V [A]	24V [A]	36V [A]																																																																													
0	0.051	0.041	0.031	0.023	0.016																																																																													
20	0.426	0.312	0.214	0.161	0.117																																																																													
40	0.787	0.590	0.398	0.298	0.207																																																																													
60	1.162	0.872	0.580	0.441	0.293																																																																													
80	1.572	1.156	0.765	0.578	0.392																																																																													
100	1.968	1.450	0.960	0.717	0.479																																																																													
110	2.184	1.600	1.052	0.781	0.532																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.051</td><td>0.041</td><td>0.031</td><td>0.023</td><td>0.016</td></tr> <tr><td>20</td><td>0.426</td><td>0.312</td><td>0.214</td><td>0.161</td><td>0.117</td></tr> <tr><td>40</td><td>0.787</td><td>0.590</td><td>0.398</td><td>0.298</td><td>0.207</td></tr> <tr><td>60</td><td>1.162</td><td>0.872</td><td>0.580</td><td>0.441</td><td>0.293</td></tr> <tr><td>80</td><td>1.572</td><td>1.156</td><td>0.765</td><td>0.578</td><td>0.392</td></tr> <tr><td>100</td><td>1.968</td><td>1.450</td><td>0.960</td><td>0.717</td><td>0.479</td></tr> <tr><td>110</td><td>2.184</td><td>1.600</td><td>1.052</td><td>0.781</td><td>0.532</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.051	0.041	0.031	0.023	0.016	20	0.426	0.312	0.214	0.161	0.117	40	0.787	0.590	0.398	0.298	0.207	60	1.162	0.872	0.580	0.441	0.293	80	1.572	1.156	0.765	0.578	0.392	100	1.968	1.450	0.960	0.717	0.479	110	2.184	1.600	1.052	0.781	0.532	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.051	0.041	0.031	0.023	0.016																																																																													
20	0.426	0.312	0.214	0.161	0.117																																																																													
40	0.787	0.590	0.398	0.298	0.207																																																																													
60	1.162	0.872	0.580	0.441	0.293																																																																													
80	1.572	1.156	0.765	0.578	0.392																																																																													
100	1.968	1.450	0.960	0.717	0.479																																																																													
110	2.184	1.600	1.052	0.781	0.532																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model	STMGFW152415																																																																																	
Item	Input Power (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																																																
Object	_____																																																																																	
1.Graph																																																																																		
<p style="text-align: center;"> —△— Input Volt. 9V ---□--- Input Volt. 12V ---*--- Input Volt. 18V ---○--- Input Volt. 24V ---◇--- Input Volt. 36V </p>  <table border="1" style="margin-left: auto; margin-right: auto;"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [W]</th> <th>12V [W]</th> <th>18V [W]</th> <th>24V [W]</th> <th>36V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.48</td><td>0.49</td><td>0.56</td><td>0.55</td><td>0.57</td></tr> <tr><td>40</td><td>3.81</td><td>3.73</td><td>3.84</td><td>3.86</td><td>4.22</td></tr> <tr><td>80</td><td>7.05</td><td>7.08</td><td>7.13</td><td>7.13</td><td>7.46</td></tr> <tr><td>110</td><td>10.46</td><td>10.42</td><td>10.38</td><td>10.55</td><td>10.54</td></tr> <tr><td>110</td><td>14.03</td><td>13.75</td><td>13.74</td><td>13.81</td><td>14.10</td></tr> <tr><td>100</td><td>17.64</td><td>17.32</td><td>17.23</td><td>17.13</td><td>17.23</td></tr> <tr><td>110</td><td>19.50</td><td>19.08</td><td>18.86</td><td>18.71</td><td>19.13</td></tr> </tbody> </table>	Load Ration [%]	9V [W]	12V [W]	18V [W]	24V [W]	36V [W]	0	0.48	0.49	0.56	0.55	0.57	40	3.81	3.73	3.84	3.86	4.22	80	7.05	7.08	7.13	7.13	7.46	110	10.46	10.42	10.38	10.55	10.54	110	14.03	13.75	13.74	13.81	14.10	100	17.64	17.32	17.23	17.13	17.23	110	19.50	19.08	18.86	18.71	19.13																																		
Load Ration [%]	9V [W]	12V [W]	18V [W]	24V [W]	36V [W]																																																																													
0	0.48	0.49	0.56	0.55	0.57																																																																													
40	3.81	3.73	3.84	3.86	4.22																																																																													
80	7.05	7.08	7.13	7.13	7.46																																																																													
110	10.46	10.42	10.38	10.55	10.54																																																																													
110	14.03	13.75	13.74	13.81	14.10																																																																													
100	17.64	17.32	17.23	17.13	17.23																																																																													
110	19.50	19.08	18.86	18.71	19.13																																																																													
2.Values																																																																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.48</td><td>0.49</td><td>0.56</td><td>0.55</td><td>0.57</td></tr> <tr><td>20</td><td>3.81</td><td>3.73</td><td>3.84</td><td>3.86</td><td>4.22</td></tr> <tr><td>40</td><td>7.05</td><td>7.08</td><td>7.13</td><td>7.13</td><td>7.46</td></tr> <tr><td>60</td><td>10.46</td><td>10.42</td><td>10.38</td><td>10.55</td><td>10.54</td></tr> <tr><td>80</td><td>14.03</td><td>13.75</td><td>13.74</td><td>13.81</td><td>14.10</td></tr> <tr><td>100</td><td>17.64</td><td>17.32</td><td>17.23</td><td>17.13</td><td>17.23</td></tr> <tr><td>110</td><td>19.50</td><td>19.08</td><td>18.86</td><td>18.71</td><td>19.13</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.48	0.49	0.56	0.55	0.57	20	3.81	3.73	3.84	3.86	4.22	40	7.05	7.08	7.13	7.13	7.46	60	10.46	10.42	10.38	10.55	10.54	80	14.03	13.75	13.74	13.81	14.10	100	17.64	17.32	17.23	17.13	17.23	110	19.50	19.08	18.86	18.71	19.13	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ration [%]		Input Power [W]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.48	0.49	0.56	0.55	0.57																																																																													
20	3.81	3.73	3.84	3.86	4.22																																																																													
40	7.05	7.08	7.13	7.13	7.46																																																																													
60	10.46	10.42	10.38	10.55	10.54																																																																													
80	14.03	13.75	13.74	13.81	14.10																																																																													
100	17.64	17.32	17.23	17.13	17.23																																																																													
110	19.50	19.08	18.86	18.71	19.13																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

COSEL

Model STMGFW152415


Item Efficiency (by Input Voltage)

Object

Temperature 25°C
Testing Circuitry Figure A

1. Graph

---□--- Load 50%
 —△— Load 100%



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.5	85.2	84.6
9.0	85.0	85.0
12.0	85.5	86.7
15.0	86.2	87.8
18.0	86.2	87.7
24.0	85.7	87.7
30.0	85.3	86.7
36.0	85.2	87.2
40.0	85.2	87.2

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	STMGFW152415
Item	Efficiency (by Load Current)
Object	

1.Graph

Load Ration [%]	9[V]	12[V]	18[V]	24[V]	36[V]
0	-	-	-	-	-
20	79.0	80.6	78.3	77.9	71.2
40	85.2	84.9	84.2	84.3	80.5
60	86.2	86.5	86.8	86.2	85.5
80	85.6	87.4	87.5	87.0	85.9
100	85.1	86.7	87.7	87.7	87.2
110	84.7	86.6	87.6	88.3	86.4
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ration [%]	Efficiency [%]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	-	-	-	-	-
20	79.0	80.6	78.3	77.9	71.2
40	85.2	84.9	84.2	84.3	80.5
60	86.2	86.5	86.8	86.2	85.5
80	85.6	87.4	87.5	87.0	85.9
100	85.1	86.7	87.7	87.7	87.2
110	84.7	86.6	87.6	88.3	86.4
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Model	STMGFW152415	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+15V0.5A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>15.078</td><td>14.977</td></tr> <tr><td>9.0</td><td>15.077</td><td>14.977</td></tr> <tr><td>12.0</td><td>15.077</td><td>14.977</td></tr> <tr><td>15.0</td><td>15.077</td><td>14.978</td></tr> <tr><td>18.0</td><td>15.078</td><td>14.978</td></tr> <tr><td>24.0</td><td>15.078</td><td>14.978</td></tr> <tr><td>30.0</td><td>15.078</td><td>14.978</td></tr> <tr><td>36.0</td><td>15.079</td><td>14.978</td></tr> <tr><td>40.0</td><td>15.079</td><td>14.978</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	15.078	14.977	9.0	15.077	14.977	12.0	15.077	14.977	15.0	15.077	14.978	18.0	15.078	14.978	24.0	15.078	14.978	30.0	15.078	14.978	36.0	15.079	14.978	40.0	15.079	14.978
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8.5	15.078	14.977																																	
9.0	15.077	14.977																																	
12.0	15.077	14.977																																	
15.0	15.077	14.978																																	
18.0	15.078	14.978																																	
24.0	15.078	14.978																																	
30.0	15.078	14.978																																	
36.0	15.079	14.978																																	
40.0	15.079	14.978																																	
Object																																			
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>-15.088</td><td>-14.978</td></tr> <tr><td>9.0</td><td>-15.086</td><td>-14.979</td></tr> <tr><td>12.0</td><td>-15.086</td><td>-14.979</td></tr> <tr><td>15.0</td><td>-15.086</td><td>-14.980</td></tr> <tr><td>18.0</td><td>-15.086</td><td>-14.980</td></tr> <tr><td>24.0</td><td>-15.086</td><td>-14.980</td></tr> <tr><td>30.0</td><td>-15.086</td><td>-14.980</td></tr> <tr><td>36.0</td><td>-15.085</td><td>-14.980</td></tr> <tr><td>40.0</td><td>-15.085</td><td>-14.980</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	-15.088	-14.978	9.0	-15.086	-14.979	12.0	-15.086	-14.979	15.0	-15.086	-14.980	18.0	-15.086	-14.980	24.0	-15.086	-14.980	30.0	-15.086	-14.980	36.0	-15.085	-14.980	40.0	-15.085	-14.980
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
8.5	-15.088	-14.978																																	
9.0	-15.086	-14.979																																	
12.0	-15.086	-14.979																																	
15.0	-15.086	-14.980																																	
18.0	-15.086	-14.980																																	
24.0	-15.086	-14.980																																	
30.0	-15.086	-14.980																																	
36.0	-15.085	-14.980																																	
40.0	-15.085	-14.980																																	
Note: Slanted line shows the range of the rated input voltage.																																			

COSEL


Model	STMGFW152415	Temperature 25°C																																																																															
Item	Load Regulation	Testing Circuitry	Figure A																																																																														
Object	+15V0.5A																																																																																
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.539</td><td>15.531</td><td>15.522</td><td>15.516</td><td>15.514</td></tr> <tr><td>0.10</td><td>15.197</td><td>15.197</td><td>15.196</td><td>15.196</td><td>15.196</td></tr> <tr><td>0.20</td><td>15.116</td><td>15.116</td><td>15.116</td><td>15.116</td><td>15.115</td></tr> <tr><td>0.30</td><td>15.064</td><td>15.061</td><td>15.061</td><td>15.061</td><td>15.060</td></tr> <tr><td>0.40</td><td>15.020</td><td>15.016</td><td>15.016</td><td>15.017</td><td>15.016</td></tr> <tr><td>0.50</td><td>14.979</td><td>14.979</td><td>14.979</td><td>14.979</td><td>14.979</td></tr> <tr><td>0.55</td><td>14.958</td><td>14.961</td><td>14.961</td><td>14.961</td><td>14.961</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	15.539	15.531	15.522	15.516	15.514	0.10	15.197	15.197	15.196	15.196	15.196	0.20	15.116	15.116	15.116	15.116	15.115	0.30	15.064	15.061	15.061	15.061	15.060	0.40	15.020	15.016	15.016	15.017	15.016	0.50	14.979	14.979	14.979	14.979	14.979	0.55	14.958	14.961	14.961	14.961	14.961	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0.00	15.539	15.531	15.522	15.516	15.514																																																																												
0.10	15.197	15.197	15.196	15.196	15.196																																																																												
0.20	15.116	15.116	15.116	15.116	15.115																																																																												
0.30	15.064	15.061	15.061	15.061	15.060																																																																												
0.40	15.020	15.016	15.016	15.017	15.016																																																																												
0.50	14.979	14.979	14.979	14.979	14.979																																																																												
0.55	14.958	14.961	14.961	14.961	14.961																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
Object	-15V0.5A																																																																																
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.556</td><td>-15.550</td><td>-15.543</td><td>-15.538</td><td>-15.532</td></tr> <tr><td>0.10</td><td>-15.198</td><td>-15.198</td><td>-15.198</td><td>-15.197</td><td>-15.197</td></tr> <tr><td>0.20</td><td>-15.116</td><td>-15.117</td><td>-15.117</td><td>-15.117</td><td>-15.116</td></tr> <tr><td>0.30</td><td>-15.064</td><td>-15.061</td><td>-15.062</td><td>-15.061</td><td>-15.061</td></tr> <tr><td>0.40</td><td>-15.020</td><td>-15.017</td><td>-15.018</td><td>-15.017</td><td>-15.017</td></tr> <tr><td>0.50</td><td>-14.979</td><td>-14.979</td><td>-14.980</td><td>-14.980</td><td>-14.979</td></tr> <tr><td>0.55</td><td>-14.958</td><td>-14.961</td><td>-14.962</td><td>-14.962</td><td>-14.962</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-15.556	-15.550	-15.543	-15.538	-15.532	0.10	-15.198	-15.198	-15.198	-15.197	-15.197	0.20	-15.116	-15.117	-15.117	-15.117	-15.116	0.30	-15.064	-15.061	-15.062	-15.061	-15.061	0.40	-15.020	-15.017	-15.018	-15.017	-15.017	0.50	-14.979	-14.979	-14.980	-14.980	-14.979	0.55	-14.958	-14.961	-14.962	-14.962	-14.962	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0.00	-15.556	-15.550	-15.543	-15.538	-15.532																																																																												
0.10	-15.198	-15.198	-15.198	-15.197	-15.197																																																																												
0.20	-15.116	-15.117	-15.117	-15.117	-15.116																																																																												
0.30	-15.064	-15.061	-15.062	-15.061	-15.061																																																																												
0.40	-15.020	-15.017	-15.018	-15.017	-15.017																																																																												
0.50	-14.979	-14.979	-14.980	-14.980	-14.979																																																																												
0.55	-14.958	-14.961	-14.962	-14.962	-14.962																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
Note:	Slanted line shows the range of the rated load current.																																																																																

COSEL

Model	STMGFW152415
Item	Ripple Voltage (by Load Current)
Object	+15V0.5A

Temperature 25°C
 Testing Circuitry Figure B

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.000	20	30
0.100	25	30
0.200	25	30
0.300	25	30
0.400	25	30
0.500	25	30
0.550	25	30
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form


COSEL

Model STMGFW152415

Item Ripple Voltage (by Load Current)

Object -15V0.5A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig. Complex Ripple Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values


Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.000	25	30
0.100	25	30
0.200	25	30
0.300	25	30
0.400	25	30
0.500	25	30
0.550	25	30
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current

COSEL

Model	STMGFW152415
Item	Ripple-Noise
Object	+15V0.5A

1. Graph



Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.000	40	45
0.100	40	45
0.200	40	45
0.300	40	45
0.400	40	45
0.500	40	45
0.550	40	45
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

COSEL

Model	STMGFW152415
Item	Ripple-Noise
Object	-15V0.5A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.000	30	45
0.100	30	45
0.200	30	45
0.300	30	45
0.400	30	45
0.500	30	45
0.550	30	45
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current





Fig.Complex Ripple Noise Wave Form

COSEL

Model	STMGFW152415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.5A

1.Graph



Testing Circuitry Figure B


2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	30	40
-20	30	35
0	25	30
25	25	30
60	25	30
65	25	30
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

Object	-15V0.5A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	40	40
-20	30	30
0	25	30
25	25	30
60	25	30
65	25	30
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	STMGFW152415	Testing Circuitry Figure A																																																																													
Item	Ambient Temperature Drift																																																																														
Object	+15V0.5A	2.Values																																																																													
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>14.913</td><td>14.914</td><td>14.915</td><td>14.916</td><td>14.916</td></tr> <tr><td>-20</td><td>14.939</td><td>14.939</td><td>14.940</td><td>14.941</td><td>14.941</td></tr> <tr><td>0</td><td>14.958</td><td>14.959</td><td>14.960</td><td>14.960</td><td>14.960</td></tr> <tr><td>10</td><td>14.967</td><td>14.967</td><td>14.968</td><td>14.968</td><td>14.968</td></tr> <tr><td>25</td><td>14.975</td><td>14.975</td><td>14.976</td><td>14.977</td><td>14.977</td></tr> <tr><td>30</td><td>14.978</td><td>14.978</td><td>14.979</td><td>14.979</td><td>14.979</td></tr> <tr><td>40</td><td>14.982</td><td>14.982</td><td>14.983</td><td>14.983</td><td>14.983</td></tr> <tr><td>50</td><td>14.986</td><td>14.986</td><td>14.986</td><td>14.987</td><td>14.987</td></tr> <tr><td>60</td><td>14.988</td><td>14.989</td><td>14.989</td><td>14.989</td><td>14.989</td></tr> <tr><td>65</td><td>14.989</td><td>14.989</td><td>14.990</td><td>14.990</td><td>14.990</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-40	14.913	14.914	14.915	14.916	14.916	-20	14.939	14.939	14.940	14.941	14.941	0	14.958	14.959	14.960	14.960	14.960	10	14.967	14.967	14.968	14.968	14.968	25	14.975	14.975	14.976	14.977	14.977	30	14.978	14.978	14.979	14.979	14.979	40	14.982	14.982	14.983	14.983	14.983	50	14.986	14.986	14.986	14.987	14.987	60	14.988	14.989	14.989	14.989	14.989	65	14.989	14.989	14.990	14.990	14.990	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																														
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																										
-40	14.913	14.914	14.915	14.916	14.916																																																																										
-20	14.939	14.939	14.940	14.941	14.941																																																																										
0	14.958	14.959	14.960	14.960	14.960																																																																										
10	14.967	14.967	14.968	14.968	14.968																																																																										
25	14.975	14.975	14.976	14.977	14.977																																																																										
30	14.978	14.978	14.979	14.979	14.979																																																																										
40	14.982	14.982	14.983	14.983	14.983																																																																										
50	14.986	14.986	14.986	14.987	14.987																																																																										
60	14.988	14.989	14.989	14.989	14.989																																																																										
65	14.989	14.989	14.990	14.990	14.990																																																																										
--	-	-	-	-	-																																																																										
Object	-15V0.5A	2.Values																																																																													
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>-14.914</td><td>-14.916</td><td>-14.917</td><td>-14.917</td><td>-14.918</td></tr> <tr><td>-20</td><td>-14.940</td><td>-14.941</td><td>-14.942</td><td>-14.942</td><td>-14.943</td></tr> <tr><td>0</td><td>-14.960</td><td>-14.960</td><td>-14.961</td><td>-14.962</td><td>-14.962</td></tr> <tr><td>10</td><td>-14.967</td><td>-14.968</td><td>-14.969</td><td>-14.969</td><td>-14.969</td></tr> <tr><td>25</td><td>-14.975</td><td>-14.976</td><td>-14.977</td><td>-14.978</td><td>-14.978</td></tr> <tr><td>30</td><td>-14.978</td><td>-14.979</td><td>-14.980</td><td>-14.980</td><td>-14.980</td></tr> <tr><td>40</td><td>-14.982</td><td>-14.983</td><td>-14.984</td><td>-14.985</td><td>-14.984</td></tr> <tr><td>50</td><td>-14.986</td><td>-14.987</td><td>-14.987</td><td>-14.988</td><td>-14.987</td></tr> <tr><td>60</td><td>-14.989</td><td>-14.989</td><td>-14.990</td><td>-14.990</td><td>-14.990</td></tr> <tr><td>65</td><td>-14.989</td><td>-14.990</td><td>-14.990</td><td>-14.991</td><td>-14.991</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-40	-14.914	-14.916	-14.917	-14.917	-14.918	-20	-14.940	-14.941	-14.942	-14.942	-14.943	0	-14.960	-14.960	-14.961	-14.962	-14.962	10	-14.967	-14.968	-14.969	-14.969	-14.969	25	-14.975	-14.976	-14.977	-14.978	-14.978	30	-14.978	-14.979	-14.980	-14.980	-14.980	40	-14.982	-14.983	-14.984	-14.985	-14.984	50	-14.986	-14.987	-14.987	-14.988	-14.987	60	-14.989	-14.989	-14.990	-14.990	-14.990	65	-14.989	-14.990	-14.990	-14.991	-14.991	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																														
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																										
-40	-14.914	-14.916	-14.917	-14.917	-14.918																																																																										
-20	-14.940	-14.941	-14.942	-14.942	-14.943																																																																										
0	-14.960	-14.960	-14.961	-14.962	-14.962																																																																										
10	-14.967	-14.968	-14.969	-14.969	-14.969																																																																										
25	-14.975	-14.976	-14.977	-14.978	-14.978																																																																										
30	-14.978	-14.979	-14.980	-14.980	-14.980																																																																										
40	-14.982	-14.983	-14.984	-14.985	-14.984																																																																										
50	-14.986	-14.987	-14.987	-14.988	-14.987																																																																										
60	-14.989	-14.989	-14.990	-14.990	-14.990																																																																										
65	-14.989	-14.990	-14.990	-14.991	-14.991																																																																										
--	-	-	-	-	-																																																																										

Note: Slanted line shows the range of the rated ambient temperature.



Model	STMGFW152415
Item	Output Voltage Accuracy

Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 9 - 36V

Load Current (AVR 1) : 0 - 0.5A (AVR 2) : 0 - 0.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+15V0.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	9	0	15.564	±314	±2.1	
Minimum Voltage	-20	9	0.5	14.936			

Object		-15V0.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	9	0	-15.586	±323	±2.2	
Minimum Voltage	-20	9	0.5	-14.940			


coSEL

Model STMGFW152415

Item Time Lapse Drift


Object +15V0.5A

1.Graph



Object -15V0.5A

1.Graph

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	14.963
0.5	14.971
1.0	14.971
2.0	14.971
3.0	14.971
4.0	14.971
5.0	14.971
6.0	14.971
7.0	14.971
8.0	14.971


2.Values

Time since start [H]	Output Voltage [V]
0.0	-14.978
0.5	-14.987
1.0	-14.987
2.0	-14.987
3.0	-14.987
4.0	-14.987
5.0	-14.987
6.0	-14.987
7.0	-14.987
8.0	-14.987

COSEL


Model	STMGFW152415	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.5A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	4.6	5.3	3.9	5.2	
100 %		0.6	4.6	5.2	2.0	2.6	



COSEL


Model STMGFW152415

Item Rise and Fall Time

Object -15V0.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	4.7	5.4	3.9	5.5	
100 %		0.7	4.7	5.4	2.0	2.7	




COSEL

Model	STMGFW152415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.5A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	8.0	8.2
-20	8.0	8.2
0	8.0	8.2
10	8.0	8.2
25	8.0	8.2
30	8.0	8.2
40	8.0	8.2
50	8.0	8.2
60	8.0	8.2
65	8.0	8.2
--	-	-

Object -15V0.5A


1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	8.0	8.2
-20	8.0	8.2
0	8.0	8.2
10	8.0	8.2
25	7.9	8.1
30	7.9	8.1
40	7.9	8.1
50	7.9	8.1
60	7.9	8.1
65	7.9	8.1
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)