



TEST DATA OF STMGFW154815

Regulated DC Power Supply
January 30, 2013

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Ripple Voltage (by Load Current)	8
9. Ripple-Noise	10
10. Ripple Voltage (by Ambient Temperature)	12
11. Ambient Temperature Drift	13
12. Output Voltage Accuracy	14
13. Time Lapse Drift	15
14. Rise and Fall Time	16
15. Minimum Input Voltage for Regulated Output Voltage	18
16. Overcurrent Protection	19
17. Figure of Testing Circuitry	20

(Final Page 20)

Model	STMGFW154815	Temperature 25°C Testing Circuitry Figure A																																																																																
Item	Input Current (by Input Voltage)																																																																																	
Object	— △ — Load 100% --- □ --- Load 50% --- ○ --- Load 0%																																																																																	
1.Graph	<p>The graph plots Input Current [A] on the y-axis (0.0 to 2.0) against Input Voltage [V] on the x-axis (0 to 80). Three data series are shown: Load 100% (triangles), Load 50% (squares), and Load 0% (circles). All series show a sharp increase in current from approximately 0.05A at 15V to about 0.8A at 20V. After 20V, the current decreases as the input voltage increases. The Load 100% curve is the highest, followed by Load 50%, and then Load 0%. A slanted line on the graph indicates the rated input voltage range.</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>10.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.000</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.002</td><td>0.000</td><td>0.002</td></tr> <tr><td>17.0</td><td>0.024</td><td>0.435</td><td>0.859</td></tr> <tr><td>17.5</td><td>0.024</td><td>0.425</td><td>0.833</td></tr> <tr><td>18.0</td><td>0.023</td><td>0.409</td><td>0.970</td></tr> <tr><td>24.0</td><td>0.017</td><td>0.308</td><td>0.718</td></tr> <tr><td>36.0</td><td>0.013</td><td>0.207</td><td>0.476</td></tr> <tr><td>48.0</td><td>0.009</td><td>0.154</td><td>0.354</td></tr> <tr><td>62.0</td><td>0.008</td><td>0.123</td><td>0.226</td></tr> <tr><td>69.0</td><td>0.007</td><td>0.111</td><td>0.212</td></tr> <tr><td>75.5</td><td>0.007</td><td>0.104</td><td>0.196</td></tr> <tr><td>76.0</td><td>0.007</td><td>0.103</td><td>0.195</td></tr> <tr><td>80.0</td><td>0.007</td><td>0.098</td><td>0.186</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.000	0.000	0.000	10.0	0.000	0.000	0.000	15.0	0.002	0.000	0.000	16.0	0.002	0.000	0.002	16.5	0.002	0.000	0.002	17.0	0.024	0.435	0.859	17.5	0.024	0.425	0.833	18.0	0.023	0.409	0.970	24.0	0.017	0.308	0.718	36.0	0.013	0.207	0.476	48.0	0.009	0.154	0.354	62.0	0.008	0.123	0.226	69.0	0.007	0.111	0.212	75.5	0.007	0.104	0.196	76.0	0.007	0.103	0.195	80.0	0.007	0.098	0.186	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
5.0	0.000	0.000	0.000																																																																															
10.0	0.000	0.000	0.000																																																																															
15.0	0.002	0.000	0.000																																																																															
16.0	0.002	0.000	0.002																																																																															
16.5	0.002	0.000	0.002																																																																															
17.0	0.024	0.435	0.859																																																																															
17.5	0.024	0.425	0.833																																																																															
18.0	0.023	0.409	0.970																																																																															
24.0	0.017	0.308	0.718																																																																															
36.0	0.013	0.207	0.476																																																																															
48.0	0.009	0.154	0.354																																																																															
62.0	0.008	0.123	0.226																																																																															
69.0	0.007	0.111	0.212																																																																															
75.5	0.007	0.104	0.196																																																																															
76.0	0.007	0.103	0.195																																																																															
80.0	0.007	0.098	0.186																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

COSEL


COSEL

Model	STMGFW154815	Temperature 25°C																																																																													
Item	Input Power (by Load Current)	Testing Circuitry Figure A																																																																													
Object	—																																																																														
1.Graph	<p>—△— Input Volt. 18V</p> <p>---□--- Input Volt. 24V</p> <p>—*— Input Volt. 36V</p> <p>—○— Input Volt. 48V</p> <p>—◇— Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18[V] [W]</th> <th>24[V] [W]</th> <th>36[V] [W]</th> <th>48[V] [W]</th> <th>76[V] [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.42</td><td>0.41</td><td>0.48</td><td>0.48</td><td>0.60</td></tr> <tr><td>20</td><td>3.67</td><td>3.68</td><td>3.82</td><td>3.79</td><td>4.23</td></tr> <tr><td>40</td><td>6.98</td><td>7.03</td><td>7.10</td><td>7.06</td><td>7.44</td></tr> <tr><td>60</td><td>10.33</td><td>10.33</td><td>10.33</td><td>10.47</td><td>10.58</td></tr> <tr><td>80</td><td>13.85</td><td>13.60</td><td>13.60</td><td>13.76</td><td>14.16</td></tr> <tr><td>100</td><td>17.42</td><td>17.16</td><td>17.14</td><td>17.00</td><td>17.19</td></tr> <tr><td>110</td><td>19.25</td><td>18.91</td><td>18.73</td><td>18.66</td><td>19.08</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	18[V] [W]	24[V] [W]	36[V] [W]	48[V] [W]	76[V] [W]	0	0.42	0.41	0.48	0.48	0.60	20	3.67	3.68	3.82	3.79	4.23	40	6.98	7.03	7.10	7.06	7.44	60	10.33	10.33	10.33	10.47	10.58	80	13.85	13.60	13.60	13.76	14.16	100	17.42	17.16	17.14	17.00	17.19	110	19.25	18.91	18.73	18.66	19.08	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-						
Load Ration [%]	18[V] [W]	24[V] [W]	36[V] [W]	48[V] [W]	76[V] [W]																																																																										
0	0.42	0.41	0.48	0.48	0.60																																																																										
20	3.67	3.68	3.82	3.79	4.23																																																																										
40	6.98	7.03	7.10	7.06	7.44																																																																										
60	10.33	10.33	10.33	10.47	10.58																																																																										
80	13.85	13.60	13.60	13.76	14.16																																																																										
100	17.42	17.16	17.14	17.00	17.19																																																																										
110	19.25	18.91	18.73	18.66	19.08																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
2.Values																																																																															
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.42</td><td>0.41</td><td>0.48</td><td>0.48</td><td>0.60</td></tr> <tr><td>20</td><td>3.67</td><td>3.68</td><td>3.82</td><td>3.79</td><td>4.23</td></tr> <tr><td>40</td><td>6.98</td><td>7.03</td><td>7.10</td><td>7.06</td><td>7.44</td></tr> <tr><td>60</td><td>10.33</td><td>10.33</td><td>10.33</td><td>10.47</td><td>10.58</td></tr> <tr><td>80</td><td>13.85</td><td>13.60</td><td>13.60</td><td>13.76</td><td>14.16</td></tr> <tr><td>100</td><td>17.42</td><td>17.16</td><td>17.14</td><td>17.00</td><td>17.19</td></tr> <tr><td>110</td><td>19.25</td><td>18.91</td><td>18.73</td><td>18.66</td><td>19.08</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.42	0.41	0.48	0.48	0.60	20	3.67	3.68	3.82	3.79	4.23	40	6.98	7.03	7.10	7.06	7.44	60	10.33	10.33	10.33	10.47	10.58	80	13.85	13.60	13.60	13.76	14.16	100	17.42	17.16	17.14	17.00	17.19	110	19.25	18.91	18.73	18.66	19.08	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																																														
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																										
0	0.42	0.41	0.48	0.48	0.60																																																																										
20	3.67	3.68	3.82	3.79	4.23																																																																										
40	6.98	7.03	7.10	7.06	7.44																																																																										
60	10.33	10.33	10.33	10.47	10.58																																																																										
80	13.85	13.60	13.60	13.76	14.16																																																																										
100	17.42	17.16	17.14	17.00	17.19																																																																										
110	19.25	18.91	18.73	18.66	19.08																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										

COSEL

Model	STMGFW154815	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	—																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>86.7</td> <td>85.8</td> </tr> <tr> <td>18</td> <td>86.3</td> <td>86.1</td> </tr> <tr> <td>24</td> <td>86.9</td> <td>87.6</td> </tr> <tr> <td>30</td> <td>87.0</td> <td>88.8</td> </tr> <tr> <td>36</td> <td>86.9</td> <td>87.8</td> </tr> <tr> <td>48</td> <td>85.8</td> <td>88.5</td> </tr> <tr> <td>60</td> <td>86.2</td> <td>87.2</td> </tr> <tr> <td>76</td> <td>82.5</td> <td>87.6</td> </tr> <tr> <td>80</td> <td>81.7</td> <td>87.4</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	86.7	85.8	18	86.3	86.1	24	86.9	87.6	30	87.0	88.8	36	86.9	87.8	48	85.8	88.5	60	86.2	87.2	76	82.5	87.6	80	81.7	87.4
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
17	86.7	85.8																																	
18	86.3	86.1																																	
24	86.9	87.6																																	
30	87.0	88.8																																	
36	86.9	87.8																																	
48	85.8	88.5																																	
60	86.2	87.2																																	
76	82.5	87.6																																	
80	81.7	87.4																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	STMGFW154815
Item	Efficiency (by Load Current)
Object	—

1. Graph

Load Ration [%]	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
0	-	-	-	-	-
20	82.0	81.9	79.2	79.6	71.2
40	86.3	85.6	84.8	85.4	80.9
60	87.4	87.5	87.5	86.3	85.4
80	86.9	88.6	88.6	87.5	85.1
100	86.4	87.7	87.9	88.6	87.6
110	86.1	87.6	88.4	88.8	86.8
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Ration [%]	Efficiency [%]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0	-	-	-	-	-
20	82.0	81.9	79.2	79.6	71.2
40	86.3	85.6	84.8	85.4	80.9
60	87.4	87.5	87.5	86.3	85.4
80	86.9	88.6	88.6	87.5	85.1
100	86.4	87.7	87.9	88.6	87.6
110	86.1	87.6	88.4	88.8	86.8
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Model	STMGFW154815	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+15V0.5A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>15.102</td><td>15.000</td></tr> <tr><td>18</td><td>15.100</td><td>15.000</td></tr> <tr><td>24</td><td>15.100</td><td>15.000</td></tr> <tr><td>30</td><td>15.100</td><td>15.000</td></tr> <tr><td>36</td><td>15.101</td><td>15.000</td></tr> <tr><td>48</td><td>15.101</td><td>15.000</td></tr> <tr><td>60</td><td>15.101</td><td>15.000</td></tr> <tr><td>76</td><td>15.102</td><td>15.000</td></tr> <tr><td>80</td><td>15.102</td><td>15.000</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	15.102	15.000	18	15.100	15.000	24	15.100	15.000	30	15.100	15.000	36	15.101	15.000	48	15.101	15.000	60	15.101	15.000	76	15.102	15.000	80	15.102	15.000
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	15.102	15.000																																	
18	15.100	15.000																																	
24	15.100	15.000																																	
30	15.100	15.000																																	
36	15.101	15.000																																	
48	15.101	15.000																																	
60	15.101	15.000																																	
76	15.102	15.000																																	
80	15.102	15.000																																	
Object			2.Values																																
1.Graph			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>-15.110</td><td>-15.000</td></tr> <tr><td>18</td><td>-15.108</td><td>-15.001</td></tr> <tr><td>24</td><td>-15.108</td><td>-15.001</td></tr> <tr><td>30</td><td>-15.108</td><td>-15.002</td></tr> <tr><td>36</td><td>-15.108</td><td>-15.002</td></tr> <tr><td>48</td><td>-15.108</td><td>-15.003</td></tr> <tr><td>60</td><td>-15.108</td><td>-15.003</td></tr> <tr><td>76</td><td>-15.108</td><td>-15.002</td></tr> <tr><td>80</td><td>-15.108</td><td>-15.002</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	-15.110	-15.000	18	-15.108	-15.001	24	-15.108	-15.001	30	-15.108	-15.002	36	-15.108	-15.002	48	-15.108	-15.003	60	-15.108	-15.003	76	-15.108	-15.002	80	-15.108	-15.002
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	-15.110	-15.000																																	
18	-15.108	-15.001																																	
24	-15.108	-15.001																																	
30	-15.108	-15.002																																	
36	-15.108	-15.002																																	
48	-15.108	-15.003																																	
60	-15.108	-15.003																																	
76	-15.108	-15.002																																	
80	-15.108	-15.002																																	
Note: Slanted line shows the range of the rated input voltage.																																			

coSEL

Model	STMGFW154815	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Load Regulation																																																																																			
Object	+15V0.5A																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.597</td><td>15.587</td><td>15.575</td><td>15.572</td><td>15.582</td></tr> <tr><td>0.10</td><td>15.223</td><td>15.223</td><td>15.223</td><td>15.223</td><td>15.223</td></tr> <tr><td>0.20</td><td>15.139</td><td>15.139</td><td>15.139</td><td>15.139</td><td>15.139</td></tr> <tr><td>0.30</td><td>15.086</td><td>15.083</td><td>15.083</td><td>15.083</td><td>15.083</td></tr> <tr><td>0.40</td><td>15.043</td><td>15.039</td><td>15.039</td><td>15.039</td><td>15.039</td></tr> <tr><td>0.50</td><td>15.001</td><td>15.001</td><td>15.001</td><td>15.001</td><td>15.001</td></tr> <tr><td>0.55</td><td>14.981</td><td>14.983</td><td>14.984</td><td>14.984</td><td>14.984</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	15.597	15.587	15.575	15.572	15.582	0.10	15.223	15.223	15.223	15.223	15.223	0.20	15.139	15.139	15.139	15.139	15.139	0.30	15.086	15.083	15.083	15.083	15.083	0.40	15.043	15.039	15.039	15.039	15.039	0.50	15.001	15.001	15.001	15.001	15.001	0.55	14.981	14.983	14.984	14.984	14.984	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																			
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																															
0.00	15.597	15.587	15.575	15.572	15.582																																																																															
0.10	15.223	15.223	15.223	15.223	15.223																																																																															
0.20	15.139	15.139	15.139	15.139	15.139																																																																															
0.30	15.086	15.083	15.083	15.083	15.083																																																																															
0.40	15.043	15.039	15.039	15.039	15.039																																																																															
0.50	15.001	15.001	15.001	15.001	15.001																																																																															
0.55	14.981	14.983	14.984	14.984	14.984																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Object	-15V0.5A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.582</td><td>-15.577</td><td>-15.571</td><td>-15.567</td><td>-15.566</td></tr> <tr><td>0.10</td><td>-15.222</td><td>-15.222</td><td>-15.222</td><td>-15.222</td><td>-15.221</td></tr> <tr><td>0.20</td><td>-15.139</td><td>-15.140</td><td>-15.140</td><td>-15.140</td><td>-15.140</td></tr> <tr><td>0.30</td><td>-15.086</td><td>-15.084</td><td>-15.084</td><td>-15.084</td><td>-15.084</td></tr> <tr><td>0.40</td><td>-15.043</td><td>-15.040</td><td>-15.040</td><td>-15.040</td><td>-15.040</td></tr> <tr><td>0.50</td><td>-15.001</td><td>-15.001</td><td>-15.002</td><td>-15.002</td><td>-15.002</td></tr> <tr><td>0.55</td><td>-14.980</td><td>-14.983</td><td>-14.985</td><td>-14.985</td><td>-14.985</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-15.582	-15.577	-15.571	-15.567	-15.566	0.10	-15.222	-15.222	-15.222	-15.222	-15.221	0.20	-15.139	-15.140	-15.140	-15.140	-15.140	0.30	-15.086	-15.084	-15.084	-15.084	-15.084	0.40	-15.043	-15.040	-15.040	-15.040	-15.040	0.50	-15.001	-15.001	-15.002	-15.002	-15.002	0.55	-14.980	-14.983	-14.985	-14.985	-14.985	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																			
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																															
0.00	-15.582	-15.577	-15.571	-15.567	-15.566																																																																															
0.10	-15.222	-15.222	-15.222	-15.222	-15.221																																																																															
0.20	-15.139	-15.140	-15.140	-15.140	-15.140																																																																															
0.30	-15.086	-15.084	-15.084	-15.084	-15.084																																																																															
0.40	-15.043	-15.040	-15.040	-15.040	-15.040																																																																															
0.50	-15.001	-15.001	-15.002	-15.002	-15.002																																																																															
0.55	-14.980	-14.983	-14.985	-14.985	-14.985																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																			
Note:	Slanted line shows the range of the rated load current.																																																																																			


COSEL

Model STMGFW154815

Item Ripple Voltage (by Load Current)

Object +15V0.5A

1. Graph

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.000	20	30
0.100	35	40
0.200	35	40
0.300	35	40
0.400	40	40
0.500	40	45
0.550	40	45
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL

Model	STMGFW154815	
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B
Object	-15V0.5A	
1. Graph		
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		
<p>Ripple [mVp-p]</p>		
<p>Fig. Complex Ripple Wave Form</p>		
2. Values		
Load Current [A]	Ripple Voltage [mV]	
Input Volt. 18 [V]	Input Volt. 76 [V]	
0.000	30	30
0.100	30	30
0.200	30	30
0.300	30	30
0.400	35	35
0.500	35	35
0.550	35	35
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current

COSEL

Model	STMGFW154815																																																																													
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																																																												
Object	+15V0.5A																																																																													
1. Graph																																																																														
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0.0 to 0.6 A. Two curves are shown: one for Input Volt. 18V (solid line with triangle markers) and one for Input Volt. 76V (dashed line with circle markers). Both curves show an increase in Ripple-Noise as Load Current increases. A slanted line indicates the range of the rated load current.</p>		2. Values																																																																												
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>25</td><td>40</td></tr> <tr><td>0.100</td><td>40</td><td>40</td></tr> <tr><td>0.200</td><td>40</td><td>40</td></tr> <tr><td>0.300</td><td>40</td><td>50</td></tr> <tr><td>0.400</td><td>50</td><td>55</td></tr> <tr><td>0.500</td><td>50</td><td>55</td></tr> <tr><td>0.550</td><td>50</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.000	25	40	0.100	40	40	0.200	40	40	0.300	40	50	0.400	50	55	0.500	50	55	0.550	50	55	--	-	-	--	-	-	--	-	-	--	-	-	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>25</td><td>40</td></tr> <tr><td>0.100</td><td>40</td><td>40</td></tr> <tr><td>0.200</td><td>40</td><td>40</td></tr> <tr><td>0.300</td><td>40</td><td>50</td></tr> <tr><td>0.400</td><td>50</td><td>55</td></tr> <tr><td>0.500</td><td>50</td><td>55</td></tr> <tr><td>0.550</td><td>50</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.000	25	40	0.100	40	40	0.200	40	40	0.300	40	50	0.400	50	55	0.500	50	55	0.550	50	55	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																																																													
	Input Volt. 18 [V]	Input Volt. 76 [V]																																																																												
0.000	25	40																																																																												
0.100	40	40																																																																												
0.200	40	40																																																																												
0.300	40	50																																																																												
0.400	50	55																																																																												
0.500	50	55																																																																												
0.550	50	55																																																																												
--	-	-																																																																												
--	-	-																																																																												
--	-	-																																																																												
--	-	-																																																																												
Load Current [A]	Ripple-Noise [mV]																																																																													
	Input Volt. 18 [V]	Input Volt. 76 [V]																																																																												
0.000	25	40																																																																												
0.100	40	40																																																																												
0.200	40	40																																																																												
0.300	40	50																																																																												
0.400	50	55																																																																												
0.500	50	55																																																																												
0.550	50	55																																																																												
--	-	-																																																																												
--	-	-																																																																												
--	-	-																																																																												
--	-	-																																																																												
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																																																														

COSEL


Model STMGFW154815

Item Ripple-Noise

Object -15V0.5A

Temperature 25°C
Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.000	40	40
0.100	40	40
0.200	40	45
0.300	45	45
0.400	50	50
0.500	50	50
0.550	55	55
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current





Fig.Complex Ripple Noise Wave Form

COSEL

Model	STMGFW154815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.5A

1.Graph



Testing Circuitry Figure B


2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	50	55
-20	45	50
0	40	50
25	40	45
60	40	45
65	40	45
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

Object	-15V0.5A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	40	45
-20	35	40
0	35	35
25	35	35
60	35	35
65	35	35
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

<p>Model STMGFW154815</p> <p>Item Ambient Temperature Drift</p> <p>Object +15V0.5A</p>	Testing Circuitry Figure A																																																																																	
	2.Values																																																																																	
	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>14.942</td><td>14.943</td><td>14.944</td><td>14.944</td><td>14.944</td></tr> <tr> <td>-20</td><td>14.965</td><td>14.966</td><td>14.967</td><td>14.967</td><td>14.967</td></tr> <tr> <td>0</td><td>14.984</td><td>14.984</td><td>14.984</td><td>14.984</td><td>14.984</td></tr> <tr> <td>10</td><td>14.990</td><td>14.990</td><td>14.991</td><td>14.991</td><td>14.991</td></tr> <tr> <td>25</td><td>14.998</td><td>14.998</td><td>14.998</td><td>14.998</td><td>14.999</td></tr> <tr> <td>30</td><td>15.000</td><td>15.000</td><td>15.000</td><td>15.001</td><td>15.001</td></tr> <tr> <td>40</td><td>15.004</td><td>15.003</td><td>15.004</td><td>15.004</td><td>15.004</td></tr> <tr> <td>50</td><td>15.006</td><td>15.006</td><td>15.007</td><td>15.007</td><td>15.007</td></tr> <tr> <td>60</td><td>15.008</td><td>15.009</td><td>15.009</td><td>15.009</td><td>15.009</td></tr> <tr> <td>65</td><td>15.009</td><td>15.009</td><td>15.010</td><td>15.010</td><td>15.009</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-40	14.942	14.943	14.944	14.944	14.944	-20	14.965	14.966	14.967	14.967	14.967	0	14.984	14.984	14.984	14.984	14.984	10	14.990	14.990	14.991	14.991	14.991	25	14.998	14.998	14.998	14.998	14.999	30	15.000	15.000	15.000	15.001	15.001	40	15.004	15.003	15.004	15.004	15.004	50	15.006	15.006	15.007	15.007	15.007	60	15.008	15.009	15.009	15.009	15.009	65	15.009	15.009	15.010	15.010	15.009	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
-40	14.942	14.943	14.944	14.944	14.944																																																																													
-20	14.965	14.966	14.967	14.967	14.967																																																																													
0	14.984	14.984	14.984	14.984	14.984																																																																													
10	14.990	14.990	14.991	14.991	14.991																																																																													
25	14.998	14.998	14.998	14.998	14.999																																																																													
30	15.000	15.000	15.000	15.001	15.001																																																																													
40	15.004	15.003	15.004	15.004	15.004																																																																													
50	15.006	15.006	15.007	15.007	15.007																																																																													
60	15.008	15.009	15.009	15.009	15.009																																																																													
65	15.009	15.009	15.010	15.010	15.009																																																																													
--	-	-	-	-	-																																																																													
<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>14.942</td><td>14.943</td><td>14.944</td><td>14.944</td><td>14.944</td></tr> <tr> <td>-20</td><td>14.965</td><td>14.966</td><td>14.967</td><td>14.967</td><td>14.967</td></tr> <tr> <td>0</td><td>14.984</td><td>14.984</td><td>14.984</td><td>14.984</td><td>14.984</td></tr> <tr> <td>10</td><td>14.990</td><td>14.990</td><td>14.991</td><td>14.991</td><td>14.991</td></tr> <tr> <td>25</td><td>14.998</td><td>14.998</td><td>14.998</td><td>14.998</td><td>14.999</td></tr> <tr> <td>30</td><td>15.000</td><td>15.000</td><td>15.000</td><td>15.001</td><td>15.001</td></tr> <tr> <td>40</td><td>15.004</td><td>15.003</td><td>15.004</td><td>15.004</td><td>15.004</td></tr> <tr> <td>50</td><td>15.006</td><td>15.006</td><td>15.007</td><td>15.007</td><td>15.007</td></tr> <tr> <td>60</td><td>15.008</td><td>15.009</td><td>15.009</td><td>15.009</td><td>15.009</td></tr> <tr> <td>65</td><td>15.009</td><td>15.009</td><td>15.010</td><td>15.010</td><td>15.009</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-40	14.942	14.943	14.944	14.944	14.944	-20	14.965	14.966	14.967	14.967	14.967	0	14.984	14.984	14.984	14.984	14.984	10	14.990	14.990	14.991	14.991	14.991	25	14.998	14.998	14.998	14.998	14.999	30	15.000	15.000	15.000	15.001	15.001	40	15.004	15.003	15.004	15.004	15.004	50	15.006	15.006	15.007	15.007	15.007	60	15.008	15.009	15.009	15.009	15.009	65	15.009	15.009	15.010	15.010	15.009	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
-40	14.942	14.943	14.944	14.944	14.944																																																																													
-20	14.965	14.966	14.967	14.967	14.967																																																																													
0	14.984	14.984	14.984	14.984	14.984																																																																													
10	14.990	14.990	14.991	14.991	14.991																																																																													
25	14.998	14.998	14.998	14.998	14.999																																																																													
30	15.000	15.000	15.000	15.001	15.001																																																																													
40	15.004	15.003	15.004	15.004	15.004																																																																													
50	15.006	15.006	15.007	15.007	15.007																																																																													
60	15.008	15.009	15.009	15.009	15.009																																																																													
65	15.009	15.009	15.010	15.010	15.009																																																																													
--	-	-	-	-	-																																																																													
<p>Object -15V0.5A</p> <p>1.Graph</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>-14.941</td><td>-14.942</td><td>-14.943</td><td>-14.944</td><td>-14.945</td></tr> <tr> <td>-20</td><td>-14.964</td><td>-14.966</td><td>-14.967</td><td>-14.967</td><td>-14.968</td></tr> <tr> <td>0</td><td>-14.982</td><td>-14.983</td><td>-14.984</td><td>-14.985</td><td>-14.985</td></tr> <tr> <td>10</td><td>-14.989</td><td>-14.990</td><td>-14.991</td><td>-14.991</td><td>-14.992</td></tr> <tr> <td>25</td><td>-14.997</td><td>-14.998</td><td>-14.999</td><td>-14.999</td><td>-14.999</td></tr> <tr> <td>30</td><td>-14.999</td><td>-15.000</td><td>-15.001</td><td>-15.001</td><td>-15.002</td></tr> <tr> <td>40</td><td>-15.003</td><td>-15.003</td><td>-15.005</td><td>-15.005</td><td>-15.005</td></tr> <tr> <td>50</td><td>-15.006</td><td>-15.007</td><td>-15.008</td><td>-15.008</td><td>-15.008</td></tr> <tr> <td>60</td><td>-15.009</td><td>-15.009</td><td>-15.010</td><td>-15.010</td><td>-15.010</td></tr> <tr> <td>65</td><td>-15.009</td><td>-15.010</td><td>-15.011</td><td>-15.011</td><td>-15.011</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-40	-14.941	-14.942	-14.943	-14.944	-14.945	-20	-14.964	-14.966	-14.967	-14.967	-14.968	0	-14.982	-14.983	-14.984	-14.985	-14.985	10	-14.989	-14.990	-14.991	-14.991	-14.992	25	-14.997	-14.998	-14.999	-14.999	-14.999	30	-14.999	-15.000	-15.001	-15.001	-15.002	40	-15.003	-15.003	-15.005	-15.005	-15.005	50	-15.006	-15.007	-15.008	-15.008	-15.008	60	-15.009	-15.009	-15.010	-15.010	-15.010	65	-15.009	-15.010	-15.011	-15.011	-15.011	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
-40	-14.941	-14.942	-14.943	-14.944	-14.945																																																																													
-20	-14.964	-14.966	-14.967	-14.967	-14.968																																																																													
0	-14.982	-14.983	-14.984	-14.985	-14.985																																																																													
10	-14.989	-14.990	-14.991	-14.991	-14.992																																																																													
25	-14.997	-14.998	-14.999	-14.999	-14.999																																																																													
30	-14.999	-15.000	-15.001	-15.001	-15.002																																																																													
40	-15.003	-15.003	-15.005	-15.005	-15.005																																																																													
50	-15.006	-15.007	-15.008	-15.008	-15.008																																																																													
60	-15.009	-15.009	-15.010	-15.010	-15.010																																																																													
65	-15.009	-15.010	-15.011	-15.011	-15.011																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																																																		



Model	STMGFW154815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 0.5A (AVR 2) : 0 - 0.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V0.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	18	0	15.619	±327	±2.2
Minimum Voltage	-20	18	0.5	14.965		

Object	-15V0.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	18	0	-15.612	±324	±2.2
Minimum Voltage	-20	18	0.5	-14.964		

COSEL

Model	STMGFW154815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.5A																								
1.Graph		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>14.986</td></tr> <tr><td>0.5</td><td>14.995</td></tr> <tr><td>1.0</td><td>14.995</td></tr> <tr><td>2.0</td><td>14.995</td></tr> <tr><td>3.0</td><td>14.995</td></tr> <tr><td>4.0</td><td>14.995</td></tr> <tr><td>5.0</td><td>14.995</td></tr> <tr><td>6.0</td><td>14.995</td></tr> <tr><td>7.0</td><td>14.995</td></tr> <tr><td>8.0</td><td>14.995</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	14.986	0.5	14.995	1.0	14.995	2.0	14.995	3.0	14.995	4.0	14.995	5.0	14.995	6.0	14.995	7.0	14.995	8.0	14.995
Time since start [H]	Output Voltage [V]																								
0.0	14.986																								
0.5	14.995																								
1.0	14.995																								
2.0	14.995																								
3.0	14.995																								
4.0	14.995																								
5.0	14.995																								
6.0	14.995																								
7.0	14.995																								
8.0	14.995																								
Object -15V0.5A		2.Values																							
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-15.001</td></tr> <tr><td>0.5</td><td>-15.009</td></tr> <tr><td>1.0</td><td>-15.009</td></tr> <tr><td>2.0</td><td>-15.009</td></tr> <tr><td>3.0</td><td>-15.010</td></tr> <tr><td>4.0</td><td>-15.010</td></tr> <tr><td>5.0</td><td>-15.010</td></tr> <tr><td>6.0</td><td>-15.010</td></tr> <tr><td>7.0</td><td>-15.010</td></tr> <tr><td>8.0</td><td>-15.009</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-15.001	0.5	-15.009	1.0	-15.009	2.0	-15.009	3.0	-15.010	4.0	-15.010	5.0	-15.010	6.0	-15.010	7.0	-15.010	8.0	-15.009
Time since start [H]	Output Voltage [V]																								
0.0	-15.001																								
0.5	-15.009																								
1.0	-15.009																								
2.0	-15.009																								
3.0	-15.010																								
4.0	-15.010																								
5.0	-15.010																								
6.0	-15.010																								
7.0	-15.010																								
8.0	-15.009																								

COSEL


Model STMGFW154815

Item Rise and Fall Time

Object +15V0.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.0	4.8	5.8	4.8	5.1	
100 %		1.0	4.9	5.9	2.4	2.5	



COSEL

Model STMGFW154815


Item Rise and Fall Time

Object -15V0.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph


Input Volt. 48 V



2. Values

[ms]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.0	5.0	6.0	4.8	5.4
100 %		1.0	5.0	6.0	2.4	2.7



COSEL

Model	STMGFW154815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.5A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	15.8	16.2
-20	15.9	16.2
0	16.3	16.2
10	16.3	16.2
25	16.2	16.1
30	16.2	16.2
40	16.3	16.2
50	16.2	16.2
60	16.2	16.1
65	16.2	16.1
--	-	-

Object	-15V0.5A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	15.8	16.1
-20	15.8	16.1
0	16.2	16.1
10	16.2	16.1
25	16.2	16.1
30	16.2	16.1
40	16.2	16.1
50	16.2	16.1
60	16.2	16.1
65	16.2	16.1
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	STMGFW154815	Temperature 25°C																																																																																			
Item	Overcurrent Protection	Testing Circuitry Figure A																																																																																			
Object	+15V0.5A																																																																																				
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 	2.Values																																																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>0.798</td><td>0.939</td><td>1.079</td><td>1.100</td><td>1.079</td></tr> <tr><td>14.3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	15.0	0.798	0.939	1.079	1.100	1.079	14.3	-	-	-	-	-	13.5	-	-	-	-	-	12.0	-	-	-	-	-	10.5	-	-	-	-	-	9.0	-	-	-	-	-	7.5	-	-	-	-	-	6.0	-	-	-	-	-	4.5	-	-	-	-	-	3.0	-	-	-	-	-	1.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																
15.0	0.798	0.939	1.079	1.100	1.079																																																																																
14.3	-	-	-	-	-																																																																																
13.5	-	-	-	-	-																																																																																
12.0	-	-	-	-	-																																																																																
10.5	-	-	-	-	-																																																																																
9.0	-	-	-	-	-																																																																																
7.5	-	-	-	-	-																																																																																
6.0	-	-	-	-	-																																																																																
4.5	-	-	-	-	-																																																																																
3.0	-	-	-	-	-																																																																																
1.5	-	-	-	-	-																																																																																
0.0	-	-	-	-	-																																																																																
Object	-15V0.5A	2.Values																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-15.0</td><td>0.795</td><td>0.936</td><td>1.075</td><td>1.105</td><td>1.075</td></tr> <tr><td>-14.3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-15.0	0.795	0.936	1.075	1.105	1.075	-14.3	-	-	-	-	-	-13.5	-	-	-	-	-	-12.0	-	-	-	-	-	-10.5	-	-	-	-	-	-9.0	-	-	-	-	-	-7.5	-	-	-	-	-	-6.0	-	-	-	-	-	-4.5	-	-	-	-	-	-3.0	-	-	-	-	-	-1.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																
-15.0	0.795	0.936	1.075	1.105	1.075																																																																																
-14.3	-	-	-	-	-																																																																																
-13.5	-	-	-	-	-																																																																																
-12.0	-	-	-	-	-																																																																																
-10.5	-	-	-	-	-																																																																																
-9.0	-	-	-	-	-																																																																																
-7.5	-	-	-	-	-																																																																																
-6.0	-	-	-	-	-																																																																																
-4.5	-	-	-	-	-																																																																																
-3.0	-	-	-	-	-																																																																																
-1.5	-	-	-	-	-																																																																																
0.0	-	-	-	-	-																																																																																
		<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																																																			




Figure A




Figure B (Ripple and Ripple noise Characteristic)