



TEST DATA OF STMGFW304805

Regulated DC Power Supply
January 29, 2013

Approved by :

Takahiro Yoneda

Design Manager

Prepared by :

Satoshi Kinoshita

Satoshi Kinoshita

Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage) ······	1
2. Input Current (by Load Current) ······	2
3. Input Power (by Load Current) ······	3
4. Efficiency (by Input Voltage) ······	4
5. Efficiency (by Load Current) ······	5
6. Line Regulation ······	6
7. Load Regulation ······	7
8. Ripple Voltage (by Load Current) ······	8
9. Ripple-Noise ······	10
10. Ripple Voltage (by Ambient Temperature) ······	12
11. Ambient Temperature Drift ······	13
12. Output Voltage Accuracy ······	14
13. Time Lapse Drift ······	15
14. Rise and Fall Time ······	16
15. Minimum Input Voltage for Regulated Output Voltage ······	18
16. Overcurrent Protection ······	19
17. Overvoltage Protection ······	20
18. Figure of Testing Circuitry ······	21

(Final Page 21)


COSEL

Model	STMGFW304805	Temperature	25°C
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A
Object			
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□-- Load 50% - - -○-- Load 0%</p>		
2.Values			
Input Voltage [V]	Input Current [A]		
[V]	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
5.0	0.000	0.000	0.000
10.0	0.000	0.000	0.000
15.0	0.000	0.000	0.000
16.0	0.000	0.000	0.000
16.5	0.000	0.000	0.000
17.0	0.016	0.696	1.482
17.5	0.016	0.673	1.433
18.0	0.015	0.652	1.329
24.0	0.014	0.490	0.985
36.0	0.012	0.332	0.658
48.0	0.012	0.253	0.496
62.0	0.012	0.201	0.408
69.0	0.012	0.183	0.370
75.5	0.012	0.170	0.340
76.0	0.012	0.169	0.322
77.0	0.012	0.167	0.334
78.0	0.012	0.165	0.330

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	STMGFW304805
Item	Input Current (by Load Current)
Object	—




Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ration [%]	Input Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0	0.015	0.014	0.012	0.012	0.012
20	0.281	0.211	0.143	0.111	0.079
40	0.535	0.399	0.271	0.208	0.140
60	0.790	0.592	0.398	0.302	0.200
80	1.056	0.788	0.527	0.399	0.260
100	1.329	0.985	0.658	0.496	0.322
110	1.460	1.086	0.724	0.546	0.353
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

COSEL

Model	STMGFW304805	Temperature	25°C																																																																													
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																																													
Object	_____																																																																															
1.Graph		2.Values																																																																														
 <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.28</td> <td>0.33</td> <td>0.46</td> <td>0.60</td> <td>0.96</td> </tr> <tr> <td>20</td> <td>5.05</td> <td>5.06</td> <td>5.16</td> <td>5.36</td> <td>6.00</td> </tr> <tr> <td>40</td> <td>9.59</td> <td>9.56</td> <td>9.76</td> <td>9.97</td> <td>10.65</td> </tr> <tr> <td>60</td> <td>14.21</td> <td>14.15</td> <td>14.31</td> <td>14.52</td> <td>15.21</td> </tr> <tr> <td>80</td> <td>18.94</td> <td>18.83</td> <td>18.96</td> <td>19.13</td> <td>19.80</td> </tr> <tr> <td>100</td> <td>23.78</td> <td>23.60</td> <td>23.66</td> <td>23.82</td> <td>24.47</td> </tr> <tr> <td>110</td> <td>26.26</td> <td>26.02</td> <td>26.04</td> <td>26.18</td> <td>26.81</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Ration [%]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.28	0.33	0.46	0.60	0.96	20	5.05	5.06	5.16	5.36	6.00	40	9.59	9.56	9.76	9.97	10.65	60	14.21	14.15	14.31	14.52	15.21	80	18.94	18.83	18.96	19.13	19.80	100	23.78	23.60	23.66	23.82	24.47	110	26.26	26.02	26.04	26.18	26.81	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0	0.28	0.33	0.46	0.60	0.96																																																																											
20	5.05	5.06	5.16	5.36	6.00																																																																											
40	9.59	9.56	9.76	9.97	10.65																																																																											
60	14.21	14.15	14.31	14.52	15.21																																																																											
80	18.94	18.83	18.96	19.13	19.80																																																																											
100	23.78	23.60	23.66	23.82	24.47																																																																											
110	26.26	26.02	26.04	26.18	26.81																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

COSEL

Model	STMGFW304805	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	—																																		
1.Graph			2.Values																																
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (10 to 90). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>84.9</td> <td>85.1</td> </tr> <tr> <td>18</td> <td>85.6</td> <td>85.6</td> </tr> <tr> <td>24</td> <td>85.7</td> <td>86.3</td> </tr> <tr> <td>30</td> <td>85.2</td> <td>86.3</td> </tr> <tr> <td>36</td> <td>84.6</td> <td>86.1</td> </tr> <tr> <td>48</td> <td>83.0</td> <td>85.5</td> </tr> <tr> <td>60</td> <td>81.3</td> <td>84.8</td> </tr> <tr> <td>76</td> <td>78.7</td> <td>83.2</td> </tr> <tr> <td>80</td> <td>78.0</td> <td>83.0</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	84.9	85.1	18	85.6	85.6	24	85.7	86.3	30	85.2	86.3	36	84.6	86.1	48	83.0	85.5	60	81.3	84.8	76	78.7	83.2	80	78.0	83.0
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
17	84.9	85.1																																	
18	85.6	85.6																																	
24	85.7	86.3																																	
30	85.2	86.3																																	
36	84.6	86.1																																	
48	83.0	85.5																																	
60	81.3	84.8																																	
76	78.7	83.2																																	
80	78.0	83.0																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	STMGFW304805	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Efficiency (by Load Current)																																																																																		
Object	_____																																																																																		
1.Graph	<p>Efficiency [%]</p> <p>Load Ration [%]</p> <ul style="list-style-type: none"> —△— Input Volt. 18V - - ■ - - Input Volt. 24V - · * · - - Input Volt. 36V - · ○ · - - Input Volt. 48V - · ◇ · - - Input Volt. 76V 																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>80.6</td><td>80.4</td><td>78.8</td><td>75.9</td><td>67.8</td></tr> <tr> <td>40</td><td>84.9</td><td>85.2</td><td>83.4</td><td>81.7</td><td>76.4</td></tr> <tr> <td>60</td><td>86.0</td><td>86.3</td><td>85.4</td><td>84.1</td><td>80.3</td></tr> <tr> <td>80</td><td>86.0</td><td>86.5</td><td>85.9</td><td>85.1</td><td>82.3</td></tr> <tr> <td>100</td><td>85.6</td><td>86.2</td><td>86.0</td><td>85.5</td><td>83.2</td></tr> <tr> <td>110</td><td>85.3</td><td>86.1</td><td>86.0</td><td>85.5</td><td>83.5</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Load Ration [%]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	-	-	20	80.6	80.4	78.8	75.9	67.8	40	84.9	85.2	83.4	81.7	76.4	60	86.0	86.3	85.4	84.1	80.3	80	86.0	86.5	85.9	85.1	82.3	100	85.6	86.2	86.0	85.5	83.2	110	85.3	86.1	86.0	85.5	83.5	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																																																		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																														
0	-	-	-	-	-																																																																														
20	80.6	80.4	78.8	75.9	67.8																																																																														
40	84.9	85.2	83.4	81.7	76.4																																																																														
60	86.0	86.3	85.4	84.1	80.3																																																																														
80	86.0	86.5	85.9	85.1	82.3																																																																														
100	85.6	86.2	86.0	85.5	83.2																																																																														
110	85.3	86.1	86.0	85.5	83.5																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														

Model	STMGFW304805	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+5V2A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>5.123</td><td>5.076</td></tr> <tr><td>18</td><td>5.123</td><td>5.076</td></tr> <tr><td>24</td><td>5.121</td><td>5.076</td></tr> <tr><td>30</td><td>5.119</td><td>5.076</td></tr> <tr><td>36</td><td>5.119</td><td>5.076</td></tr> <tr><td>48</td><td>5.118</td><td>5.076</td></tr> <tr><td>60</td><td>5.118</td><td>5.076</td></tr> <tr><td>76</td><td>5.117</td><td>5.075</td></tr> <tr><td>80</td><td>5.117</td><td>5.075</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	5.123	5.076	18	5.123	5.076	24	5.121	5.076	30	5.119	5.076	36	5.119	5.076	48	5.118	5.076	60	5.118	5.076	76	5.117	5.075	80	5.117	5.075
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	5.123	5.076																																	
18	5.123	5.076																																	
24	5.121	5.076																																	
30	5.119	5.076																																	
36	5.119	5.076																																	
48	5.118	5.076																																	
60	5.118	5.076																																	
76	5.117	5.075																																	
80	5.117	5.075																																	
Object -5V2A			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>-5.127</td><td>-5.077</td></tr> <tr><td>18</td><td>-5.127</td><td>-5.077</td></tr> <tr><td>24</td><td>-5.123</td><td>-5.077</td></tr> <tr><td>30</td><td>-5.122</td><td>-5.077</td></tr> <tr><td>36</td><td>-5.122</td><td>-5.078</td></tr> <tr><td>48</td><td>-5.121</td><td>-5.078</td></tr> <tr><td>60</td><td>-5.121</td><td>-5.078</td></tr> <tr><td>76</td><td>-5.120</td><td>-5.078</td></tr> <tr><td>80</td><td>-5.120</td><td>-5.078</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	-5.127	-5.077	18	-5.127	-5.077	24	-5.123	-5.077	30	-5.122	-5.077	36	-5.122	-5.078	48	-5.121	-5.078	60	-5.121	-5.078	76	-5.120	-5.078	80	-5.120	-5.078
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	-5.127	-5.077																																	
18	-5.127	-5.077																																	
24	-5.123	-5.077																																	
30	-5.122	-5.077																																	
36	-5.122	-5.078																																	
48	-5.121	-5.078																																	
60	-5.121	-5.078																																	
76	-5.120	-5.078																																	
80	-5.120	-5.078																																	
Note: Slanted line shows the range of the rated input voltage.																																			

COSEL

<p>Model STMGFW304805</p> <p>Item Load Regulation</p> <p>Object +5V2A</p>	Temperature 25°C Testing Circuitry Figure A																																																																																
	2.Values																																																																																
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.625</td><td>5.604</td><td>5.684</td><td>5.759</td><td>5.816</td></tr> <tr><td>0.4</td><td>5.162</td><td>5.159</td><td>5.157</td><td>5.156</td><td>5.156</td></tr> <tr><td>0.8</td><td>5.135</td><td>5.132</td><td>5.130</td><td>5.129</td><td>5.129</td></tr> <tr><td>1.2</td><td>5.113</td><td>5.112</td><td>5.110</td><td>5.110</td><td>5.109</td></tr> <tr><td>1.6</td><td>5.094</td><td>5.093</td><td>5.092</td><td>5.092</td><td>5.091</td></tr> <tr><td>2.0</td><td>5.075</td><td>5.075</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>2.2</td><td>5.066</td><td>5.067</td><td>5.067</td><td>5.067</td><td>5.067</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	5.625	5.604	5.684	5.759	5.816	0.4	5.162	5.159	5.157	5.156	5.156	0.8	5.135	5.132	5.130	5.129	5.129	1.2	5.113	5.112	5.110	5.110	5.109	1.6	5.094	5.093	5.092	5.092	5.091	2.0	5.075	5.075	5.075	5.075	5.075	2.2	5.066	5.067	5.067	5.067	5.067	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																												
0.0	5.625	5.604	5.684	5.759	5.816																																																																												
0.4	5.162	5.159	5.157	5.156	5.156																																																																												
0.8	5.135	5.132	5.130	5.129	5.129																																																																												
1.2	5.113	5.112	5.110	5.110	5.109																																																																												
1.6	5.094	5.093	5.092	5.092	5.091																																																																												
2.0	5.075	5.075	5.075	5.075	5.075																																																																												
2.2	5.066	5.067	5.067	5.067	5.067																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																																
Object -5V2A	2.Values																																																																																
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																																
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																	
					BC - 10735																																																																												


COSEL

Model	STMGFW304805	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+5V2A																																								
1.Graph		2.Values																																							
<p>Y-axis: Ripple Voltage [mV] X-axis: Load Current [A]</p> <p>Legend: —○— Input Volt. 18V -●- Input Volt. 76V </p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>18 [V]</th> <th>76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.4</td><td>10</td><td>10</td></tr> <tr><td>0.8</td><td>10</td><td>10</td></tr> <tr><td>1.2</td><td>10</td><td>10</td></tr> <tr><td>1.6</td><td>10</td><td>10</td></tr> <tr><td>2.0</td><td>10</td><td>10</td></tr> <tr><td>2.2</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>		Load Current [A]	Ripple Voltage [mV]		18 [V]	76 [V]	0.0	10	10	0.4	10	10	0.8	10	10	1.2	10	10	1.6	10	10	2.0	10	10	2.2	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	18 [V]	76 [V]																																							
0.0	10	10																																							
0.4	10	10																																							
0.8	10	10																																							
1.2	10	10																																							
1.6	10	10																																							
2.0	10	10																																							
2.2	10	10																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									

COSEL

Model	STMGFW304805
Item	Ripple Voltage (by Load Current)
Object	-5V2A

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	10	10
0.4	10	10
0.8	10	10
1.2	10	10
1.6	10	10
2.0	10	10
2.2	10	10
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	STMGFW304805
Item	Ripple-Noise
Object	+5V2A

Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	20	20
0.4	20	20
0.8	20	20
1.2	20	20
1.6	20	20
2.0	20	20
2.2	20	20
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form


COSEL

Model STMGFW304805

Item Ripple-Noise

Object -5V2A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure B

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	20	20
0.4	20	20
0.8	20	20
1.2	20	20
1.6	20	20
2.0	20	20
2.2	20	20
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current





Fig.Complex Ripple Noise Wave Form

COSEL

Model	STMGFW304805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2A

1.Graph



Testing Circuitry Figure B


2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	20	20
-20	20	20
0	15	15
25	15	15
60	15	15
65	15	15
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

Object	-5V2A
--------	-------

1.Graph





2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	25	25
-20	25	25
0	20	20
25	20	20
60	20	20
65	20	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	STMGFW304805	Testing Circuitry Figure A																																																																																
Item	Ambient Temperature Drift																																																																																	
Object	+5V2A																																																																																	
1.Graph	 <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> — △ — Input Volt. 18V --- □ --- Input Volt. 24V --- * --- Input Volt. 36V --- ○ --- Input Volt. 48V --- ◆ --- Input Volt. 76V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>5.051</td><td>5.052</td><td>5.052</td><td>5.052</td><td>5.053</td></tr> <tr> <td>-20</td><td>5.061</td><td>5.062</td><td>5.062</td><td>5.062</td><td>5.062</td></tr> <tr> <td>0</td><td>5.069</td><td>5.070</td><td>5.070</td><td>5.069</td><td>5.069</td></tr> <tr> <td>10</td><td>5.072</td><td>5.073</td><td>5.072</td><td>5.072</td><td>5.072</td></tr> <tr> <td>25</td><td>5.076</td><td>5.076</td><td>5.076</td><td>5.075</td><td>5.075</td></tr> <tr> <td>30</td><td>5.076</td><td>5.077</td><td>5.077</td><td>5.076</td><td>5.076</td></tr> <tr> <td>40</td><td>5.078</td><td>5.078</td><td>5.078</td><td>5.077</td><td>5.077</td></tr> <tr> <td>50</td><td>5.079</td><td>5.079</td><td>5.078</td><td>5.078</td><td>5.078</td></tr> <tr> <td>60</td><td>5.079</td><td>5.079</td><td>5.079</td><td>5.078</td><td>5.078</td></tr> <tr> <td>65</td><td>5.079</td><td>5.079</td><td>5.079</td><td>5.078</td><td>5.078</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-40	5.051	5.052	5.052	5.052	5.053	-20	5.061	5.062	5.062	5.062	5.062	0	5.069	5.070	5.070	5.069	5.069	10	5.072	5.073	5.072	5.072	5.072	25	5.076	5.076	5.076	5.075	5.075	30	5.076	5.077	5.077	5.076	5.076	40	5.078	5.078	5.078	5.077	5.077	50	5.079	5.079	5.078	5.078	5.078	60	5.079	5.079	5.079	5.078	5.078	65	5.079	5.079	5.079	5.078	5.078	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
-40	5.051	5.052	5.052	5.052	5.053																																																																													
-20	5.061	5.062	5.062	5.062	5.062																																																																													
0	5.069	5.070	5.070	5.069	5.069																																																																													
10	5.072	5.073	5.072	5.072	5.072																																																																													
25	5.076	5.076	5.076	5.075	5.075																																																																													
30	5.076	5.077	5.077	5.076	5.076																																																																													
40	5.078	5.078	5.078	5.077	5.077																																																																													
50	5.079	5.079	5.078	5.078	5.078																																																																													
60	5.079	5.079	5.079	5.078	5.078																																																																													
65	5.079	5.079	5.079	5.078	5.078																																																																													
--	-	-	-	-	-																																																																													
Object	-5V2A																																																																																	
1.Graph	 <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> — △ — Input Volt. 18V --- □ --- Input Volt. 24V --- * --- Input Volt. 36V --- ○ --- Input Volt. 48V --- ◆ --- Input Volt. 76V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>-40</td><td>-5.050</td><td>-5.050</td><td>-5.051</td><td>-5.052</td><td>-5.052</td></tr> <tr> <td>-20</td><td>-5.061</td><td>-5.061</td><td>-5.061</td><td>-5.062</td><td>-5.062</td></tr> <tr> <td>0</td><td>-5.069</td><td>-5.069</td><td>-5.069</td><td>-5.070</td><td>-5.070</td></tr> <tr> <td>10</td><td>-5.072</td><td>-5.072</td><td>-5.073</td><td>-5.073</td><td>-5.073</td></tr> <tr> <td>25</td><td>-5.076</td><td>-5.075</td><td>-5.076</td><td>-5.077</td><td>-5.077</td></tr> <tr> <td>30</td><td>-5.077</td><td>-5.076</td><td>-5.077</td><td>-5.077</td><td>-5.078</td></tr> <tr> <td>40</td><td>-5.078</td><td>-5.078</td><td>-5.079</td><td>-5.079</td><td>-5.079</td></tr> <tr> <td>50</td><td>-5.079</td><td>-5.079</td><td>-5.080</td><td>-5.080</td><td>-5.080</td></tr> <tr> <td>60</td><td>-5.080</td><td>-5.080</td><td>-5.080</td><td>-5.081</td><td>-5.081</td></tr> <tr> <td>65</td><td>-5.080</td><td>-5.080</td><td>-5.080</td><td>-5.081</td><td>-5.081</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-40	-5.050	-5.050	-5.051	-5.052	-5.052	-20	-5.061	-5.061	-5.061	-5.062	-5.062	0	-5.069	-5.069	-5.069	-5.070	-5.070	10	-5.072	-5.072	-5.073	-5.073	-5.073	25	-5.076	-5.075	-5.076	-5.077	-5.077	30	-5.077	-5.076	-5.077	-5.077	-5.078	40	-5.078	-5.078	-5.079	-5.079	-5.079	50	-5.079	-5.079	-5.080	-5.080	-5.080	60	-5.080	-5.080	-5.080	-5.081	-5.081	65	-5.080	-5.080	-5.080	-5.081	-5.081	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
-40	-5.050	-5.050	-5.051	-5.052	-5.052																																																																													
-20	-5.061	-5.061	-5.061	-5.062	-5.062																																																																													
0	-5.069	-5.069	-5.069	-5.070	-5.070																																																																													
10	-5.072	-5.072	-5.073	-5.073	-5.073																																																																													
25	-5.076	-5.075	-5.076	-5.077	-5.077																																																																													
30	-5.077	-5.076	-5.077	-5.077	-5.078																																																																													
40	-5.078	-5.078	-5.079	-5.079	-5.079																																																																													
50	-5.079	-5.079	-5.080	-5.080	-5.080																																																																													
60	-5.080	-5.080	-5.080	-5.081	-5.081																																																																													
65	-5.080	-5.080	-5.080	-5.081	-5.081																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																																																		



Model	STMGFW304805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 2A (AVR 2) : 0 - 2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+5V2A			Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]		Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	76		0	5.853		
Minimum Voltage	-20	18		2	5.061	±396	±7.9

Object	-5V2A			Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]		Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	76		0	-5.778		
Minimum Voltage	-20	18		2	-5.061	±359	±7.2


COSEL

Model STMGFW304805

Item Time Lapse Drift


Object +5V2A

1.Graph

Input Volt. 48V
Load 100%

Object -5V2A

1.Graph

Input Volt. 48V
Load 100%Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	5.062
0.5	5.065
1.0	5.065
2.0	5.065
3.0	5.065
4.0	5.065
5.0	5.065
6.0	5.065
7.0	5.065
8.0	5.065

2.Values

Time since start [H]	Output Voltage [V]
0.0	-5.084
0.5	-5.090
1.0	-5.090
2.0	-5.090
3.0	-5.090
4.0	-5.090
5.0	-5.090
6.0	-5.090
7.0	-5.090
8.0	-5.090

COSEL

Model STMGFW304805


Temperature 25°C
Testing Circuitry Figure A

Item Rise and Fall Time

Object +5V2A

1. Graph


Input Volt. 48 V



2. Values

[ms]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		2.0	8.4	10.4	3.5	1.0
100 %		2.0	8.5	10.5	1.8	0.5



COSEL


Model	STMGFW304805	Temperature Testing Circuitry Object	25°C Figure A
Item	Rise and Fall Time		
Object	-5V2A		

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.1	8.7	10.8	3.5	1.1	
100 %		2.1	8.5	10.6	1.8	0.7	



COSEL

Model	STMGFW304805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	16.1	16.0
-20	16.1	16.2
0	16.1	16.4
10	16.1	16.4
25	16.1	16.4
30	16.1	16.4
40	16.1	16.4
50	16.1	16.4
60	16.1	16.4
65	16.1	16.4
--	-	-

Object	-5V2A
--------	-------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	15.8	15.7
-20	15.9	15.8
0	15.9	16.2
10	15.9	16.2
25	15.9	16.2
30	15.9	16.2
40	15.8	16.1
50	15.9	16.1
60	15.9	16.1
65	15.9	16.1
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	STMGFW304805
Item	Overcurrent Protection
Object	+5V2A
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 18V —□— Input Volt. 24V —*— Input Volt. 36V —○— Input Volt. 48V —◇— Input Volt. 76V <p>Output Voltage [V]</p> <p>Load Current [A]</p>
Object	-5V2A
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 18V —□— Input Volt. 24V —*— Input Volt. 36V —○— Input Volt. 48V —◇— Input Volt. 76V <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current. Intermittent operation occurs when overcurrent protection is activated.</p>

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
5.00	3.235	3.666	3.931	3.853	3.104
4.75	-	-	-	-	-
4.50	-	-	-	-	-
4.00	-	-	-	-	-
3.50	-	-	-	-	-
3.00	-	-	-	-	-
2.50	-	-	-	-	-
2.00	-	-	-	-	-
1.50	-	-	-	-	-
1.00	-	-	-	-	-
0.50	-	-	-	-	-
0.00	-	-	-	-	-


2.Values

Output Voltage [V]	Load Current [A]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-5.00	3.195	3.654	3.946	3.856	3.124
-4.75	-	-	-	-	-
-4.50	-	-	-	-	-
-4.00	-	-	-	-	-
-3.50	-	-	-	-	-
-3.00	-	-	-	-	-
-2.50	-	-	-	-	-
-2.00	-	-	-	-	-
-1.50	-	-	-	-	-
-1.00	-	-	-	-	-
-0.50	-	-	-	-	-
0.00	-	-	-	-	-

COSEL

Model	STMGFW304805
Item	Overvoltage Protection
Object	+10V2A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt.	Input Volt.
48[V]	13.44	13.44
76[V]	13.59	13.59
0	13.73	13.73
25	13.94	13.94
60	14.16	14.23
65	14.23	14.23
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

coSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)