

TEST DATA OF STMGF304815

Regulated DC Power Supply
January 29, 2013

Approved by : Takahiro Yoneda
Takahiro Yoneda Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple Voltage (by Load Current)	8
9.Ripple-Noise	10
10.Ripple Voltage (by Ambient Temperature)	12
11.Ambient Temperature Drift	13
12.Output Voltage Accuracy	14
13.Time Lapse Drift	15
14.Rise and Fall Time	16
15.Minimum Input Voltage for Regulated Output Voltage	18
16.Overcurrent Protection	19
17.Overvoltage Protection	20
18.Figure of Testing Circuitry	21

(Final Page 21)



Model		STMGFW304815		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph		<p>—△— Load 100%</p> <p>---□--- Load 50%</p> <p>---○--- Load 0%</p>		2.Values																																																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.002</td><td>0.001</td><td>0.001</td></tr> <tr><td>10.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>17.0</td><td>0.030</td><td>1.005</td><td>2.075</td></tr> <tr><td>17.5</td><td>0.029</td><td>0.975</td><td>2.020</td></tr> <tr><td>18.0</td><td>0.029</td><td>0.946</td><td>1.938</td></tr> <tr><td>24.0</td><td>0.027</td><td>0.712</td><td>1.434</td></tr> <tr><td>36.0</td><td>0.022</td><td>0.481</td><td>0.955</td></tr> <tr><td>48.0</td><td>0.019</td><td>0.367</td><td>0.722</td></tr> <tr><td>76.0</td><td>0.017</td><td>0.245</td><td>0.471</td></tr> <tr><td>80.0</td><td>0.017</td><td>0.235</td><td>0.453</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.002	0.001	0.001	10.0	0.002	0.002	0.002	15.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.5	0.002	0.002	0.002	17.0	0.030	1.005	2.075	17.5	0.029	0.975	2.020	18.0	0.029	0.946	1.938	24.0	0.027	0.712	1.434	36.0	0.022	0.481	0.955	48.0	0.019	0.367	0.722	76.0	0.017	0.245	0.471	80.0	0.017	0.235	0.453	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
5.0	0.002	0.001	0.001																																																																																	
10.0	0.002	0.002	0.002																																																																																	
15.0	0.002	0.002	0.002																																																																																	
16.0	0.002	0.002	0.002																																																																																	
16.5	0.002	0.002	0.002																																																																																	
17.0	0.030	1.005	2.075																																																																																	
17.5	0.029	0.975	2.020																																																																																	
18.0	0.029	0.946	1.938																																																																																	
24.0	0.027	0.712	1.434																																																																																	
36.0	0.022	0.481	0.955																																																																																	
48.0	0.019	0.367	0.722																																																																																	
76.0	0.017	0.245	0.471																																																																																	
80.0	0.017	0.235	0.453																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



Model		STMGF304815		Temperature 25°C																																																																														
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 18V ---□--- Input Volt. 24V ---*--- Input Volt. 36V ---○--- Input Volt. 48V ---◇--- Input Volt. 76V 		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.029</td><td>0.027</td><td>0.022</td><td>0.019</td><td>0.017</td></tr> <tr><td>20</td><td>0.395</td><td>0.301</td><td>0.206</td><td>0.158</td><td>0.110</td></tr> <tr><td>40</td><td>0.760</td><td>0.574</td><td>0.391</td><td>0.300</td><td>0.202</td></tr> <tr><td>60</td><td>1.140</td><td>0.857</td><td>0.576</td><td>0.438</td><td>0.291</td></tr> <tr><td>80</td><td>1.528</td><td>1.137</td><td>0.764</td><td>0.581</td><td>0.381</td></tr> <tr><td>100</td><td>1.938</td><td>1.434</td><td>0.955</td><td>0.722</td><td>0.471</td></tr> <tr><td>110</td><td>2.135</td><td>1.585</td><td>1.061</td><td>0.799</td><td>0.517</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.029	0.027	0.022	0.019	0.017	20	0.395	0.301	0.206	0.158	0.110	40	0.760	0.574	0.391	0.300	0.202	60	1.140	0.857	0.576	0.438	0.291	80	1.528	1.137	0.764	0.581	0.381	100	1.938	1.434	0.955	0.722	0.471	110	2.135	1.585	1.061	0.799	0.517	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Ration [%]	Input Current [A]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0	0.029	0.027	0.022	0.019	0.017																																																																													
20	0.395	0.301	0.206	0.158	0.110																																																																													
40	0.760	0.574	0.391	0.300	0.202																																																																													
60	1.140	0.857	0.576	0.438	0.291																																																																													
80	1.528	1.137	0.764	0.581	0.381																																																																													
100	1.938	1.434	0.955	0.722	0.471																																																																													
110	2.135	1.585	1.061	0.799	0.517																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model		STMGFW304815		Temperature 25°C																																																																														
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V - · · * · · - · · Input Volt. 36V - · · ○ · · - · · Input Volt. 48V - - - ◇ - - - Input Volt. 76V </p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.52</td> <td>0.65</td> <td>0.80</td> <td>0.91</td> <td>1.31</td> </tr> <tr> <td>20</td> <td>7.12</td> <td>7.23</td> <td>7.41</td> <td>7.57</td> <td>8.33</td> </tr> <tr> <td>40</td> <td>13.70</td> <td>13.78</td> <td>14.06</td> <td>14.36</td> <td>15.36</td> </tr> <tr> <td>60</td> <td>20.51</td> <td>20.49</td> <td>20.71</td> <td>21.03</td> <td>22.08</td> </tr> <tr> <td>80</td> <td>27.51</td> <td>27.37</td> <td>27.50</td> <td>27.79</td> <td>28.88</td> </tr> <tr> <td>100</td> <td>34.76</td> <td>34.46</td> <td>34.40</td> <td>34.65</td> <td>35.76</td> </tr> <tr> <td>110</td> <td>38.51</td> <td>38.05</td> <td>37.94</td> <td>38.19</td> <td>39.23</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Ration [%]	Input Power [W]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.52	0.65	0.80	0.91	1.31	20	7.12	7.23	7.41	7.57	8.33	40	13.70	13.78	14.06	14.36	15.36	60	20.51	20.49	20.71	21.03	22.08	80	27.51	27.37	27.50	27.79	28.88	100	34.76	34.46	34.40	34.65	35.76	110	38.51	38.05	37.94	38.19	39.23	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0	0.52	0.65	0.80	0.91	1.31																																																																													
20	7.12	7.23	7.41	7.57	8.33																																																																													
40	13.70	13.78	14.06	14.36	15.36																																																																													
60	20.51	20.49	20.71	21.03	22.08																																																																													
80	27.51	27.37	27.50	27.79	28.88																																																																													
100	34.76	34.46	34.40	34.65	35.76																																																																													
110	38.51	38.05	37.94	38.19	39.23																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													




<p>Model STMGFW304815</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Efficiency (by Input Voltage)</p>																																		
<p>Object _____</p>																																		
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>87.1</td><td>85.4</td></tr> <tr><td>18</td><td>87.7</td><td>86.0</td></tr> <tr><td>24</td><td>87.5</td><td>87.1</td></tr> <tr><td>30</td><td>86.9</td><td>87.2</td></tr> <tr><td>36</td><td>86.3</td><td>87.1</td></tr> <tr><td>48</td><td>84.7</td><td>86.5</td></tr> <tr><td>60</td><td>82.9</td><td>85.4</td></tr> <tr><td>76</td><td>80.1</td><td>83.9</td></tr> <tr><td>80</td><td>79.2</td><td>83.4</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	87.1	85.4	18	87.7	86.0	24	87.5	87.1	30	86.9	87.2	36	86.3	87.1	48	84.7	86.5	60	82.9	85.4	76	80.1	83.9	80	79.2	83.4
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	87.1	85.4																																
18	87.7	86.0																																
24	87.5	87.1																																
30	86.9	87.2																																
36	86.3	87.1																																
48	84.7	86.5																																
60	82.9	85.4																																
76	80.1	83.9																																
80	79.2	83.4																																



Model	STMGFW304815				Temperature	25°C				
Item	Efficiency (by Load Current)				Testing Circuitry	Figure A				
Object	_____				2.Values					
1.Graph	<div style="display: flex; justify-content: space-between;"> <div style="width: 20%;"> <p>—△— Input Volt. 18V</p> <p>---□--- Input Volt. 24V</p> <p>---*--- Input Volt. 36V</p> <p>---○--- Input Volt. 48V</p> <p>---◇--- Input Volt. 76V</p> </div> <div style="width: 80%;"> </div> </div>									
					Load Ration [%]	Efficiency [%]				
						Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
					0	-	-	-	-	-
					20	84.1	83.0	80.9	79.2	72.0
					40	87.4	87.0	85.2	83.4	78.0
					60	87.6	87.7	86.8	85.5	81.4
					80	87.2	87.6	87.2	86.3	83.0
					100	86.2	87.0	87.2	86.5	83.8
					110	85.6	86.7	86.9	86.4	84.1
					--	-	-	-	-	-
					--	-	-	-	-	-
					--	-	-	-	-	-
					--	-	-	-	-	-




<p>Model STMGF304815</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																	
<p>Item Line Regulation</p>																																			
<p>Object +15V1A</p>																																			
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>15.062</td><td>14.979</td></tr> <tr><td>18</td><td>15.063</td><td>14.980</td></tr> <tr><td>24</td><td>15.061</td><td>14.981</td></tr> <tr><td>30</td><td>15.061</td><td>14.983</td></tr> <tr><td>36</td><td>15.060</td><td>14.983</td></tr> <tr><td>48</td><td>15.058</td><td>14.982</td></tr> <tr><td>60</td><td>15.057</td><td>14.980</td></tr> <tr><td>76</td><td>15.054</td><td>14.978</td></tr> <tr><td>80</td><td>15.054</td><td>14.978</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	15.062	14.979	18	15.063	14.980	24	15.061	14.981	30	15.061	14.983	36	15.060	14.983	48	15.058	14.982	60	15.057	14.980	76	15.054	14.978	80	15.054	14.978	
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	15.062	14.979																																	
18	15.063	14.980																																	
24	15.061	14.981																																	
30	15.061	14.983																																	
36	15.060	14.983																																	
48	15.058	14.982																																	
60	15.057	14.980																																	
76	15.054	14.978																																	
80	15.054	14.978																																	
<p>Object -15V1A</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																	
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>			<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>-15.075</td><td>-14.983</td></tr> <tr><td>18</td><td>-15.074</td><td>-14.983</td></tr> <tr><td>24</td><td>-15.071</td><td>-14.982</td></tr> <tr><td>30</td><td>-15.068</td><td>-14.981</td></tr> <tr><td>36</td><td>-15.067</td><td>-14.981</td></tr> <tr><td>48</td><td>-15.067</td><td>-14.982</td></tr> <tr><td>60</td><td>-15.068</td><td>-14.984</td></tr> <tr><td>76</td><td>-15.069</td><td>-14.986</td></tr> <tr><td>80</td><td>-15.069</td><td>-14.987</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	-15.075	-14.983	18	-15.074	-14.983	24	-15.071	-14.982	30	-15.068	-14.981	36	-15.067	-14.981	48	-15.067	-14.982	60	-15.068	-14.984	76	-15.069	-14.986	80	-15.069	-14.987
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	-15.075	-14.983																																	
18	-15.074	-14.983																																	
24	-15.071	-14.982																																	
30	-15.068	-14.981																																	
36	-15.067	-14.981																																	
48	-15.067	-14.982																																	
60	-15.068	-14.984																																	
76	-15.069	-14.986																																	
80	-15.069	-14.987																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	15.294	15.281	15.281	15.286	15.306
0.2	15.150	15.145	15.140	15.138	15.136
0.4	15.100	15.096	15.092	15.090	15.086
0.6	15.058	15.056	15.054	15.052	15.047
0.8	15.020	15.019	15.018	15.017	15.012
1.0	14.983	14.985	14.986	14.985	14.980
1.1	14.966	14.968	14.970	14.969	14.966
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-



2.Values

Load Current [A]	Output Voltage [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.0	-15.344	-15.387	-15.429	-15.443	-15.447
0.2	-15.156	-15.155	-15.155	-15.159	-15.167
0.4	-15.101	-15.096	-15.092	-15.092	-15.095
0.6	-15.058	-15.054	-15.050	-15.050	-15.052
0.8	-15.020	-15.017	-15.014	-15.014	-15.017
1.0	-14.984	-14.982	-14.981	-14.982	-14.986
1.1	-14.966	-14.966	-14.966	-14.967	-14.971
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-



<p>Model STMGF304815</p>		<p>Temperature 25°C</p>																																							
<p>Item Ripple Voltage (by Load Current)</p>		<p>Testing Circuitry Figure B</p>																																							
<p>Object +15V1A</p>																																									
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 18V</p> <p>- -○- - Input Volt. 76V</p> </div> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>30</td></tr> <tr><td>0.2</td><td>30</td><td>40</td></tr> <tr><td>0.4</td><td>30</td><td>40</td></tr> <tr><td>0.6</td><td>30</td><td>40</td></tr> <tr><td>0.8</td><td>30</td><td>40</td></tr> <tr><td>1.0</td><td>30</td><td>45</td></tr> <tr><td>1.1</td><td>30</td><td>45</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated output current</p>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	20	30	0.2	30	40	0.4	30	40	0.6	30	40	0.8	30	40	1.0	30	45	1.1	30	45	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 18 [V]	Input Volt. 76 [V]																																							
0.0	20	30																																							
0.2	30	40																																							
0.4	30	40																																							
0.6	30	40																																							
0.8	30	40																																							
1.0	30	45																																							
1.1	30	45																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																									



<p>Model STMGFW304815</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple Voltage (by Load Current)</p>																																								
<p>Object -15V1A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 18V - - -○- - - Input Volt. 76V</p> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>0.2</td><td>15</td><td>20</td></tr> <tr><td>0.4</td><td>15</td><td>20</td></tr> <tr><td>0.6</td><td>15</td><td>20</td></tr> <tr><td>0.8</td><td>15</td><td>20</td></tr> <tr><td>1.0</td><td>15</td><td>20</td></tr> <tr><td>1.1</td><td>15</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+15V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	15	20	0.2	15	20	0.4	15	20	0.6	15	20	0.8	15	20	1.0	15	20	1.1	15	20	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	15	20																																						
0.2	15	20																																						
0.4	15	20																																						
0.6	15	20																																						
0.8	15	20																																						
1.0	15	20																																						
1.1	15	20																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model STMGF304815</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +15V1A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 18V -·-○-·- Input Volt. 76V</p> </div> <p>Ripple-Noise [mV]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>25</td><td>40</td></tr> <tr><td>0.2</td><td>35</td><td>40</td></tr> <tr><td>0.4</td><td>35</td><td>40</td></tr> <tr><td>0.6</td><td>35</td><td>40</td></tr> <tr><td>0.8</td><td>35</td><td>50</td></tr> <tr><td>1.0</td><td>35</td><td>50</td></tr> <tr><td>1.1</td><td>35</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-15V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	25	40	0.2	35	40	0.4	35	40	0.6	35	40	0.8	35	50	1.0	35	50	1.1	35	50	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	25	40																																						
0.2	35	40																																						
0.4	35	40																																						
0.6	35	40																																						
0.8	35	50																																						
1.0	35	50																																						
1.1	35	50																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise [mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								




<p>Model STMGF304815</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple-Noise																																							
Object	-15V1A																																							
<p>1. Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 18V -·-○-·- Input Volt. 76V</p> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>30</td><td>35</td></tr> <tr><td>0.2</td><td>30</td><td>35</td></tr> <tr><td>0.4</td><td>30</td><td>35</td></tr> <tr><td>0.6</td><td>30</td><td>35</td></tr> <tr><td>0.8</td><td>30</td><td>40</td></tr> <tr><td>1.0</td><td>30</td><td>40</td></tr> <tr><td>1.1</td><td>30</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	30	35	0.2	30	35	0.4	30	35	0.6	30	35	0.8	30	40	1.0	30	40	1.1	30	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	30	35																																						
0.2	30	35																																						
0.4	30	35																																						
0.6	30	35																																						
0.8	30	40																																						
1.0	30	40																																						
1.1	30	40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Fig. Complex Ripple Noise Wave Form</p>																																								



Model	STMGF304815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V1A

Testing Circuitry Figure B

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	80	80
-20	60	60
0	40	50
25	30	45
60	30	45
65	30	45
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

Object	-15V1A
--------	--------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-40	40	40
-20	35	35
0	25	30
25	15	20
60	15	20
65	15	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Model		STMGF304815		Testing Circuitry Figure A																																																																														
Item		Ambient Temperature Drift		2.Values																																																																														
Object		+15V1A		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>14.916</td><td>14.919</td><td>14.923</td><td>14.924</td><td>14.921</td></tr> <tr><td>-20</td><td>14.939</td><td>14.941</td><td>14.943</td><td>14.943</td><td>14.940</td></tr> <tr><td>0</td><td>14.958</td><td>14.960</td><td>14.962</td><td>14.962</td><td>14.958</td></tr> <tr><td>10</td><td>14.967</td><td>14.969</td><td>14.970</td><td>14.970</td><td>14.966</td></tr> <tr><td>25</td><td>14.977</td><td>14.979</td><td>14.980</td><td>14.980</td><td>14.976</td></tr> <tr><td>30</td><td>14.980</td><td>14.982</td><td>14.984</td><td>14.983</td><td>14.979</td></tr> <tr><td>40</td><td>14.986</td><td>14.987</td><td>14.989</td><td>14.988</td><td>14.984</td></tr> <tr><td>50</td><td>14.991</td><td>14.993</td><td>14.994</td><td>14.993</td><td>14.989</td></tr> <tr><td>60</td><td>14.995</td><td>14.997</td><td>14.998</td><td>14.997</td><td>14.994</td></tr> <tr><td>65</td><td>14.996</td><td>14.998</td><td>14.999</td><td>14.998</td><td>14.995</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-40	14.916	14.919	14.923	14.924	14.921	-20	14.939	14.941	14.943	14.943	14.940	0	14.958	14.960	14.962	14.962	14.958	10	14.967	14.969	14.970	14.970	14.966	25	14.977	14.979	14.980	14.980	14.976	30	14.980	14.982	14.984	14.983	14.979	40	14.986	14.987	14.989	14.988	14.984	50	14.991	14.993	14.994	14.993	14.989	60	14.995	14.997	14.998	14.997	14.994	65	14.996	14.998	14.999	14.998	14.995	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
-40	14.916	14.919	14.923	14.924	14.921																																																																													
-20	14.939	14.941	14.943	14.943	14.940																																																																													
0	14.958	14.960	14.962	14.962	14.958																																																																													
10	14.967	14.969	14.970	14.970	14.966																																																																													
25	14.977	14.979	14.980	14.980	14.976																																																																													
30	14.980	14.982	14.984	14.983	14.979																																																																													
40	14.986	14.987	14.989	14.988	14.984																																																																													
50	14.991	14.993	14.994	14.993	14.989																																																																													
60	14.995	14.997	14.998	14.997	14.994																																																																													
65	14.996	14.998	14.999	14.998	14.995																																																																													
--	-	-	-	-	-																																																																													
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 18V ---□--- Input Volt. 24V -...*...- Input Volt. 36V -...○...- Input Volt. 48V -...◇...- Input Volt. 76V 																																																																																
Object		-15V1A		2.Values																																																																														
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 18V ---□--- Input Volt. 24V -...*...- Input Volt. 36V -...○...- Input Volt. 48V -...◇...- Input Volt. 76V 																																																																																
Object		-15V1A		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>-14.916</td><td>-14.917</td><td>-14.919</td><td>-14.921</td><td>-14.925</td></tr> <tr><td>-20</td><td>-14.939</td><td>-14.939</td><td>-14.939</td><td>-14.941</td><td>-14.945</td></tr> <tr><td>0</td><td>-14.958</td><td>-14.958</td><td>-14.959</td><td>-14.960</td><td>-14.964</td></tr> <tr><td>10</td><td>-14.967</td><td>-14.966</td><td>-14.967</td><td>-14.968</td><td>-14.972</td></tr> <tr><td>25</td><td>-14.977</td><td>-14.976</td><td>-14.976</td><td>-14.977</td><td>-14.981</td></tr> <tr><td>30</td><td>-14.980</td><td>-14.979</td><td>-14.979</td><td>-14.980</td><td>-14.984</td></tr> <tr><td>40</td><td>-14.985</td><td>-14.985</td><td>-14.984</td><td>-14.986</td><td>-14.989</td></tr> <tr><td>50</td><td>-14.990</td><td>-14.990</td><td>-14.990</td><td>-14.991</td><td>-14.994</td></tr> <tr><td>60</td><td>-14.994</td><td>-14.994</td><td>-14.993</td><td>-14.995</td><td>-14.998</td></tr> <tr><td>65</td><td>-14.995</td><td>-14.995</td><td>-14.994</td><td>-14.996</td><td>-14.999</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-40	-14.916	-14.917	-14.919	-14.921	-14.925	-20	-14.939	-14.939	-14.939	-14.941	-14.945	0	-14.958	-14.958	-14.959	-14.960	-14.964	10	-14.967	-14.966	-14.967	-14.968	-14.972	25	-14.977	-14.976	-14.976	-14.977	-14.981	30	-14.980	-14.979	-14.979	-14.980	-14.984	40	-14.985	-14.985	-14.984	-14.986	-14.989	50	-14.990	-14.990	-14.990	-14.991	-14.994	60	-14.994	-14.994	-14.993	-14.995	-14.998	65	-14.995	-14.995	-14.994	-14.996	-14.999	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
-40	-14.916	-14.917	-14.919	-14.921	-14.925																																																																													
-20	-14.939	-14.939	-14.939	-14.941	-14.945																																																																													
0	-14.958	-14.958	-14.959	-14.960	-14.964																																																																													
10	-14.967	-14.966	-14.967	-14.968	-14.972																																																																													
25	-14.977	-14.976	-14.976	-14.977	-14.981																																																																													
30	-14.980	-14.979	-14.979	-14.980	-14.984																																																																													
40	-14.985	-14.985	-14.984	-14.986	-14.989																																																																													
50	-14.990	-14.990	-14.990	-14.991	-14.994																																																																													
60	-14.994	-14.994	-14.993	-14.995	-14.998																																																																													
65	-14.995	-14.995	-14.994	-14.996	-14.999																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated ambient temperature.																																																																																		



COSEL		Testing Circuitry Figure A
Model	STMGEFW304815	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 60°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 1A (AVR 2) : 0 - 1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+15V1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	76	0	15.312	±187	±1.2	
Minimum Voltage	-20	18	1	14.939			

Object		-15V1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	76	0	-15.450	±256	±1.7	
Minimum Voltage	-20	18	1	-14.939			




COSEL																									
Model	STMGF304815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V1A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.964</td></tr> <tr><td>0.5</td><td>14.983</td></tr> <tr><td>1.0</td><td>14.983</td></tr> <tr><td>2.0</td><td>14.982</td></tr> <tr><td>3.0</td><td>14.982</td></tr> <tr><td>4.0</td><td>14.982</td></tr> <tr><td>5.0</td><td>14.982</td></tr> <tr><td>6.0</td><td>14.982</td></tr> <tr><td>7.0</td><td>14.982</td></tr> <tr><td>8.0</td><td>14.982</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	14.964	0.5	14.983	1.0	14.983	2.0	14.982	3.0	14.982	4.0	14.982	5.0	14.982	6.0	14.982	7.0	14.982	8.0	14.982
Time since start [H]	Output Voltage [V]																								
0.0	14.964																								
0.5	14.983																								
1.0	14.983																								
2.0	14.982																								
3.0	14.982																								
4.0	14.982																								
5.0	14.982																								
6.0	14.982																								
7.0	14.982																								
8.0	14.982																								
Object	-15V1A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.971</td></tr> <tr><td>0.5</td><td>-14.990</td></tr> <tr><td>1.0</td><td>-14.990</td></tr> <tr><td>2.0</td><td>-14.990</td></tr> <tr><td>3.0</td><td>-14.990</td></tr> <tr><td>4.0</td><td>-14.990</td></tr> <tr><td>5.0</td><td>-14.989</td></tr> <tr><td>6.0</td><td>-14.989</td></tr> <tr><td>7.0</td><td>-14.989</td></tr> <tr><td>8.0</td><td>-14.989</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-14.971	0.5	-14.990	1.0	-14.990	2.0	-14.990	3.0	-14.990	4.0	-14.990	5.0	-14.989	6.0	-14.989	7.0	-14.989	8.0	-14.989
Time since start [H]	Output Voltage [V]																								
0.0	-14.971																								
0.5	-14.990																								
1.0	-14.990																								
2.0	-14.990																								
3.0	-14.990																								
4.0	-14.990																								
5.0	-14.989																								
6.0	-14.989																								
7.0	-14.989																								
8.0	-14.989																								



Model	STMGFW304815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V1A		


1. Graph

Input Volt. 48 V



2. Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	2.1	5.7	7.8	0.2	3.3
100 %	2.0	6.4	8.4	0.2	1.6






Model	STMGFW304815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V1A		


1. Graph

Input Volt. 48 V



2. Values

		[ms]				
Load \ Time	Time	Td	Tr	Ts	Th	Tf
50 %		2.1	5.9	8.0	0.2	3.5
100 %		2.0	6.3	8.3	0.2	1.7






Model	STMGF304815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V1A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	16.2	16.3
-20	16.3	16.4
0	16.3	16.3
10	16.3	16.2
25	16.3	16.1
30	16.3	16.1
40	16.4	16.2
50	16.2	16.3
60	16.2	16.4
65	16.4	16.4
--	-	-

Object	-15V1A
--------	--------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	15.9	16.1
-20	16.1	16.2
0	16.1	16.2
10	16.1	16.0
25	16.1	16.0
30	16.2	15.9
40	16.1	16.0
50	16.0	16.2
60	16.0	16.1
65	16.2	16.2
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model STMGF304815		Temperature 25°C Testing Circuitry Figure A																																																																																		
Item Overcurrent Protection																																																																																				
Object +15V1A																																																																																				
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 45%;"> <p>△ Input Volt. 18V</p> <p>□ Input Volt. 24V</p> <p>* Input Volt. 36V</p> <p>○ Input Volt. 48V</p> <p>◇ Input Volt. 76V</p> </div> </div>	<p>2.Values</p> <table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>1.602</td><td>1.811</td><td>1.951</td><td>1.923</td><td>1.633</td></tr> <tr><td>14.3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	15.0	1.602	1.811	1.951	1.923	1.633	14.3	-	-	-	-	-	13.5	-	-	-	-	-	12.0	-	-	-	-	-	10.5	-	-	-	-	-	9.0	-	-	-	-	-	7.5	-	-	-	-	-	6.0	-	-	-	-	-	4.5	-	-	-	-	-	3.0	-	-	-	-	-	1.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																			
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																															
15.0	1.602	1.811	1.951	1.923	1.633																																																																															
14.3	-	-	-	-	-																																																																															
13.5	-	-	-	-	-																																																																															
12.0	-	-	-	-	-																																																																															
10.5	-	-	-	-	-																																																																															
9.0	-	-	-	-	-																																																																															
7.5	-	-	-	-	-																																																																															
6.0	-	-	-	-	-																																																																															
4.5	-	-	-	-	-																																																																															
3.0	-	-	-	-	-																																																																															
1.5	-	-	-	-	-																																																																															
0.0	-	-	-	-	-																																																																															
Object -15V1A		Temperature 25°C Testing Circuitry Figure A																																																																																		
Item Overcurrent Protection																																																																																				
Object -15V1A																																																																																				
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 45%;"> <p>△ Input Volt. 18V</p> <p>□ Input Volt. 24V</p> <p>* Input Volt. 36V</p> <p>○ Input Volt. 48V</p> <p>◇ Input Volt. 76V</p> </div> </div>	<p>2.Values</p> <table border="1" style="width:100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-15.0</td><td>1.590</td><td>1.811</td><td>1.952</td><td>1.925</td><td>1.634</td></tr> <tr><td>-14.3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-15.0	1.590	1.811	1.952	1.925	1.634	-14.3	-	-	-	-	-	-13.5	-	-	-	-	-	-12.0	-	-	-	-	-	-10.5	-	-	-	-	-	-9.0	-	-	-	-	-	-7.5	-	-	-	-	-	-6.0	-	-	-	-	-	-4.5	-	-	-	-	-	-3.0	-	-	-	-	-	-1.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																			
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																															
-15.0	1.590	1.811	1.952	1.925	1.634																																																																															
-14.3	-	-	-	-	-																																																																															
-13.5	-	-	-	-	-																																																																															
-12.0	-	-	-	-	-																																																																															
-10.5	-	-	-	-	-																																																																															
-9.0	-	-	-	-	-																																																																															
-7.5	-	-	-	-	-																																																																															
-6.0	-	-	-	-	-																																																																															
-4.5	-	-	-	-	-																																																																															
-3.0	-	-	-	-	-																																																																															
-1.5	-	-	-	-	-																																																																															
0.0	-	-	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																																																				



Model		STMGFW304815	Testing Circuitry Figure A																																						
Item		Overvoltage Protection																																							
Object		+30V1A																																							
1.Graph		<p> —△— Input Volt. 48V - - - □ - - - Input Volt. 76V </p> <p style="text-align: center;">Ambient Temperature [°C] Load 0%</p>	2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-40</td><td>38.39</td><td>38.43</td></tr> <tr><td>-20</td><td>38.39</td><td>38.43</td></tr> <tr><td>0</td><td>38.67</td><td>38.79</td></tr> <tr><td>25</td><td>39.50</td><td>39.61</td></tr> <tr><td>60</td><td>40.52</td><td>40.63</td></tr> <tr><td>65</td><td>40.65</td><td>40.77</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 48[V]	Input Volt. 76[V]	-40	38.39	38.43	-20	38.39	38.43	0	38.67	38.79	25	39.50	39.61	60	40.52	40.63	65	40.65	40.77	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 48[V]	Input Volt. 76[V]																																							
-40	38.39	38.43																																							
-20	38.39	38.43																																							
0	38.67	38.79																																							
25	39.50	39.61																																							
60	40.52	40.63																																							
65	40.65	40.77																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									




Figure A




Figure B (Ripple and Ripple noise Characteristic)