

Date : Mar.25,2005

Temperature increase of main components

Model: SUCS/SUCW1048


1. Conditions

- (1) Input :DC 36 - 76 [V]
 (2) Output :Rated output
 (3) Cooling method :Convection cooling
 (4) Mounting method :Shown as Fig.1.1

2. Result

Table 2.1 Temperature increase of main components

Table 2.1 Temperature increase of main components										
No.	Parts name	Symbol No.	Increase (ΔT)						Rated temp. [°C]	Reference
			[deg.]							
			3.3V	5V	12V	15V	$\pm 12V$	$\pm 15V$		
1	Switching Transistor	TR31	51	54	59	58	49	51	150	Junction Temp.
2	Transformer	T11	52	51	51	47	43	46	155	
3	Rectifying MOS-FET	TR51	51	49	—	—	—	—	150	Junction Temp.
4	Rectifying Diode	D52	48	48	49	53	35	38	150	Junction Temp.
5	Photocoupler	PC11	43	43	43	44	33	36	125	Junction Temp.
6	Input Choke Coil	L11	41	40	41	40	36	36	130	
7	Output Choke Coil	L51	46	43	33	33	28	31	120	
8	Output Capacitor	C51	46	44	37	37	31	34	125	
9	Power Control IC	IC11	47	47	48	47	42	43	150	
10										
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										



(Side view)

Fig.1.1 Mounting method
(Normal position)