



# TEST DATA OF SUCS30512

Regulated DC Power Supply  
Mar 22, 2005

Approved by : Tetsuo Sugimori  
Tetsuo Sugimori Design Manager

Prepared by : Hayato Nakatsubo  
Hayato Nakatsubo Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Figure of Testing Circuitry . . . . .	18


(Final Page 18)

**COSEL**

Model	SUCCS30512	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____																																																																																		
1.Graph		<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Load 100% (△)</li> <li>Load 50% (□)</li> <li>Load 0% (○)</li> </ul> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	
		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>1.70</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.49</td><td>0.083</td><td>0.961</td><td>0.018</td></tr> <tr><td>2.83</td><td>0.075</td><td>0.800</td><td>2.067</td></tr> <tr><td>3.00</td><td>0.074</td><td>0.717</td><td>1.805</td></tr> <tr><td>4.00</td><td>0.062</td><td>0.518</td><td>1.043</td></tr> <tr><td>4.50</td><td>0.058</td><td>0.457</td><td>0.896</td></tr> <tr><td>5.00</td><td>0.055</td><td>0.410</td><td>0.790</td></tr> <tr><td>6.00</td><td>0.050</td><td>0.345</td><td>0.644</td></tr> <tr><td>7.00</td><td>0.049</td><td>0.300</td><td>0.559</td></tr> <tr><td>8.00</td><td>0.049</td><td>0.268</td><td>0.490</td></tr> <tr><td>9.00</td><td>0.051</td><td>0.246</td><td>0.437</td></tr> <tr><td>10.00</td><td>0.054</td><td>0.229</td><td>0.403</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	1.70	0.000	0.000	0.000	2.00	0.000	0.000	0.000	2.49	0.083	0.961	0.018	2.83	0.075	0.800	2.067	3.00	0.074	0.717	1.805	4.00	0.062	0.518	1.043	4.50	0.058	0.457	0.896	5.00	0.055	0.410	0.790	6.00	0.050	0.345	0.644	7.00	0.049	0.300	0.559	8.00	0.049	0.268	0.490	9.00	0.051	0.246	0.437	10.00	0.054	0.229	0.403	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.00	0.000	0.000	0.000																																																																																
1.70	0.000	0.000	0.000																																																																																
2.00	0.000	0.000	0.000																																																																																
2.49	0.083	0.961	0.018																																																																																
2.83	0.075	0.800	2.067																																																																																
3.00	0.074	0.717	1.805																																																																																
4.00	0.062	0.518	1.043																																																																																
4.50	0.058	0.457	0.896																																																																																
5.00	0.055	0.410	0.790																																																																																
6.00	0.050	0.345	0.644																																																																																
7.00	0.049	0.300	0.559																																																																																
8.00	0.049	0.268	0.490																																																																																
9.00	0.051	0.246	0.437																																																																																
10.00	0.054	0.229	0.403																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

**COSEL**

Model	SUCS30512
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	0.058	0.055	0.051
0.050	0.216	0.196	0.130
0.100	0.380	0.340	0.207
0.150	0.549	0.488	0.284
0.200	0.715	0.646	0.362
0.250	0.905	0.774	0.440
0.275	1.008	0.854	0.480
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	SUCCS30512	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	—	—	—																																																			
1. Graph																																																						
<p style="text-align: center;"> <span style="margin-right: 10px;">—△— Input Volt. 4.5V</span> <span style="margin-right: 10px;">---□--- Input Volt. 5V</span> <span style="margin-right: 10px;">---○--- Input Volt. 9V</span> </p> <p>The graph plots Input Power [W] on the y-axis (0.0 to 5.0) against Load Current [A] on the x-axis (0.00 to 0.30). Three data series are shown: 4.5V (solid line with triangles), 5V (dashed line with squares), and 9V (dash-dot line with circles). All curves are linear. A solid slanted line is drawn through the origin, passing through approximately (0.12, 2.4) and (0.28, 4.4), representing the rated load current range.</p>																																																						
2. Values																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.26</td><td>0.28</td><td>0.47</td></tr> <tr><td>0.050</td><td>0.96</td><td>0.98</td><td>1.18</td></tr> <tr><td>0.100</td><td>1.68</td><td>1.68</td><td>1.87</td></tr> <tr><td>0.150</td><td>2.41</td><td>2.40</td><td>2.56</td></tr> <tr><td>0.200</td><td>3.18</td><td>3.15</td><td>3.27</td></tr> <tr><td>0.250</td><td>4.00</td><td>3.91</td><td>3.97</td></tr> <tr><td>0.275</td><td>4.44</td><td>4.32</td><td>4.33</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	0.26	0.28	0.47	0.050	0.96	0.98	1.18	0.100	1.68	1.68	1.87	0.150	2.41	2.40	2.56	0.200	3.18	3.15	3.27	0.250	4.00	3.91	3.97	0.275	4.44	4.32	4.33	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.000	0.26	0.28	0.47																																																			
0.050	0.96	0.98	1.18																																																			
0.100	1.68	1.68	1.87																																																			
0.150	2.41	2.40	2.56																																																			
0.200	3.18	3.15	3.27																																																			
0.250	4.00	3.91	3.97																																																			
0.275	4.44	4.32	4.33																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model	SUCS30512	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—																																		
1.Graph																																			
<p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Input Voltage [V] on the x-axis (3 to 9). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight increase in efficiency from approximately 73% at 4V to about 77% at 7V, followed by a gradual decline to around 70% at 9.5V. A slanted line on the graph indicates the rated input voltage range.</p>																																			
2.Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>73.8</td> <td>73.6</td> </tr> <tr> <td>4.5</td> <td>74.2</td> <td>75.8</td> </tr> <tr> <td>5.0</td> <td>74.4</td> <td>77.0</td> </tr> <tr> <td>6.0</td> <td>73.8</td> <td>77.9</td> </tr> <tr> <td>7.0</td> <td>72.3</td> <td>78.0</td> </tr> <tr> <td>8.0</td> <td>70.5</td> <td>77.2</td> </tr> <tr> <td>9.0</td> <td>68.6</td> <td>76.4</td> </tr> <tr> <td>9.5</td> <td>67.4</td> <td>75.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.0	73.8	73.6	4.5	74.2	75.8	5.0	74.4	77.0	6.0	73.8	77.9	7.0	72.3	78.0	8.0	70.5	77.2	9.0	68.6	76.4	9.5	67.4	75.8	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
4.0	73.8	73.6																																	
4.5	74.2	75.8																																	
5.0	74.4	77.0																																	
6.0	73.8	77.9																																	
7.0	72.3	78.0																																	
8.0	70.5	77.2																																	
9.0	68.6	76.4																																	
9.5	67.4	75.8																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

**COSEL**

Model	SUCS30512
Item	Efficiency (by Load Current)
Object	_____

1.Graph

Load Current [A]	Efficiency [%]		
	Input Volt. 4.5V	Input Volt. 5V	Input Volt. 9V
0.00	-	-	-
0.050	63.1	62.3	51.4
0.100	72.2	72.2	64.7
0.150	75.2	75.6	70.8
0.200	76.0	76.8	74.1
0.250	75.5	77.4	76.2
0.275	74.9	77.0	76.8
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values


Load Current [A]	Efficiency [%]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	-	-	-
0.050	63.1	62.3	51.4
0.100	72.2	72.2	64.7
0.150	75.2	75.6	70.8
0.200	76.0	76.8	74.1
0.250	75.5	77.4	76.2
0.275	74.9	77.0	76.8
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	SUCS30512
Item	Line Regulation
Object	+12V0.25A

Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph




Note: Slanted line shows the range of the rated input voltage.

## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.0	12.064	12.062
4.5	12.064	12.062
5.0	12.064	12.062
6.0	12.064	12.062
7.0	12.064	12.062
8.0	12.064	12.062
9.0	12.063	12.062
9.5	12.064	12.062
--	-	-

**COSEL**

Model	SUCS30512
Item	Load Regulation
Object	+12V0.25A



Temperature 25°C  
Testing Circuitry Figure A

## 2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	12.066	12.066	12.065
0.050	12.065	12.065	12.064
0.100	12.064	12.064	12.064
0.150	12.063	12.063	12.063
0.200	12.063	12.063	12.062
0.250	12.062	12.062	12.062
0.275	12.062	12.062	12.062
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	SUCS30512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.25A		

Input Volt. 5 V  
 Cycle 100 mS



Min. Load (0A) ↔  
 Load 100% (0.25A)

200mV/div

2ms/div

2ms/div

Min. Load (0A) ↔  
 Load 50% (0.125A)

200mV/div

2ms/div

2ms/div

Load 50% (0.125A) ↔  
 Load 100% (0.25A)

200mV/div

2ms/div

2ms/div

**COSEL**


Model	SUCS30512	Temperature Testing Circuitry 25°C Figure B																																			
Item	Ripple Voltage (by Load Current)																																				
Object	+12V0.25A																																				
1.Graph		2.Values																																			
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 4.5V (solid line with triangle markers) and Input Volt. 9V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.00 to 0.30. The y-axis represents Ripple Voltage [mV] from 0 to 50. A slanted line is drawn through the data points, indicating the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 4.5V)</th> <th>Ripple Voltage [mV] (Input Volt. 9V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>1</td></tr> <tr><td>0.050</td><td>2</td><td>1</td></tr> <tr><td>0.100</td><td>2</td><td>1</td></tr> <tr><td>0.150</td><td>3</td><td>1</td></tr> <tr><td>0.200</td><td>4</td><td>2</td></tr> <tr><td>0.250</td><td>5</td><td>3</td></tr> <tr><td>0.275</td><td>6</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 9V)	0.00	2	1	0.050	2	1	0.100	2	1	0.150	3	1	0.200	4	2	0.250	5	3	0.275	6	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 9V)																																			
0.00	2	1																																			
0.050	2	1																																			
0.100	2	1																																			
0.150	3	1																																			
0.200	4	2																																			
0.250	5	3																																			
0.275	6	4																																			
--	-	-																																			
--	-	-																																			
--	-	-																																			
--	-	-																																			
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																					
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																					

**COSEL**

Model	SUCS30512
Item	Ripple-Noise
Object	+12V0.25A

 Temperature 25°C  
 Testing Circuitry Figure B

## 1.Graph




Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2.Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	4	5
0.050	5	6
0.100	6	7
0.150	7	7
0.200	7	7
0.250	8	8
0.275	8	8
--	-	-
--	-	-
--	-	-
--	-	-



**COSEL**
**Model** SUCS30512

**Item** Ripple Voltage (by Ambient Temp.)


**Object** +12V0.25A

**1. Graph**

**Measured by 100 MHz Oscilloscope.**
**Note:** Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure B**
**2. Values**

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	7	9
-40	7	9
-20	6	9
0	6	8
25	4	6
55	4	5
60	4	5
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	SUCS30512	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+12V0.25A																																																						
1.Graph	<p style="text-align: center;"> <span style="display: inline-block; width: 1em; height: 1em; border-left: 1px solid black; border-bottom: 1px solid black; margin-right: 0.2em;"></span> Input Volt. 4.5V  <span style="display: inline-block; width: 1em; height: 1em; border-top: 1px dashed black; border-right: 1px dashed black; border-bottom: 1px solid black; border-left: none; margin-right: 0.2em;"></span> Input Volt. 5V  <span style="display: inline-block; width: 1em; height: 1em; border-top: 1px dashed black; border-right: 1px dashed black; border-left: none; border-bottom: 1px solid black; margin-right: 0.2em;"></span> Input Volt. 9V       </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Load 100%</p>																																																						
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.000</td><td>12.002</td><td>12.003</td></tr> <tr><td>-40</td><td>12.023</td><td>12.025</td><td>12.026</td></tr> <tr><td>-20</td><td>12.040</td><td>12.041</td><td>12.042</td></tr> <tr><td>0</td><td>12.053</td><td>12.054</td><td>12.054</td></tr> <tr><td>25</td><td>12.061</td><td>12.062</td><td>12.062</td></tr> <tr><td>55</td><td>12.063</td><td>12.062</td><td>12.062</td></tr> <tr><td>60</td><td>12.062</td><td>12.062</td><td>12.062</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.000	12.002	12.003	-40	12.023	12.025	12.026	-20	12.040	12.041	12.042	0	12.053	12.054	12.054	25	12.061	12.062	12.062	55	12.063	12.062	12.062	60	12.062	12.062	12.062	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																				
-60	12.000	12.002	12.003																																																				
-40	12.023	12.025	12.026																																																				
-20	12.040	12.041	12.042																																																				
0	12.053	12.054	12.054																																																				
25	12.061	12.062	12.062																																																				
55	12.063	12.062	12.062																																																				
60	12.062	12.062	12.062																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	SUCS30512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.25A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 9V

Load Current : 0 - 0.25A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	55	4.5	0	12.066	±22	±0.2
Minimum Voltage	-40	4.5	0.25	12.023		

**COSEL**

Model	SUCCS30512	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.25A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.063</td></tr> <tr><td>0.5</td><td>12.061</td></tr> <tr><td>1.0</td><td>12.061</td></tr> <tr><td>2.0</td><td>12.061</td></tr> <tr><td>3.0</td><td>12.061</td></tr> <tr><td>4.0</td><td>12.061</td></tr> <tr><td>5.0</td><td>12.061</td></tr> <tr><td>6.0</td><td>12.061</td></tr> <tr><td>7.0</td><td>12.061</td></tr> <tr><td>8.0</td><td>12.061</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.063	0.5	12.061	1.0	12.061	2.0	12.061	3.0	12.061	4.0	12.061	5.0	12.061	6.0	12.061	7.0	12.061	8.0	12.061
Time since start [H]	Output Voltage [V]																								
0.0	12.063																								
0.5	12.061																								
1.0	12.061																								
2.0	12.061																								
3.0	12.061																								
4.0	12.061																								
5.0	12.061																								
6.0	12.061																								
7.0	12.061																								
8.0	12.061																								

**COSEL**


Model SUCS30512

Item Rise and Fall Time

Object +12V0.25A

Temperature 25°C  
Testing Circuitry Figure A


## 1.Graph



## 2.Values

[mS]


Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.2	6.3	6.5	0.1	2.4
100 %		0.2	6.4	6.6	0.1	1.2



**COSEL**

Model	SUCS30512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A

## 1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	2.1	2.8
-40	2.2	2.7
-20	2.2	2.8
0	2.2	2.9
25	2.2	3.0
55	2.3	3.1
60	2.3	3.1
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**


Model SUCS30512

Item Overcurrent Protection

Object +12V0.25A

## 1.Graph

Input Volt. 4.5V  
 Input Volt. 5V  
 Input Volt. 9V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
12.0	0.25	0.25	0.25
11.4	0.42	0.42	0.42
10.8	0.43	0.43	0.42
9.6	0.45	0.45	0.43
8.4	0.46	0.46	0.44
7.2	0.48	0.48	0.45
6.0	0.50	0.49	0.45
4.8	0.51	0.50	0.45
3.6	0.51	0.50	0.45
2.4	0.50	0.48	0.43
1.2	0.46	0.44	0.40
0.0	0.43	0.43	0.43

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)